

# FCC RF Exposure

EUT Description: Digital Camera

Model No.: DC201

FCC ID: 2BRYA-DC201

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

| Frequency (MHz) | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power (mW) | Min test separation distance (mm) | Result | Limit (mW/cm <sup>2</sup> ) | SAR Test Exclusion |
|-----------------|--------------------|---------------------|------------------------|-----------------------------------|--------|-----------------------------|--------------------|
| 2412            | 5.02               | 5±1(6)              | 3.981                  | 5                                 | 1.237  | 3.0                         | Pass               |

Note:

PK Output power = conducted power.

Conducted power see the test report HK2509195370-E, antenna gain=1.36dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 1.237 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm