

TEST REPORT

Product Name : Professional audio speaker
Model Number : PARTY12, JPS120W, JPS122W,
JPS125W, JPS135W, JPS7010DSP,
JPS7012DSP, JPS7015DSP,
JPS8010DSP, JPS8012DSP,
JPS8015DSP, JPS8810DSP,
JPS8812DSP, JPS8815DSP
FCC ID : 2BRZL-PARTY12

Prepared for : JUMBOAUDIO ELECTRONICS CO., LTD.
Address : NO. 15 YANGJIA , WANSHIXU VILLAGE, ZHUANGSHI
STREET, ZHENHAI DISTRICT, NINGBO, CHINA

Prepared by : EMTEK (NINGBO) CO., LTD.
Address : BNo. 8, Building 8, Lane 216, Qingyi Road, Ningbo
High-Tech Zone, Ningbo, Zhejiang, China

Tel: +86-574-27907998
Fax: +86-574-27721538

Report Number : ENB2603040220W00201R
Date(s) of Tests : March 04, 2026 to March 27, 2026
Date of issue : March 29, 2026

Table of Contents

1 TEST RESULT CERTIFICATION.....	3
2 EUT TECHNICAL DESCRIPTION	5
3 SUMMARY OF TEST RESULT	6
4 TEST METHODOLOGY.....	7
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
4.2 MEASUREMENT EQUIPMENT USED	7
4.3 DESCRIPTION OF TEST MODES	8
5 FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES.....	9
5.2 EQUIPMENT	9
5.3 LABORATORY ACCREDITATIONS AND LISTINGS.....	9
6 TEST SYSTEM UNCERTAINTY	10
7 SETUP OF EQUIPMENT UNDER TEST	11
7.1 RADIO FREQUENCY TEST SETUP 1	11
7.2 RADIO FREQUENCY TEST SETUP 2	11
7.3 CONDUCTED EMISSION TEST SETUP	13
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	14
7.5 SUPPORT EQUIPMENT	14
8 FREQUENCY HOPPING SYSTEM REQUIREMENTS	15
8.1 Standard Applicable	15
8.2 EUT Pseudorandom Frequency Hopping Sequence.....	15
8.3 Equal Hopping Frequency Use.....	16
8.4 Frequency Hopping System	16
9 TEST REQUIREMENTS.....	17
9.1 20DB&99%BANDWIDTH.....	17
9.2 CARRIER FREQUENCY SEPARATION.....	26
9.3 NUMBER OF HOPPING FREQUENCIES	28
9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME).....	30
9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	32
9.6 CONDUCTED SUPRIOUS EMISSION	36
9.7 RADIATED SPURIOUS EMISSION	51
9.8 CONDUCTED EMISSION TEST.....	69
9.9 ANTENNA APPLICATION	76

1 TEST RESULT CERTIFICATION

Applicant	:	JUMBOAUDIO ELECTRONICS CO., LTD.
Address	:	NO. 15 YANGJIA , WANSHIXU VILLAGE, ZHUANGSHI STREET, ZHENHAI DISTRICT, NINGBO,CHINA
Manufacturer	:	JUMBOAUDIO ELECTRONICS CO., LTD.
Address	:	NO. 15 YANGJIA , WANSHIXU VILLAGE, ZHUANGSHI STREET, ZHENHAI DISTRICT, NINGBO,CHINA
Trade Mark	:	N/A
EUT	:	Professional audio speaker
Model No.	:	PARTY12, JPS120W, JPS122W, JPS125W, JPS135W, JPS7010DSP, JPS7012DSP, JPS7015DSP, JPS8010DSP, JPS8012DSP, JPS8015DSP, JPS8810DSP, JPS8812DSP, JPS8815DSP

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS
IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021) IC RSS-247 Issue 4(07-2025)	PASS

The above equipment was tested by EMTEK(NINGBO) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.247, IC RSS-247 Issue 4 and IC RSS-GEN, Issue 5.

The test results of this report relate only to the tested sample identified in this report

Date of Test : March 04, 2026 to March 22, 2026

Prepared by : WK Luo
WK Luo /Engineer

Reviewer : June Gao
June Gao /Supervisor

Approved & Authorized Signer : Tony Wei
Tony Wei /Manager

Modified History

Version	Report No.	Revision Date	Summary
/	ENB2603040220W00201R	/	Original Report



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product:	Professional audio speaker
Model Number:	PARTY12, JPS120W, JPS122W, JPS125W, JPS135W, JPS7010DSP, JPS7012DSP, JPS7015DSP, JPS8010DSP, JPS8012DSP, JPS8015DSP, JPS8810DSP, JPS8812DSP, JPS8815DSP (Note: All models are only different in appearance, and the schematic design and PCB Layout are the same. We chose PARTY12 for RF test.) PARTY12: The main model has an appearance of a square plastic box with a handle in the middle, and it is equipped with two 12-inch speakers. JPS120W, JPS122W, JPS125W, JPS135W: The appearance of these four models is a curved plastic box with a handle at the rear. Among them, JPS120W has two 10-inch speakers, JPS122W has two 12-inch speakers, JPS125W has two 15-inch speakers, and JPS135W has three 15-inch speakers. JPS7010DSP, JPS7012DSP, JPS7015DSP: The appearance of these three models is similar to the plastic boxes of electric vehicles. Among them, JPS7010DSP has two 10-inch speakers, JPS7012DSP has two 12-inch speakers, and JPS7015DSP has two 15-inch speakers. JPS8010DSP, JPS8012DSP, JPS8015DSP: The appearance of these three models is similar to the RCF-shaped plastic style. Among them, JPS8010DSP has two 10-inch speakers, JPS8012DSP has two 12-inch speakers, and JPS8015DSP has two 15-inch speakers. JPS8810DSP, JPS8812DSP, JPS8815DSP: The three models have a similar appearance to a handle plastic box. Among them, JPS8810DSP has two 10-inch speakers, JPS8812DSP has two 12-inch speakers, and JPS8815DSP has two 15-inch speakers.
Device Type:	Bluetooth V5.0
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 Channels
Antenna Type	PCB Antenna
Antenna Gain:	1.70 dBi
Test Voltage:	AC 100-240V, 50/60Hz
Temperature Range:	0° C ~ +40° C

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	IC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	RSS-247.5.1 RSS-Gen.6.7	Emission Bandwidth	PASS	
15.247(a)(1)	RSS-247.5.1	Carrier Frequency Separation	PASS	
15.247(a)(1)	RSS-247.5.1	Number of Hopping Frequencies	PASS	
15.247(a)(1)	RSS-247.5.1	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	RSS-247.5.4 RSS-Gen 6.12	Maximum Peak Conducted Output Power	PASS	
15.247(d)	RSS-247.5.5	Conducted Spurious Emissions	PASS	
15.247(d) 15.209 15.205	RSS-Gen 8.9 RSS-Gen 8.10 RSS-Gen 6.13 RSS-247.3.3 RSS-247.5.5	Radiated Spurious Emissions	PASS	
15.207	RSS-Gen 8.8	Conducted Emission	PASS	
15.203 15.247(b)	RSS-Gen 6.8 RSS-247.5.4	Antenna Application	PASS	
15.247 (a) (1)/g/h	-	Frequency Hopping System	PASS	
NOTE1: N/A (Not Applicable)				
NOTE2: According to ANSI C63.10-2020, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.				

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **FCC ID:2BRZL-PARTY12** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021)

IC RSS-247 Issue 4(07-2025)

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101384	2026/1/8	1Year
AMN	Rohde & Schwarz	ENV216	101161	2026/1/8	1Year

For Spurious Emissions Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESU 26	100154	2026/1/8	1Year
Pre-Amplifier	Lunar EM	LNA30M3G-25	J10100000070	2026/1/8	1Year
Bilog Antenna	Schwarzbeck	VULB9163	661	2024/5/12	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1177	2024/5/12	2 Year
Pre-Amplifier	SKET	LNPA_0118G-45	SK2019051801	2026/1/8	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2024/5/12	2 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2026/1/8	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2024/5/12	2 Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2026/1/8	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2026/1/8	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2026/1/8	1Year

For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Signal Analyzer	Agilent	N9010A	MY53470879	2026/1/8	1Year
Vector Signal Generator	Agilent	N5182B	MY53050878	2026/1/8	1Year
Analog Signal Generator	Agilent	N5171B	MY53050553	2026/1/8	1Year
RF Control Unit(Power Meter)	Tonscend	JS0806-2	\	2026/1/8	1Year
Temperature&Humidity Chamber	ESPEC	EL-02KA	12107166	2026/1/8	1Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation(DH5); 2Mbps for $\pi/4$ -DQPSK modulation(2DH5); 3Mbps for 8DPSK modulation(3DH5);)were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480
Note: $f_c = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 79					

Test Frequency and channel for Bluetooth

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (NINGBO) CO., LTD.

No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech Zone, Ningbo, Zhejiang, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description
EMC Lab.

: Accredited by CNAS

The Certificate Registration Number is L6666.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Designation by FCC

Designation Number: CN1354

Test Firm Registration Number: 427606

Accredited by A2LA

The Certificate Number is 4321.03.

Accredited by ISED

The Conformity Assessment Body Identifier is CN0114

Name of Firm
Site Location

: EMTEK (NINGBO) CO., LTD.

: No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech Zone, Ningbo, Zhejiang, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Test Parameter	Measurement Uncertainty
Frequency error	$\pm 20\text{Hz}$
Occupied Bandwidth	$\pm 0.5\text{KHz}$
Transmitter output power	$\pm 0.6\text{dB}$
Conducted spurious emissions	$\pm 3.2\text{dB}$
Radiated spurious emissions	$\pm 4.5\text{dB}$
Temperature	$\pm 1.2^{\circ}\text{C}$
Humidity	$\pm 3\%$
DC voltages	$\pm 0.25\text{V}$
Time	$\pm 1\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


8.2 EUT Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB&99%BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-247.5.1 and RSS-Gen.6.7

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) = 100 kHz.

Set Span = approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.

Test Results


Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

20dB Emission Bandwidth

Test Mode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	1.002	2401.466	2402.468	---	---
DH5	Ant1	2441	0.960	2440.502	2441.462	---	---
DH5	Ant1	2480	0.981	2479.481	2480.462	---	---
2DH5	Ant1	2402	1.299	2401.331	2402.630	---	---
2DH5	Ant1	2441	1.302	2440.325	2441.627	---	---
2DH5	Ant1	2480	1.287	2479.337	2480.624	---	---
3DH5	Ant1	2402	1.332	2401.313	2402.645	---	---
3DH5	Ant1	2441	1.293	2440.328	2441.621	---	---
3DH5	Ant1	2480	1.281	2479.319	2480.600	---	---







DH5-Ant1-2402



DH5-Ant1-2441




DH5-Ant1-2480




2DH5-Ant1-2402



2DH5-Ant1-2441




2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441




3DH5-Ant1-2480


Occupied Channel Bandwidth

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.86797	2401.5491	2402.4170	---	---
DH5	Ant1	2441	0.87678	2440.5350	2441.4118	---	---
DH5	Ant1	2480	0.87352	2479.5225	2480.3961	---	---
2DH5	Ant1	2402	1.2039	2401.3761	2402.5800	---	---
2DH5	Ant1	2441	1.2039	2440.3689	2441.5728	---	---
2DH5	Ant1	2480	1.1830	2479.3780	2480.5610	---	---
3DH5	Ant1	2402	1.2111	2401.3784	2402.5895	---	---
3DH5	Ant1	2441	1.1979	2440.3790	2441.5769	---	---
3DH5	Ant1	2480	1.2177	2479.3595	2480.5772	---	---







DH5-Ant1-2402



DH5-Ant1-2441




DH5-Ant1-2480





2DH5-Ant1-2402



2DH5-Ant1-2441



2DH5-Ant1-2480



9.2 CARRIER FREQUENCY SEPARATION

9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

According to IC RSS-247.5.1

9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.2.4 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW = 300kHz. Set VBW = 300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test Results

Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: For GFSK, pi/4-DQPSK, 8DPSK Limit = 20dB bandwidth * 2/3

TestMode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.692	≥0.668	PASS
2DH5	Ant1	Hop	1.024	≥0.868	PASS
3DH5	Ant1	Hop	1.098	≥0.888	PASS



9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

According to IC RSS-247.5.1

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.3.4 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2400-2483.5MHz)

RBW = 300KHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

Test Results


Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A


TestMode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS



DH5-Ant1-Hop-PASS



2DH5-Ant1-Hop-PASS



3DH5-Ant1-Hop-PASS

9.4 AVERAGE TIME OF OCCUPANCY (DWEELL TIME)

9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-247.5.1

9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the averagetime of occupancy on any channel shall not be greater than 0.4s within a period of 0.4smultiplied by the number of hopping channels employed.

9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.4.4 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW $\geq$ RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subpara graphs of this Section.

9.4.5 Test Results

Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: Total Hops(DH5)=(1600/6/79)*31.6


Total Hops(2DH5)=(1596/6/79)*31.6

Total Hops(3DH5)=(1602/6/79)*31.6


Dwell Time=Burst Width*Total Hops

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:


TestMode	Antenna	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH5	Ant1	Hop	2.889	106.67	0.308	≤ 0.4	PASS
2DH5	Ant1	Hop	2.885	106.67	0.308	≤ 0.4	PASS
3DH5	Ant1	Hop	2.887	106.67	0.308	≤ 0.4	PASS



DH5-Ant1-Hop-PASS



2DH5-Ant1-Hop-PASS



3DH5-Ant1-Hop-PASS

9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

According to IC RSS-247.5.4 and RSS-Gen 6.12

9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.5.4 Test Procedure

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel(about 8MHz)

Set RBW > the 20 dB bandwidth of the emission being measured(about 3MHz)

Set VBW ≥ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

Test Results

Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	4.89	≤20.97	PASS
DH5	Ant1	2441	3.36	≤20.97	PASS
DH5	Ant1	2480	2.04	≤20.97	PASS
2DH5	Ant1	2402	4.82	≤20.97	PASS
2DH5	Ant1	2441	3.23	≤20.97	PASS
2DH5	Ant1	2480	1.94	≤20.97	PASS
3DH5	Ant1	2402	5.34	≤20.97	PASS
3DH5	Ant1	2441	3.45	≤20.97	PASS
3DH5	Ant1	2480	2.26	≤20.97	PASS




DH5-Ant1-2402-PASS




DH5-Ant1-2441-PASS




DH5-Ant1-2480-PASS




2DH5-Ant1-2402-PASS



2DH5-Ant1-2441-PASS



2DH5-Ant1-2480-PASS



3DH5-Ant1-2402-PASS



3DH5-Ant1-2441-PASS



3DH5-Ant1-2480-PASS

9.6 CONDUCTED SUPRIIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-247.5.5

9.6.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximumconducetedlevel.

Note that the channel found to contain the maximum conduceted level can be used to establish the reference level.

■ Band-edge measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW $\geq 1\%$ of the span=100kHzSet VBW $\geq 3 \times$ RBW

Set Sweep = autoSet Detector function = peakSet Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz).Set RBW = 100 kHzSet VBW $\geq$ RBW

Set Sweep = autoSet Detector function = peakSet Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.

9.6.5 Test Results

Temperature:	25°C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

■ Reference level measurement

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
DH5	Ant1	2402	2401.83	4.27
DH5	Ant1	2441	2441.14	2.46
DH5	Ant1	2480	2479.82	1.09
2DH5	Ant1	2402	2401.80	3.77
2DH5	Ant1	2441	2440.82	2.54
2DH5	Ant1	2480	2479.81	1.11
3DH5	Ant1	2402	2402.00	3.28
3DH5	Ant1	2441	2440.82	2.55
3DH5	Ant1	2480	2479.80	1.07

■ Band-edge measurement

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	4.27	-43.97	≤-15.73	PASS
DH5	Ant1	High	2480	1.09	-47.51	≤-18.91	PASS
DH5	Ant1	Low	Hop 2402	1.98	-45.23	≤-18.02	PASS
DH5	Ant1	High	Hop 2480	1.38	-45.2	≤-18.62	PASS
2DH5	Ant1	Low	2402	3.77	-45.97	≤-16.23	PASS
2DH5	Ant1	High	2480	1.11	-47.86	≤-18.89	PASS
2DH5	Ant1	Low	Hop 2402	-2.08	-48.64	≤-22.08	PASS
2DH5	Ant1	High	Hop 2480	-5.77	-46.78	≤-25.77	PASS
3DH5	Ant1	Low	2402	3.28	-46.42	≤-16.72	PASS
3DH5	Ant1	High	2480	1.07	-48.27	≤-18.93	PASS
3DH5	Ant1	Low	Hop 2402	-3.17	-46.3	≤-23.17	PASS
3DH5	Ant1	High	Hop 2480	-5.48	-48.44	≤-25.48	PASS

■ Emission level measurement

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	30~1000	4.27	-45.5	≤-15.73	PASS
DH5	Ant1	2402	1000~26500	4.27	-43	≤-15.73	PASS
DH5	Ant1	2441	30~1000	2.46	-46.39	≤-17.54	PASS
DH5	Ant1	2441	1000~26500	2.46	-43.68	≤-17.54	PASS
DH5	Ant1	2480	30~1000	1.09	-47.53	≤-18.91	PASS
DH5	Ant1	2480	1000~26500	1.09	-45.21	≤-18.91	PASS
2DH5	Ant1	2402	30~1000	3.77	-50.38	≤-16.23	PASS
2DH5	Ant1	2402	1000~26500	3.77	-43.45	≤-16.23	PASS
2DH5	Ant1	2441	30~1000	2.54	-48.11	≤-17.46	PASS
2DH5	Ant1	2441	1000~26500	2.54	-45.23	≤-17.46	PASS
2DH5	Ant1	2480	30~1000	1.11	-52.69	≤-18.89	PASS
2DH5	Ant1	2480	1000~26500	1.11	-45.72	≤-18.89	PASS
3DH5	Ant1	2402	30~1000	3.28	-49.52	≤-16.72	PASS
3DH5	Ant1	2402	1000~26500	3.28	-44.5	≤-16.72	PASS
3DH5	Ant1	2441	30~1000	2.55	-47.35	≤-17.45	PASS
3DH5	Ant1	2441	1000~26500	2.55	-45.49	≤-17.45	PASS
3DH5	Ant1	2480	30~1000	1.07	-49.65	≤-18.93	PASS
3DH5	Ant1	2480	1000~26500	1.07	-46.5	≤-18.93	PASS

■ Reference level measurement




DH5-Ant1-2402-PASS



DH5-Ant1-2441-PASS




DH5-Ant1-2480-PASS



2DH5-Ant1-2402-PASS



2DH5-Ant1-2441-PASS



2DH5-Ant1-2480-PASS



3DH5-Ant1-2402-PASS





3DH5-Ant1-2441-PASS




3DH5-Ant1-2480-PASS

■ Band-edge measurement







DH5-Ant1-Hop 2480-PASS




2DH5-Ant1-2402-PASS



2DH5-Ant1-2480-PASS






2DH5-Ant1-Hop_2402-PASS




2DH5-Ant1-Hop_2480-PASS




3DH5-Ant1-2402-PASS




■ Emission level measurement




DH5-Ant1-2402-30~1000-PASS




DH5-Ant1-2402-1000~26500-PASS




DH5-Ant1-2441-30~1000-PASS




DH5-Ant1-2441-1000~26500-PASS




DH5-Ant1-2480-30~1000-PASS




DH5-Ant1-2480-1000~26500-PASS




2DH5-Ant1-2402-30~1000-PASS




2DH5-Ant1-2402-1000~26500-PASS




2DH5-Ant1-2441-30~1000-PASS






2DH5-Ant1-2441-1000~26500-PASS



2DH5-Ant1-2480-30~1000-PASS




2DH5-Ant1-2480-1000~26500-PASS






3DH5-Ant1-2441-1000~26500-PASS



3DH5-Ant1-2480-30~1000-PASS



3DH5-Ant1-2480-1000~26500-PASS

9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-Gen and RSS-247

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);


Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 02:50:47




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4803.500	67.94	-8.8	59.14	74.00	14.86	PK+	H	PASS
2	4803.500	58.02	-8.8	49.22	54.00	4.78	AVG	H	PASS
3	7602.000	44.55	-0.06	44.49	74.00	29.51	PK+	H	PASS
4	7602.000	34.70	-0.06	34.64	54.00	19.36	AVG	H	PASS
5	17907.000	43.41	12.53	55.94	74.00	18.06	PK+	H	PASS
6	17907.000	33.55	12.53	46.08	54.00	7.92	AVG	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 02:53:36




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4804.000	64.82	-8.8	56.02	74.00	17.98	PK+	V	PASS
2	4804.000	55.63	-8.8	46.83	54.00	7.17	AVG	V	PASS
3	7206.000	46.48	-0.56	45.92	74.00	28.08	PK+	V	PASS
4	7206.000	36.72	-0.56	36.16	54.00	17.84	AVG	V	PASS
5	17823.500	43.00	11.93	54.93	74.00	19.07	PK+	V	PASS
6	17823.500	33.05	11.93	44.98	54.00	9.02	AVG	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 02:57:19




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4882.500	58.07	-8.2	49.87	74.00	24.13	PK+	V	PASS
2	4882.500	47.65	-8.2	39.45	54.00	14.55	AVG	V	PASS
3	7323.000	43.94	-0.37	43.57	74.00	30.43	PK+	V	PASS
4	7323.000	34.01	-0.37	33.64	54.00	20.36	AVG	V	PASS
5	17989.500	42.65	13.53	56.18	74.00	17.82	PK+	V	PASS
6	17989.500	32.84	13.53	46.37	54.00	7.63	AVG	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 03:00:26




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4882.500	60.22	-8.2	52.02	74.00	21.98	PK+	H	PASS
2	4882.500	50.38	-8.2	42.18	54.00	11.82	AVG	H	PASS
3	7323.000	46.17	-0.37	45.80	74.00	28.20	PK+	H	PASS
4	7323.000	36.04	-0.37	35.67	54.00	18.33	AVG	H	PASS
5	17942.000	42.41	12.95	55.36	74.00	18.64	PK+	H	PASS
6	17942.000	33.01	12.95	45.96	54.00	8.04	AVG	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for 3DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 03:04:10




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4959.500	54.99	-7.42	47.57	74.00	26.43	PK+	H	PASS
2	4959.500	44.77	-7.42	37.35	54.00	16.65	AVG	H	PASS
3	7440.000	45.00	-0.13	44.87	74.00	29.13	PK+	H	PASS
4	7440.000	34.95	-0.13	34.82	54.00	19.18	AVG	H	PASS
5	17797.500	43.44	11.75	55.19	74.00	18.81	PK+	H	PASS
6	17797.500	33.77	11.75	45.52	54.00	8.48	AVG	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 03:06:52



Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	4960.000	52.44	-7.41	45.03	74.00	28.97	PK+	V	PASS
2	4960.000	42.60	-7.41	35.19	54.00	18.81	AVG	V	PASS
3	7440.000	44.45	-0.13	44.32	74.00	29.68	PK+	V	PASS
4	7440.000	34.85	-0.13	34.72	54.00	19.28	AVG	V	PASS
5	17925.000	42.19	12.75	54.94	74.00	19.06	PK+	V	PASS
6	17925.000	32.43	12.75	45.18	54.00	8.82	AVG	V	PASS


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (5)The test frequency range, 18GHz~25GHz test result on peak is lower than average limit, all is the noise base, therefore no data appear in the report.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst(8DPSK) result recorded was report as below:

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for 3DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 02:43:12




Final_Result

(Margin=Limit-Meas.(Reading + Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2354.300	28.10	29.99	58.09	74.00	15.91	PK+	V	PASS
2	2354.300	18.19	29.99	48.18	54.00	5.82	AVG	V	PASS
3	2390.000	26.52	30.06	56.58	74.00	17.42	PK+	V	PASS
4	2390.000	16.31	30.06	46.37	54.00	7.63	AVG	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for 3DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 02:44:35




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBµV/m)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2378.300	28.31	30.05	58.36	74.00	15.64	PK+	H	PASS
2	2378.300	18.38	30.05	48.43	54.00	5.57	AVG	H	PASS
3	2390.000	25.58	30.06	55.64	74.00	18.36	PK+	H	PASS
4	2390.000	15.68	30.06	45.74	54.00	8.26	AVG	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for 3DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 03:09:18




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2483.500	26.43	30.34	56.77	74.00	17.23	PK+	V	PASS
2	2483.500	16.18	30.34	46.52	54.00	7.48	AVG	V	PASS
3	2488.500	28.85	30.36	59.21	74.00	14.79	PK+	V	PASS
4	2488.500	19.01	30.36	49.37	54.00	4.63	AVG	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for 3DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-23 03:10:44



Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2483.500	26.32	30.34	56.66	74.00	17.34	PK+	H	PASS
2	2483.500	16.43	30.34	46.77	54.00	7.23	AVG	H	PASS
3	2499.100	27.28	30.39	57.67	74.00	16.33	PK+	H	PASS
4	2499.100	17.46	30.39	47.85	54.00	6.15	AVG	H	PASS


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission below 1GHz(30MHz to 1GHz)

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) for 2402 MHz result recorded was report as below:

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 03:45:29




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	39.797	60.98	-24.58	36.40	40.00	3.60	QPK	H	PASS
2	47.460	60.83	-24.11	36.72	40.00	3.28	QPK	H	PASS
3	331.379	53.50	-20.89	32.61	46.00	13.39	QPK	H	PASS
4	353.945	55.65	-20.63	35.02	46.00	10.98	QPK	H	PASS
5	395.205	55.22	-20.47	34.75	46.00	11.25	QPK	H	PASS
6	658.560	46.14	-15.05	31.09	46.00	14.91	QPK	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 03:41:43




Final Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	33.201	58.51	-25.11	33.40	40.00	6.60	QPK	V	PASS
2	40.445	60.72	-24.51	36.21	40.00	3.79	QPK	V	PASS
3	79.858	63.53	-26.92	36.61	40.00	3.39	QPK	V	PASS
4	263.576	56.05	-22.76	33.29	46.00	12.71	QPK	V	PASS
5	289.766	58.06	-22.5	35.56	46.00	10.44	QPK	V	PASS
6	353.980	48.24	-20.63	27.61	46.00	18.39	QPK	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 03:55:07




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	40.185	60.14	-24.54	35.60	40.00	4.40	QPK	H	PASS
2	47.757	60.71	-24.11	36.60	40.00	3.40	QPK	H	PASS
3	308.778	52.45	-21.88	30.57	46.00	15.43	QPK	H	PASS
4	331.379	52.69	-20.89	31.80	46.00	14.20	QPK	H	PASS
5	353.980	53.96	-20.63	33.33	46.00	12.67	QPK	H	PASS
6	658.657	46.67	-15.05	31.62	46.00	14.38	QPK	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 03:50:46




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	33.589	60.64	-25.08	35.56	40.00	4.44	QPK	V	PASS
2	40.610	61.57	-24.5	37.07	40.00	2.93	QPK	V	PASS
3	47.557	60.89	-24.11	36.78	40.00	3.22	QPK	V	PASS
4	79.858	63.10	-26.92	36.18	40.00	3.82	QPK	V	PASS
5	237.078	58.29	-23.41	34.88	46.00	11.12	QPK	V	PASS
6	289.863	58.96	-22.5	36.46	46.00	9.54	QPK	V	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 04:25:38




Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	40.767	60.18	-24.48	35.70	40.00	4.30	QPK	H	PASS
2	47.169	58.21	-24.1	34.11	40.00	5.89	QPK	H	PASS
3	237.095	56.05	-23.41	32.64	46.00	13.36	QPK	H	PASS
4	331.379	52.44	-20.89	31.55	46.00	14.45	QPK	H	PASS
5	342.534	52.80	-20.75	32.05	46.00	13.95	QPK	H	PASS
6	353.980	52.71	-20.63	32.08	46.00	13.92	QPK	H	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-21 04:19:32



Final_Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV/m)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	33.104	58.58	-25.12	33.46	40.00	6.54	QPK	V	PASS
2	40.379	60.11	-24.52	35.59	40.00	4.41	QPK	V	PASS
3	45.617	58.39	-24.07	34.32	40.00	5.68	QPK	V	PASS
4	47.751	58.90	-24.11	34.79	40.00	5.21	QPK	V	PASS
5	78.694	61.36	-26.94	34.42	40.00	5.58	QPK	V	PASS
6	289.766	57.46	-22.5	34.96	46.00	11.04	QPK	V	PASS

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207
According to IC RSS-Gen 8.8

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

9.8.4 Test Procedure


The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

All the modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-22 01:48:11




Final Result (Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.268	18.53	10.41	28.94	61.18	32.24	QPK	L1	GND	PASS
2	0.268	11.30	10.41	21.71	51.18	29.47	AVG	L1	GND	PASS
3	26.106	26.13	11.34	37.47	60.00	22.53	QPK	L1	GND	PASS
4	26.106	24.08	11.34	35.42	50.00	14.58	AVG	L1	GND	PASS
5	26.567	26.34	11.37	37.71	60.00	22.29	QPK	L1	GND	PASS
6	26.567	24.59	11.37	35.96	50.00	14.04	AVG	L1	GND	PASS
7	27.453	27.06	11.43	38.49	60.00	21.51	QPK	L1	GND	PASS
8	27.453	23.89	11.43	35.32	50.00	14.68	AVG	L1	GND	PASS
9	27.906	26.18	11.46	37.64	60.00	22.36	QPK	L1	GND	PASS
10	27.906	24.86	11.46	36.32	50.00	13.68	AVG	L1	GND	PASS
11	28.362	26.29	11.49	37.78	60.00	22.22	QPK	L1	GND	PASS
12	28.362	23.92	11.49	35.41	50.00	14.59	AVG	L1	GND	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2402MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-22 01:53:28




Final_Result (Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.268	19.72	10.37	30.09	61.18	31.09	QPK	N	GND	PASS
2	0.268	12.59	10.37	22.96	51.18	28.22	AVG	N	GND	PASS
3	26.097	24.82	11.26	36.08	60.00	23.92	QPK	N	GND	PASS
4	26.097	21.44	11.26	32.70	50.00	17.30	AVG	N	GND	PASS
5	26.554	24.82	11.29	36.11	60.00	23.89	QPK	N	GND	PASS
6	26.554	22.97	11.29	34.26	50.00	15.74	AVG	N	GND	PASS
7	27.440	25.70	11.34	37.04	60.00	22.96	QPK	N	GND	PASS
8	27.440	22.22	11.34	33.56	50.00	16.44	AVG	N	GND	PASS
9	27.897	26.51	11.37	37.88	60.00	22.12	QPK	N	GND	PASS
10	27.897	23.34	11.37	34.71	50.00	15.29	AVG	N	GND	PASS
11	28.340	25.06	11.4	36.46	60.00	23.54	QPK	N	GND	PASS
12	28.340	23.81	11.4	35.21	50.00	14.79	AVG	N	GND	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No. :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-22 01:59:42




Final_Result (Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.270	19.64	10.37	30.01	61.12	31.11	QPK	N	GND	PASS
2	0.270	12.54	10.37	22.91	51.12	28.21	AVG	N	GND	PASS
3	0.273	19.24	10.37	29.61	61.03	31.42	QPK	N	GND	PASS
4	0.273	11.13	10.37	21.50	51.03	29.53	AVG	N	GND	PASS
5	25.627	24.74	11.25	35.99	60.00	24.01	QPK	N	GND	PASS
6	25.627	22.28	11.25	33.53	50.00	16.47	AVG	N	GND	PASS
7	26.079	24.29	11.26	35.55	60.00	24.45	QPK	N	GND	PASS
8	26.079	21.86	11.26	33.12	50.00	16.88	AVG	N	GND	PASS
9	26.527	25.02	11.29	36.31	60.00	23.69	QPK	N	GND	PASS
10	26.527	22.44	11.29	33.73	50.00	16.27	AVG	N	GND	PASS
11	26.979	24.08	11.32	35.40	60.00	24.60	QPK	N	GND	PASS
12	26.979	21.19	11.32	32.51	50.00	17.49	AVG	N	GND	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2441MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%


DateTime:2026-03-22 02:08:24

**Final_Result** (Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.268	18.46	10.41	28.87	61.18	32.31	QPK	L1	GND	PASS
2	0.268	11.69	10.41	22.10	51.18	29.08	AVG	L1	GND	PASS
3	26.513	24.71	11.37	36.08	60.00	23.92	QPK	L1	GND	PASS
4	26.513	21.53	11.37	32.90	50.00	17.10	AVG	L1	GND	PASS
5	26.952	25.32	11.4	36.72	60.00	23.28	QPK	L1	GND	PASS
6	26.952	21.52	11.4	32.92	50.00	17.08	AVG	L1	GND	PASS
7	27.409	24.15	11.43	35.58	60.00	24.42	QPK	L1	GND	PASS
8	27.409	20.46	11.43	31.89	50.00	18.11	AVG	L1	GND	PASS
9	27.848	24.64	11.45	36.09	60.00	23.91	QPK	L1	GND	PASS
10	27.848	21.10	11.45	32.55	50.00	17.45	AVG	L1	GND	PASS
11	28.318	25.48	11.49	36.97	60.00	23.03	QPK	L1	GND	PASS
12	28.318	19.37	11.49	30.86	50.00	19.14	AVG	L1	GND	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-22 02:17:03




Final Result

(Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.266	18.57	10.41	28.98	61.24	32.26	QPK	L1	GND	PASS
2	0.266	11.39	10.41	21.80	51.24	29.44	AVG	L1	GND	PASS
3	0.266	18.60	10.41	29.01	61.24	32.23	QPK	L1	GND	PASS
4	0.266	11.40	10.41	21.81	51.24	29.43	AVG	L1	GND	PASS
5	26.496	25.08	11.36	36.44	60.00	23.56	QPK	L1	GND	PASS
6	26.496	20.87	11.36	32.23	50.00	17.77	AVG	L1	GND	PASS
7	26.943	25.05	11.4	36.45	60.00	23.55	QPK	L1	GND	PASS
8	26.943	21.92	11.4	33.32	50.00	16.68	AVG	L1	GND	PASS
9	27.396	24.59	11.43	36.02	60.00	23.98	QPK	L1	GND	PASS
10	27.396	20.88	11.43	32.31	50.00	17.69	AVG	L1	GND	PASS
11	27.843	24.54	11.45	35.99	60.00	24.01	QPK	L1	GND	PASS
12	27.843	21.43	11.45	32.88	50.00	17.12	AVG	L1	GND	PASS
13	28.291	23.83	11.49	35.32	60.00	24.68	QPK	L1	GND	PASS
14	28.291	21.25	11.49	32.74	50.00	17.26	AVG	L1	GND	PASS

Project No. :	ENB2603040220W002	Customer :	JUMBOAUDIO
Sample No :	ENB2603040220W002-1-1	EUT :	Professional audio speaker
Model :	PARTY12	Mode :	TX 2480MHz for DH5
Voltage :	AC 100-240V, 50/60Hz	Engineer :	WK Luo
Temp :	16°C	Humi :	47%

DateTime:2026-03-22 02:22:01



Final_Result (Margin=Limit-Meas.(Reading +Corr.))

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE	Verdict
1	0.264	20.46	10.37	30.83	61.30	30.47	QPK	N	GND	PASS
2	0.264	12.21	10.37	22.58	51.30	28.72	AVG	N	GND	PASS
3	26.030	24.86	11.26	36.12	60.00	23.88	QPK	N	GND	PASS
4	26.030	22.06	11.26	33.32	50.00	16.68	AVG	N	GND	PASS
5	26.487	25.09	11.29	36.38	60.00	23.62	QPK	N	GND	PASS
6	26.487	21.82	11.29	33.11	50.00	16.89	AVG	N	GND	PASS
7	26.930	25.62	11.32	36.94	60.00	23.06	QPK	N	GND	PASS
8	26.930	22.13	11.32	33.45	50.00	16.55	AVG	N	GND	PASS
9	27.378	25.53	11.34	36.87	60.00	23.13	QPK	N	GND	PASS
10	27.378	23.04	11.34	34.38	50.00	15.62	AVG	N	GND	PASS
11	28.282	26.40	11.39	37.79	60.00	22.21	QPK	N	GND	PASS
12	28.282	22.33	11.39	33.72	50.00	16.28	AVG	N	GND	PASS

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC 47 CFR Part 15.247 (b)	If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.
RSS-247 Section 5.4	If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

9.9.2 Result

PASS.

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached documentInternal Photos to show the antenna connector.

*** End of Report ***