

FCC PART 15.247

TEST REPORT

For

Ningbo Betta Technology Co., Ltd.

3rd Floor, Building 1, No. 211 Xingguang Road High-tech Zone Ningbo City, Zhejiang Province, China

FCC ID: 2BS32-BETTANEO25

Report Type: Original Report	Product Name: Betta Neo
Report Number:	RKSA260120001-00A
Report Date:	2026-04-30
Reviewed By:	Bard Liu 
Approved By:	Kyle Xu 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.bac corp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS.....	16
APPLICABLE STANDARD	16
TEST SYSTEM SETUP.....	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
TEST RESULTS SUMMARY.....	17
TEST DATA: SEE APPENDIX	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
TEST SYSTEM SETUP.....	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	20
TEST RESULTS SUMMARY.....	20
TEST DATA: SEE APPENDIX	20
FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA: SEE APPENDIX	21
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA: SEE APPENDIX	22
FCC §15.247(D) - 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE & CONDUCTED SPURIOUS EMISSION	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA: SEE APPENDIX	24

FCC §15.247(E) - POWER SPECTRAL DENSITY	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA: SEE APPENDIX	25
APPENDIX - TEST DATA	26
AC LINE CONDUCTED EMISSIONS	26
SPURIOUS EMISSIONS.....	29
6 DB EMISSION BANDWIDTH	36
MAXIMUM CONDUCTED OUTPUT POWER.....	37
100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	38
CONDUCTED SPURIOUS EMISSION.....	39
POWER SPECTRAL DENSITY	40
EUT PHOTOGRAPHS	41
TEST SETUP PHOTOGRAPHS	42

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA260120001-00A	R1V1	2026-04-30	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Ningbo Betta Technology Co. ,Ltd.
Product Name:	Betta Neo
Tested Model:	BETTANEO25
Power Supply:	DC 10V from adapter & DC 7.3V from battery & 0V-10V from charged via solar
RF Function:	LORA
Operating Band/Frequency:	915 MHz
Maximum Peak Output Power:	13.02 dBm
Channel Number:	1
Modulation Type:	CSS
Antenna Type:	Spring Antenna
★Maximum Antenna Gain:	-4.04 dBi

Adapter Information:

Model: SAW12J-100-1000U

Input: AC 100-240V~50/60Hz, 0.5A

Output: DC 10V, 1000mA

Note: The maximum antenna gain was provided by the applicant.

All measurement and test data in this report was gathered from production sample serial number: RKSA260120001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2026-01-20.)

Objective

This report is prepared for *Ningbo Betta Technology Co. ,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list as below:

Channel	Frequency (MHz)
1	915

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The system was configured for testing in an engineering mode, which was provided by manufacturer.



Mode	Frequency (MHz)	★Power Level
LORA	915	Default

Note: The power level was declared by the applicant.

Environmental Conditions & Test Information

Test Date:	2026-02-11
Temperature:	18.5 °C
Relative Humidity:	41 %
ATM Pressure:	102.9 kPa
Test Engineer:	Neil Zhou

Test Mode	Channel (MHz)	Duty Cycle (%)	Ton(ms)	Ton+off(ms)	10log(1/x) (dB)
LORA	915	4.647	4.647	100	13.33

Duty Cycle:**Note:**

1. "x" means the Duty Cycle.
2. Offset (10.5dB) = Attenuator (10dB) + cable loss (0.5dB)

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Power strip	/	/

External I/O Cable


Cable Description	Length(m)	From Port	To Port
Power Cable 1	1.0	Power strip	AC Source/LISN
Power Cable 2	1.0	EUT	Adapter

Block Diagram of Test Setup


For conducted emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge & Conducted spurious emission	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2026-03-13	2027-03-12
Sunol Sciences	Hybrid Antenna	JB3	A090314-1	2024-11-08	2027-11-07
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Sonoma Instrument	Amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-8	008	2026-03-13	2027-03-12
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2026-03-13	2027-03-12
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2026-03-13	2027-03-12
Narda	6dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
Microtronics	High-pass filter	BRC50722	G013	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2026-03-16	2027-03-15
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2023-06-27	2026-06-26
A.H.Systems, inc	Amplifier	PAM-0118P	512	2026-03-16	2027-03-15
Narda	Attenuator	10dB	010	2026-03-13	2027-03-12
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-11	011	2026-03-16	2027-03-15
MICRO-COAX	Coaxial Cable	Cable-12	012	2026-03-16	2027-03-15
MICRO-COAX	Coaxial Cable	Cable-13	013	2026-03-16	2027-03-15
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2026-03-16	2027-03-15
N/A	Attenuator	10 dB	N/A	2025-04-09	2026-04-08
N/A	Attenuator	10 dB	N/A	2026-03-13	2027-03-12
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	101746	2025-04-09	2026-04-08
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	0357.8810.54	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-08	2026-04-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
LORA	915	-4.04	0.39	13.5	22.39	20	0.0018	0.61

Note:

1. For the above tune up power were declared by the manufacturer.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a Spring antenna for LORA and the antenna gain is -4.04 dBi, the antenna permanently attached to EUT. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz - 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2020 clause 6.2

During the conducted emission test, the EUT or adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


Test System Setup

9 kHz - 30 MHz:



30 MHz - 1 GHz:



1 GHz - 10 GHz:

Note: The antenna of the EUT located at a height of 1.5 m above the floor.

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement	Detector
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	Peak/QP/Average	Peak/QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	Peak/QP/Average	Peak/QP/Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
Above 1GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Test Procedure

According to ANSI C63.10-2020 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz - 1GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.8.1

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “–6 dB down amplitude”. If a marker is below this “–6 dB down amplitude” value, then it shall be as close as possible to this value.



Note: Offset (10.5dB) = Attenuator (10dB) + cable loss (0.5dB)

Test Data: See Appendix

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10:2020 sub-clause 11.9.1.1

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq [3 \times \text{RBW}]$.
- c) Set span $\geq [3 \times \text{RBW}]$.
- d) Sweep time = No faster than coupled (auto) time.
- e) Detector = peak.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



Note: Offset (10.5dB) = Attenuator (10dB) + cable loss (0.5dB)

Test Data: See Appendix

FCC §15.247(D) - 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE & CONDUCTED SPURIOUS EMISSION


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + cable loss (0.5dB)

Conducted Spurious Emission

Applicable Standard


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Note: Offset (11dB) = Attenuator (10dB) + Cable Loss (1.0dB)

Test Data: See Appendix

FCC §15.247(E) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 * \text{RBW}$.
3. Set the span > 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Note: Offset (10.5dB) = Attenuator (10dB) + cable loss (0.5dB)


Test Data: See Appendix

APPENDIX - TEST DATA

AC LINE CONDUCTED EMISSIONS


Environmental Conditions & Test Information

Test Date:	2026-02-06
Temperature:	15.6 °C
Relative Humidity:	42 %
ATM Pressure:	102.8 kPa
Test Result:	Pass
Test Engineer:	Jack He

EUT operation mode: Transmitting

Site : CE
Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Line
: DET:Peak
Project No. : RKSA260120001
Model : BETTANEO25
Phase : L
Voltage : 120V/60Hz
Mode : Transmitting
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 15.6°C
Humidity : 42%
Atmospheric pressure: 102.8kPa
Test Engineer : Jack He
Check by : Bard Liu

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.158	19.96	20.42	40.38	65.59	-25.21	Peak
2	0.214	16.68	20.45	37.13	63.06	-25.93	Peak
3	0.260	15.01	20.40	35.41	61.45	-26.04	Peak
4	0.421	14.14	20.29	34.43	57.43	-23.00	Peak
5	13.717	18.50	20.25	38.75	60.00	-21.25	Peak
6	22.357	13.29	20.58	33.87	60.00	-26.13	Peak



Site : CE
Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Neutral
: DET:Peak
Project No. : RKSA260120001
Model : BETTANE025
Phase : N
Voltage : 120V/60Hz
Mode : Transmitting
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 15.6℃
Humidity : 42%
Atmospheric pressure: 102.8kPa
Test Engineer : Jack He
Check by : Bard Liu

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.179	20.58	20.41	40.99	64.55	-23.56	Peak
2	0.400	17.88	20.31	38.19	57.84	-19.65	Peak
3	1.385	17.05	20.22	37.27	56.00	-18.73	Peak
4	2.825	15.96	20.25	36.21	56.00	-19.79	Peak
5	13.514	19.47	20.25	39.72	60.00	-20.28	Peak
6	22.135	14.13	20.59	34.72	60.00	-25.28	Peak

SPURIOUS EMISSIONS


Environmental Conditions & Test Information

Test Item:	SPURIOUS EMISSIONS		
	9kHz - 30MHz	30MHz - 1GHz	1 GHz - 10 GHz
Test Date:	2026-02-09~2026-04-29	2026-02-09~2026-04-02	2026-04-27
Temperature:	16.8 ~19.6°C	16.8~20.6 °C	20.1 °C
Relative Humidity:	39~43 %	43~49 %	50 %
ATM Pressure:	102.2~102.4 kPa	101.7~102.8 kPa	101.5 kPa
Test Result:	Pass	Pass	Pass
Test Engineer:	Scarf Yang	Scarf Yang	Destine Hu


EUT operation mode: Transmitting

9kHz~30MHz:
Adapter charging
Parallel(worst case)

9kHz~150kHz



150kHz~30MHz



9 kHz~150 kHz


Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.028740	46.48	PK	-0.60	118.43	71.95
0.061170	52.82	PK	-5.11	111.87	59.05
0.067938	50.96	PK	-5.90	110.96	60
0.122646	36.55	PK	-10.17	105.83	69.28

150 kHz~30 MHz

Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.150000	50.97	PK	-11.34	104.08	53.11
1.284300	43.67	PK	-28.55	65.43	21.76
4.388700	37.51	PK	-31.97	69.54	32.03
17.164500	30.81	PK	-33.15	69.54	38.73


9kHz~30MHz:
solar battery charging
Parallel(worst case)

9kHz~150kHz



Project No.RKSA260120001
Date: 29.APR.2026 19:05:34
Tester:Scarf Yang

150kHz~30MHz



Project No.RKSA260120001
Date: 29.APR.2026 19:12:50
Tester:Scarf Yang

9 kHz~150 kHz

Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.020280	48.03	PK	-0.56	121.46	73.43
0.032688	46.01	PK	-1.04	117.32	71.31
0.039174	44.34	PK	-2.08	110.96	66.62
0.041712	43.88	PK	-2.48	115.20	71.32

150 kHz~30 MHz

Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.150000	47.59	PK	-11.34	104.08	56.49
1.045500	41.80	PK	-27.76	67.22	25.42
4.388700	36.42	PK	-31.97	69.54	33.12
6.299100	32.16	PK	-32.26	69.54	37.38


30MHz - 1GHz Adapter charging

Channel: 915 MHz

Common Information

Project No: RKSA260120001
 EUT Model: BETTANEO25
 Test Mode: LORA
 Standard: FCC Part 15.247
 Test Equipment: ESCI, JB3, 310N
 Receiver Setting: RBW:100 kHz, VBW: 300 kHz, Sweep Time: Auto
 Temperature: 16.8°C
 Humidity: 43%
 Barometric Pressure: 102.8kPa
 Test Engineer: Scarf Yang
 Check Engineer: Hardy Huang
 Test Date: 2026/2/9

LORA Fundamental




Final Result

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
33.758750	24.68	40.00	15.32	V	-6.7
163.981250	32.76	43.50	10.74	V	-12.3
227.152500	34.27	46.00	11.73	H	-13.1
237.216250	35.20	46.00	10.80	H	-12.5
308.026250	33.34	46.00	12.66	H	-10.1
380.048750	33.92	46.00	12.08	H	-8.5

30MHz - 1GHz
solar battery charging**Channel: 915 MHz****Common Information**

Project No: RKSA260120001
EUT Model: BETTANEO25
Test Mode: LORA
Standard: FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW:100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 20.6°C
Humidity: 49%
Barometric Pressure: 101.7kPa
Test Engineer: Scarf Yang
Check Engineer: Bard Liu
Test Date: 2026/4/2

LORA Fundamental


**Final Result**

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
83.471250	25.05	40.00	14.95	V	-17.1
160.707500	33.18	43.50	10.32	H	-12.2
174.287500	30.84	43.50	12.66	H	-12.8
222.181250	32.64	46.00	13.36	H	-13.3
255.282500	34.04	46.00	11.96	H	-12.1
289.232500	34.26	46.00	11.74	H	-10.3

1GHz - 10GHz:**915 MHz****Common Information**

Project No.: RKSA260120001
EUT Model: BETTANEO25
Test Mode: LoRa
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1°C
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1830.250000	---	40.07	54.00	13.93	H	-12.5
1830.250000	40.90	---	74.00	33.10	H	-12.5
3660.400000	---	44.96	54.00	9.04	H	-5.8
3660.400000	46.00	---	74.00	28.00	H	-5.8
4573.900000	45.00	---	74.00	29.00	V	-4.2
4573.900000	---	42.25	54.00	11.75	V	-4.2
6403.600000	---	44.03	54.00	9.97	V	-0.7
6403.600000	46.90	---	74.00	27.10	V	-0.7
8477.200000	---	44.24	54.00	9.76	V	4.7
8477.200000	52.20	---	74.00	21.80	V	4.7
9784.000000	47.62	---	74.00	26.38	V	5.7
9784.000000	---	45.81	54.00	8.19	V	5.7

6 dB EMISSION BANDWIDTH


Environmental Conditions & Test Information

Test Date:	2026-02-11
Temperature:	18.5 °C
Relative Humidity:	41 %
ATM Pressure:	102.9 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting

Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
915	0.583	≥ 0.5

915 MHz



MAXIMUM CONDUCTED OUTPUT POWER


Environmental Conditions & Test Information

Test Date:	2026-02-11
Temperature:	18.5 °C
Relative Humidity:	41 %
ATM Pressure:	102.9 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting

Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
915	13.02	30	Pass

915 MHz




100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

Environmental Conditions & Test Information

Test Date:	2026-02-11
Temperature:	18.5 °C
Relative Humidity:	41 %
ATM Pressure:	102.9 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


EUT operation mode: Transmitting

Left Side



ProjectNo.:RKSA260120001 Tester:Neil Zhou
Date: 11.FEB.2026 10:44:23

Right Side



ProjectNo.:RKSA260120001 Tester:Neil Zhou
Date: 11.FEB.2026 10:51:43


CONDUCTED SPURIOUS EMISSION

Environmental Conditions & Test Information

Test Date:	2026-04-29
Temperature:	19.6 °C
Relative Humidity:	43 %
ATM Pressure:	102.4 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Frequency (MHz)	Result (dB)	Limit (dB)	Result
915	50.01	20	Pass

915 MHz



POWER SPECTRAL DENSITY


Environmental Conditions & Test Information

Test Date:	2026-02-11
Temperature:	18.5 °C
Relative Humidity:	41 %
ATM Pressure:	102.9 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting

Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
915	0.58	≤ 8

915 MHz



EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******