

FCC TEST REPORT

FCC ID:2BS3G-CS-RTK

Report No..... : ZHT-250804101W03
Product..... : RTK Station
Trademark..... : Crostars
Model(s)..... : CS-RTK
Model Difference..... : /
Applicant..... : SHANGHAI CROSS STARS CULTURAL TECHNOLOGY LLC.,CO
Address..... : Room 201H, No. 1366, Yangshupu Road, Yangpu District, Shanghai
(centralized registration place), China
Manufacturer..... : Shenzhen Beitian Communication Co., Ltd
Address..... : Floor 9, Unit 1, Fucheng Digital Innovation Park, No.15 Shijing Road,
Fumin Community, Fucheng Street, Longhua District, Shenzhen, China
Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.
Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai
Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Date of Receipt..... : Aug. 4, 2025
Date of Test(s)..... : Aug. 4, 2025 to Nov. 7, 2025
Date of Issue..... : Nov. 7, 2025
Standard..... : FCC Part 15 Subpart C Section 15.249
Test procedure..... : ANSI C63.10-2020

In the configuration tested, the EUT complied with the standards specified above.

Prepared by

Reviewed by:

Approved by:

Leon Li

Leon Li/ Engineer

Baret Wu

Baret Wu/ Director

Levi Lee

Levi Lee/ Manager

Note: This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Table of Contents

Page

1.SUMMARY OF TEST RESULTS	3
2. GENERAL INFORMATION	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 DESCRIPTION OF TEST MODES	5
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	6
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	6
3. TEST FACILITY AND TEST INSTRUMENT USED	7
3.1 TEST FACILITY	7
3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS	7
3.3 TESTING SOFTWARE	9
3.4 MEASUREMENT UNCERTAINTY	9
4. EMC EMISSION TEST	10
4.1 CONDUCTED EMISSION MEASUREMENT	10
4.2 RADIATED EMISSION MEASUREMENT	12
5. CHANNEL BANDWIDTH	23
5.1 APPLIED PROCEDURES / LIMIT	23
5.2 TEST PROCEDURE	23
5.3 DEVIATION FROM STANDARD	23
5.4 TEST SETUP	23
5.5 EUT OPERATION CONDITIONS	23
5.6 TEST RESULTS	24
6.ANTENNA REQUIREMENT	26
7. TEST SETUP PHOTO	27
8. EUT CONSTRUCTIONAL DETAILS	27

1.SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203	Antennarequirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	N/A	
FCC part 15.249	Fundamental &Radiated Spurious Emission Measurement	PASS	
FCC part 15.215 (c)	20dB Channel Bandwidth	PASS	

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	RTK Station
Model No.:	CS-RTK
Model Different.:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	903.125-927.125MHz
Modulation Type:	Lora
Antenna Type:	TNC-RP Foldable Antenna with Rubber Rod
Antenna gain:	3.5dBi
Sample Number:	250804101YP001
Power supply:	Input: DC 12V  2A or DC 14.8 V by Battery
Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	903.125MHz	2	904.125MHz	3	905.125MHz	4	906.125MHz
5	907.125MHz	6	908.125MHz	7	909.125MHz	8	910.125MHz
9	911.125MHz	10	912.125MHz	11	913.125MHz	12	914.125MHz
13	915.125MHz	14	916.125MHz	15	917.125MHz	16	918.125MHz
17	919.125MHz	18	920.125MHz	19	921.125MHz	20	922.125MHz
21	923.125MHz	22	924.125MHz	23	925.125MHz	24	926.125MHz
24	927.125MHz						

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	903.125MHz
The middle channel	915.125MHz
The Highest channel	927.125MHz

2.2 DESCRIPTION OF TEST MODES


Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: The EUT use new battery during the test. The test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission



RF Conducted Emission



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo (Beijing) Co., Ltd	ThinkPad E480	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) The test software is the RF_Setting V1.0 which can set the EUT into the individual test modes.
Power set point: Default value

**3. TEST FACILITY AND TEST INSTRUMENT USED****3.1 TEST FACILITY**

Guangdong Zhonghan Testing Technology Co., Ltd.

Add.: Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number: 255941

Designation Number: CN0325

IC Registered No.: 29832

CAB identifier: CN0143

3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
2	Loop Antenna	TESEQ	HLA6121	58357	Sept. 8, 2025	Sept. 7, 2026
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	May 6, 2025	May 5, 2026
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 7, 2025	May 6, 2026
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	May 15, 2025	May 14, 2026
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	May 15, 2025	May 14, 2026
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	Oct. 20, 2025	Oct. 19, 2026
8	Amplifier	AEROFLEX	100KHz-40GHz	097	Oct. 20, 2025	Oct. 19, 2026
9	Spectrum Analyzer	R&S	FSV40	101413	Oct. 20, 2025	Oct. 19, 2026
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 7, 2025	May 6, 2026
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	May 7, 2025	May 6, 2026
12	Single Generator	Agilent	N5182A	MY48180575	May 7, 2025	May 6, 2026
13	Power Sensor	MWRFTest	MW100-RFCB	/	May 7, 2025	May 6, 2026
14	Power Amplifier Shielding Room	EMToni	2m3m3m	/	Nov. 25, 2021	Nov. 24, 2026
15	CABLE	EMToni	DA800-NM-NM-11000MM	/	May 6, 2025	May 5, 2026

Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
LISN	R&S	ENV216	102794	May 6, 2025	May 5, 2026
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	May 7, 2025	May 6, 2026
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	May 7, 2025	May 6, 2026
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 8, 2025	May 7, 2026
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 8, 2025	May 7, 2026
CABLE	EMToni	G223-NM-BNCM-2000MM	/	May 7, 2025	May 6, 2026

Conducted Test Instrument

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	Oct. 20, 2025	Oct. 19, 2026
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 7, 2025	May 6, 2026
3	Power Sensor	MWRTest	MW100-RFCB	/	May 7, 2025	May 6, 2026

3.3 TESTING SOFTWARE

Project	Software name	Edition
RF Conducted	MTS 8310	2.0.0.0
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$U=0.92\text{dB}$
2	RF conducted power	$U=0.16\text{dB}$
3	Spurious emissions conducted	$U=0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$U=1.6\text{dB}$
5	All radiated emissions (<1G)	$U=5.1\text{dB}$
6	All radiated emissions (>1G)	$U=4.65\text{dB}$
7	Temperature	$U=0.5^{\circ}\text{C}$
8	Humidity	$U=2\%$
9	Occupied Bandwidth	$U=4.96\%$
10	Power Spectral Density	$U=0.71\text{dB}$

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is included

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:


(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 TEST RESULTS

N/A

The Product is powered by the DC only, the test item is not applicable.



Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10-2020				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


4.2.3 DEVIATION FROM TEST STANDARD

No deviation




4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

Field strength of Harmonics and Spurious Emissions
Only the worst-case (908.4MHz TX) were record in the report.

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

Field Strength of The Fundamental Signal

Note: maximum permissible field strength is 50mV/m(93.98dB μ V/m).

Between 30MHz – 1GHz

Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 14.8V		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.0660	23.97	-8.85	15.12	40.00	-24.88	QP
2	48.5247	24.17	-8.53	15.64	40.00	-24.36	QP
3	62.0401	25.63	-9.94	15.69	40.00	-24.31	QP
4	206.0714	29.91	-9.76	20.15	43.50	-23.35	QP
5	315.1166	30.14	-6.88	23.26	46.00	-22.74	QP
6 *	903.1250	87.72	3.48	91.20	46.00	45.20	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
903.125	87.72	3.48	91.20	93.98	-2.78	Peak



Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 14.8V		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.0160	24.25	-8.61	15.64	40.00	-24.36	QP
2	53.7244	24.55	-8.79	15.76	40.00	-24.24	QP
3	217.9761	34.06	-9.32	24.74	46.00	-21.26	QP
4	282.6277	33.47	-7.53	25.94	46.00	-20.06	QP
5	318.4524	32.06	-6.81	25.25	46.00	-20.75	QP
6 *	903.1250	87.27	3.48	90.75	46.00	44.75	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
903.125	87.27	3.48	90.75	93.98	-3.23	Peak



Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 14.8V		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.8284	24.38	-8.81	15.57	40.00	-24.43	QP
2	62.0401	25.63	-9.94	15.69	40.00	-24.31	QP
3	215.6928	30.09	-9.41	20.68	43.50	-22.82	QP
4	282.6277	30.91	-7.53	23.38	46.00	-22.62	QP
5	304.2477	31.15	-7.12	24.03	46.00	-21.97	QP
6 *	915.1250	87.09	3.61	90.70	46.00	44.70	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
915.125	87.09	3.61	90.70	93.98	-3.28	Peak



Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 14.8V		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.7244	22.55	-8.79	13.76	40.00	-26.24	QP
2	190.7573	27.41	-10.60	16.81	43.50	-26.69	QP
3	249.9541	30.35	-8.15	22.20	46.00	-23.80	QP
4	282.6277	32.97	-7.53	25.44	46.00	-20.56	QP
5	317.3365	31.03	-6.84	24.19	46.00	-21.81	QP
6 *	915.1250	87.65	3.61	91.26	46.00	45.26	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
915.125	87.65	3.61	91.26	93.98	-2.72	Peak



Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 14.8V		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	48.5015	24.67	-8.53	16.14	40.00	-23.86	QP
2	61.9950	27.13	-9.93	17.20	40.00	-22.80	QP
3	213.7632	32.90	-9.47	23.43	43.50	-20.07	QP
4	281.9945	32.91	-7.54	25.37	46.00	-20.63	QP
5	300.3672	34.35	-7.20	27.15	46.00	-18.85	QP
6 *	927.1250	89.15	3.73	92.88	46.00	46.88	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
927.125	89.15	3.73	92.88	93.98	-1.1	Peak



Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 14.8V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	217.5440	36.06	-9.34	26.72	46.00	-19.28	QP
2	242.5252	30.26	-8.42	21.84	46.00	-24.16	QP
3	263.8190	30.50	-7.89	22.61	46.00	-23.39	QP
4	296.1836	33.66	-7.28	26.38	46.00	-19.62	QP
5	316.5890	34.53	-6.85	27.68	46.00	-18.32	QP
6 *	927.1250	89.66	3.73	93.39	46.00	47.39	peak

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
927.125	89.66	3.72	93.39	93.98	-0.59	Peak

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Channel: 908.42MHz									
V	1816.84	60.14	30.55	5.77	24.66	60.02	74	-13.98	Pk
V	1816.84	46.66	30.55	5.77	24.66	46.54	54	-7.46	AV
V	2725.26	59.75	30.33	6.32	24.55	60.29	74	-13.71	Pk
V	2725.26	47.06	30.33	6.32	24.55	47.6	54	-6.4	AV
H	1816.84	59.47	30.55	5.77	24.66	59.35	74	-14.65	Pk
H	1816.84	46.25	30.55	5.77	24.66	46.13	54	-7.87	AV
H	2725.26	59.68	30.33	6.32	24.55	60.22	74	-13.78	Pk
H	2725.26	46.14	30.33	6.32	24.55	46.68	54	-7.32	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10-2020

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249(c)	Bandwidth	902-928	PASS

5.2 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1%-5%OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULTS

Temperature:	25.1 °C	Relative Humidity:	53%
Test Mode :	Lora	Test Voltage:	DC 14.8V

Mode	20dB Emission Bandwidth (kHz)	Result
903.125MHz	142.6	Pass
915.125MHz	144.8	
927.125MHz	144.1	

Test plots





**6.ANTENNA REQUIREMENT**

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antennas are TNC-RP Foldable Antenna with Rubber Rod, the best case gain of the antennas are 3.5dBi, reference to the appendix II for details.	

7. TEST SETUP PHOTO

Reference to the appendix I for details.

8. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ **END OF REPORT** ※※※※※