



## RF EXPOSURE REPORT

For

### Quanzhou Earphonic Electronics Technology Co., Ltd.

Room 501, No. 8, Binnan Ninth Road, Xiamei Town, Nan'an City, Fujian  
Province, China

**FCC ID: 2BS47-NEK-N01-AD**


|                       |                                                                                                                                                                                                                                                                                |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b>   | <b>Product Name:</b>                                                                                                                                                                                                                                                           |
| Original Report       | WALKIE TALKIE Bluetooth                                                                                                                                                                                                                                                        |
| <b>Report Number:</b> | 2507X36039E-RF-03                                                                                                                                                                                                                                                              |
| <b>Report Date:</b>   | 2025-11-26                                                                                                                                                                                                                                                                     |
| <b>Reviewed By:</b>   | Ash Lin                                                                                                                                                                                     |
| <b>Approved By:</b>   | Miles Chen                                                                                                                                                                                  |
| <b>Prepared By:</b>   | Bay Area Compliance Laboratories Corp. (Xiamen)<br>Unit 102, No. 902 Meifeng South Road, Binhai West Avenue,<br>Science and Technology Innovation Park, Torch High tech<br>Zone Xiamen<br>Tel: +86-592-3200111<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

**TABLE OF CONTENTS**

**REPORT REVISION HISTORY.....3**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....4

**RF EXPOSURE EVALUATION .....5**

    MEASUREMENT RESULT .....5

**EUT PHOTOGRAPHS.....6**

**REPORT REVISION HISTORY**

| Number of Revisions | Report No.        | Version | Issue Date | Description     |
|---------------------|-------------------|---------|------------|-----------------|
| 0                   | 2507X36039E-RF-03 | R1V1    | 2025-11-26 | Initial Release |

**GENERAL INFORMATION****Product Description for Equipment under Test (EUT)**

|                                                                                                                                                                                                                                                                                             |                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Product Name:                                                                                                                                                                                                                                                                               | WALKIE TALKIE Bluetooth                      |
| Tested Model:                                                                                                                                                                                                                                                                               | NEK-N01-AD                                   |
| Multiple Model(s):                                                                                                                                                                                                                                                                          | AC-HB8-AD, N01-AD, BQ-N01-AD, BT-02-AD       |
| Trade Mark:                                                                                                                                                                                                                                                                                 | EARPHONIC, ANYSECU, VROESA, BinQi, ABBREE    |
| Power Supply:                                                                                                                                                                                                                                                                               | DC 5V from USB port or DC 3.7V from battery  |
| Maximum Peak Conducted Output Power:                                                                                                                                                                                                                                                        | BLE: 1.89dBm<br>BT: 7.01dBm                  |
| Frequency Range:                                                                                                                                                                                                                                                                            | 2402-2480 MHz                                |
| Modulation Technique:                                                                                                                                                                                                                                                                       | BLE: GFSK<br>BT: GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Antenna Type:                                                                                                                                                                                                                                                                               | PCB Antenna                                  |
| ★Maximum Antenna Gain:                                                                                                                                                                                                                                                                      | 1dBi                                         |
| EUT Received Status:                                                                                                                                                                                                                                                                        | Good                                         |
| <i>Note:</i><br>1. The Maximum Antenna Gain was declared by manufacturer.<br>2. The difference between tested model and series model are model name and trade name, please refer to declaration letter for more detail.<br>3. The EUT supplied by the applicant was received on 2025-09-01. |                                              |

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on the Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone Xiamen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

## RF EXPOSURE EVALUATION

---

### Applicable Standard

According to §2.1093, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances < 50 mm are determined by:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} < 3.0 \text{ for 1-g SAR and } < 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### Measurement Result

#### For BLE:

The max conducted power including tune-up tolerance is 2.0 dBm (1.58 mW).

$$\left[ \frac{\text{(max. power of channel, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} = 1.58/5 \cdot (\sqrt{2.480}) = 0.5 < 3.0$$

#### For BT:

The max conducted power including tune-up tolerance is 7.5 dBm (5.62 mW).

$$\left[ \frac{\text{(max. power of channel, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} = 5.62/5 \cdot (\sqrt{2.480}) = 1.8 < 3.0$$

**Result: Compliant. The stand-alone SAR evaluation is not necessary**

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2507X36039E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2507X36039E-RF-INP EUT INTERNAL PHOTOGRAPHS.

### **Declarations**

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $k=2$  with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***