**Shenzhen Global Test Service Co.,Ltd.**
No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

# FCC PART 15 SUBPART C TEST REPORT

## FCC PART 15.247

| | |
|---|---|
| **Report Reference No.....:** | **GTS20251121009-2-01** |
| **FCC ID..... :** | **2BS6P-TL2025** |
| Compiled by ( position+printed name+signature)..: | File administrators Peter Xiao Peter Xiao |
| Supervised by ( position+printed name+signature)..: | Test Engineer Evan Ouyang Evan OuYang |
| Approved by ( position+printed name+signature)..: | Manager Jason Hu Jason Hu |
| Date of issue.....: | Nov.28, 2025 |
| **Representative Laboratory Name.:** | **Shenzhen Global Test Service Co.,Ltd.** |
| Address..... : | No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong,China |
| **Applicant's name.....:** | **Building Blocks Childcare Consultants** |
| Address..... : | 2215 Portofino Ave, Homestead, FL 33033, USA Minor Outlying Islands |
| **Test specification.....:** | |
| Standard.....: | **FCC Part 15.247** |
| TRF Originator.....: | Shenzhen Global Test Service Co.,Ltd. |
| Master TRF.....: | Dated 2014-12 |

**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

| | |
|---|---|
| **Test item description.....:** | **Teddy Luv Bluetooth Plush Bear** |
| Trade Mark.....: | N/A |
| Manufacturer.....: | Yangzhou Amigo toys Co.,ltd |
| Model/Type reference.....: | TL2025 |
| Listed Models .....: | N/A |
| Modulation Type.....: | GFSK |
| Operation Frequency.....: | From 2402MHz to 2480MHz |
| Hardware Version .....: | N/A |
| Software Version.....: | N/A |
| Rating.....: | DC5V 1A |
| Result.....: | **PASS** |

# TEST REPORT

| Test Report No. : | GTS20251121009-2-01 | Nov.28, 2025<br>Date of issue |
|---|---|---|

| | | |
|---|---|---|
| Equipment under Test | : | Teddy Luv Bluetooth Plush Bear |
| Model /Type | : | TL2025 |
| Listed model | : | N/A |
| **Applicant** | : | **Building Blocks Childcare Consultants** |
| Address | : | 2215 Portofino Ave, Homestead, FL 33033, USA Minor Outlying Islands |
| **Manufacturer** | : | **Yangzhou Amigo toys Co.,ltd** |
| Address | : | No.398 Situmiao Road,hanjiang district,yangzhou city jiangsu province China |

| **Test Result**: | **PASS** |
|---|---|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

# Contents

**1. TEST STANDARDS ..... 4**
**2. SUMMARY ..... 5**
2.1. General Remarks ..... 5
2.2. Product Description ..... 5
2.3. Equipment Under Test ..... 6
2.4. Short description of the Equipment under Test (EUT) ..... 6
2.5. EUT operation mode ..... 6
2.6. Block Diagram of Test Setup ..... 7
2.7. EUT Exercise Software ..... 7
2.8. Special Accessories ..... 7
2.9. External I/O Cable ..... 7
2.10. Related Submittal(s) / Grant (s) ..... 7
2.11. Modifications ..... 7
**3. TEST ENVIRONMENT ..... 8**
3.1. Address of the test laboratory ..... 8
3.2. Test Facility ..... 8
3.3. Environmental conditions ..... 8
3.4. Statement of the measurement uncertainty ..... 8
3.5. Test Description ..... 9
3.6. Equipments Used during the Test ..... 10
**4. TEST CONDITIONS AND RESULTS ..... 11**
4.1. AC Power Conducted Emission ..... 11
4.2. Radiated Emission ..... 13
4.3. On Time and Duty Cycle ..... 18
4.4. Maximum Peak Output Power ..... 19
4.5. Power Spectral Density ..... 20
4.6. 99% and 6dB Bandwidth ..... 21
4.7. Conducted Spurious Emissions and Band Edge Compliance of RF Emission ..... 22
4.8. Antenna Requirement ..... 24
**5. TEST SETUP PHOTOS OF THE EUT ..... 25**
**6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT ..... 27**
6.1. External photos of the EUT ..... 27
6.2. Internal photos of the EUT ..... 30

# 1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSIC63.10-2020+Cor.1-2023+C63.10a-2024: American National Standard for Testing Unlicensed Wireless Devices
KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

# 2. SUMMARY

## 2.1. General Remarks

| | | |
|---|---|---|
| Date of receipt of test sample | : | Nov.14, 2025 |
| | | |
| Testing commenced on | : | Nov.15, 2025 |
| | | |
| Testing concluded on | : | Nov.26, 2025 |

## 2.2. Product Description

| | |
|---|---|
| Product Name: | Teddy Luv Bluetooth Plush Bear |
| Trade Mark: | N/A |
| Model/Type reference: | TL2025 |
| List Model: | N/A |
| Model Declaration | N/A |
| Power supply: | DC5V 1A |
| Hardware Version | N/A |
| Software Version | N/A |
| Sample ID | GTS20251121009-2-S001-1# & GTS20251121009-2-S001-2# |
| Bluetooth | |
| Frequency Range | 2402MHz ~ 2480MHz |
| Channel Number | 40 channels for Bluetooth (DTS) |
| Channel Spacing | 2MHz for Bluetooth (DTS) |
| Modulation Type | GFSK for Bluetooth (DTS) |
| Antenna Description | ANT1 used for BT TX/RX, -0.58 dBi(Max.) for 2.4G band |

## 2.3. Equipment Under Test

## Power supply system utilised

| | | | | | |
|---|---|---|---|---|---|
| Power supply voltage | : | ○ | 230V / 50 Hz | ○ | 120V / 60Hz |
| | | ○ | 12 V DC | ○ | 24 V DC |
| | | ● | Other (specified in blank below) | | |

DC5V

## 2.4. Short description of the Equipment under Test (EUT)

This is a Teddy Luv Bluetooth Plush Bear.
For more details, refer to the user's manual of the EUT.

## 2.5. EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing .There are 40 channels provided to the EUT. Channel 00/19/39 was selected to test.

| Mode of Operations | Frequency Range (MHz) | Data Rate (Mbps) |
|---|---|---|
| (BLE) | 2402 | 1 |
| | 2440 | 1 |
| | 2480 | 1 |
| For Conducted Emission | | |
| Test Mode | TX Mode | |
| For Radiated Emission | | |
| Test Mode | TX Mode | |

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---|---|---|---|
| **0** | **2402** | 20 | 2442 |
| 1 | 2404 | 21 | 2444 |
| 2 | 2406 | 22 | 2446 |
| -- | -- | -- | -- |
| -- | -- | -- | -- |
| 18 | 2438 | 38 | 2478 |
| **19** | **2440** | **39** | **2480** |

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case(AC 120V/60Hz).

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, which was determined to be BT LE mode (MCH).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be BT LE mode(MCH).

## 2.6. Block Diagram of Test Setup




## 2.7. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (adb model) provided by application.

## 2.8. Special Accessories

| Manufacturer | Description | Model | Serial Number | Certificate |
|---|---|---|---|---|
| HANJIA | Adapter | HJ1012240520 | / | SDOC |
| - | - | - | / | SDOC |

Note: The PC and Earphone is only used for auxiliary testing.

## 2.9. External I/O Cable

| I/O Port Description | Quantity | Cable |
|---|---|---|
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |

## 2.10. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2BS6P-TL2025** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.11. Modifications

No modifications were implemented to meet testing criteria.

# 3. TEST ENVIRONMENT

## 3.1. Address of the test laboratory

**Shenzhen Global Test Service Co.,Ltd.**
No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong,China.

## 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)
Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.
A2LA (Certificate No. 4758.01)
Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.
Industry Canada Registration Number. is 24189.
FCC Designation Number is CN1401.
FCC Registered Test Site Number is 684561.

## 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---|---|
| Temperature: | 15-35 ° C |
| | |
| Humidity: | 30-60 % |
| | |
| Atmospheric pressure: | 950-1050mbar |

## 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.
Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test | Range | Measurement Uncertainty | Notes |
|---|---|---|---|
| Radiated Emission | 30~1000MHz | 4.10 dB | (1) |
| Radiated Emission | 1~18GHz | 4.32 dB | (1) |
| Radiated Emission | 18-40GHz | 5.54 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB | (1) |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 3.5. Test Description

| Applied Standard: FCC Part 15 Subpart C | | | | |
|---|---|---|---|---|
| FCC Rules | Description of Test | Test Sample | Result | Remark |
| / | On Time and Duty Cycle | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.247(b) | Maximum Conducted Output Power | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.247(e) | Power Spectral Density | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.247(a)(2) | 6dB Bandwidth | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §2.1047 | 99% Occupied Bandwidth | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.209, §15.247(d) | Conducted Spurious Emissions and Band Edges Test | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.209, §15.247(d) | Radiated Spurious Emissions | GTS20251121009-2-S001-1#<br>GTS20251121009-2-S001-2# | Compliant | Note 1 |
| §15.205 | Emissions at Restricted Band | GTS20251121009-2-S001-1# | Compliant | Appendix A |
| §15.207(a) | AC Conducted Emissions | GTS20251121009-2-S001-2# | Compliant | Note 1 |
| §15.203<br>§15.247(c) | Antenna Requirements | GTS20251121009-2-S001-1# | Compliant | Note 1 |
| §15.247(i)§2.1093 | RF Exposure | / | Compliant | Note 2 |

Remark:
1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

## 3.6. Equipments Used during the Test

| Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|---|---|---|---|---|---|
| Artificial Mains | CYBERTEK | EM5040A | E1850400205 | 2025/07/07 | 2026/07/06 |
| LISN | R&S | ESH2-Z5 | 893606/008 | 2025/07/07 | 2026/07/06 |
| EMI Test Receiver | R&S | ESPI 3 | / | 2025/07/04 | 2026/07/03 |
| Test Receiver | R&S | ESCI 7 | 101102 | 2025/07/04 | 2026/07/03 |
| Spectrum Analyzer | Agilent | N9020A | MY48010425 | 2025/07/04 | 2026/07/03 |
| Spectrum Analyzer | R&S | FSV40-N | 101800 | 2025/07/04 | 2026/07/03 |
| Vector Signal generator | Agilent | N5181A | MY49060502 | 2025/07/15 | 2026/07/14 |
| Signal generator | Agilent | N5182A | MY50141550 | 2025/07/04 | 2026/07/03 |
| Climate Chamber | ESPEC | EL-10KA | A20120523 | 2025/07/15 | 2026/07/14 |
| Controller | EM Electronics | Controller EM 1000 | N/A | N/A | N/A |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 01622 | 2024/12/16 | 2025/12/15 |
| Active Loop Antenna | Beijing Da Ze Technology Co.,Ltd. | ZN30900C | / | 2025/07/04 | 2026/07/03 |
| By-log Antenna | SCHWARZBECK | VULB9163 | 00976 | 2025/07/15 | 2026/07/14 |
| Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2025/07/15 | 2026/07/14 |
| Amplifier | SKET | LAPA_30M01G-32 | SK20240104001 | 2025/01/21 | 2026/01/20 |
| Amplifier | EMCI | EMC012645SE | 980340 | 2025/01/21 | 2026/01/20 |
| Amplifier | Schwarzbeck | BBV9179 | 9719-025 | 2025/01/21 | 2026/01/20 |
| Temperature/Humidity Meter | HUATU | HTC-1 | / | 2025/07/16 | 2026/07/15 |
| High-Pass Filter | Stest | 1 | / | 2025/07/04 | 2026/07/03 |
| High-Pass Filter | Stest | 2 | / | 2025/07/04 | 2026/07/03 |
| RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | RE01 | 2025/07/15 | 2026/07/14 |
| RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | RE02 | 2025/07/15 | 2026/07/14 |
| Data acquisition card | Agilent | U2531A | TW53323507 | 2025/07/15 | 2026/07/14 |
| Power Sensor | Keysight | E9301A | MY41495308 | 2025/07/04 | 2026/07/03 |
| Control Unit | Tonscend | JS0806-2 | / | 2025/07/07 | 2026/07/06 |
| Control Unit | Tonscend | JS0806-2 | / | 2025/07/07 | 2026/07/06 |
| integrated measuring instrument | R&S | CMW500 | 107519 | 2025/07/04 | 2026/07/03 |
| EMI Test Software | Tonscend | JS1120-1 | Ver 2.6.8.0518 | / | / |
| EMI Test Software | Tonscend | JS1120-3 | Ver 2.5.77.0418 | / | / |
| EMI Test Software | Tonscend | JS32-CE | Ver 2.5 | / | / |
| EMI Test Software | Tonscend | JS32-RE | Ver 2.5.1.8 | / | / |

Note: 1. The Cal.Interval was one year.

# 4. TEST CONDITIONS AND RESULTS

## 4.1. AC Power Conducted Emission

**TEST CONFIGURATION**




**TEST PROCEDURE**

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024.
2 Support equipment, if needed, was placed as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024
3 All I/O cables were positioned to simulate typical actual usage as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024
4 The EUT received AC 120V power, the received AC120V/60Hz or AC 240V/50Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

**AC Power Conducted Emission Limit**

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

| Frequency range (MHz) | Limit (dBuV) | |
|---|---|---|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |
| * Decreases with the logarithm of the frequency. | | |

**DISTURBANCE Calculation**

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

**CD (dBuV) = RA (dBuV) + PL (dB) + CL (dB)**

| | |
|---|---|
| Where CD = Conducted Disturbance | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | PL = 10 dB Pulse Limiter Factor |

## TEST RESULTS

Remark: We measured Conducted Emission at GFSK mode from 150 KHz to 30MHz in AC120V and the worst case was recorded.

| Temperature | 24.7℃ | Humidity | 51% |
|---|---|---|---|
| Test Engineer | Evan Ouyang | Configurations | BT |

| Power supply: | AC 120V/60Hz | Polarization | L |
|---|---|---|---|




Final Data List

| NO. | Frequency [MHz] | QP Reading [dBμV] | AVG. Reading [dBμV] | Factor [dB] | QP Result [dBμV] | AVG. Result [dBμV] | QP Limit [dBμV] | AVG. Limit [dBμV] | QP Margin [dB] | AVG. Margin [dB] | Line | Remark |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.24 | 37.08 | 28.43 | 10.13 | 47.21 | 38.56 | 62.10 | 52.10 | 14.89 | 13.54 | L1 | PASS |
| 2 | 0.384 | 31.79 | 30.33 | 10.15 | 41.94 | 40.48 | 58.19 | 48.19 | 16.25 | 7.71 | L1 | PASS |
| 3 | 1.329 | 24.08 | 12.81 | 10.22 | 34.30 | 23.03 | 56.00 | 46.00 | 21.70 | 22.97 | L1 | PASS |
| 4 | 2.445 | 25.26 | 9.83 | 10.30 | 35.56 | 20.13 | 56.00 | 46.00 | 20.44 | 25.87 | L1 | PASS |
| 5 | 3.1605 | 25.47 | 12.90 | 10.34 | 35.81 | 23.24 | 56.00 | 46.00 | 20.19 | 22.76 | L1 | PASS |
| 6 | 6.198 | 21.88 | 2.86 | 10.49 | 32.37 | 13.35 | 60.00 | 50.00 | 27.63 | 36.65 | L1 | PASS |

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

| Power supply: | AC 120V/60Hz | Polarization | N |
|---|---|---|---|




Final Data List

| NO. | Frequency [MHz] | QP Reading [dBμV] | AVG. Reading [dBμV] | Factor [dB] | QP Result [dBμV] | AVG. Result [dBμV] | QP Limit [dBμV] | AVG. Limit [dBμV] | QP Margin [dB] | AVG. Margin [dB] | Line | Remark |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.2265 | 40.25 | 32.13 | 10.14 | 50.39 | 42.27 | 62.58 | 52.58 | 12.19 | 10.31 | N | PASS |
| 2 | 0.393 | 36.43 | 25.36 | 10.16 | 46.59 | 35.52 | 58.00 | 48.00 | 11.41 | 12.48 | N | PASS |
| 3 | 0.447 | 31.74 | 28.13 | 10.21 | 41.95 | 38.34 | 56.93 | 46.93 | 14.98 | 8.59 | N | PASS |
| 4 | 0.744 | 27.74 | 17.90 | 10.24 | 37.98 | 28.14 | 56.00 | 46.00 | 18.02 | 17.86 | N | PASS |
| 5 | 2.4495 | 29.20 | 12.43 | 10.30 | 39.50 | 22.73 | 56.00 | 46.00 | 16.50 | 23.27 | N | PASS |
| 6 | 6.198 | 25.62 | 7.94 | 10.49 | 36.11 | 18.43 | 60.00 | 50.00 | 23.89 | 31.57 | N | PASS |

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

## 4.2. Radiated Emission

**TEST CONFIGURATION**

Frequency range 9 KHz – 30MHz




Frequency range 30MHz – 1000MHz




Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 30MHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|---|---|---|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Ultra-Broadband Antenna | 3 |
| 1GHz-18GHz | Double Ridged Horn Antenna | 3 |
| 18GHz-25GHz | Horn Anternna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|---|---|---|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz,Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz,Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz,Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

**FS = RA + AF + CL - AG**

| | |
|---|---|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

Transd=AF +CL-AG

**RADIATION LIMIT**

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m) | Radiated (μV/m) |
|---|---|---|---|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

**TEST RESULTS**

Remark: We measured Radiated Emission at GFSK mode from 9kHz to 25GHz in AC120V and the worst case was recorded.

| | | | |
|---|---|---|---|
| Temperature | 24.4℃ | Humidity | 48% |
| Test Engineer | Evan Ouyang | Configurations | BT |

**For 9 KHz~30MHz**

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Over Limit (dBuV) | Remark |
|---|---|---|---|---|
| - | - | - | - | See Note |

Note:
The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.

**For 30MHz to 1000MHz**

## Horizontal




| Suspected List | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity | Remark |
| 1 | 37.275 | 31.00 | -5.92 | 25.08 | 40.00 | 14.92 | 100 | 299 | PK | Horizonta | PASS |
| 2 | 52.795 | 28.36 | -3.16 | 25.20 | 40.00 | 14.80 | 100 | 316 | PK | Horizonta | PASS |
| 3 | 100.325 | 29.29 | -4.58 | 24.71 | 43.50 | 18.79 | 100 | 222 | PK | Horizonta | PASS |
| 4 | 183.26 | 33.04 | -5.97 | 27.07 | 43.50 | 16.43 | 100 | 323 | PK | Horizonta | PASS |
| 5 | 502.39 | 27.34 | 2.34 | 29.68 | 46.00 | 16.32 | 100 | 36 | PK | Horizonta | PASS |
| 6 | 814.73 | 23.78 | 7.31 | 31.09 | 46.00 | 14.91 | 100 | 252 | PK | Horizonta | PASS |

Note:1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

## Vertical




| Suspected List | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity | Remark |
| 1 | 43.095 | 34.44 | -3.58 | 30.86 | 40.00 | 9.14 | 100 | 10 | PK | Vertical | PASS |
| 2 | 129.91 | 34.76 | -7.68 | 27.08 | 43.50 | 16.42 | 100 | 135 | PK | Vertical | PASS |
| 3 | 143.975 | 36.16 | -7.58 | 28.58 | 43.50 | 14.92 | 100 | 327 | PK | Vertical | PASS |
| 4 | 175.5 | 34.75 | -6.32 | 28.43 | 43.50 | 15.07 | 100 | 34 | PK | Vertical | PASS |
| 5 | 438.37 | 25.49 | 1.64 | 27.13 | 46.00 | 18.87 | 100 | 104 | PK | Vertical | PASS |
| 6 | 796.785 | 24.69 | 7.13 | 31.82 | 46.00 | 14.18 | 100 | 0 | PK | Vertical | PASS |

Note:1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

**For 1GHz to 25GHz**

BT LE

Channel 0 / 2402 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4804.00 | 50.60 | 32.44 | 30.25 | 7.95 | 60.74 | 74.00 | -13.26 | Peak | Horizontal |
| 4804.00 | 35.46 | 32.44 | 30.25 | 7.95 | 45.60 | 54.00 | -8.40 | Average | Horizontal |
| 4804.00 | 49.64 | 31.60 | 36.50 | 7.00 | 51.74 | 74.00 | -22.26 | Peak | Vertical |
| 4804.00 | 35.73 | 31.60 | 36.50 | 7.00 | 37.83 | 54.00 | -16.17 | Average | Vertical |

Channel 19 / 2440 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4880.00 | 50.62 | 32.52 | 30.31 | 8.12 | 60.95 | 74.00 | -13.05 | Peak | Horizontal |
| 4880.00 | 37.39 | 32.52 | 30.31 | 8.12 | 47.72 | 54.00 | -6.28 | Average | Horizontal |
| 4880.00 | 50.09 | 31.02 | 36.50 | 7.60 | 52.21 | 74.00 | -21.79 | Peak | Vertical |
| 4880.00 | 36.25 | 31.02 | 36.50 | 7.60 | 38.37 | 54.00 | -15.63 | Average | Vertical |

Channel 39 / 2480 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4960.00 | 51.18 | 32.68 | 30.27 | 7.88 | 61.47 | 74.00 | -12.53 | Peak | Horizontal |
| 4960.00 | 36.52 | 32.68 | 30.27 | 7.88 | 46.81 | 54.00 | -7.19 | Average | Horizontal |
| 4960.00 | 51.09 | 31.58 | 36.20 | 7.82 | 54.29 | 74.00 | -19.71 | Peak | Vertical |
| 4960.00 | 38.60 | 31.58 | 36.20 | 7.82 | 41.80 | 54.00 | -12.20 | Average | Vertical |

Notes:

1). Measuring frequencies from 9 KHz~10$^{th}$ harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
2). Radiated emissions measured in frequency range from 9 KHz~10$^{th}$ harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
3). Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4). Measured= Reading- Pre. Fac.+ Ant. Fac.+ Cab. Loss
5). Margin = Measured- Limit

## 4.3. On Time and Duty Cycle

**LIMIT**

None; for reporting purpose only.

**TEST PROCEDURE**

1. Set the center frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=8MHz, Sweep time= auto couple;
3. Detector = AV;
4. Trace mode = Single hold.

**TEST CONFIGURATION**




**TEST RESULTS**

For reporting purpose only.

Please refer to Appendix A.7.

## 4.4. Maximum Peak Output Power

**TEST CONFIGURATION**

**TEST PROCEDURE**

According to KDB 558074 D01 15.247 Measurement Guidance v05r02 Section 8.3.1 Maximum peak conducted output power, 8.3.1.3 The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

**LIMIT**

The Maximum Peak Output Power Measurement is 30dBm.

**TEST RESULTS**

For reporting purpose only.

Please refer to Appendix A.3.

## 4.5. Power Spectral Density

**TEST CONFIGURATION**

**TEST PROCEDURE**

1.Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2.Set the RBW =3 kHz.
3.Set the VBW =10 KHz.
4.Set the span to 1.5 times the DTS channel bandwidth.
5.Detector = peak.
6.Sweep time = auto couple.
7.Trace mode = max hold.
8.Allow trace to fully stabilize.
9.Use the peak marker function to determine the maximum power level.
10.If measured value exceeds limit,reduce RBW(no less than 3 kHz)and repeat.
11.The resulting peak PSD level less than 8 dBm.

**LIMIT**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

**TEST RESULTS**

For reporting purpose only.

Please refer to Appendix A.4.

## 4.6. 99% and 6dB Bandwidth

**TEST CONFIGURATION**

**TEST PROCEDURE**

6dB Bandwidth :
The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.
The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
According to KDB 558074 D01 DTS Meas Guidance v05r02 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.
1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99% Bandwidth:
According to section 6.9.3 of ANSIC63.10-2020+Cor.1-2023+C63.10a-2024, for the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

1.The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Set RBW = 1%~5% OBW; VBW≥3*RBW (for occupied bandwidth measurement).
3. Measured the 6dB bandwidth and 99% occupied bandwidth by related function of the spectrum analyzer.

**LIMIT**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

**TEST RESULTS**

For reporting purpose only.

Please refer to Appendix A.1.

Please refer to Appendix A.2.

## 4.7. Conducted Spurious Emissions and Band Edge Compliance of RF Emission

**TEST REQUIREMENT**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**TEST CONFIGURATION**




**TEST PROCEDURE**

1.The EUT was placed on a turn table which is 1.5m above ground plane.
2.Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT.
3.And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4.Repeat above procedures until all frequency measurements have been completed..
5.The distance between test antenna and EUT was 3 meter:
6.Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|---|---|---|
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

**LIMIT**

Below -20dB of the highest emission level in operating band.
Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

**TEST RESULTS**

### 4.6.1 For Radiated Bandedge Measurement

For reporting purpose only.

Please refer to Appendix A.8.

### 4.6.2 For Conducted Bandedge Measurement

For reporting purpose only.

Please refer to Appendix A.5.

### 4.6.3 For Conducted Spurious Emissions Measurement

For reporting purpose only.

Please refer to Appendix A.6.

## 4.8. Antenna Requirement

**Standard Applicable**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

**Test Result**

The antenna used for this product is internal Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only -0.58dBi.

Reference to the **Internal photos.**

# 5. TEST SETUP PHOTOS OF THE EUT

Photo of Radiated Emissions Measurement

Fig. 1

Fig. 2

Photo of Conducted Emission Measurement

Fig. 3



Fig. 4

# 6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

## 6.1. External photos of the EUT

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

## 6.2. Internal photos of the EUT

Fig. 7



Fig. 8

.



Fig. 9



Fig. 10



Fig. 11




Fig. 12


GND
5V
VBAT
Rout+
Rout-
Lout+
Lout-
M38
V446

Fig. 13


RF Chip
24.000
AF25C122459-65A4

Fig. 14



Fig. 15



Fig. 16

Fig. 17

**.....End of Report.....**