

Test Report

Product: WIFI6+BTDM5.2 module

Trade Mark: N/A

Model Number: SY135S

FCC ID: 2BS8J-SY135S

Prepared for

Hangzhou Vision Link Intelligence Technology Co., Ltd
Room 117, No. 68 Shengtao Shanyun, Xingzhou Garden, Wenxin
Subdistrict, West Lake District, Hangzhou City, Zhejiang Province, China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	6
1.1	DESCRIPTION OF EUT	6
1.2	TEST MODE.....	6
1.3	OPERATION CHANNEL LIST	6
1.4	TEST SETUP	7
1.5	POWER SETTING CONFIGURATION PARAMETERS	7
1.6	ANCILLARY EQUIPMENT	8
2	SUMMARY OF TEST RESULT.....	9
3	TEST FACILITIES AND ACCREDITATIONS	10
3.1	TEST LABORATORY	10
3.2	ENVIRONMENTAL CONDITIONS	10
3.3	MEASUREMENT UNCERTAINTY	10
3.4	TEST SOFTWARE	11
4	LIST OF TEST EQUIPMENT.....	12
5	TEST ITEM AND RESULTS	14
5.1	ANTENNA REQUIREMENT	14
5.1.1	<i>Standard Requirement</i>	14
5.1.2	<i>Test Result</i>	14
5.2	CONDUCTED EMISSION	15
5.2.1	<i>Limits</i>	15
5.2.2	<i>Test Procedures</i>	15
5.2.3	<i>Test Setup</i>	16
5.2.4	<i>Test Result</i>	16
5.3	RADIATED EMISSION	17
5.3.1	<i>Limits</i>	17
5.3.2	<i>Test Procedures</i>	17
5.3.3	<i>Test Setup</i>	17
5.3.4	<i>Test Result</i>	18
5.3.5	<i>Radiated Band Edge</i>	23
5.4	PEAK OUTPUT POWER	24
5.4.1	<i>Limit</i>	24
5.4.2	<i>Test Procedure</i>	24
5.4.3	<i>Test Setup</i>	24
5.4.4	<i>Test Results</i>	24
5.5	20dB OCCUPIED CHANNEL BANDWIDTH.....	28
5.5.1	<i>Limit</i>	28
5.5.2	<i>Test Procedure</i>	28
5.5.3	<i>Test Setup</i>	28
5.5.4	<i>Test results</i>	28
5.6	CARRIER FREQUENCY SEPARATION	34
5.6.1	<i>Limit</i>	34
5.6.2	<i>Test Procedure</i>	34
5.6.3	<i>Test Setup</i>	34
5.6.4	<i>Test Results</i>	34
5.7	HOPPING CHANNEL NUMBER	40
5.7.1	<i>Limit</i>	40
5.7.2	<i>Test Procedure</i>	40
5.7.3	<i>Test Setup</i>	40
5.7.4	<i>Test Results</i>	40
5.8	DWELL TIME.....	43
5.8.1	<i>Limit</i>	43

5.8.2	Test Procedure	43
5.8.3	Test Setup.....	43
5.8.4	Test Results	43
5.9	CONDUCTED BAND EDGE	54
5.9.1	Limit	54
5.9.2	Test Procedure	54
5.9.3	Test Setup.....	54
5.9.4	Test Results	54
5.10	SPURIOUS RF CONDUCTED EMISSIONS.....	61
5.10.1	Limit	61
5.10.2	Test Procedure.....	61
5.10.3	Test Setup.....	61
5.10.4	Test Results	61
6	PHOTOGRAPHS OF THE TEST SETUP.....	65
7	PHOTOGRAPHS OF THE EUT	66

TEST RESULT CERTIFICATION

Applicant's Name..... : Hangzhou Vision Link Intelligence Technology Co., Ltd
Room 117, No. 68 Shengtao Shanyun, Xingzhou Garden,
Address : Wenxin Subdistrict, West Lake District, Hangzhou City, Zhejiang
Province, China

Manufacturer's Name : Hangzhou Vision Link Intelligence Technology Co., Ltd
Room 117, No. 68 Shengtao Shanyun, Xingzhou Garden,
Address : Wenxin Subdistrict, West Lake District, Hangzhou City, Zhejiang
Province, China

Product description

Product name : WIFI6+BTDM5.2 module

Model Number : SY135S

Standards : FCC Part 15.247

Test procedure : IEEE/ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test

Date (s) of performance of tests : Nov. 21, 2025~Dec. 12, 2025

Test Result..... : **Pass**

Testing Engineer :

Zoe Su

(Z o e S u)

Technical Manager :

Ming Liu

(M i n g L i u)

Authorized Signatory :

Leo Su

(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	WIFI6+BTDM5.2 module
Model name:	SY135S
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	2402-2480MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Bit Rate of transmitter:	1 Mbps, 2Mbps, 3Mbps
Antenna type:	External Antenna
Antenna gain:	2.4dBi
Max. output power:	6.35dBm
Hardware version:	V14
Software version:	10.17.32
Battery:	N/A
Power supply:	Input: DC 3.3V, 0.5A
Adapter information:	N/A

1.2 Test Mode

Test Mode	Channel	Frequency (MHz)
1	00	2402
2	39	2441
3	78	2480

1.3 Operation Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460

05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	--	--
26	2428	53	2455	--	--

1.4 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Power setting configuration parameters

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Test software Version		N/A	
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters	Default	Default	Default
RF cable			
Description	Connector	Length	Supplied by
Antenna Cable	SMA	10cm	Applicant

Note: Disclaimer: the loss of RF cable is too small and can be ignored.

1.6 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Notebook	BDR-WDH	A3RQPM242 0002411	Honor Terminal Co., Ltd.
Battery	/	/	/

Note: The laptop is used to assist the RF test. In order to prevent the laptop from causing unnecessary impact on the test, the laptop will be removed from the test environment after the EUT successfully transmits at a fixed frequency using the laptop.

2 Summary of Test Result

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna requirement	Pass	
2	15.207	Conducted emission	N/A	
3	15.247(d)	Band edge	Pass	
4	15.205/15.209	Spurious emission	Pass	
5	15.247(b)(1)	Peak output power	Pass	
6	15.247(a)(1)	20dB occupied bandwidth	Pass	
7	15.247(a)(1)	Carrier Frequencies Separation	Pass	
8	15.247(a)(1)	Hopping channel number	Pass	
9	15.247(a)(1)	Dwell time	Pass	
10	15.247(d)	Spurious RF Conducted Emissions	Pass	

Note: "N/A" means the test item not applicable.

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(9kHz-30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Occupied Bandwidth	$\pm 3\%$	
Temperature	± 1 degree	
Humidity	± 5 %	

3.4 Test Software

Software name	Manufacturer	Model	Version
Conducted Emission test Software	Farad	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission test Software	Farad	EZ-EMC	FA-03A2
RF Test System	MWRF	MTS 8310	2.0.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2024-05-18	2026-05-17
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2024-05-18	2026-05-17
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 9170	01193	2024-05-18	2026-05-17
4	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2025-05-07	2026-05-06
5	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2025-05-07	2026-05-06
6	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2025-05-07	2026-05-06
7	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
8	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
9	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2025-05-13	2026-05-12
10	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2024-05-18	2026-05-17
11	HB-E076	Preamplifier	Hewlett Packard	8447D	1937A02278	2025-05-07	2026-05-06
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2025-05-07	2026-05-06
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2025-05-07	2026-05-06
3	HB-E016	Absorb clamp	ZHINAN	ZN23201	N/A	2025-05-10	2026-05-09
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2025-05-10	2026-05-09
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2025-05-07	2026-05-06
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaioq Signal Generator	Agilent	N5181A	MY47070421	2025-05-07	2026-05-06
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2025-05-08	2026-05-07

3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2025-05-08	2026-05-07
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2025-05-07	2026-05-06
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2025-05-08	2026-05-07
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2025-05-09	2026-05-08

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is External Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission

5.2.1 Limits

Limits – Class B		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50
Note: 1. the tighter limit applies at the band edges. 2. the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.		

5.2.2 Test Procedures

a) EUT Operating Conditions


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.
- g) For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup



5.2.4 Test Result

Note: The device is a DC power supply and does not apply to conducted emissions.

5.3 Radiated Emission

5.3.1 Limits

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures


- The radiated emission tests were performed in the 3 meters.
- The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup


Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.3.4 Test Result

Below 30MHz


EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Pressure:	1010 hPa	Test Voltage:	DC 3.3V from battery
Test Mode:	TX	Polarization:	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass


Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.

30MHz – 1GHz



EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Test Mode:	TX Mode	Phase:	Horizontal
Test Voltage:	DC 3.3V from battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	119.8555	35.52	-15.40	20.12	43.50	-23.38	QP
2	139.8507	48.12	-14.11	34.01	43.50	-9.49	QP
3 !	340.7816	53.15	-11.25	41.90	46.00	-4.10	QP
4 *	379.9141	52.37	-10.17	42.20	46.00	-3.80	QP
5 !	400.4318	50.29	-9.37	40.92	46.00	-5.08	QP
6 !	460.7271	49.46	-7.97	41.49	46.00	-4.51	QP

1GHz-25GHz

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Low Channel (2402 MHz) --Above 1G									
4804.025	42.87	4.83	33.5	30.80	50.40	74.00	-23.60	Pk	Vertical
4804.025	31.82	4.83	33.5	30.80	39.35	54.00	-14.65	AV	Vertical
7206.265	42.76	5.83	37.79	31.40	54.98	74.00	-19.02	Pk	Vertical
7206.265	31.93	5.83	37.79	31.40	44.15	54.00	-9.85	AV	Vertical
4804.109	42.81	4.83	33.5	30.80	50.34	74.00	-23.66	Pk	Horizontal
4804.109	31.79	4.83	33.5	30.80	39.32	54.00	-14.68	AV	Horizontal
7206.224	42.85	5.83	37.79	31.40	55.07	74.00	-18.93	Pk	Horizontal
7206.224	32.19	5.83	37.79	31.40	44.41	54.00	-9.59	AV	Horizontal
Mid Channel (2441 MHz) --Above 1G									
4882.396	44.10	4.89	33.76	30.80	51.95	74.00	-22.05	Pk	Vertical
4882.396	31.90	4.89	33.76	30.80	39.75	54.00	-14.25	AV	Vertical
7323.241	44.45	5.95	38.25	31.70	56.95	74.00	-17.05	Pk	Vertical
7323.241	32.86	5.95	38.25	31.70	45.36	54.00	-8.64	AV	Vertical
4882.108	43.86	4.89	33.76	30.80	51.71	74.00	-22.29	Pk	Horizontal
4882.108	32.04	4.89	33.76	30.80	39.89	54.00	-14.11	AV	Horizontal
7323.132	43.85	5.95	38.25	31.70	56.35	74.00	-17.65	Pk	Horizontal
7323.132	33.01	5.95	38.25	31.70	45.51	54.00	-8.49	AV	Horizontal
High Channel (2480 MHz) -- Above 1G									
4960.397	42.91	4.95	34.33	30.80	51.39	74.00	-22.61	Pk	Vertical
4960.397	32.18	4.95	34.33	30.80	40.66	54.00	-13.34	AV	Vertical
7440.201	43.54	6.11	37.60	31.74	55.51	74.00	-18.49	Pk	Vertical
7440.201	32.33	6.11	37.60	31.74	44.30	54.00	-9.70	AV	Vertical
4960.225	42.92	4.95	34.33	30.80	51.40	74.00	-22.60	Pk	Horizontal
4960.225	31.96	4.95	34.33	30.80	40.44	54.00	-13.56	AV	Horizontal
7440.298	43.21	6.11	37.60	31.74	55.18	74.00	-18.82	Pk	Horizontal
7440.298	32.24	6.11	37.60	31.74	44.21	54.00	-9.79	AV	Horizontal

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor.
3. All modes have been tested, and only the worst mode 8DPSK mode in the report.

5.3.5 Radiated Band Edge

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detect or Type	Comment
3Mbps- Non-hopping									
2310.00	46.04	3.40	27.80	32.41	44.83	74	-29.17	Pk	Horizontal
2310.00	33.35	3.40	27.80	32.41	32.14	54	-21.86	AV	Horizontal
2310.00	44.94	3.40	27.80	32.41	43.73	74	-30.27	Pk	Vertical
2310.00	33.70	3.40	27.80	32.41	32.49	54	-21.51	AV	Vertical
2390.00	45.53	3.45	27.70	32.49	44.19	74	-29.81	Pk	Vertical
2390.00	34.39	3.45	27.70	32.49	33.05	54	-20.95	AV	Vertical
2390.00	46.38	3.45	27.70	32.49	45.04	74	-28.96	Pk	Horizontal
2390.00	34.49	3.45	27.70	32.49	33.15	54	-20.85	AV	Horizontal
2400.00	46.67	3.46	27.80	32.54	45.39	74	-28.61	Pk	Vertical
2400.00	34.55	3.46	27.80	32.54	33.27	54	-20.73	AV	Vertical
2400.00	46.04	3.46	27.80	32.54	44.76	74	-29.24	Pk	Horizontal
2400.00	34.31	3.46	27.80	32.54	33.03	54	-20.97	AV	Horizontal
2483.50	47.19	3.48	28.53	32.55	46.65	74	-27.35	Pk	Vertical
2483.50	34.10	3.48	28.53	32.55	33.56	54	-20.44	AV	Vertical
2483.50	46.25	3.48	28.53	32.55	45.71	74	-28.29	Pk	Horizontal
2483.50	33.85	3.48	28.53	32.55	33.31	54	-20.69	AV	Horizontal
2500.00	45.45	3.49	29.20	32.66	45.48	74	-28.52	Pk	Vertical
2500.00	33.86	3.49	29.20	32.66	33.89	54	-20.11	AV	Vertical
2500.00	45.27	3.49	29.20	32.66	45.30	74	-28.70	Pk	Horizontal
2500.00	33.74	3.49	29.20	32.66	33.77	54	-20.23	AV	Horizontal
3Mbps- hopping									
2400.00	47.10	3.46	27.80	32.54	45.82	74	-28.18	Pk	Vertical
2400.00	34.55	3.46	27.80	32.54	33.27	54	-20.73	AV	Vertical
2400.00	45.96	3.46	27.80	32.54	44.68	74	-29.32	Pk	Horizontal
2400.00	34.58	3.46	27.80	32.54	33.30	54	-20.70	AV	Horizontal
2483.50	47.27	3.48	28.53	32.55	46.73	74	-27.27	Pk	Vertical
2483.50	34.14	3.48	28.53	32.55	33.60	54	-20.40	AV	Vertical
2483.50	46.35	3.48	28.53	32.55	45.81	74	-28.19	Pk	Horizontal
2483.50	34.00	3.48	28.53	32.55	33.46	54	-20.54	AV	Horizontal

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor.
3. All modes have been tested, and only the worst mode 8DPSK mode in the report.

5.4 Peak Output Power


5.4.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(1)	Peak output power	Power<0.125W (21dBm)	2400-2483.5

5.4.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=2MHz, VBW=10MHz, Detector=Peak
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.4.3 Test Setup



5.4.4 Test Results

EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Test Mode:	TX Mode /CH00, CH39, CH78	Test Voltage:	DC 3.3V from battery

GFSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	3.15	21
CH39	2441	4.09	21
CH78	2480	3.23	21


$\pi/4$ -DQPSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	5.99	21
CH39	2441	4.6	21
CH78	2480	6.01	21

8DPSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	6.28	21
CH39	2441	4.94	21
CH78	2480	6.35	21

Test plots



8DPSK on Channel 00 	8DPSK on Channel 39 
8DPSK on Channel 78 	/ /

5.5 20dB Occupied Channel Bandwidth

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247a(1)	20dB bandwidth	N/A	2400-2483.5


5.5.2 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak

5.5.3 Test Setup



5.5.4 Test results

EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Test Mode:	TX Mode	Test Voltage:	DC 3.3V from battery

Mode	Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
GFSK	2402	947	N/A	Pass
	2441	948	N/A	Pass
	2480	946	N/A	Pass
$\pi/4$ -DQPSK	2402	1325	N/A	Pass
	2441	1324	N/A	Pass
	2480	1324	N/A	Pass
8DPSK	2402	1308	N/A	Pass
	2441	1306	N/A	Pass
	2480	1308	N/A	Pass

Test plots

GFSK mode

TX CH00



TX CH39



TX CH78



$\pi/4$ -DQPSK

TX CH00



TX CH39



TX CH78



8DPSK mode

TX CH00



TX CH39



TX CH78



5.6 Carrier Frequency Separation


5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Channel Separation	>25kHz or >two-thirds of the 20 dB bandwidth (Which is greater)	2400-2483.5

5.6.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=30 kHz, VBW=100 kHz, detector= Peak, Sweep Time =auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

5.6.3 Test Setup



5.6.4 Test Results

EUT:	WiFi6+BTDM5.2 module	Model Name:	SY135S
Pressure:	1012 hPa	Test Voltage:	DC 3.3V from battery
Test Mode:	GFSK, $\pi/4$ -DQPSK, 8DPSK /CH00, CH39, CH78		

Mode	Channel	Frequency (MHz)	Test Result (kHz)	Limit (kHz)		Result
GFSK	Low	2402	1000	631	2/3 of 20dB BW	Pass
	Middle	2441	1002	632	2/3 of 20dB BW	Pass
	High	2480	1002	631	2/3 of 20dB BW	Pass
$\pi/4$ -DQPSK	Low	2402	1000	883	2/3 of 20dB BW	Pass
	Middle	2441	1000	883	2/3 of 20dB BW	Pass
	High	2480	1002	883	2/3 of 20dB BW	Pass
8DPSK	Low	2402	1000	872	2/3 of 20dB BW	Pass
	Middle	2441	1002	871	2/3 of 20dB BW	Pass
	High	2480	1002	872	2/3 of 20dB BW	Pass

Test plots











5.7 Hopping Channel Number

5.7.1 Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

5.7.2 Test Procedure

The testing follows IEEE / ANSI C63.10-2020 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.


VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.3 Test Setup



5.7.4 Test Results

Mode	Quantity of Hopping Channel	Limit	Results
GFSK, $\pi/4$ -DQPSK, 8DPSK	79	>15	Pass

Test plots



8DPSK mode



5.8 Dwell Time


5.8.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Dwell time	0.4 sec	2400-2483.5

5.8.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.
- (9) The EUT was set to the Hopping Mode for Dwell Time Test.

5.8.3 Test Setup



5.8.4 Test Results

EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Pressure:	1012 hPa	Test Voltage:	DC 3.3V from battery
Test Mode:	GFSK, $\pi/4$ -DQPSK, 8DPSK /CH39		


Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
1-DH1	2441	Ant1	0.375	119.625	319	31600	400	Pass
1-DH3	2441	Ant1	1.631	256.067	157	31600	400	Pass
1-DH5	2441	Ant1	2.879	328.206	114	31600	400	Pass
2-DH1	2441	Ant1	0.359	114.88	320	31600	400	Pass
2-DH3	2441	Ant1	1.611	252.927	157	31600	400	Pass
2-DH5	2441	Ant1	2.858	300.09	105	31600	400	Pass
3-DH1	2441	Ant1	0.358	114.202	319	31600	400	Pass
3-DH3	2441	Ant1	1.611	248.094	154	31600	400	Pass
3-DH5	2441	Ant1	2.861	320.432	112	31600	400	Pass

Note:


For GFSK, $\pi/4$ -DQPSK, 8DPSK: The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$



Total Dwell Time(ms)=Pulse Time (ms)* Burst Count



Dwell NVNT 1-DH1 2441MHz Ant1 One Burst





Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated












Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated





Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated







Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



5.9 Conducted Band Edge

5.9.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.9.2 Test Procedure

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

5.9.3 Test Setup




5.9.4 Test Results

EUT:	WIFI6+BTDM5.2 module	Model Name:	SY135S
Pressure:	1012 hPa	Test Voltage:	DC 3.3V from battery

Test plots

GFSK: Band Edge, Left Side



GFSK: Band Edge, Right Side



$\pi/4$ -DQPSK: Band Edge, Left Side



$\pi/4$ -DQPSK: Band Edge, Right Side



8DPSK: Band Edge, Left Side



8DPSK: Band Edge, Right Side



Hopping Mode

Test plots


GFSK: Band Edge, Left Side



GFSK: Band Edge, Right Side




$\pi/4$ -DQPSK: Band Edge, Left Side



$\pi/4$ -DQPSK: Band Edge, Right Side



8DPSK: Band Edge, Left Side



8DPSK: Band Edge, Right Side



5.10 Spurious RF Conducted Emissions


5.10.1 Limit

Below -20dB of the highest emission level in operating band.

5.10.2 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW=300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.10.3 Test Setup




5.10.4 Test Results


Note:

1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.


GFSK on Channel 00




GFSK on Channel 00




GFSK on Channel 39



GFSK on Channel 39




GFSK on Channel 78




GFSK on Channel 78




$\pi/4$ -DQPSK on Channel 00




$\pi/4$ -DQPSK on Channel 00




$\pi/4$ -DQPSK on Channel 39




$\pi/4$ -DQPSK on Channel 39




$\pi/4$ -DQPSK on Channel 78




$\pi/4$ -DQPSK on Channel 78




8DPSK on Channel 00



8DPSK on Channel 00




8DPSK on Channel 39




8DPSK on Channel 39



8DPSK on Channel 78




8DPSK on Channel 78



6 Photographs of the Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



7 Photographs of the EUT

Please refer to report HB20251121059E-01 for product photos.

******* END OF REPORT *******