

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 1 of 73

Applicant : Hangzhou Cyberstar Co., Ltd.
Address of Applicant : Ruili Center Building, No.568 Taiming street. Xiaoshan District, Hangzhou City

Product Name : New Technology Pet Quadruped Robot
Brand Name : Cyberstar
Model Name : Cyber1
Sample Acquisition Method : Sent by Client
Sample No. : E25110007-01#02

FCC ID : 2BS8P-CYBER1


Standards : FCC CFR47 Part 15.247, Subpart C

Date of Receipt : 2025-11-07
Date of Test : 2025-11-19~ 2025-12-13
Date of Issue : 2025-12-16

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by:



(Erik Yang)

Reviewed by:



(Jennifer Zhou)

Approved by:



(Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 2 of 73

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
3.3	SUPPORT SOFTWARE	9
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement</i>	11
4.1.2	<i>Maximum conducted (average) output power</i>	12
4.1.3	<i>6dB Bandwidth</i>	15
4.1.4	<i>Maximum conducted output power spectral density</i>	22
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	29
4.1.6	<i>Radiated Emission</i>	52
4.1.7	<i>Band Edge (Restricted-band band-edge)</i>	53
4.2	MAINS EMISSIONS	54
4.2.1	<i>Conducted Emission on AC Mains</i>	54
5	APPENDIXES	57
5.1	EXTERNAL PHOTO OF THE SAMPLE	57
5.2	INTERNAL PHOTO OF THE SAMPLE	61
5.3	SET-UP FOR CONDUCTED EMISSIONS	72
5.4	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	72
5.5	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHz	73
5.6	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHz	73

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 3 of 73

1 General Information

1.1 Testing Laboratory

Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd
Address	No.1298, Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	Hangzhou Cyberstar Co., Ltd.
Applicant Company Address	Ruili Center Bullding, No.568 Taiming street. Xiaoshan District, Hangzhou City
Contact Person	Duan Xincheng
Telephone	+86 18868010846
Email	info@cyberstars.com.cn
Manufacturer Company Name	Hangzhou Cyberstar Co., Ltd.
Manufacturer Company Address	Ruili Center Bullding, No.568 Taiming street. Xiaoshan District, Hangzhou City

1.3 Details of EUT

Product Name	New Technology Pet Quadruped Robot
Brand Name	Cyberstar
Test Model Name	Cyber1
FCC ID	2BS8P-CYBER1
Mode of Operation	WLAN 802.11b/g/n(HT20/HT40)
Max RF Output Power	IEEE 802.11b: 17.15dBm IEEE 802.11g: 15.65dBm IEEE 802.11n(20): 14.55dBm IEEE 802.11n(40): 14.17dBm
Frequency Range	2400MHz ~ 2483.5MHz
Channel Separation	5 MHz
Number of channels	11
Modulation Type	DSSS, OFDM
Antenna Type	Internal Antenna
Antenna Gain	3.89dBi
Extreme Temperature Range	0°C~ +40°C
Test Voltage	DC 28.8V 2A by Battery Power Unit (Manufacturer: SHENZHEN GREEN DIGITAL POWER TECH CO.,LTD, Model:G168-336050, Input: AC 100-240V 2.2A 50/60Hz,

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 4 of 73

	Output: DC 33.6V 5A)
Hardware Version	V2.1
Software Version	V0.23
RF power setting in TEST SW	802.11b: adb_rtwpriv command_mp_txpower dbm=16 802.11g: adb_rtwpriv command_mp_txpower dbm=14 802.11n(HT20): adb_rtwpriv command_mp_txpower dbm=13 802.11n(HT40): adb_rtwpriv command_mp_txpower dbm=13

Note:

1. The above information was declared by the manufacture.
2. For more details, please refer to the User's manual of the EUT.

Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2.412GHz	5	2.432GHz	9	2.452GHz
2	2.417GHz	6	2.437GHz	10	2.457GHz
3	2.422GHz	7	2.442GHz	11	2.462GHz
4	2.427GHz	8	2.447GHz		

Note:

For 20MHz bandwidth system use Channel 1 to Channel 11

For 40MHz bandwidth system use Channel 3 to Channel 9

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 5 of 73

1.5 Test Summary

Test Item	FCC Rules	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	PASS
Maximum conducted (average) output power	FCC Part 15.247(b)(3)	PASS
6dB Bandwidth	FCC Part 15.247(a)(2)	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	PASS

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 6 of 73

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	15-35
Humidity (%RH)	30-60
Barometric Pressure (mbar)	860-1060

Note: Actual values will be recorded during the test.

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020A	MY54101709	2025-06-30	2026-06-29
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2025-06-10	2026-06-09
Signal Generator	Rohde & Schwarz	SMR27	100184	2025-06-30	2026-06-29
USB Wideband Power Sensor	Keysight	U2021XA	MY57200011	2025-11-10	2026-11-09
USB Wideband Power Sensor	Keysight	U2021XA	MY56090008	2025-11-10	2026-11-09
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2025-06-09	2026-06-08
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2025-06-09	2026-06-08
V-network	SCHWARZBECK	NSLK 8127	8127-902	2025-06-09	2026-06-08
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2025-06-09	2026-06-08
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2025-03-24	2027-03-23
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2025-06-22	2027-06-21
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2025-06-23	2027-06-22
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2025-06-22	2027-06-21
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2025-06-09	2026-06-08
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2025-06-10	2028-06-09
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2025-06-10	2028-06-09
Test Software	BL	BL410_E	Version:2.1.1.436	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

TEST REPORT

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission		$\pm 1.04\text{dB}$
Radiated Emission	30MHz-1GHz	$\pm 5.00\text{dB}$
	1GHz-40GHz	$\pm 5.46\text{dB}$
Conducted Emission on AC Mains	150KHz-30MHz	$\pm 3.36\text{dB}$
Occupied Channel Bandwidth		$\pm 39.26\text{KHz}$
Maximum Conducted Output Power		$\pm 1.06\text{dB}$
Maximum Conducted Output Power Spectral Density		$\pm 1.12\text{dB}$

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 8 of 73

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software to control EUT work in continuous transmitting mode. Select test channel as below:

For 802.11b/g/n (HT20)

Channel	Frequency
The lowest channel (CH1)	2412MHz
The middle channel (CH6)	2437MHz
The highest channel (CH11)	2462MHz

For 802.11n(HT40)

Channel	Frequency
The lowest channel (CH3)	2422MHz
The middle channel (CH6)	2437MHz
The highest channel (CH9)	2452MHz

Through Pre-scan under all rate at lowest channel, the data rate as below table described is the worst case, so we choose these data rate for test.

Type	Data rate
802.11b	11Mbps
802.11g	12Mbps
802.11n(20M)	MCS3
802.11n(40M)	MCS3

The basic operation modes are:

- A. On
 - 1. WLAN mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
- B. Standby
- C. Off

TEST REPORT

3.2 Special Accessories and Auxiliary Equipment


Description	Manufacturer	Model Name	Serial No.
Laptop 1	HP	HP ZHAN 66 Pro G1	5CD7438R1J
Laptop 2	Lenovo	TP00083A	PF-0PRDGN
USB Cable	N/A	N/A	1.00m Unshielded
Power Unit	GREEN DIGITAL POWER	G168-336050	2508-9575B

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	adb_rtwpriv command_mp

3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

TEST REPORT

Diagram of Measurement Equipment Configuration for Conduction Measurement




Diagram of Measurement Equipment Configuration for Transmitter Measurement





Diagram of Measurement Equipment Configuration for conducted output power setup



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 11 of 73

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard	: FCC Part 15.247(b)(4), Part 15.203
Requirement	: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.89dBi. The antenna is an Internal antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 12 of 73

4.1.2 Maximum conducted (average) output power

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3)
Requirement : ANSI C63.10-2020, Clause 11.9.2.3.1
KDB 558074 D01 v05r02, Clause 8.3.2
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 22.5°C
Relative humidity : 35%

Table 1: Maximum conducted (average) output power

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum conducted (average) output power		Limit (W)
			(dBm)	(mW)	
802.11b	100	2412	17.15	51.88	≤1
		2437	17.09	51.17	
		2462	17.14	51.76	
802.11g	100	2412	15.43	34.91	
		2437	15.29	33.81	
		2462	15.65	36.73	
802.11n(HT20)	100	2412	14.33	27.10	
		2437	14.25	26.61	
		2462	14.55	28.51	
802.11n(HT40)	100	2422	14.01	25.18	
		2437	13.99	25.06	
		2452	14.17	26.12	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 13 of 73

Figure 1: Duty Cycle, 802.11b, 2412MHz





Figure 2: Duty Cycle, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 14 of 73

Figure 3: Duty Cycle, 802.11n20, 2412MHz





Figure 4: Duty Cycle, 802.11n40, 2422MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 15 of 73

4.1.3 6dB Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.247(a)(2)

Requirement : ANSI C63.10-2020, Clause 11.8.2
KDB 558074 D01 v05r02, Clause 8.2

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 22.5°C

Relative humidity : 35%

Table 2: 6dB Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Applicable Limit (MHz)
802.11b	2412	9.02	≥0.5
	2437	9.15	
	2462	9.18	
802.11g	2412	15.05	
	2437	15.12	
	2462	15.10	
802.11n(HT20)	2412	17.52	
	2437	17.68	
	2462	17.31	
802.11n(HT40)	2422	35.19	
	2437	35.47	
	2452	35.16	

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 16 of 73

Figure 5: 6dB Bandwidth, 802.11b, 2412MHz





Figure 6: 6dB Bandwidth, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 17 of 73

Figure 7: 6dB Bandwidth, 802.11b, 2462MHz





Figure 8: 6dB Bandwidth, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 18 of 73

Figure 9: 6dB Bandwidth, 802.11g, 2437MHz





Figure 10: 6dB Bandwidth, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 19 of 73

Figure 11: 6dB Bandwidth, 802.11n(HT20), 2412MHz





Figure 12: 6dB Bandwidth, 802.11n(HT20), 2437MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 20 of 73

Figure 13: 6dB Bandwidth, 802.11n(HT20), 2462MHz





Figure 14: 6dB Bandwidth, 802.11n(HT40), 2422MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 21 of 73

Figure 15: 6dB Bandwidth, 802.11n(HT40), 2437MHz





Figure 16: 6dB Bandwidth, 802.11n(HT40), 2452MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 22 of 73

4.1.4 Maximum conducted output power spectral density

RESULT:

PASS

Test standard : FCC Part 15.247(e)
Requirement : ANSI C63.10-2020, Clause 11.10.3
KDB 558074 D01 v05r02, Clause 8.4
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 22.5°C
Relative humidity : 35%

Table 3: Maximum (average) conducted output power spectral density

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum (average) conducted output power spectral density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	100	2412	-12.97	≤8
		2437	-13.43	
		2462	-13.11	
802.11g	100	2412	-14.94	
		2437	-14.44	
		2462	-14.28	
802.11n(HT20)	100	2412	-18.55	
		2437	-18.41	
		2462	-18.11	
802.11n(HT40)	100	2422	-21.16	
		2437	-20.89	
		2452	-20.76	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured PSD to compute the average PSD during the actual transmission time

TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 23 of 73

Figure 17: Power Spectral Density, 802.11b, 2412MHz





Figure 18: Power Spectral Density, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 24 of 73

Figure 19: Power Spectral Density, 802.11b, 2462MHz





Figure 20: Power Spectral Density, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 25 of 73

Figure 21: Power Spectral Density, 802.11g, 2437MHz





Figure 22: Power Spectral Density, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 26 of 73

Figure 23: Power Spectral Density, 802.11n(HT20), 2412MHz





Figure 24: Power Spectral Density, 802.11n(HT20), 2437MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 27 of 73

Figure 25: Power Spectral Density, 802.11n(HT20), 2462MHz





Figure 26: Power Spectral Density, 802.11n(HT40), 2422MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 28 of 73

Figure 27: Power Spectral Density, 802.11n(HT40), 2437MHz





Figure 28: Power Spectral Density, 802.11n(HT40), 2452MHz



TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 29 of 73

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.209
Requirement	: ANSI C63.10-2020, Clause 11.11.1 KDB 558074 D01 v05r02, Clause 8.5
Kind of test site	: Shielded room

Test setup

Test Channel	: Low/Middle/High for spurious, Low/High for Band Edge
Operation Mode	: A.1.a
Ambient temperature	: 22.5°C
Relative humidity	: 35%

For details refer to following test plot.


TEST REPORT

Report No.: SHE25110007-01AE

Date: 2025-12-16

Page 30 of 73

Figure 29: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2412MHz Carrier Level



Band Edge

