

DC Charger For Electric Vehicles	
Product Name: <u>DC Charging Station</u>	Type Designation: <u>ANSI-DCL360B</u>
Rated Output Power: <u>360kW</u>	Environmental Condition: <u>Indoor/Outdoor</u>
Number Of Phases: <u>3P+N+PE</u>	Rated Input Frequency: <u>50/60Hz</u>
Input Voltage: <u>AC480V±10%</u>	Rated Input Current: <u>434A</u>
Output Voltage: <u>DC200~1000V</u>	Output Current: <u>0-600A</u>
Single Output Power: <u>300kW</u>	Single Output Current: <u>0-300A</u>
Operating Temperature: <u>-25~+55°C</u>	IP Degree: <u>IP54</u>
FCC ID: <u>2BS9EANSIDC</u>	contain FCC ID: <u>XMR201909EC25AFX</u>
Factory Code: _____	Production Date: _____



CONFORMS TO ILL. STD. 2202
CERTIFIED TO CSA STD. C22.2#346
CANICES-002(A)/NMB-002(A) FOR USE WITH ELECTRIC
VEHICLES, TYPE 4 ENCLOSURE conforms to UL Std. 2202/
Certified to CSA Std. C22.2#346 INDOOR/OUTDOOR USE.
VENTILATION NOT REQUIRED, OPERATING TEMP -25°C TO 55°C







Shenzhen Hongjiali New Energy Co., Ltd

