

Shenzhen Xiangboyi Technology Co. Ltd

Specification Confirmation Letter

一. Test System and Equipment

二. Product Description

三. Device Description

四. Matching Circuits

五. Active Test Tata

六. EngineeringDrawing

—. Test System and Equipment

	ITEM	Equipment
S parameter	Return Loss VSWR	Network Analyzer A338/A333 HP8753D
Active testing	1. TRP 2. TIS	Comprehensive testing instrument Agilent 8960 CMW500
Passive Test		Darkroom: 5 * 3 * 3 Network analyzer: HP8753D



二. Product Description

Technical requirements	Technical index	NOTE
Band	BT	
Range Of Frequency	BT: 2400-2500Mhz	
VSWR	2400-2500Mhz<3.0	Center Frequency
Impedance	50 Ω	
Polarization	Linear polarization	
operating temperature	-20℃ / +55℃	
storage temperature	-25℃ / +65℃	
Salt Fog	24h (24h alternating wet & dry)	
RoHS Compliant	yes	

≡. Device Description


EUT PHOTO



ANT PHOTO



四. Matching Circuits



Element	Value	Vender
E1(0201)	NA	
E2(0201)	0Ω	
E3(0201)	NA	
E4(0201)	0Ω	

五. Active Test Data

WIFI BAND	802.11a : 54Mbps (5G)					
Channel	CH36	CH149	CH161			
TRP	12.92	13.36	13.06			
TIS			-71.31			

WIFI BAND	802.11b : 11Mbps (2.4G)			802.11g : 54Mbps (2.4G)		
Channel	CH1	CH6	CH11	CH1	CH6	CH11
TRP	16.54	16.47	16.82	12.62	12.25	12.57
TIS			-82.85			-70.88


WIFI BAND	802.11n : MCS7 (2.4G)					
Channel	CH1	CH6	CH11			
TRP	12.92	12.67	12.59			
TIS			-71.39			

2024/08/08 14:00


BT		
Freq (MHz)	Eff1 (%)	Gain (dBi)
2400	44.95	1.44
2410	43.35	1.29
2420	45.42	1.46
2430	46.31	0.54
2440	45.79	1.52
2450	42.11	0.36
2460	45.5	1.24
2470	41.8	0.74
2480	41.63	2.43
2490	45.95	2.26
2500	42.45	4.17

BT


Horizontal



E1 Face



E2 Face



六. Engineering Drawing

