

FCC&IC TEST REPORT

Report No..... : AB25090098FW02

FCC ID..... : **2BSMF-ZEN75**

IC..... : **34643-ZEN75**

Applicant..... : Shanhaihehe (shenzhen) culture media Co., Ltd.

Address..... : 501(6B) Taihuawutongdao Hangcheng Road, Baoan, Shenzhen

Manufacturer..... : Shanhaihehe (shenzhen) culture media Co., Ltd.

Address..... : 501(6B) Taihuawutongdao Hangcheng Road, Baoan, Shenzhen

Product Name..... : Tri-Mode Low-Profile Mechanical Keyboard

Trade Mark..... :  **CERAKEY**

Test Model..... : ZEN75

Additional Model(s)..... : /


Standard..... : FCC 47 CFR Part 15 Subpart C (Part 15.249);Canada RSS-Gen Issue 5 (2018-04);Canada RSS-Gen Amendment 1 (2019-03);Canada RSS-Gen Amendment 2 (2021-02);Canada RSS-210 Issue 11 (2024-06)

Date of Receipt..... : 2025.12.02

Date of Test Date..... : 2025.12.02-2025.12.10

Date of Issue..... : 2025.12.10

Test Result..... : Pass

Compiled by:	Huaijie Li	
(Printed Name + Signature)		-----
Supervised by:	David Huang	
(Printed Name + Signature)		-----
Approved by:	Jay Liu	
(Printed Name + Signature)		-----

Testing Laboratory Name..... : Aibo Standard Technology (Shenzhen) Co., Ltd.

Address..... : 101, Building B, Tuori New Energy Industrial Park, High-tech Park,
Tianliao Community, Yutang Street, Guangming District, Shenzhen
City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC&IC TEST REPORT

EUT.....	: Tri-Mode Low-Profile Mechanical Keyboard
Test Model.....	: ZEN75
Applicant.....	: Shanhaihehe (shenzhen) culture media Co., Ltd.
Address.....	: 501(6B) Taihuawutongdao Hangcheng Road, Baoan, Shenzhen
Manufacturer.....	: Shanhaihehe (shenzhen) culture media Co., Ltd.
Address.....	: 501(6B) Taihuawutongdao Hangcheng Road, Baoan, Shenzhen
Factory.....	: Foshan IF2 Electronic Intelligent Manufacturing Co.,LTD
Address.....	: 7thFloor,Building10A,CIMC,No.15ShunyeWestRoad,XingtanTown,Shunde District,Foshancity,China

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

REPORT VERSION

Version No.	Issue Date	Description
01	2025.12.10	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. GENERAL DESCRIPTION OF EUT	5
1.2. DESCRIPTION OF SUPPORT EQUIPMENT	6
1.3. DESCRIPTION OF EXTERNAL I/O	6
1.4. GENERAL DESCRIPTION OF APPLIED STANDARDS	7
1.5. DESCRIPTION OF TEST FACILITY	7
1.6. MEASUREMENT UNCERTAINTY	8
1.7. ENVIRONMENTAL CONDITIONS	8
1.8. DESCRIPTION OF TEST MODES	9
2. SUMMARY OF TEST RESULT	11
3. MEASUREMENT INSTRUMENTS LIST	12
4. RADIATED EMISSIONS MEASUREMENT	13
4.1. LIMIT	13
4.2. TEST SETUP	14
4.3. TEST PROCEDURE	15
4.4. TEST RESULT	16
5. 20DB BANDWIDTH AND OCCUPIED BANDWIDTH	21
5.1. LIMIT	21
5.2. TEST SETUP	21
5.3. TEST PROCEDURE	21
5.4. TEST RESULT	22
6. POWER LINE CONDUCTED EMISSION	24
6.1. LIMIT	24
6.2. TEST SETUP	24
6.3. TEST PROCEDURE	24
6.4. TEST RESULT	25
7. PHOTOGRAPHS OF TEST SETUP	28
8. EXTERNAL PHOTOGRAPHS OF THE EUT	28
9. INTERNAL PHOTOGRAPHS OF THE EUT	28

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	Tri-Mode Low-Profile Mechanical Keyboard
Trade Mark:	 CERAKEY
Test Model:	ZEN75
Additional Model(s):	/
Model Difference:	/
Hardware Version:	0020
Software Version:	V0.3.14
Power Supply:	Battery 3.7V,1800mAh*2, 6.66Wh Charged By DC Port or 5V DC port
Test Sample(s) Number:	AB25090098-01 (Engineer Sample)
Radio Specification Subject to this Report	
Frequency Range:	2404-2476MHz
Modulation Type:	GFSK
Channel Spacing:	$\geq 6\text{MHz}$
Channel Number(s):	16
Antenna Type:	Internal Antenna
Antenna Gain:	2.59dBi(Max.)

1.2. DESCRIPTION OF SUPPORT EQUIPMENT

Manufacturer	Description	Model	Serial Number	Certificate
Lenovo	Notebook	B470	WB05067151	CE
Shenzhen ACT Industrial Co., Ltd.	Fast Charger	APS-KI015AWE-G	---	Applicant

1.3. DESCRIPTION OF EXTERNAL I/O

I/O Port Description	Quantity	Cable
/	/	/

1.4. GENERAL DESCRIPTION OF APPLIED STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#) - Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz and 24.0-24.25 GHz.

[IEEE/ANSI/USEMCSC C63.10-2020](#) - American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

[Canada RSS-210 Issue 11 \(2024-06\)](#)-Licence-Exempt Radio Apparatus:CategoryI Equipment

[Canada RSS-Gen Issue 5 \(2018-04\)](#)-General Requirements forCompliance of Radio

Apparatus

[Canada RSS-Gen Amendment 1 \(March 2019\)](#)- A minor amendment has been made to section 3.6 Related documents toadd a reference to Radio Standards Specification (RSS-HAC), Hearing AidCompatibility and Volume Control, which shall be used in conjunction withapplicable RsS(s).

[Canada RSS-Gen Amendment 2 \(February 2021\)](#)-Radio Standards Procedure RSP-102, Special Authorization Procedure forTerminal, Radio, Broadcasting and Interference-Causing Equipment to beCertified, Registered or Deemed in Compliance With Technical EquipmentStandards,replaces section 2.9 of this document.

1.5. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: aibo@aibonorm.com

Website: www.Aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

Company Number: 33924

CAB identifier: CN0185

1.6. MEASUREMENT UNCERTAINTY

The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Items	Measurement Uncertainty
Power Line Conducted Emission (9kHz~ 150kHz)	±3.62dB
Power Line Conducted Emission (150kHz~30MHz)	±3.38dB
Radiated Emission (9kHz~30MHz)	±3.10dB
Radiated Emission (30MHz~ 1GHz)	±4.90dB
Radiated Emission (1GHz~ 18GHz)	±3.88dB
Radiated Emission (8GHz~40GHz)	±5.32dB
RF Conducted Power	±0.57dB
Conducted Spurious Emissions	±1.60dB
RF Frequency	±6.0 x 10 ⁻⁷
Occupied Channel Bandwidth	±28.87KHz

Note: All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95 % level of confidence.

1.7. ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	+15°C ~ +35°C
Lative Humidity	20 % ~ 75 %
Air Pressure	98KPa ~ 101KPa

1.8. DESCRIPTION OF TEST MODES

The EUT was tested under the following mode.

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	BW	
A	√	√	√	√	DC 3.7V from Battery or USB Port
RE<1G: Radiated Emission below 1GHz RE≥1G: Radiated Emission above 1GHz PLC: Power Line Conducted Emission BW: 20db bandwidth					

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	TESTED FREQUENCY
Low	2404 MHz
Middle	2438 MHz
High	2476 MHz

Channel List

Channel	Freq. (MHz)
1	2404
2	2408
3	2414
4	2418
5	2422
6	2426
7	2436
8	2438
9	2440
10	2444
11	2452
12	2458
13	2462
14	2466
15	2470
16	2476

Note: The more detailed channel, please refer to the product specifications

Power setting during the test:

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Frequency	2404MHz	2438MHz	2476MHz
RF Power Parameter(s)	Default	Default	Default

2. SUMMARY OF TEST RESULT

FCC 47 CFR Part 15 Subpart C (SECTION 15.249)&RSS-210 Test Cases			
FCC&IC Rule	Description of Test Item(s)	Result	REMARK
Part 15.203	Antenna Requirement	Pass	No antenna connector is used
Part 15.207(a) RSS-Gen 8.8	Conducted Emission	Pass	Compliant
Part 15.205 RSS-Gen 8.10 Table 7	Restricted Band of Operation	Pass	Compliant
Part 15.209,Part 15.249(a) RSS-210B10 (a),B10 (b)	Radiated Emission	Pass	Compliant
Part 15.215(c) RSS-Gen 6.7	20dB Bandwidth Test&Occupied Bandwidth Measuremen	Pass	Compliant

3. MEASUREMENT INSTRUMENTS LIST

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	EMI Test Receiver	R&S	ESCI	101196	01/20/2025	01/19/2026
2	Loop Antenna	Schwarzbeck	FMZB 1519	1519-025	02/19/2025	02/18/2026
3	Power Amplifier	HZEMC	HPA-9K0133	HYP A23029	02/19/2025	02/18/2026
4	Broadband Antenna	Schwarzbeck	VULB 9168	01763	02/19/2025	02/18/2026
5	Attenuator	PRM	ATT50-6-3	ATT50-6-3	01/20/2025	01/19/2026
6	Spectrum Analyzer	R&S	FSV40-N	101365	01/20/2025	01/19/2026
7	Horn Antenna	Schwarzbeck	BBHA 9120 D	02786	02/19/2025	02/18/2026
8	Horn Antenna	Schwarzbeck	ZLB7-18-40G-77	072410839	02/19/2025	02/18/2026
9	Power Amplifier	HZEMC	PA0118-43	HYP A23030	02/19/2025	02/18/2026
10	Power Amplifier	HZEMC	PA01840-45	HYP A23031	02/19/2025	02/18/2026
11	Spectrum Analyzer	R&S	FSV40-N	101365	01/20/2025	01/19/2026
12	MXG Vector Signal Generator	Agilent	N5182A	MY47070153	01/20/2025	01/19/2026
13	MXA Signal Analyzer	Keysight	N9020A	MY52091389	01/20/2025	01/19/2026
14	RF Automatic Test System (Included Power Sensor)	MWRFTest	MW100-RFCB	MW220802AB-44	01/20/2025	01/19/2026
15	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	118780	01/20/2025	01/19/2026
16	DC POWER SUPPLY	MAISHENG	MT-305DS	2021040016	02/28/2025	02/27/2026
17	Const Temp. & Humidity Chamber	GRT	GR-HWX-150L	GR25010601	01/20/2025	01/19/2026
18	EMI Test Receiver	R&S	ESCI	101196	01/20/2025	01/19/2026
19	LISN	R&S	ENV216	102374	01/20/2025	01/19/2026
20	Pulse Limiter	Schwarzbeck	ESH3-Z2	0357.8810.54	01/20/2025	01/19/2026
21	ISN CAT6	Schwarzbeck	NTFM	#246	01/20/2025	01/19/2026

Test Software		
Software name	Model	Version
Conducted Emission Measurement Software	FASLAB	V4.1
Radiated Emission Measurement Software	FASLAB	V4.1
Bluetooth and WIFI Test System	MTS 8310	V3.0.0.0

4. RADIATED EMISSIONS MEASUREMENT

4.1. LIMIT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in FCC 15.209 and IC RSS-210 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to § 15.249(a) and IC RSS-210, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in § 15.35 for limiting peak emissions apply.

NOTE:


1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2. TEST SETUP


Below 30MHz test setup



Below 1GHz test setup



Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.3. TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.4. TEST RESULT

Radiated Spurious Emissions 9kHz~1GHz, the worst case middle channel in the Radiated Spurious Emissions above 1GHz was tested.

Radiated Emission Test Data (30MHz to 1GHz)

Environmental Conditions	24.6°C , 53.4% RH	Test Engineer	He Chen
Worst Test Mode:	TX Middle Channel	Polarity:	Horizontal



No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
1	95.960	34.24	-16.68	17.56	43.50	25.94	QPK	100	H	225.8	PASS
2	143.490	28.01	-12.39	15.62	43.50	27.88	QPK	100	H	221.5	PASS
3	268.620	40.93	-13.29	27.64	46.00	18.36	QPK	100	H	9.2	PASS
4	321.000	46.76	-11.6	35.16	46.00	10.84	QPK	100	H	96.1	PASS
5	366.590	43.98	-10.64	33.34	46.00	12.66	QPK	100	H	292.0	PASS
6	520.820	31.71	-7.17	24.54	46.00	21.46	QPK	100	H	273.7	PASS

Remark:

Emission Level = Reading + Factor;


Factor = Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Limit - Emission Level.

9KHz~30MHz have been test and test data more than 20dB margin.

Radiated Emission Test Data (30MHz to 1GHz)

Environmental Conditions	24.6°C , 53.4% RH	Test Engineer	Jacey Fu
Worst Test Mode:	TX Middle Channel	Polarity:	Vertical



No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
1	44.550	27.55	-13.21	14.34	40.00	25.66	QPK	100	V	160.3	PASS
2	142.520	25.05	-12.49	12.56	43.50	30.94	QPK	100	V	64.7	PASS
3	313.240	38.50	-11.83	26.67	46.00	19.33	QPK	100	V	57.4	PASS
4	369.500	37.80	-10.52	27.28	46.00	18.72	QPK	100	V	156.8	PASS
5	526.640	32.45	-7	25.45	46.00	20.55	QPK	100	V	360.0	PASS
6	619.760	31.39	-4.9	26.49	46.00	19.51	QPK	100	V	31.4	PASS

Remark:

Emission Level = Reading + Factor;

Factor = Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Limit - Emission Level.

9KHz~30MHz have been test and test data more than 20dB margin.

ABOVE 1GHz WORST-CASE DATA:

Field strength of fundamental&Radiated Emission Test Data (Above 1GHz)							
Environmental Conditions			24.6℃ , 53.4% RH		Test Engineer		He Chen
Lowest Channel (Worst Case: 2.4G_2404MHz)							
Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (PEAK/AVG)	Polar (H/V)
1196.000	51.92	-11.74	40.18	74.00	33.82	PK+	H
1198.000	47.95	-11.72	36.23	54.00	17.77	AVG	H
2390.000	47.14	-8.68	38.46	54.00	15.54	AVG	H
2392.000	52.63	-8.68	43.95	74.00	30.05	PK+	H
*2404.000	92.72	-3.57	89.15	-	-	PK+	H
*2404.000	86.21	-3.57	82.64	-	-	AVG	H
4995.000	49.37	-12.68	36.69	74.00	37.31	PK+	H
5010.000	38.89	-12.65	26.24	54.00	27.76	AVG	H
1774.000	53.55	-10.9	42.65	74.00	31.35	PK+	V
1966.000	47.99	-9.94	38.05	54.00	15.95	AVG	V
2390.000	51.74	-8.68	43.06	54.00	10.94	AVG	V
2392.000	55.32	-8.68	46.64	74.00	27.36	PK+	V
*2404.080	90.87	-3.57	87.30	-	-	PK+	V
*2404.080	83.82	-3.57	80.25	-	-	AVG	V
4785.000	56.66	-14.24	42.42	74.00	31.58	PK+	V
4785.000	45.23	-14.24	30.99	54.00	23.01	AVG	V
Middle Channel (Worst Case: 2.4G_2438MHz)							
Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (PEAK/AVG)	Polar (H/V)
1198.000	48.44	-11.72	36.72	54.00	17.28	AVG	H
1200.000	51.06	-11.7	39.36	74.00	34.64	PK+	H
1782.000	50.85	-10.87	39.98	74.00	34.02	PK+	H
1782.000	47.06	-10.87	36.19	54.00	17.81	AVG	H
*2438.080	95.79	-3.54	92.25	-	-	PK+	
*2438.080	88.42	-3.54	84.88	-	-	AVG	
2392.000	52.24	-8.68	43.56	74.00	30.44	PK+	H
2392.000	47.59	-8.68	38.91	54.00	15.09	AVG	H
1198.000	46.51	-11.72	34.79	54.00	19.21	AVG	V
1200.000	51.50	-11.7	39.80	74.00	34.20	PK+	V
2390.000	59.46	-8.68	50.78	74.00	23.22	PK+	V
2390.000	57.06	-8.68	48.38	54.00	5.62	AVG	V
*2438.080	93.59	-3.54	90.05	-	-	PK+	
*2438.080	86.24	-3.54	82.70	-	-	AVG	
4770.000	53.90	-14.36	39.54	74.00	34.46	PK+	V
4770.000	43.40	-14.36	29.04	54.00	24.96	AVG	V

Highest Channel (Worst Case: 2.4G_2476MHz)							
Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (PEAK/AVG)	Polar (H/V)
1196.000	51.31	-11.74	39.57	74.00	34.43	PK+	H
1196.000	47.56	-11.74	35.82	54.00	18.18	AVG	H
2390.000	53.47	-8.68	44.79	74.00	29.21	PK+	H
2392.000	50.29	-8.68	41.61	54.00	12.39	AVG	H
*2476.060	97.53	-3.51	94.02	-	-	PK+	H
*2476.060	90.30	-3.51	86.79	-	-	AVG	H
2696.000	55.37	-8.35	47.02	74.00	26.98	PK+	H
2696.000	49.46	-8.35	41.11	54.00	12.89	AVG	H
1198.000	50.86	-11.72	39.14	74.00	34.86	PK+	V
1198.000	47.53	-11.72	35.81	54.00	18.19	AVG	V
1396.000	47.79	-11	36.79	54.00	17.21	AVG	V
1396.000	49.66	-11	38.66	74.00	35.34	PK+	V
1770.000	54.64	-10.92	43.72	74.00	30.28	PK+	V
1770.000	47.34	-10.92	36.42	54.00	17.58	AVG	V
*2476.060	93.44	-3.51	89.93	-	-	PK+	V
*2476.060	86.48	-3.51	82.97	-	-	AVG	V
Remark: Emission Level = Reading + Factor; Factor = Antenna Factor + Cable Loss – Pre-amplifier; Margin= Limit - Emission Level. Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 18GHz to 25GHz.							

Radiated Band Edges Test Data							
Environmental Conditions			24.6℃ , 53.4% RH		Test Engineer		He Chen
Lowest Channel (Worst Case: 2.4G_2404MHz)							
Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (PEAK/AVG)	Polar (H/V)
2310.000	46.94	-3.34	43.60	74.00	30.40	PK+	H
2390.080	54.41	-3.55	50.86	74.00	23.14	PK+	H
2399.880	62.36	-3.58	58.78	74.00	15.22	PK+	H
2310.000	33.39	-3.34	30.05	54.00	23.95	AVG	H
2390.080	33.98	-3.55	30.43	54.00	23.57	AVG	H
2399.880	34.36	-3.58	30.78	54.00	23.22	AVG	H
2310.000	45.62	-3.34	42.28	74.00	31.72	PK+	V
2390.080	53.67	-3.55	50.12	74.00	23.88	PK+	V
2399.880	60.45	-3.58	56.87	74.00	17.13	PK+	V
2310.000	33.44	-3.34	30.10	54.00	23.90	AVG	V
2390.080	34.12	-3.55	30.57	54.00	23.43	AVG	V
2399.880	34.80	-3.58	31.22	54.00	22.78	AVG	V
Highest Channel Worst Case: 2.4G_2476MHz)							
Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (PEAK/AVG)	Polar (H/V)
2483.440	62.85	-3.51	59.34	74.00	14.66	PK+	H
2500.000	51.87	-3.5	48.37	74.00	25.63	PK+	H
2483.440	34.30	-3.51	30.79	54.00	23.21	AVG	H
2500.000	34.25	-3.5	30.75	54.00	23.25	AVG	H
2483.440	56.71	-3.51	53.20	74.00	20.80	PK+	V
2500.000	48.32	-3.5	44.82	74.00	29.18	PK+	V
2483.440	34.16	-3.51	30.65	54.00	23.35	AVG	V
2500.000	34.30	-3.5	30.80	54.00	23.20	AVG	V
Remark: Emission Level = Reading + Factor; Factor = Antenna Factor + Cable Loss – Pre-amplifier; Margin= Limit - Emission Level. The emission levels of other frequencies were greater than 20dB margin.							


5. 20DB BANDWIDTH AND OCCUPIED BANDWIDTH

5.1. LIMIT

According to FCC 15.215(c) and RSS-Gen, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

According to RSS-Gen 6.7, The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

5.2. TEST SETUP



5.3. TEST PROCEDURE

For 20dB Bandwidth Measurement:

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.
- The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB. Measured the 20dB bandwidth by related function of the spectrum analyzer.


For 99% Occupied Bandwidth Measurement:

- Span = approximately 1.5 to 5 times the OBW, centered on the test channel.
- RBW = 1% to 5% of the OBW.
- $VBW \geq 3 \times RBW$
- Sweep = auto;
- Detector function = peak
- Trace = max hold
- Use the 99% power bandwidth function of the instrument to measure the Occupied Bandwidth and recoded.

5.4. TEST RESULT

CHANNEL	CHANNEL FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	20dB BANDWIDTH (MHz)
Low	2404	2.063	2.325
Middle	2438	2.0755	2.310
High	2476	2.0656	2.310

Test Data: Low channel



Test Data: Middle channel



Test Data: High channel



6. POWER LINE CONDUCTED EMISSION

6.1. LIMIT


According to the rule FCC Part 15.207 and IC RSS-Gen 8.8, Conducted emissions limit, the limit for a wireless device as below:

Frequency Range (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15~0.5	66 to 56	56 to 46
0.5~5	56	46
5~30	60	50

Remark:

- The lower limit shall apply at the transition frequencies.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50MHz.

6.2. TEST SETUP



6.3. TEST PROCEDURE

Test frequency range :150KHz-30MHz

- The mains terminal disturbance voltage test was conducted in a shielded room.
- The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal

ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane.

This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

e) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4. TEST RESULT


Pass.

Remark:

For AC line conducted emissions, the maximum peak output power 2476MHz channel was tested.

Test Plots and Data of Conducted Emissions (2.4G_2476MHz)

Environmental Conditions	24.6°C , 53.4% RH	Test Engineer	He Chen
Test Voltage:	120V/60Hz	Test Power Line:	Line



No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE
1	0.228	16.32	9.99	26.31	62.52	36.21	QPK	L1	GND
2	0.228	8.56	9.99	18.55	52.52	33.97	AVG	L1	GND
3	0.404	22.25	9.99	32.24	57.77	25.53	QPK	L1	GND
4	0.404	15.32	9.99	25.31	47.77	22.46	AVG	L1	GND
5	0.472	27.79	9.99	37.78	56.48	18.70	QPK	L1	GND
6	0.472	20.80	9.99	30.79	46.48	15.69	AVG	L1	GND
7	0.657	17.56	10	27.56	56.00	28.44	QPK	L1	GND
8	0.657	8.37	10	18.37	46.00	27.63	AVG	L1	GND
9	0.743	19.68	10	29.68	56.00	26.32	QPK	L1	GND
10	0.743	7.55	10	17.55	46.00	28.45	AVG	L1	GND
11	0.915	15.92	10.01	25.93	56.00	30.07	QPK	L1	GND
12	0.915	8.00	10.01	18.01	46.00	27.99	AVG	L1	GND

Remark:


Emission Level = Reading + Correct Factor;

Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Attenuation Factor

Margin= Emission Level - Limit.

Test Plots and Data of Conducted Emissions (2.4G_2476MHz)

Environmental Conditions	24.6°C , 53.4% RH	Test Engineer	He Chen
Test Voltage:	120V/60Hz	Test Power Line:	Neutral



No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV)	Limit (dBμV)	Margin (dB)	Det.	Line	PE
1	0.390	19.66	9.99	29.65	58.06	28.41	QPK	N	GND
2	0.390	6.87	9.99	16.86	48.06	31.20	AVG	N	GND
3	0.472	22.58	9.99	32.57	56.48	23.91	QPK	N	GND
4	0.472	11.03	9.99	21.02	46.48	25.46	AVG	N	GND
5	0.754	16.18	10	26.18	56.00	29.82	QPK	N	GND
6	0.754	-0.19	10	9.81	46.00	36.19	AVG	N	GND
7	1.067	11.41	10.01	21.42	56.00	34.58	QPK	N	GND
8	1.067	0.41	10.01	10.42	46.00	35.58	AVG	N	GND
9	1.784	10.84	10.02	20.86	56.00	35.14	QPK	N	GND
10	1.784	-0.03	10.02	9.99	46.00	36.01	AVG	N	GND
11	2.536	10.02	10.03	20.05	56.00	35.95	QPK	N	GND
12	2.536	-0.23	10.03	9.80	46.00	36.20	AVG	N	GND

Remark:

Emission Level = Reading + Correct Factor;

Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Attenuation Factor

Margin= Emission Level - Limit.

7. PHOTOGRAPHS OF TEST SETUP

Please refer to Appendix B for Test Setup Photos of the EUT.

8. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to Appendix C for External Photos of the EUT.

9. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to Appendix D for Internal Photos of the EUT.

*****THE END*****