

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2BSMX-UR35-OAWA

EUT Specification

EUT	Industrial Router
Frequency band (Operating)	☒ WIFI: 2.412GHz ~ 2.462GHz ☒ LTE Band 2: TX 1850MHz -1910MHz, RX 1930MHz -1990MHz ☒ LTE Band 4: TX 1710MHz -1755MHz, RX 2110MHz -2155MHz ☒ LTE Band 5: TX 824MHz -849MHz, RX 869MHz -894MHz ☒ LTE Band 12: TX 699MHz -716MHz, RX 729MHz -746MHz ☒ LTE Band 13: TX 777MHz -787MHz, RX 746MHz -756MHz ☒ LTE Band 14: TX 788MHz -798MHz, RX 758MHz -768MHz ☒ LTE Band 66: TX 1710MHz -1780MHz, RX 2110MHz -2200MHz ☒ LTE Band 71: TX 663MHz -698MHz, RX 617MHz -652MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	2.4G WIFI: 15.42 dBm LTE Band 2: 22.49 dBm LTE Band 4: 22.82 dBm LTE Band 5: 23.50 dBm LTE Band 12: 23.55 dBm LTE Band 13: 23.72 dBm LTE Band 14: 23.81 dBm LTE Band 66: 22.61 dBm LTE Band 71: 23.22 dBm

Antenna gain (Max)	2.4G WIFI: 3.89 dBi LTE Band 2: 2.17 dBi LTE Band 4: 2.17 dBi LTE Band 5: -2.45 dBi LTE Band 12: 0.82 dBi LTE Band 13: 0.82 dBi LTE Band 14: 0.82 dBi LTE Band 66: 2.17 dBi LTE Band 71: -0.10 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm², P_{out} = output power to antenna in mW.

G = gain of antenna in linear scale, $\pi = 3.1416$

R = distance between observation point and center of the radiator in cm = 20cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$Evaluated_k$: the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$: either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k .

Measurement Result

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
2.4G WIFI	15.42	15±1	16	39.811	3.89	2.449	0.01940	1
LTE Band 2	22.49	22±1	23	199.526	2.17	1.648	0.06542	1
LTE Band 4	22.82	22±1	23	199.526	2.17	1.648	0.06542	1
LTE Band 5	23.50	23±1	24	251.189	-2.45	0.569	0.02843	0.55
LTE Band 12	23.55	23±1	24	251.189	0.82	1.208	0.06036	0.47
LTE Band 13	23.72	23±1	24	251.189	0.82	1.208	0.06036	0.52
LTE Band 14	23.81	23±1	24	251.189	0.82	1.208	0.06036	0.53
LTE Band 66	22.61	22±1	23	199.526	2.17	1.648	0.06542	1
LTE Band 71	23.22	23±1	24	251.189	-0.10	0.977	0.04883	0.44

Maximum Simultaneous transmission MPE Ratio for 4G & 2.4G WIFI

Maximum MPE ratio (4G)	Maximum MPE ratio (2.4G WIFI)	Σ MPE ratios	Limit	Results
0.12843	0.01940	0.14783	1.000	Pass

Signature:



Alan He
Date: 2026-4-10