

RF EXPOSURE EVALUATION

Equipment under test: Farrowing detector

FCC ID: 2BSNU-EFSV01SEN01

Test report reference: RRA-EMIESS24H695RFT-5A v0

MPE calculation

These equations are generally accurate in the far field of an antenna but will over predict power density in the near field, where they could be used for making a "worst case" prediction.

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)
P = power input to the antenna (in appropriate units e.g. mW)
G = power gain of the antenna in the direction of interest relative to the isotropic radiator
R = distance to the centre of radiation of the antenna (appropriate units e.g. cm)

Or

$$S = EIRP/4\pi R^2$$

Where EIRP = equivalent isotropically radiated power

Calculation:

(Calculated for max. EIRP)

EIRP: 12.9 dBm (19.4 mW) for f=915.0 MHz

Calculated at distance of 20 cm:

Power density = 0.17 mW/cm²

Limit:

3.05 mW/cm² is the reference level for G Exposure according to Rule part 1.1310(e)

Ed.	Date	Modified page(s)	Technical Verification and Quality Approval Name / Visa
0	05/12/2025	Creation	 Pellerin Bruno Technical Entity Manager



