



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT


FCC PART 15 SUBPART C 15.249

Report Reference No.....: CTL2603274021-WF02

Compiled by: Jayden Zhuo
(position+printed name+signature)

Tested by: Happy Guo
(position+printed name+signature)

Approved by: Ivan Xie
(position+printed name+signature)



Product Name.....: Internet of Things Radio

Model/Type reference.....: DMD-2H1-R2

List Model(s).....: N/A

Trade Mark.....: N/A

FCC ID.....: 2BSOF-DMD-2H1-R2

Applicant's name.....: Shenzhen Damoda Intelligent Control Technology Co., Ltd.

Address of applicant.....: 4901,Block C, Minzhi Stock Business Center, Minzhi St, Longhua Dist, Shenzhen, China

Test specification.....:

Standard.....: **FCC Part 15.249:**Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of receipt of test item.....: April. 10, 2026

Date of Test Date.....: April. 10, 2026-May. 27, 2026

Date of Issue.....: May. 28, 2026

Result.....: **Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. : CTL2603274021-WF02	May. 28, 2026 Date of issue
---	--------------------------------

Equipment under Test : Internet of Things Radio

Sample No. CTL260327102005, CTL260327102006

Model /Type : DMD-2H1-R2

Listed Models : N/A

Applicant : Shenzhen Damoda Intelligent Control Technology Co., Ltd.

Address : 4901,Block C, Minzhi Stock Business Center, Minzhi St, Longhua Dist, Shenzhen, China

Manufacturer : Shenzhen Damoda Intelligent Control Technology Co., Ltd.

Address : 4901,Block C, Minzhi Stock Business Center, Minzhi St, Longhua Dist, Shenzhen, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

**** Modified History ****

[illegible]

Table of Contents**Page**

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY.....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
1.5. AUXILIARY TEST EQUIPMENT INFORMATION.....	7
2. GENERAL INFORMATION.....	8
2.1. ENVIRONMENTAL CONDITIONS.....	8
2.2. GENERAL DESCRIPTION OF EUT.....	8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	8
2.4. EQUIPMENTS USED DURING THE TEST.....	9
2.5. RELATED SUBMITTAL(S) / GRANT(S).....	10
2.6. MODIFICATIONS.....	10
3. TEST CONDITIONS AND RESULTS.....	11
3.1. CONDUCTED EMISSIONS TEST.....	11
3.2. RADIATED EMISSIONS.....	14
3.3. OCCUPIED BANDWIDTH MEASUREMENT.....	34
3.4. ANTENNA REQUIREMENT.....	37
4. TEST SETUP PHOTOS OF THE EUT.....	38
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....	38

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#): Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 -24.25 GHz.

[ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices.

1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.203	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
Address 1:	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
Address 2:	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.2 Test location

All tests were performed at:

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
☐ Main location	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
☒ Satellite location	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.3 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC CAB identifier: CN0041

Main Company Number :9618B

Satellite Company Number:35187

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Main Company Number:9618B and Satellite Company Number:35187.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No.: CN1216. Test Firm Registration 399832.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co.,

Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test Item	Measurement Uncertainty	Notes
Transmitter power Radiated	± 2.20 dB	(1)
Occupied Bandwidth	± 0.02 ppm	(1)
Radiated Emission 30~1000MHz	± 4.08 dB	(1)
Radiated Emission Above 1GHz	± 4.32 dB	(1)
Conducted Disturbance 0.15~30MHz	± 2.96 dB	(1)
20dB Emission Bandwidth	$\pm 1.9\%$	(1)
Carrier Frequency Separation	$\pm 1.9\%$	(1)
Maximum Power Spectral Density Level	± 0.98 dB	(1)
Number of Hopping Channel	$\pm 1.9\%$	(1)
Time of Occupancy	$\pm 0.11\%$	(1)
Max Peak Conducted Output Power	± 0.98 dB	(1)
Band-edge Spurious Emission	± 1.21 dB	(1)
Conducted RF Spurious Emission	9kHz-7GHz: ± 1.09 dB 7GHz-26.5GHz: ± 3.27 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.
- (2) Decision rule for Statement of Conformity: The measurement uncertainty is not taken into account but only measured result.

1.5. Auxiliary test equipment information

Manufacturer	Description	Model	Serial Number
HUAWEI	Adapter	HW-100225C00	HC78E2N4121901

Note: This adapter is provided by the laboratory and is only for auxiliary testing. The customer delivered the goods without an adapter.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	18-28°C
Relative Humidity:	30-60%
Air Pressure:	965-1030hPa

2.2. General Description of EUT

Product Name:	Internet of Things Radio
Model/Type reference:	DMD-2H1-R2
Power supply:	Powered by a built-in 7.2V lithium battery, It supports 5V DC charging/power supply via a network port
Test Voltage	DC 5V power supply
SRD:	
Operation frequency:	903MHz-927MHz
Modulation:	GFSK
Channel number:	25
Antenna type:	External Antenna
Antenna gain:	1.75dBi provided by ☒ Applicant ☐ Manufacturer

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

Note3: The product cannot be configured to operate outside the current frequency band plan through software configuration, Third parties are not allowed to change any software parameter configuration of the product.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 25 channels provided to the EUT and Channel 01/15/25 were selected to test.

Operation Frequency

Channel	Frequency (MHz)
01	903
02	904
:	:
14	914
15	915
16	916
:	:
24	926
25	927

Preliminary tests were performed in each mode and packet length of Lora, and found worst case as bellow, finally test were conducted at those mode and recorded in this report.

RF Cable List and Details

RF Cable	RF Cable loss	RF Cable loss provided by	
RF1.13	0.5dB	☒ Applicant	☐ Manufacturer ☐ Testing Laboratory (CTL)
RG 316	0.8dB	☒ Applicant	☐ Manufacturer ☐ Testing Laboratory (CTL)

2.4. Equipments Used during the Test

Conducted Emission					
Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2026/01/05	2027/01/04
LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2026/01/05	2027/01/04
Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2026/01/05	2027/01/04
Software:					
Name of Software:			Version:		
ES-K1			V1.71		

Radiated Emissions and Band Edge					
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Loop antenna	BEIJING DA ZE TECHNOLOGY CO., LTD	ZN30900A	N/A	2025/07/02	2026/07/01
ULTRA-BROADBAND ANTENNA	Sunol Sciences Corp.	JB1 Antenna	A061713	2025/07/02	2026/07/01
Horn Antenna	Sunol Sciences Corp	DRH-118	A062013	2026/01/05	2027/01/04
Horn Antenna	Ocean Microwave	OBH100400	26999002	2025/07/02	2026/07/01
Amplifier	MRT Technology(Suzhou)Co., Ltd	MRT-AP01M06	S-001	2025/07/02	2026/07/01
Amplifier	Agilent	8449B	3008A02306	2026/01/05	2027/01/04
Amplifier	Brief&Smart	LNA-4018	2104197	2025/07/03	2026/07/02
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2026/01/05	2027/01/04
Spectrum Analyzer	RS	FSP	1164.4391.38	2025/07/03	2026/07/02
Band-stop filter	Chengdu Guanggu RF Technology Co., Ltd.	MSF2400-2483.5MS-1154	20180604001	2025/07/02	2026/07/01
Test software					
Name of Software			Version		

EZ_EMG(Below 1GHz)	V1.1.4.2
EZ_EMG(Above 1GHz)	V1.1.4.2

Maximum Peak Output Power & 20dB Bandwidth & Frequency Separation & Number of hopping frequency & Dwell Time & Out-of-band Emissions					
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Spectrum Analyzer	Keysight	N9020A	MY53420874	2025/07/03	2026/07/02
Power meter	TSTPASS	TSPS2023R	TSCB220016	2025/07/03	2026/07/02
Temperature/Humidity Meter	Ji Yu	MC501	/	2025/07/03	2026/07/02
Test Software					
Name of Software			Version		
TST-PASS			V2.0.2		

2.5. Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST CONFIGURATION




TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
2. Support equipment, if needed, was placed as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS





3.2. Radiated Emissions

Limit

According 15.249, the field strength of emissions from intentional radiators operated within 5725-5875 MHz shall not exceed 94dB μ V/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 10GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-40GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

TEST RESULTS


Field Strength of Fundamental:


Remark: This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

903MHz



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu






915MHz




Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu






Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



927MHz



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu






Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



REMARKS:

1. Emission level (dBuV/m) = Reading (dBuV)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.


Emissions radiated outside of the specified frequency bands:


Remark:

1. This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in Z position.
2. For below 1GHz testing recorded worst at low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and the emission levels from 9kHz to 30MHz are attenuated 20dB below the limit and not recorded in report.

For 30MHz-1GHz**Horizontal**

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu






Remark: $\text{Level(dBuV/m)} = \text{Reading(dBuV)} + \text{Factor(dB/m)}$
 $\text{Margin} = \text{Limit(dBuV/m)} - \text{Level(dBuV/m)}$

Frequency bands
903MHz

Horizontal




Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1 Polarization: **Horizontal** Temperature: 25(C)
Limit: FCC PART 15C Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: 903MHz
Note: CTL2603274021-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	897.7625	11.53	24.04	35.57	54.00	18.43	AVG	100	360	P	
2	898.2938	13.51	24.06	37.57	74.00	36.43	peak	100	360	P	
3	902.0000	12.18	24.17	36.35	74.00	37.65	peak	100	360	P	
4	902.0000	9.68	24.17	33.85	54.00	20.15	AVG	100	360	P	
5	928.0000	12.83	24.60	37.43	74.00	36.57	peak	100	360	P	
6	928.0000	8.30	24.60	32.90	54.00	21.10	AVG	100	360	P	
7	934.0562	13.55	24.80	38.35	74.00	35.65	peak	100	360	P	
8	934.0562	10.93	24.80	35.73	54.00	18.27	AVG	100	360	P	





927MHz

Horizontal




Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu





For 1GHz to 10GHz
903MHz

Horizontal



Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement


File :RF2

Data :#3211

Date: 2026/04/26

Time: 18:30:16

80.0 dBuV/m



Site LAB Chamber 1

Limit: FCC PART 15C ABOVE 1GHz PK

EUT:

M/N:

Mode: 903MHz

Note: CTL2603274021-WF

Polarization: **Vertical**

Power:

Distance: 3m

Temperature: 25(C)

Humidity: 50 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2947.623	50.29	-13.58	36.71	74.00	37.29	peak	150	360	P	
2	4039.212	48.02	-8.91	39.11	74.00	34.89	peak	150	360	P	
3	8248.005	48.68	-3.71	44.97	74.00	29.03	peak	150	360	P	
4	11012.253	47.31	1.11	48.42	74.00	25.58	peak	150	360	P	
5	15003.422	48.91	3.24	52.15	74.00	21.85	peak	150	360	P	
6	17639.473	47.60	6.16	53.76	74.00	20.24	peak	150	360	P	


915MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu






927MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: 927MHz
Note: CTL2603274021-WF


Polarization: **Horizontal** Temperature: 25(C)
Power: Humidity: 50 %
Distance: 3m

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1850.858	67.05	-24.00	43.05	74.00	30.95	peak	150	0	P	
2	2956.155	51.32	-13.76	37.56	74.00	36.44	peak	150	0	P	
3	4027.554	47.39	-8.93	38.46	74.00	35.54	peak	150	0	P	
4	8248.005	48.66	-3.71	44.95	74.00	29.05	peak	150	0	P	
5	11044.129	47.58	0.99	48.57	74.00	25.43	peak	150	0	P	
6	15003.422	49.63	3.24	52.87	74.00	21.13	peak	150	0	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1

Polarization: **Vertical**

Temperature: 25(C)

Limit: FCC PART 15C ABOVE 1GHz PK

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N:

Mode: 927MHz

Note: CTL2603274021-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1850.858	67.05	-24.00	43.05	74.00	30.95	peak	150	360	P	
2	2956.155	51.32	-13.76	37.56	74.00	36.44	peak	150	360	P	
3	4279.589	48.92	-10.29	38.63	74.00	35.37	peak	150	360	P	
4	7221.150	47.66	-4.09	43.57	74.00	30.43	peak	150	360	P	
5	11012.253	47.82	1.11	48.93	74.00	25.07	peak	150	360	P	
6	15003.422	49.63	3.24	52.87	74.00	21.13	peak	150	360	P	

REMARKS:

1. Emission level (dBuV/m) = Reading (dBuV)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels lower -6dB than the limit was not reported.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
7. While performing the testing, the notch filter is used for avoiding test instrument overload.

3.3. Occupied Bandwidth Measurement

Limit

N/A

Test Configuration



Test Procedure


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 2KHz RBW and 6.2KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Results


Modulation	Test Frequency (MHz)	99% OBW (KHz)	20dB bandwidth (KHz)	Result
GFSK	903	128.30	147.6	Pass

Test plot as follows:




Modulation	Test Frequency (MHz)	99% OBW (KHz)	20dB bandwidth (KHz)	Result
GFSK	915	128.69	148.5	Pass

Test plot as follows:



Modulation	Test Frequency (MHz)	99% OBW (KHz)	20dB bandwidth (KHz)	Result
GFSK	927	127.43	148.1	Pass

Test plot as follows:



3.4. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is an External Antenna, The directional gains of antenna used for transmitting is 1.75dBi.

4. Test Setup Photos of the EUT

Reference to the test report No.CTL2603274021-WF01

5. External and Internal Photos of the EUT

Reference to the test report No.CTL2603274021-WF01

***** End of Report *****