



FCC RADIO TEST REPORT

FCC ID : 2BSOW-BWS3004BAB
Equipment : Smart Birdfeeder
Brand Name : Birdbuddy
Model Name : Birdbuddy 2
Applicant : Bird Buddy Inc.
169 Madison Avenue, Suite 15233, New York, NY 10016, US
Manufacturer : Xavi Technologies (Thailand) Co., Ltd.
82 Mu 4, Takham Bangpakong, Chachoengsao 24130, Thailand
Standard : FCC Part 15 Subpart C §15.247

The product was received on Oct. 28, 2025 and testing was performed from Nov. 06, 2025 to Nov. 20, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	8
2.5 EUT Operation Test Setup	8
2.6 Measurement Results Explanation Example.....	8
3 Test Result	9
3.1 6dB and 99% Bandwidth Measurement	9
3.2 Output Power Measurement.....	10
3.3 Power Spectral Density Measurement	11
3.4 Conducted Band Edges and Spurious Emission Measurement	12
3.5 Radiated Band Edges and Spurious Emission Measurement	13
3.6 AC Conducted Emission Measurement.....	16
3.7 Antenna Requirements.....	18
4 List of Measuring Equipment.....	19
5 Measurement Uncertainty	21
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR582014-01B	01	Initial issue of report	Nov. 27, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sheng Kuo

Report Producer: Shiori Chen

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and Wi-Fi 5GHz 802.11a/n.
Antenna Type WLAN: Dipole Antenna Bluetooth: Dipole Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.94

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		


2.2 Test Mode

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :WLAN2.4GHz Tx + USB Cable (Charging from AC Adapter)
Remark: - The detailed Radiated test modes are shown in Appendix C. - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	OPPO	VCA7JBUH	N/A	N/A	N/A
2.	Adapter	Google	G9BR1 LPS	N/A	N/A	N/A
3.	Notebook	Acer	N18Q13	PD9AX201NG	N/A	Unshielded, 1.8m

2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.


8. Use the following spectrum analyzer settings:
- (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Unique (non-standard) antenna connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 18, 2024	Nov. 13, 2025~ Nov. 20, 2025	Dec. 17, 2025	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 05, 2025	Nov. 13, 2025~ Nov. 20, 2025	Mar. 04, 2026	Radiation (03CH13-HY)
Amplifier	SONOMA	310N	187282	9kHz~1GHz	Dec. 12, 2024	Nov. 13, 2025~ Nov. 20, 2025	Dec. 11, 2025	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	40103 & 07	30MHz~1GHz	Apr. 13, 2025	Nov. 13, 2025~ Nov. 20, 2025	Apr. 12, 2026	Radiation (03CH13-HY)
EXA Signal Analyzer	Keysight	N9010B	MY64320114	10Hz~44GHz	Oct. 07, 2025	Nov. 13, 2025~ Nov. 20, 2025	Oct. 06, 2026	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP215159	N/A	Sep. 08, 2025	Nov. 13, 2025~ Nov. 20, 2025	Sep. 07, 2026	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 14, 2025	Nov. 13, 2025~ Nov. 20, 2025	May 13, 2026	Radiation (03CH13-HY)
Preamplifier	EM Electronics	EM01G18G	060803	1GHz-18GHz	Jan. 08, 2025	Nov. 13, 2025~ Nov. 20, 2025	Jan. 07, 2026	Radiation (03CH13-HY)
Double Ridged Guide Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Sep. 03, 2025	Nov. 13, 2025~ Nov. 20, 2025	Sep. 02, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN12	1.53GHz Low Pass Filter	Sep. 10, 2025	Nov. 13, 2025~ Nov. 20, 2025	Sep. 09, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX12-2700 -3000-18000-6 0SS	SN2	3GHz High Pass Filter	Jul. 08, 2025	Nov. 13, 2025~ Nov. 20, 2025	Jul. 07, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN5	6.75GHz High Pass Filter	Mar. 07, 2025	Nov. 13, 2025~ Nov. 20, 2025	Mar. 06, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102E	508408-2E	N/A	Jun. 16, 2025	Nov. 13, 2025~ Nov. 20, 2025	Jun. 15, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30MHz~18GHz	Feb. 06, 2025	Nov. 13, 2025~ Nov. 20, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30MHz~18GHz	Feb. 06, 2025	Nov. 13, 2025~ Nov. 20, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Nov. 13, 2025~ Nov. 20, 2025	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Nov. 13, 2025~ Nov. 20, 2025	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Nov. 13, 2025~ Nov. 20, 2025	N/A	Radiation (03CH13-HY)
Software	Audix	N/A	RK-001124	N/A	N/A	Nov. 13, 2025~ Nov. 20, 2025	N/A	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9170	1223	18GHz-40GHz	Jul. 02, 2025	Nov. 13, 2025~ Nov. 20, 2025	Jul. 01, 2026	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 26, 2025	Nov. 13, 2025~ Nov. 20, 2025	May 25, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18GHz-40GHz	Dec. 31, 2024	Nov. 13, 2025~ Nov. 20, 2025	Dec. 30, 2025	Radiation (03CH13-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECEPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Nov. 10, 2025~ Nov. 20, 2025	Nov. 03, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Nov. 10, 2025~ Nov. 20, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101467	10HZ~44GHZ	Jan. 14, 2025	Nov. 10, 2025~ Nov. 20, 2025	Jan. 13, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Nov. 10, 2025~ Nov. 20, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24051 3	N/A	Conducted Other Test Item	N/A	Nov. 10, 2025~ Nov. 20, 2025	N/A	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 06, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 10, 2024	Nov. 06, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	TECEPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Nov. 06, 2025	Jun. 25, 2026	Conduction (CO05-HY)
Two-Line V-Network	Rohde & Schwarz	ENV216	100081	N/A	Jul. 25, 2025	Nov. 06, 2025	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Nov. 06, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Jul. 29, 2025	Nov. 06, 2025	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT2408250 1	N/A	Oct. 14, 2025	Nov. 06, 2025	Oct. 13, 2026	Conduction (CO05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
--	--------

**Test Result**

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass /Fail
					Ant1	-	Ant1	-		
11b	1M	1	1	2412	15.73	-	10.16	-	0.50	Pass
11b	1M	1	6	2437	15.22	-	10.12	-	0.50	Pass
11b	1M	1	11	2462	14.20	-	9.60	-	0.50	Pass
11b	1M	1	12	2467	13.90	-	9.21	-	0.50	Pass
11b	1M	1	13	2472	13.95	-	9.63	-	0.50	Pass
11g	6M	1	1	2412	16.78	-	14.27	-	0.50	Pass
11g	6M	1	6	2437	23.21	-	14.49	-	0.50	Pass
11g	6M	1	11	2462	16.82	-	13.81	-	0.50	Pass
11g	6M	1	12	2467	16.73	-	13.99	-	0.50	Pass
11g	6M	1	13	2472	17.54	-	14.35	-	0.50	Pass
HT20	MCS0	1	1	2412	17.81	-	15.48	-	0.50	Pass
HT20	MCS0	1	6	2437	22.72	-	15.91	-	0.50	Pass
HT20	MCS0	1	11	2462	17.81	-	15.09	-	0.50	Pass
HT20	MCS0	1	12	2467	17.74	-	15.04	-	0.50	Pass
HT20	MCS0	1	13	2472	18.32	-	15.60	-	0.50	Pass

**TEST RESULTS DATA****Average Output Power**

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	-	-	Ant1	-	Ant1	-	Ant1	-	Ant1	-	
11b	1M	1	1	2412	24.79	-	-	30.00	-	2.94	-	27.73	-	36.00	-	Pass
11b	1M	1	6	2437	24.13	-	-	30.00	-	2.94	-	27.07	-	36.00	-	Pass
11b	1M	1	11	2462	21.22	-	-	30.00	-	2.94	-	24.16	-	36.00	-	Pass
11b	1M	1	12	2467	19.80	-	-	30.00	-	2.94	-	22.74	-	36.00	-	Pass
11b	1M	1	13	2472	15.31	-	-	30.00	-	2.94	-	18.25	-	36.00	-	Pass
11g	6M	1	1	2412	17.12	-	-	30.00	-	2.94	-	20.06	-	36.00	-	Pass
11g	6M	1	6	2437	24.73	-	-	30.00	-	2.94	-	27.67	-	36.00	-	Pass
11g	6M	1	11	2462	18.26	-	-	30.00	-	2.94	-	21.20	-	36.00	-	Pass
11g	6M	1	12	2467	14.25	-	-	30.00	-	2.94	-	17.19	-	36.00	-	Pass
11g	6M	1	13	2472	-6.79	-	-	30.00	-	2.94	-	-3.85	-	36.00	-	Pass
HT20	MCS 0	1	1	2412	17.36	-	-	30.00	-	2.94	-	20.30	-	36.00	-	Pass
HT20	MCS 0	1	6	2437	24.30	-	-	30.00	-	2.94	-	27.24	-	36.00	-	Pass
HT20	MCS 0	1	11	2462	16.98	-	-	30.00	-	2.94	-	19.92	-	36.00	-	Pass
HT20	MCS 0	1	12	2467	14.37	-	-	30.00	-	2.94	-	17.31	-	36.00	-	Pass
HT20	MCS 0	1	13	2472	-6.67	-	-	30.00	-	2.94	-	-3.73	-	36.00	-	Pass




TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass /Fail
					Ant1	-	-	Ant1	-	Ant1	-	
11b	1M	1	1	2412	7.82	-	-	2.94	-	8.00	-	Pass
11b	1M	1	6	2437	7.98	-	-	2.94	-	8.00	-	Pass
11b	1M	1	11	2462	7.48	-	-	2.94	-	8.00	-	Pass
11b	1M	1	12	2467	5.81	-	-	2.94	-	8.00	-	Pass
11b	1M	1	13	2472	1.28	-	-	2.94	-	8.00	-	Pass
11g	6M	1	1	2412	-8.91	-	-	2.94	-	8.00	-	Pass
11g	6M	1	6	2437	-1.16	-	-	2.94	-	8.00	-	Pass
11g	6M	1	11	2462	-8.17	-	-	2.94	-	8.00	-	Pass
11g	6M	1	12	2467	-10.30	-	-	2.94	-	8.00	-	Pass
11g	6M	1	13	2472	-32.13	-	-	2.94	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-8.60	-	-	2.94	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-1.62	-	-	2.94	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-8.26	-	-	2.94	-	8.00	-	Pass
HT20	MCS0	1	12	2467	-10.51	-	-	2.94	-	8.00	-	Pass
HT20	MCS0	1	13	2472	-31.61	-	-	2.94	-	8.00	-	Pass


**6dB and 99% Occupied Bandwidth**

<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11gN HT20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


Power Spectral Density(dBm/3kHz)

<802.11b>






<802.11g>





<802.11gN HT20>



**Band Edges and Spurious Emission**

Number of TX = 1, Ant. 1 (Measured)









Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 12


100kHz PSD reference Level




Channel 12 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 13


100kHz PSD reference Level




Channel 13 Plot





Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz











Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot




Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz









Test Mode : 802.11g

Test Channel : 13


100kHz PSD reference Level




Channel 13 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot




Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz









Test Mode : 802.11gN20

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 12


100kHz PSD reference Level




Channel 12 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11gN20


Test Channel : 13

100kHz PSD reference Level




01:22:52 PM 11/19/2025

Channel 13 Plot




03:23:44 PM 11/19/2025

Spurious Emission 30MHz~1GHz



03:23:10 PM 11/19/2025

Spurious Emission 1GHz~26.5GHz



03:23:28 PM 11/19/2025




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	Temperature :	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO : 582014-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	26.50	55.63	29.13	L1	OFF	19.8
0.156750	29.96	---	65.63	35.67	L1	OFF	19.8
0.181500	---	24.98	54.42	29.44	L1	OFF	19.8
0.181500	28.58	---	64.42	35.84	L1	OFF	19.8
0.206250	---	24.57	53.36	28.79	L1	OFF	19.8
0.206250	27.16	---	63.36	36.20	L1	OFF	19.8
0.912750	---	23.05	46.00	22.95	L1	OFF	19.9
0.912750	24.28	---	56.00	31.72	L1	OFF	19.9
4.663500	---	25.38	46.00	20.62	L1	OFF	20.1
4.663500	26.65	---	56.00	29.35	L1	OFF	20.1
8.538000	---	26.39	50.00	23.61	L1	OFF	20.4
8.538000	29.10	---	60.00	30.90	L1	OFF	20.4

EUT Information

Report NO : 582014-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	27.71	55.88	28.17	N	OFF	19.8
0.152250	30.32	---	65.88	35.56	N	OFF	19.8
0.181500	---	25.25	54.42	29.17	N	OFF	19.8
0.181500	28.75	---	64.42	35.67	N	OFF	19.8
0.206250	---	24.64	53.36	28.72	N	OFF	19.8
0.206250	26.76	---	63.36	36.60	N	OFF	19.8
0.258000	---	23.91	51.50	27.59	N	OFF	19.8
0.258000	25.62	---	61.50	35.88	N	OFF	19.8
0.746250	---	23.09	46.00	22.91	N	OFF	19.9
0.746250	24.40	---	56.00	31.60	N	OFF	19.9
7.739250	---	30.02	50.00	19.98	N	OFF	20.3
7.739250	32.85	---	60.00	27.15	N	OFF	20.3

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Rain Lee, Jacky Hong, and White Hou.	Temperature :	21.8 ~25.7°C
		Relative Humidity :	47.6 ~ 55.4%

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 9	2400-2483.5	1	802.11b	01	2412	1Mbps	-	-
Mode 10	2400-2483.5	1	802.11b	06	2437	1Mbps	-	-
Mode 11	2400-2483.5	1	802.11b	11	2462	1Mbps	-	-
Mode 12	2400-2483.5	1	802.11b	12	2467	1Mbps	-	-
Mode 13	2400-2483.5	1	802.11b	13	2472	1Mbps	-	-
Mode 14	2400-2483.5	1	802.11g	01	2412	6Mbps	-	-
Mode 15	2400-2483.5	1	802.11g	06	2437	6Mbps	-	-
Mode 16	2400-2483.5	1	802.11g	11	2462	6Mbps	-	-
Mode 17	2400-2483.5	1	802.11g	12	2467	6Mbps	-	-
Mode 18	2400-2483.5	1	802.11g	13	2472	6Mbps	-	-
Mode 19	2400-2483.5	1	802.11n HT20	01	2412	MCS0	-	-
Mode 20	2400-2483.5	1	802.11n HT20	06	2437	MCS0	-	-
Mode 21	2400-2483.5	1	802.11n HT20	11	2462	MCS0	-	-
Mode 22	2400-2483.5	1	802.11n HT20	12	2467	MCS0	-	-
Mode 23	2400-2483.5	1	802.11n HT20	13	2472	MCS0	-	-
Mode 24	2400-2483.5	1	802.11g	01	2412	6Mbps	-	LF
Mode 25	2400-2483.5	1	802.11g	01	2412	6Mbps	-	SHF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
9	802.11b	01	2387.09	51.77	54.00	-2.23	H	Avg.	Pass	-	Band Edge
	802.11b	01	4824.00	41.42	54.00	-12.58	H	Avg.	Pass	-	Harmonic
10	802.11b	06	2389.76	42.09	54.00	-11.91	H	Avg.	Pass	-	Band Edge
	802.11b	06	4874.00	45.64	54.00	-8.36	H	Avg.	Pass	-	Harmonic
11	802.11b	11	2487.92	52.12	54.00	-1.88	H	Avg.	Pass	-	Band Edge
	802.11b	11	7386.00	43.10	54.00	-10.90	H	Avg.	Pass	-	Harmonic
12	802.11b	12	2484.80	53.53	54.00	-0.47	H	Avg.	Pass	-	Band Edge
	802.11b	12	7401.00	41.08	54.00	-12.92	H	Avg.	Pass	-	Harmonic
13	802.11b	13	2484.42	53.65	54.00	-0.35	H	Avg.	Pass	-	Band Edge
	802.11b	13	7416.00	44.81	74.00	-29.19	V	Peak	Pass	-	Harmonic
14	802.11g	01	2389.95	53.68	54.00	-0.32	H	Avg.	Pass	-	Band Edge
	802.11g	01	4824.00	39.19	74.00	-34.81	H	Peak	Pass	-	Harmonic
15	802.11g	06	2389.25	48.18	54.00	-5.82	H	Avg.	Pass	-	Band Edge
	802.11g	06	7311.00	45.92	54.00	-8.08	H	Avg.	Pass	-	Harmonic
16	802.11g	11	2483.51	53.17	54.00	-0.83	H	Avg.	Pass	-	Band Edge
	802.11g	11	7386.00	37.41	54.00	-16.59	H	Avg.	Pass	-	Harmonic
17	802.11g	12	2483.51	53.34	54.00	-0.66	H	Avg.	Pass	-	Band Edge
	802.11g	12	7401.00	44.71	74.00	-29.29	H	Peak	Pass	-	Harmonic
18	802.11g	13	2483.51	50.71	54.00	-3.29	H	Avg.	Pass	-	Band Edge
	802.11g	13	7416.00	44.50	74.00	-29.50	V	Peak	Pass	-	Harmonic
19	802.11n HT20	01	2389.95	53.44	54.00	-0.56	H	Avg.	Pass	-	Band Edge
	802.11n HT20	01	4824.00	40.26	74.00	-33.74	H	Peak	Pass	-	Harmonic
20	802.11n HT20	06	2389.88	48.90	54.00	-5.10	H	Avg.	Pass	-	Band Edge
	802.11n HT20	06	7311.00	45.38	54.00	-8.62	H	Avg.	Pass	-	Harmonic



FCC RADIO TEST REPORT

Report No.: FR582014-01B

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
21	802.11n HT20	11	2483.55	52.68	54.00	-1.32	H	Avg.	Pass	-	Band Edge
	802.11n HT20	11	7386.00	45.05	74.00	-28.95	H	Peak	Pass	-	Harmonic
22	802.11n HT20	12	2483.51	53.32	54.00	-0.68	H	Avg.	Pass	-	Band Edge
	802.11n HT20	12	7401.00	45.19	74.00	-28.81	V	Peak	Pass	-	Harmonic
23	802.11n HT20	13	2483.51	51.72	54.00	-2.28	H	Avg.	Pass	-	Band Edge
	802.11n HT20	13	7416.00	44.57	74.00	-29.43	V	Peak	Pass	-	Harmonic
24	LF	01	91.11	37.27	43.50	-6.23	H	Peak	Pass	-	LF
25	SHF	01	24870.34	43.77	74.00	-30.23	V	Peak	Pass	-	SHF



Mode	9																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11b_CH01_2412MHz																																																																																									
ANT	1																																																																																									
Pol.	Horizontal						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2386.83</td><td>60.67</td><td>74.00</td><td>-13.33</td><td>53.88</td><td>27.27</td><td>6.56</td><td>36.97</td><td>9.93</td><td>102</td><td>180</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2386.83	60.67	74.00	-13.33	53.88	27.27	6.56	36.97	9.93	102	180	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>114.23</td><td>-----</td><td>-----</td><td>107.27</td><td>27.40</td><td>6.60</td><td>36.97</td><td>9.93</td><td>102</td><td>180</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	114.23	-----	-----	107.27	27.40	6.60	36.97	9.93	102	180	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2386.83	60.67	74.00	-13.33	53.88	27.27	6.56	36.97	9.93	102	180	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	114.23	-----	-----	107.27	27.40	6.60	36.97	9.93	102	180	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2387.09</td><td>51.77</td><td>54.00</td><td>-2.23</td><td>44.98</td><td>27.27</td><td>6.56</td><td>36.97</td><td>9.93</td><td>102</td><td>180</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2387.09	51.77	54.00	-2.23	44.98	27.27	6.56	36.97	9.93	102	180	Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>110.86</td><td>-----</td><td>-----</td><td>103.91</td><td>27.40</td><td>6.59</td><td>36.97</td><td>9.93</td><td>102</td><td>180</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	110.86	-----	-----	103.91	27.40	6.59	36.97	9.93	102	180	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2387.09	51.77	54.00	-2.23	44.98	27.27	6.56	36.97	9.93	102	180	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	110.86	-----	-----	103.91	27.40	6.59	36.97	9.93	102	180	Average																																																																														



Mode	9																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11b_CH01_2412MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2387.61</td><td>56.18</td><td>74.00</td><td>-17.82</td><td>49.38</td><td>27.28</td><td>6.56</td><td>36.97</td><td>9.93</td><td>200</td><td>55</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2387.61	56.18	74.00	-17.82	49.38	27.28	6.56	36.97	9.93	200	55	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>108.66</td><td>-----</td><td>-----</td><td>101.70</td><td>27.40</td><td>6.60</td><td>36.97</td><td>9.93</td><td>200</td><td>55</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	108.66	-----	-----	101.70	27.40	6.60	36.97	9.93	200	55	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2387.61	56.18	74.00	-17.82	49.38	27.28	6.56	36.97	9.93	200	55	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	108.66	-----	-----	101.70	27.40	6.60	36.97	9.93	200	55	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2387.09</td><td>46.45</td><td>54.00</td><td>-7.55</td><td>39.66</td><td>27.27</td><td>6.56</td><td>36.97</td><td>9.93</td><td>200</td><td>55</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2387.09	46.45	54.00	-7.55	39.66	27.27	6.56	36.97	9.93	200	55	Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>105.37</td><td>-----</td><td>-----</td><td>98.42</td><td>27.40</td><td>6.59</td><td>36.97</td><td>9.93</td><td>200</td><td>55</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	105.37	-----	-----	98.42	27.40	6.59	36.97	9.93	200	55	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2387.09	46.45	54.00	-7.55	39.66	27.27	6.56	36.97	9.93	200	55	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	105.37	-----	-----	98.42	27.40	6.59	36.97	9.93	200	55	Average																																																																														







Mode	9																																																																																																															
	Harmonic																																																																																																															
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																															
ANT	1																																																																																																															
Pol.	Horizontal							Vertical																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>45.28</td><td>74.00</td><td>-28.72</td><td>61.02</td><td>32.34</td><td>9.67</td><td>58.34</td><td>0.59</td><td>229</td><td>223</td><td></td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>41.42</td><td>54.00</td><td>-12.58</td><td>57.16</td><td>32.34</td><td>9.67</td><td>58.34</td><td>0.59</td><td>229</td><td>223</td><td></td><td>Average</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	4824.00	45.28	74.00	-28.72	61.02	32.34	9.67	58.34	0.59	229	223		Peak	2	4824.00	41.42	54.00	-12.58	57.16	32.34	9.67	58.34	0.59	229	223		Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>40.10</td><td>74.00</td><td>-33.90</td><td>55.84</td><td>32.34</td><td>9.67</td><td>58.34</td><td>0.59</td><td>--</td><td>--</td><td></td><td>Peak</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	4824.00	40.10	74.00	-33.90	55.84	32.34	9.67	58.34	0.59	--	--		Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																		
		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																			
1	4824.00	45.28	74.00	-28.72	61.02	32.34	9.67	58.34	0.59	229	223		Peak																																																																																																			
2	4824.00	41.42	54.00	-12.58	57.16	32.34	9.67	58.34	0.59	229	223		Average																																																																																																			
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																			
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																				
1	4824.00	40.10	74.00	-33.90	55.84	32.34	9.67	58.34	0.59	--	--		Peak																																																																																																			



Mode	9	
	Harmonic	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL
	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL







Mode	10																																																																																										
	Band Edge - L																																																																																										
	2400-2483.5_802.11b_CH06_2437MHz																																																																																										
ANT	1																																																																																										
Pol.	Horizontal												Fundamental																																																																														
Peak	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2383.41</td><td>56.87</td><td>74.00</td><td>-17.13</td><td>50.13</td><td>27.23</td><td>6.55</td><td>36.97</td><td>9.93</td><td>100</td><td>100</td><td>Peak</td></tr></table> Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2437.00</td><td>114.52</td><td>-----</td><td>-----</td><td>107.43</td><td>27.50</td><td>6.63</td><td>36.97</td><td>9.93</td><td>100</td><td>100</td><td>Peak</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2383.41	56.87	74.00	-17.13	50.13	27.23	6.55	36.97	9.93	100	100	Peak		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	114.52	-----	-----	107.43	27.50	6.63	36.97	9.93	100	100	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2383.41	56.87	74.00	-17.13	50.13	27.23	6.55	36.97	9.93	100	100	Peak																																																																															
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2437.00	114.52	-----	-----	107.43	27.50	6.63	36.97	9.93	100	100	Peak																																																																															
Avg	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.76</td><td>42.09</td><td>54.00</td><td>-11.91</td><td>35.27</td><td>27.30</td><td>6.56</td><td>36.97</td><td>9.93</td><td>100</td><td>100</td><td>Average</td></tr></table> Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2437.00</td><td>111.10</td><td>-----</td><td>-----</td><td>104.01</td><td>27.50</td><td>6.63</td><td>36.97</td><td>9.93</td><td>100</td><td>100</td><td>Average</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.76	42.09	54.00	-11.91	35.27	27.30	6.56	36.97	9.93	100	100	Average		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	111.10	-----	-----	104.01	27.50	6.63	36.97	9.93	100	100	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2389.76	42.09	54.00	-11.91	35.27	27.30	6.56	36.97	9.93	100	100	Average																																																																															
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2437.00	111.10	-----	-----	104.01	27.50	6.63	36.97	9.93	100	100	Average																																																																															



Mode	10											
	Band Edge - R											
	2400-2483.5_802.11b_CH06_2437MHz											
ANT	1											
Pol.	Horizontal						Fundamental					
Peak												



Mode	10																																																																																									
	Band Edge - L																																																																																									
	2400-2483.5_802.11b_CH06_2437MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-11-14  Frequency (MHz) Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2387.09</td><td>53.42</td><td>74.00</td><td>-20.58</td><td>46.63</td><td>27.27</td><td>6.56</td><td>36.97</td><td>9.93</td><td>194</td><td>60</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2387.09	53.42	74.00	-20.58	46.63	27.27	6.56	36.97	9.93	194	60	Peak	Level (dBuV/m) Date: 2025-11-14  Frequency (MHz) Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>110.11</td><td>-----</td><td>-----</td><td>103.02</td><td>27.50</td><td>6.63</td><td>36.97</td><td>9.93</td><td>194</td><td>60</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	110.11	-----	-----	103.02	27.50	6.63	36.97	9.93	194	60	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2387.09	53.42	74.00	-20.58	46.63	27.27	6.56	36.97	9.93	194	60	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2437.00	110.11	-----	-----	103.02	27.50	6.63	36.97	9.93	194	60	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-11-14  Frequency (MHz) Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2389.50</td><td>40.56</td><td>54.00</td><td>-13.44</td><td>33.74</td><td>27.30</td><td>6.56</td><td>36.97</td><td>9.93</td><td>194</td><td>60</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.50	40.56	54.00	-13.44	33.74	27.30	6.56	36.97	9.93	194	60	Average	Level (dBuV/m) Date: 2025-11-14  Frequency (MHz) Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>106.77</td><td>-----</td><td>-----</td><td>99.68</td><td>27.50</td><td>6.63</td><td>36.97</td><td>9.93</td><td>194</td><td>60</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	106.77	-----	-----	99.68	27.50	6.63	36.97	9.93	194	60	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2389.50	40.56	54.00	-13.44	33.74	27.30	6.56	36.97	9.93	194	60	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2437.00	106.77	-----	-----	99.68	27.50	6.63	36.97	9.93	194	60	Average																																																																														



Mode	10										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Vertical						Fundamental				
Peak											







Mode	10																																																																																																																																																																								
	Harmonic																																																																																																																																																																								
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																																																																								
ANT	1																																																																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>48.53</td><td>74.00</td><td>-25.47</td><td>63.85</td><td>32.55</td><td>9.74</td><td>58.22</td><td>0.61</td><td>100</td><td>237 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>45.64</td><td>54.00</td><td>-8.36</td><td>60.96</td><td>32.55</td><td>9.74</td><td>58.22</td><td>0.61</td><td>100</td><td>237 Average</td></tr><tr><td>3</td><td>7311.00</td><td>51.20</td><td>74.00</td><td>-22.80</td><td>59.39</td><td>36.68</td><td>12.15</td><td>57.67</td><td>0.65</td><td>199</td><td>12 Peak</td></tr><tr><td>4</td><td>7311.00</td><td>45.39</td><td>54.00</td><td>-8.61</td><td>53.58</td><td>36.68</td><td>12.15</td><td>57.67</td><td>0.65</td><td>199</td><td>12 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	48.53	74.00	-25.47	63.85	32.55	9.74	58.22	0.61	100	237 Peak	2	4874.00	45.64	54.00	-8.36	60.96	32.55	9.74	58.22	0.61	100	237 Average	3	7311.00	51.20	74.00	-22.80	59.39	36.68	12.15	57.67	0.65	199	12 Peak	4	7311.00	45.39	54.00	-8.61	53.58	36.68	12.15	57.67	0.65	199	12 Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>45.14</td><td>74.00</td><td>-28.86</td><td>60.46</td><td>32.55</td><td>9.74</td><td>58.22</td><td>0.61</td><td>133</td><td>138 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>40.82</td><td>54.00</td><td>-13.18</td><td>56.14</td><td>32.55</td><td>9.74</td><td>58.22</td><td>0.61</td><td>133</td><td>138 Average</td></tr><tr><td>3</td><td>7311.00</td><td>50.27</td><td>74.00</td><td>-23.73</td><td>58.46</td><td>36.68</td><td>12.15</td><td>57.67</td><td>0.65</td><td>135</td><td>172 Peak</td></tr><tr><td>4</td><td>7311.00</td><td>43.84</td><td>54.00</td><td>-10.16</td><td>52.03</td><td>36.68</td><td>12.15</td><td>57.67</td><td>0.65</td><td>135</td><td>172 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	45.14	74.00	-28.86	60.46	32.55	9.74	58.22	0.61	133	138 Peak	2	4874.00	40.82	54.00	-13.18	56.14	32.55	9.74	58.22	0.61	133	138 Average	3	7311.00	50.27	74.00	-23.73	58.46	36.68	12.15	57.67	0.65	135	172 Peak	4	7311.00	43.84	54.00	-10.16	52.03	36.68	12.15	57.67	0.65	135	172 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4874.00	48.53	74.00	-25.47	63.85	32.55	9.74	58.22	0.61	100	237 Peak																																																																																																																																																														
2	4874.00	45.64	54.00	-8.36	60.96	32.55	9.74	58.22	0.61	100	237 Average																																																																																																																																																														
3	7311.00	51.20	74.00	-22.80	59.39	36.68	12.15	57.67	0.65	199	12 Peak																																																																																																																																																														
4	7311.00	45.39	54.00	-8.61	53.58	36.68	12.15	57.67	0.65	199	12 Average																																																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4874.00	45.14	74.00	-28.86	60.46	32.55	9.74	58.22	0.61	133	138 Peak																																																																																																																																																														
2	4874.00	40.82	54.00	-13.18	56.14	32.55	9.74	58.22	0.61	133	138 Average																																																																																																																																																														
3	7311.00	50.27	74.00	-23.73	58.46	36.68	12.15	57.67	0.65	135	172 Peak																																																																																																																																																														
4	7311.00	43.84	54.00	-10.16	52.03	36.68	12.15	57.67	0.65	135	172 Average																																																																																																																																																														



Mode	10	
	Harmonic	
	2400-2483.5_802.11b_CH06_2437MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL
	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL



Mode	11																																																																																		
	Band Edge																																																																																		
	2400-2483.5_802.11b_CH11_2462MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-11-13  PEAK_BE_74 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2487.46</td><td>60.29</td><td>74.00</td><td>-13.71</td><td>52.86</td><td>27.77</td><td>6.70</td><td>36.97</td><td>9.93</td><td>100</td><td>179</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2487.46	60.29	74.00	-13.71	52.86	27.77	6.70	36.97	9.93	100	179	Peak	Level (dBuV/m) Date: 2025-11-13  PEAK_74 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>112.88</td><td>-----</td><td>-----</td><td>105.66</td><td>27.60</td><td>6.66</td><td>36.97</td><td>9.93</td><td>100</td><td>179</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	112.88	-----	-----	105.66	27.60	6.66	36.97	9.93	100	179	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2487.46	60.29	74.00	-13.71	52.86	27.77	6.70	36.97	9.93	100	179	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2462.00	112.88	-----	-----	105.66	27.60	6.66	36.97	9.93	100	179	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-11-13  AVG_BE_54 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2487.92</td><td>52.12</td><td>54.00</td><td>-1.88</td><td>44.68</td><td>27.78</td><td>6.70</td><td>36.97</td><td>9.93</td><td>100</td><td>179</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2487.92	52.12	54.00	-1.88	44.68	27.78	6.70	36.97	9.93	100	179	Average	Level (dBuV/m) Date: 2025-11-13  AVG_54 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>109.77</td><td>-----</td><td>-----</td><td>102.55</td><td>27.60</td><td>6.66</td><td>36.97</td><td>9.93</td><td>100</td><td>179</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	109.77	-----	-----	102.55	27.60	6.66	36.97	9.93	100	179	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2487.92	52.12	54.00	-1.88	44.68	27.78	6.70	36.97	9.93	100	179	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2462.00	109.77	-----	-----	102.55	27.60	6.66	36.97	9.93	100	179	Average																																																																								



Mode	11																																																																																		
	Band Edge																																																																																		
	2400-2483.5_802.11b_CH11_2462MHz																																																																																		
ANT	1																																																																																		
Pol.	Vertical						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-11-14 PEAK_BE_74 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2462 2469.6 2477.2 2484.8 2492.4 2500 Frequency (MHz) Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2487.00</td><td>55.43</td><td>74.00</td><td>-18.57</td><td>47.99</td><td>27.78</td><td>6.70</td><td>36.97</td><td>9.93</td><td>100</td><td>238</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2487.00	55.43	74.00	-18.57	47.99	27.78	6.70	36.97	9.93	100	238	Peak	Level (dBuV/m) Date: 2025-11-13 PEAK_74 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>107.98</td><td>-----</td><td>-----</td><td>100.76</td><td>27.60</td><td>6.66</td><td>36.97</td><td>9.93</td><td>100</td><td>238</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	107.98	-----	-----	100.76	27.60	6.66	36.97	9.93	100	238	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2487.00	55.43	74.00	-18.57	47.99	27.78	6.70	36.97	9.93	100	238	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2462.00	107.98	-----	-----	100.76	27.60	6.66	36.97	9.93	100	238	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-11-14 AVG_BE_54 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2462 2469.6 2477.2 2484.8 2492.4 2500 Frequency (MHz) Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2487.99</td><td>47.47</td><td>54.00</td><td>-6.53</td><td>40.03</td><td>27.78</td><td>6.70</td><td>36.97</td><td>9.93</td><td>100</td><td>238</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2487.99	47.47	54.00	-6.53	40.03	27.78	6.70	36.97	9.93	100	238	Average	Level (dBuV/m) Date: 2025-11-13 AVG_54 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>104.42</td><td>-----</td><td>-----</td><td>97.20</td><td>27.60</td><td>6.66</td><td>36.97</td><td>9.93</td><td>100</td><td>238</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	104.42	-----	-----	97.20	27.60	6.66	36.97	9.93	100	238	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2487.99	47.47	54.00	-6.53	40.03	27.78	6.70	36.97	9.93	100	238	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2462.00	104.42	-----	-----	97.20	27.60	6.66	36.97	9.93	100	238	Average																																																																								



Mode	11																																																																																																																																		
	Harmonic																																																																																																																																		
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																																																		
ANT	1																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																												
Peak Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>4924.00</td><td>44.82</td><td>74.00</td><td>-29.18</td><td>59.00</td><td>32.70</td><td>9.81</td><td>58.11</td><td>0.62 195 179 Peak</td></tr><tr><td>2</td><td>7386.00</td><td>49.70</td><td>74.00</td><td>-24.30</td><td>58.17</td><td>36.46</td><td>12.21</td><td>57.79</td><td>0.65 204 13 Peak</td></tr><tr><td>3</td><td>7386.00</td><td>43.10</td><td>54.00</td><td>-10.90</td><td>51.57</td><td>36.46</td><td>12.21</td><td>57.79</td><td>0.65 204 13 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	4924.00	44.82	74.00	-29.18	59.00	32.70	9.81	58.11	0.62 195 179 Peak	2	7386.00	49.70	74.00	-24.30	58.17	36.46	12.21	57.79	0.65 204 13 Peak	3	7386.00	43.10	54.00	-10.90	51.57	36.46	12.21	57.79	0.65 204 13 Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>4924.00</td><td>42.74</td><td>74.00</td><td>-31.26</td><td>57.72</td><td>32.70</td><td>9.81</td><td>58.11</td><td>0.62 300 173 Peak</td></tr><tr><td>2</td><td>7386.00</td><td>49.17</td><td>74.00</td><td>-24.83</td><td>57.64</td><td>36.46</td><td>12.21</td><td>57.79</td><td>0.65 181 187 Peak</td></tr><tr><td>3</td><td>7386.00</td><td>41.69</td><td>54.00</td><td>-12.31</td><td>50.16</td><td>36.46</td><td>12.21</td><td>57.79</td><td>0.65 181 187 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	4924.00	42.74	74.00	-31.26	57.72	32.70	9.81	58.11	0.62 300 173 Peak	2	7386.00	49.17	74.00	-24.83	57.64	36.46	12.21	57.79	0.65 181 187 Peak	3	7386.00	41.69	54.00	-12.31	50.16	36.46	12.21	57.79	0.65 181 187 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																										
1	4924.00	44.82	74.00	-29.18	59.00	32.70	9.81	58.11	0.62 195 179 Peak																																																																																																																										
2	7386.00	49.70	74.00	-24.30	58.17	36.46	12.21	57.79	0.65 204 13 Peak																																																																																																																										
3	7386.00	43.10	54.00	-10.90	51.57	36.46	12.21	57.79	0.65 204 13 Average																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																										
1	4924.00	42.74	74.00	-31.26	57.72	32.70	9.81	58.11	0.62 300 173 Peak																																																																																																																										
2	7386.00	49.17	74.00	-24.83	57.64	36.46	12.21	57.79	0.65 181 187 Peak																																																																																																																										
3	7386.00	41.69	54.00	-12.31	50.16	36.46	12.21	57.79	0.65 181 187 Average																																																																																																																										



Mode	11	
	Harmonic	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL



Mode	12																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11b_CH12_2467MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.53</td><td>60.20</td><td>74.00</td><td>-13.80</td><td>52.80</td><td>27.75</td><td>6.69</td><td>36.97</td><td>9.93</td><td>100</td><td>181</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.53	60.20	74.00	-13.80	52.80	27.75	6.69	36.97	9.93	100	181	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2467.00</td><td>111.32</td><td>74.00</td><td>37.32</td><td>104.09</td><td>27.60</td><td>6.67</td><td>36.97</td><td>9.93</td><td>100</td><td>181</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2467.00	111.32	74.00	37.32	104.09	27.60	6.67	36.97	9.93	100	181	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.53	60.20	74.00	-13.80	52.80	27.75	6.69	36.97	9.93	100	181	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2467.00	111.32	74.00	37.32	104.09	27.60	6.67	36.97	9.93	100	181	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.80</td><td>53.53</td><td>54.00</td><td>-0.47</td><td>46.13</td><td>27.75</td><td>6.69</td><td>36.97</td><td>9.93</td><td>100</td><td>181</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.80	53.53	54.00	-0.47	46.13	27.75	6.69	36.97	9.93	100	181	Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2467.00</td><td>107.81</td><td>54.00</td><td>53.81</td><td>100.58</td><td>27.60</td><td>6.67</td><td>36.97</td><td>9.93</td><td>100</td><td>181</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2467.00	107.81	54.00	53.81	100.58	27.60	6.67	36.97	9.93	100	181	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.80	53.53	54.00	-0.47	46.13	27.75	6.69	36.97	9.93	100	181	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2467.00	107.81	54.00	53.81	100.58	27.60	6.67	36.97	9.93	100	181	Average																																																																									







Mode	12																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11b_CH12_2467MHz																																																																																			
ANT	1																																																																																			
Pol.	Vertical						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.88</td><td>56.34</td><td>74.00</td><td>-17.66</td><td>48.94</td><td>27.75</td><td>6.69</td><td>36.97</td><td>9.93</td><td>107</td><td>236</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.88	56.34	74.00	-17.66	48.94	27.75	6.69	36.97	9.93	107	236	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2467.00</td><td>106.54</td><td>-----</td><td>-----</td><td>99.31</td><td>27.60</td><td>6.67</td><td>36.97</td><td>9.93</td><td>107</td><td>236</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2467.00	106.54	-----	-----	99.31	27.60	6.67	36.97	9.93	107	236	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.88	56.34	74.00	-17.66	48.94	27.75	6.69	36.97	9.93	107	236	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2467.00	106.54	-----	-----	99.31	27.60	6.67	36.97	9.93	107	236	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.72</td><td>48.89</td><td>54.00</td><td>-5.11</td><td>41.49</td><td>27.75</td><td>6.69</td><td>36.97</td><td>9.93</td><td>107</td><td>236</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.72	48.89	54.00	-5.11	41.49	27.75	6.69	36.97	9.93	107	236	Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2467.00</td><td>183.23</td><td>-----</td><td>-----</td><td>96.00</td><td>27.60</td><td>6.67</td><td>36.97</td><td>9.93</td><td>107</td><td>236</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2467.00	183.23	-----	-----	96.00	27.60	6.67	36.97	9.93	107	236	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.72	48.89	54.00	-5.11	41.49	27.75	6.69	36.97	9.93	107	236	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2467.00	183.23	-----	-----	96.00	27.60	6.67	36.97	9.93	107	236	Average																																																																									



Mode	12																																																																																																																									
	Harmonic																																																																																																																									
	2400-2483.5_802.11b_CH12_2467MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4934.00</td><td>41.86</td><td>74.00</td><td>-32.14</td><td>56.74</td><td>32.74</td><td>9.83</td><td>58.08</td><td>0.63</td><td>-- -- Peak</td></tr><tr><td>2 7401.00</td><td>49.13</td><td>74.00</td><td>-24.87</td><td>57.67</td><td>36.40</td><td>12.22</td><td>57.81</td><td>0.65</td><td>200 12 Peak</td></tr><tr><td>3 7401.00</td><td>41.08</td><td>54.00</td><td>-12.92</td><td>49.62</td><td>36.40</td><td>12.22</td><td>57.81</td><td>0.65</td><td>200 12 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4934.00	41.86	74.00	-32.14	56.74	32.74	9.83	58.08	0.63	-- -- Peak	2 7401.00	49.13	74.00	-24.87	57.67	36.40	12.22	57.81	0.65	200 12 Peak	3 7401.00	41.08	54.00	-12.92	49.62	36.40	12.22	57.81	0.65	200 12 Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4934.00</td><td>41.62</td><td>74.00</td><td>-32.38</td><td>56.50</td><td>32.74</td><td>9.83</td><td>58.08</td><td>0.63</td><td>-- -- Peak</td></tr><tr><td>2 7401.00</td><td>47.30</td><td>74.00</td><td>-26.70</td><td>55.84</td><td>36.40</td><td>12.22</td><td>57.81</td><td>0.65</td><td>193 358 Peak</td></tr><tr><td>3 7401.00</td><td>40.00</td><td>54.00</td><td>-14.00</td><td>48.54</td><td>36.40</td><td>12.22</td><td>57.81</td><td>0.65</td><td>193 358 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4934.00	41.62	74.00	-32.38	56.50	32.74	9.83	58.08	0.63	-- -- Peak	2 7401.00	47.30	74.00	-26.70	55.84	36.40	12.22	57.81	0.65	193 358 Peak	3 7401.00	40.00	54.00	-14.00	48.54	36.40	12.22	57.81	0.65	193 358 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 4934.00	41.86	74.00	-32.14	56.74	32.74	9.83	58.08	0.63	-- -- Peak																																																																																																																	
2 7401.00	49.13	74.00	-24.87	57.67	36.40	12.22	57.81	0.65	200 12 Peak																																																																																																																	
3 7401.00	41.08	54.00	-12.92	49.62	36.40	12.22	57.81	0.65	200 12 Average																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 4934.00	41.62	74.00	-32.38	56.50	32.74	9.83	58.08	0.63	-- -- Peak																																																																																																																	
2 7401.00	47.30	74.00	-26.70	55.84	36.40	12.22	57.81	0.65	193 358 Peak																																																																																																																	
3 7401.00	40.00	54.00	-14.00	48.54	36.40	12.22	57.81	0.65	193 358 Average																																																																																																																	



Mode	12	
	Harmonic	
	2400-2483.5_802.11b_CH12_2467MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL



Mode	13																																																																									
	Band Edge																																																																									
	2400-2483.5_802.11b_CH13_2472MHz																																																																									
ANT	1																																																																									
Pol.	Horizontal	Fundamental																																																																								
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2484.34 60.68 74.00 -13.32 53.29 27.74 6.69 36.97 9.93 100 179 Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg									1 2484.34 60.68 74.00 -13.32 53.29 27.74 6.69 36.97 9.93 100 179 Peak									Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2472.00 100.21 ----- 100.95 27.62 6.68 36.97 9.93 100 179 Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg									1 2472.00 100.21 ----- 100.95 27.62 6.68 36.97 9.93 100 179 Peak								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg																																																																										
1 2484.34 60.68 74.00 -13.32 53.29 27.74 6.69 36.97 9.93 100 179 Peak																																																																										
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg																																																																										
1 2472.00 100.21 ----- 100.95 27.62 6.68 36.97 9.93 100 179 Peak																																																																										
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2484.42 53.65 54.00 -0.35 46.26 27.74 6.69 36.97 9.93 100 179 Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg									1 2484.42 53.65 54.00 -0.35 46.26 27.74 6.69 36.97 9.93 100 179 Average									Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2472.00 104.61 ----- 97.33 27.64 6.68 36.97 9.93 100 179 Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg									1 2472.00 104.61 ----- 97.33 27.64 6.68 36.97 9.93 100 179 Average								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg																																																																										
1 2484.42 53.65 54.00 -0.35 46.26 27.74 6.69 36.97 9.93 100 179 Average																																																																										
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dB/dB dB dB dB dB cm deg																																																																										
1 2472.00 104.61 ----- 97.33 27.64 6.68 36.97 9.93 100 179 Average																																																																										



Mode	13																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH13_2472MHz																																																																																	
ANT	1																																																																																	
Pol.	Vertical					Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2484.46 56.65 74.00 -17.35 49.26 27.74 6.69 36.97 9.93 100 239 Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2484.46 56.65 74.00 -17.35 49.26 27.74 6.69 36.97 9.93 100 239 Peak									Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2472.00 102.63 ----- 95.37 27.62 6.68 36.97 9.93 100 239 Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2472.00 102.63 ----- 95.37 27.62 6.68 36.97 9.93 100 239 Peak								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																																		
1 2484.46 56.65 74.00 -17.35 49.26 27.74 6.69 36.97 9.93 100 239 Peak																																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																																		
1 2472.00 102.63 ----- 95.37 27.62 6.68 36.97 9.93 100 239 Peak																																																																																		
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2484.57 48.69 54.00 -5.31 41.29 27.75 6.69 36.97 9.93 100 239 Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2484.57 48.69 54.00 -5.31 41.29 27.75 6.69 36.97 9.93 100 239 Average									Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2472.00 99.12 ----- 91.89 27.60 6.67 36.97 9.93 100 239 Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2472.00 99.12 ----- 91.89 27.60 6.67 36.97 9.93 100 239 Average								
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																																		
1 2484.57 48.69 54.00 -5.31 41.29 27.75 6.69 36.97 9.93 100 239 Average																																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																																		
1 2472.00 99.12 ----- 91.89 27.60 6.67 36.97 9.93 100 239 Average																																																																																		



Mode	13																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5_802.11b_CH13_2472MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4944.00</td><td>40.11</td><td>74.00</td><td>-33.89</td><td>54.92</td><td>32.78</td><td>9.84</td><td>58.06</td><td>0.63</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7416.00</td><td>44.13</td><td>74.00</td><td>-29.87</td><td>52.74</td><td>36.34</td><td>12.23</td><td>57.83</td><td>0.65</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4944.00	40.11	74.00	-33.89	54.92	32.78	9.84	58.06	0.63	--	Peak	2	7416.00	44.13	74.00	-29.87	52.74	36.34	12.23	57.83	0.65	--	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4944.00</td><td>40.45</td><td>74.00</td><td>-33.55</td><td>55.26</td><td>32.78</td><td>9.84</td><td>58.06</td><td>0.63</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7416.00</td><td>44.81</td><td>74.00</td><td>-29.19</td><td>53.42</td><td>36.34</td><td>12.23</td><td>57.83</td><td>0.65</td><td>--</td><td>Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4944.00	40.45	74.00	-33.55	55.26	32.78	9.84	58.06	0.63	--	Peak	2	7416.00	44.81	74.00	-29.19	53.42	36.34	12.23	57.83	0.65	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4944.00	40.11	74.00	-33.89	54.92	32.78	9.84	58.06	0.63	--	Peak																																																																																																														
2	7416.00	44.13	74.00	-29.87	52.74	36.34	12.23	57.83	0.65	--	Peak																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4944.00	40.45	74.00	-33.55	55.26	32.78	9.84	58.06	0.63	--	Peak																																																																																																														
2	7416.00	44.81	74.00	-29.19	53.42	36.34	12.23	57.83	0.65	--	Peak																																																																																																														



Mode	13	
	Harmonic	
	2400-2483.5_802.11b_CH13_2472MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL
	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL



Mode	14																																																																																		
	Band Edge																																																																																		
	2400-2483.5_802.11g_CH01_2412MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2389.95</td><td>70.83</td><td>74.00</td><td>-3.17</td><td>64.01</td><td>27.30</td><td>6.56</td><td>36.97</td><td>9.93</td><td>146</td><td>186</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2389.95	70.83	74.00	-3.17	64.01	27.30	6.56	36.97	9.93	146	186	Peak	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2412.00</td><td>112.70</td><td>-----</td><td>-----</td><td>105.75</td><td>27.40</td><td>6.59</td><td>36.97</td><td>9.93</td><td>146</td><td>186</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2412.00	112.70	-----	-----	105.75	27.40	6.59	36.97	9.93	146	186	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2389.95	70.83	74.00	-3.17	64.01	27.30	6.56	36.97	9.93	146	186	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2412.00	112.70	-----	-----	105.75	27.40	6.59	36.97	9.93	146	186	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2389.95</td><td>53.68</td><td>54.00</td><td>-0.32</td><td>46.06</td><td>27.30</td><td>6.56</td><td>36.97</td><td>9.93</td><td>146</td><td>186</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2389.95	53.68	54.00	-0.32	46.06	27.30	6.56	36.97	9.93	146	186	Average	Level (dBuV/m) Date: 2025-11-14 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2412.00</td><td>105.24</td><td>-----</td><td>-----</td><td>98.28</td><td>27.40</td><td>6.60</td><td>36.97</td><td>9.93</td><td>146</td><td>186</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2412.00	105.24	-----	-----	98.28	27.40	6.60	36.97	9.93	146	186	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2389.95	53.68	54.00	-0.32	46.06	27.30	6.56	36.97	9.93	146	186	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2412.00	105.24	-----	-----	98.28	27.40	6.60	36.97	9.93	146	186	Average																																																																								