



FCC RADIO TEST REPORT

FCC ID : 2BSOW-BWS3004BAB
Equipment : Smart Birdfeeder, Camera
Brand Name : Birdbuddy
Model Name : Neo Lite, Birdbuddy Nook
Applicant : Bird Buddy Inc.
169 Madison Avenue, Suite 15233, New York, NY 10016, US
Manufacturer : Xavi Technologies (Thailand) Co., Ltd.
82 Mu 4, Takham Bangpakong, Chachoengsao 24130, Thailand
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 27, 2026 and testing was performed from Jun. 02, 2026 to Jul. 06, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	5
2 Test Configuration of Equipment Under Test.....	6
2.1 Carrier Frequency Channel	6
2.2 Test Mode.....	6
2.3 Connection Diagram of Test System.....	7
2.4 Support Unit used in test configuration and system	7
2.5 EUT Operation Test Setup	7
3 Test Result.....	8
3.1 Output Power Measurement.....	8
3.2 Radiated Band Edges and Spurious Emission Measurement	9
3.3 Antenna Requirements	12
4 List of Measuring Equipment	13
5 Measurement Uncertainty	14
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission Test Result	
Appendix C. Duty Cycle Plots	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR582014-02A	01	Initial issue of report	Jul. 16, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.247(a)(2)	6dB Bandwidth	Pass	See Note
-	2.1049	99% Occupied Bandwidth	Pass	See Note
3.1	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
-	15.247(e)	Power Spectral Density	Pass	See Note
-	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	See Note
3.2	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	
-	15.207	AC Conducted Emission	Pass	See Note
3.3	15.203	Antenna Requirement	Pass	-

Note: This is a variant report by closing WLAN 5GHz and the addition of the Equipment Name and Model Name for the applicant's company internal product planning purpose. After assessing, except for Conducted Power and Radiated Emission are carrying out, all the other test cases were performed on original report which can be referred to Sporton Report Number FR582014-01A.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sheng Kuo

Report Producer: Shiori Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth-LE and Wi-Fi 2.4GHz 802.11b/g/n.
Antenna Type Bluetooth: Dipole Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.94

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Remark: The detailed Radiated test modes are shown in Appendix B.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	Google	G9BR1 LPS	N/A	N/A	N/A
2.	Notebook	Acer	N18Q13	PD9AX201NG	N/A	Unshielded, 1.8m

2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Output Power Measurement

3.1.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of Average Output Power

Please refer to Appendix A.

3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.


8. Use the following spectrum analyzer settings:
- (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.2.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.2.7 Duty Cycle

Please refer to Appendix C.

3.2.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.3 Antenna Requirements

3.3.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.3.2 Antenna Anti-Replacement Construction

Unique (non-standard) antenna connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Jun. 23, 2026~ Jul. 06, 2026	Dec. 11, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 04, 2026	Jun. 23, 2026~ Jul. 06, 2026	Mar. 03, 2027	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	40103 & 07	30MHz~1GHz	Apr. 12, 2026	Jun. 23, 2026~ Jul. 06, 2026	Apr. 11, 2027	Radiation (03CH13-HY)
Amplifier	SONOMA	310N	187282	9kHz~1GHz	Dec. 11, 2025	Jun. 23, 2026~ Jul. 06, 2026	Dec. 10, 2026	Radiation (03CH13-HY)
Double Ridged Guide Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Sep. 03, 2025	Jun. 23, 2026~ Jul. 06, 2026	Sep. 02, 2026	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 13, 2026	Jun. 23, 2026~ Jul. 06, 2026	May 12, 2027	Radiation (03CH13-HY)
Preamplifier	EMEC	EM01G18G	060803	1GHz-18GHz	Jan. 07, 2026	Jun. 23, 2026~ Jul. 06, 2026	Jan. 06, 2027	Radiation (03CH13-HY)
Signal Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Dec. 05, 2025	Jun. 23, 2026~ Jul. 06, 2026	Dec. 04, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102E	508408-2E	30MHz~40GHz	Jun. 15, 2026	Jun. 23, 2026~ Jul. 06, 2026	Jun. 14, 2027	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30MHz~18GHz	Feb. 05, 2026	Jun. 23, 2026~ Jul. 06, 2026	Feb. 04, 2027	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30MHz~18GHz	Feb. 05, 2026	Jun. 23, 2026~ Jul. 06, 2026	Feb. 04, 2027	Radiation (03CH13-HY)
Notch Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN12	1.53GHz Low Pass Filter	Sep. 10, 2025	Jun. 23, 2026~ Jul. 06, 2026	Sep. 09, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX12-2700 -3000-18000-6 0SS	SN2	3GHz High Pass Filter	Jul. 08, 2025	Jun. 23, 2026~ Jul. 06, 2026	Jul. 07, 2026	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 23, 2026~ Jul. 06, 2026	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jun. 23, 2026~ Jul. 06, 2026	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 23, 2026~ Jul. 06, 2026	N/A	Radiation (03CH13-HY)
Software	Audix	E3	RK-002392	N/A	N/A	Jun. 23, 2026~ Jul. 06, 2026	N/A	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 02, 2025	Jun. 23, 2026~ Jul. 06, 2026	Dec. 01, 2026	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9170	1230	18GHz-40GHz	Nov. 05, 2025	Jun. 23, 2026~ Jul. 06, 2026	Nov. 04, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18GHz~40GHz	Dec. 18, 2025	Jun. 23, 2026~ Jul. 06, 2026	Dec. 17, 2026	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP215159	N/A	Sep. 08, 2025	Jun. 23, 2026~ Jul. 06, 2026	Sep. 07, 2026	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Jun. 02, 2026~ Jun. 11, 2026	Nov. 03, 2026	Conducted (TH05-HY)
USB RF Power Sensor	DARE	RPR3006W	17I00015SNO 37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Jun. 02, 2026~ Jun. 11, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Nov. 12, 2025	Jun. 02, 2026~ Jun. 11, 2026	Nov. 11, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900067 (BOX7)	N/A	Jul. 02, 2025	Jun. 02, 2026~ Jun. 11, 2026	Jul. 01, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final version_24051 3	N/A	Conducted Other Test Item	N/A	Jun. 02, 2026~ Jun. 11, 2026	N/A	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.2 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jay Chen	Temperature:	21~25	°C
Test Date:	2026/6/2~2026/6/11	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.66	30.00	2.94	9.60	36.00	Pass
BLE	1Mbps	1	19	2440	6.26	30.00	2.94	9.20	36.00	Pass
BLE	1Mbps	1	39	2480	6.15	30.00	2.94	9.09	36.00	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	6.14	30.00	2.94	9.08	36.00	Pass
BLE	2Mbps	1	19	2440	6.23	30.00	2.94	9.17	36.00	Pass
BLE	2Mbps	1	39	2480	6.18	30.00	2.94	9.12	36.00	Pass



Appendix B. Radiated Spurious Emission Test Data

Test Engineer:	Rain Lee, Jacky Hong, and White Hou	Temperature:	21.2~26.3 °C
		Relative Humidity:	45.2~53.6 %

Note symbol

-L	Low channel location
-R	High channel location





B1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE_GSKF	19	2440	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE_GSKF	00	2402	2Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE_GSKF	39	2480	2Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE_GSKF	39	2480	2Mbps	-	LF
Mode 5	2400-2483.5	1	Bluetooth-LE_GSKF	39	2480	2Mbps	-	SHF

B2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE_GSKF	19	2497.12	40.88	54.00	-13.12	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GSKF	19	7320.00	46.13	74.00	-27.87	V	Peak	Pass	-	Harmonic
2	Bluetooth-LE_GSKF	00	2389.98	40.64	54.00	-13.36	H	Avg.	Pass	-	Band Edge
2	Bluetooth-LE_GSKF	00	4804.00	42.00	74.00	-32.00	H	Peak	Pass	-	Harmonic
3	Bluetooth-LE_GSKF	39	2483.52	45.55	54.00	-8.45	H	Avg.	Pass	-	Band Edge
3	Bluetooth-LE_GSKF	39	7440.00	44.60	74.00	-29.40	H	Peak	Pass	-	Harmonic
4	LF	39	94.02	35.77	43.50	-7.73	H	Peak	Pass	-	LF
5	SHF	39	24909.00	51.40	74.00	-22.60	V	Peak	Pass	-	SHF



Mode	1																																																																																																			
	Band Edge - L																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2380.20</td><td>51.81</td><td>74.00</td><td>-22.19</td><td>44.94</td><td>27.20</td><td>6.68</td><td>36.94</td><td>9.93</td><td>200</td><td>168</td><td>Peak</td></tr></tbody></table> Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>73.06</td><td>-----</td><td>-----</td><td>65.81</td><td>27.50</td><td>6.76</td><td>36.94</td><td>9.93</td><td>200</td><td>168</td><td>Peak</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2380.20	51.81	74.00	-22.19	44.94	27.20	6.68	36.94	9.93	200	168	Peak		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	73.06	-----	-----	65.81	27.50	6.76	36.94	9.93	200	168	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2380.20	51.81	74.00	-22.19	44.94	27.20	6.68	36.94	9.93	200	168	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	73.06	-----	-----	65.81	27.50	6.76	36.94	9.93	200	168	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.56</td><td>40.23</td><td>54.00</td><td>-13.77</td><td>33.25</td><td>27.30</td><td>6.69</td><td>36.94</td><td>9.93</td><td>200</td><td>168</td><td>Average</td></tr></tbody></table> Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>72.13</td><td>-----</td><td>-----</td><td>64.88</td><td>27.50</td><td>6.76</td><td>36.94</td><td>9.93</td><td>200</td><td>168</td><td>Average</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.56	40.23	54.00	-13.77	33.25	27.30	6.69	36.94	9.93	200	168	Average		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	72.13	-----	-----	64.88	27.50	6.76	36.94	9.93	200	168	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2389.56	40.23	54.00	-13.77	33.25	27.30	6.69	36.94	9.93	200	168	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	72.13	-----	-----	64.88	27.50	6.76	36.94	9.93	200	168	Average																																																																																								



Mode	1																																																						
	Band Edge - R																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																						
ANT	1																																																						
Pol.	Horizontal						Fundamental																																																
Peak	Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.84</td><td>52.12</td><td>74.00</td><td>-21.88</td><td>44.43</td><td>27.88</td><td>6.83</td><td>36.95</td><td>9.93</td><td>200</td><td>168</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.84	52.12	74.00	-21.88	44.43	27.88	6.83	36.95	9.93	200	168	Peak	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2497.84	52.12	74.00	-21.88	44.43	27.88	6.83	36.95	9.93	200	168	Peak																																											
Avg	Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2498.02</td><td>40.86</td><td>54.00</td><td>-13.14</td><td>33.17</td><td>27.88</td><td>6.83</td><td>36.95</td><td>9.93</td><td>200</td><td>168</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2498.02	40.86	54.00	-13.14	33.17	27.88	6.83	36.95	9.93	200	168	Average	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2498.02	40.86	54.00	-13.14	33.17	27.88	6.83	36.95	9.93	200	168	Average																																											



Mode	1																																																																																																			
	Band Edge - L																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2327.68</td><td>51.84</td><td>74.00</td><td>-22.16</td><td>45.04</td><td>27.20</td><td>6.60</td><td>36.93</td><td>9.93</td><td>327</td><td>126</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2327.68	51.84	74.00	-22.16	45.04	27.20	6.60	36.93	9.93	327	126	Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>70.48</td><td>-----</td><td>-----</td><td>63.23</td><td>27.50</td><td>6.76</td><td>36.94</td><td>9.93</td><td>327</td><td>126</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	70.48	-----	-----	63.23	27.50	6.76	36.94	9.93	327	126	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2327.68	51.84	74.00	-22.16	45.04	27.20	6.60	36.93	9.93	327	126	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	70.48	-----	-----	63.23	27.50	6.76	36.94	9.93	327	126	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.78</td><td>40.22</td><td>54.00</td><td>-13.78</td><td>33.25</td><td>27.29</td><td>6.69</td><td>36.94</td><td>9.93</td><td>327</td><td>126</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.78	40.22	54.00	-13.78	33.25	27.29	6.69	36.94	9.93	327	126	Average	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>69.32</td><td>-----</td><td>-----</td><td>62.07</td><td>27.50</td><td>6.76</td><td>36.94</td><td>9.93</td><td>327</td><td>126</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	69.32	-----	-----	62.07	27.50	6.76	36.94	9.93	327	126	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2388.78	40.22	54.00	-13.78	33.25	27.29	6.69	36.94	9.93	327	126	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	69.32	-----	-----	62.07	27.50	6.76	36.94	9.93	327	126	Average																																																																																								







Mode	1																																													
	Band Edge - R																																													
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																													
ANT	1																																													
Pol.	Vertical	Fundamental																																												
Peak	Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2498.32</td><td>52.43</td><td>74.00</td><td>-21.57</td><td>44.74</td><td>27.88</td><td>6.83</td><td>36.95</td><td>9.93</td><td>327</td><td>126</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2498.32	52.43	74.00	-21.57	44.74	27.88	6.83	36.95	9.93	327	126	Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	2498.32	52.43	74.00	-21.57	44.74	27.88	6.83	36.95	9.93	327	126	Peak																																		
Avg	Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.12</td><td>40.88</td><td>54.00</td><td>-13.12</td><td>33.20</td><td>27.87</td><td>6.83</td><td>36.95</td><td>9.93</td><td>327</td><td>126</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.12	40.88	54.00	-13.12	33.20	27.87	6.83	36.95	9.93	327	126	Average	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	2497.12	40.88	54.00	-13.12	33.20	27.87	6.83	36.95	9.93	327	126	Average																																		



Mode	1																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>41.77</td><td>74.00</td><td>-32.23</td><td>55.61</td><td>32.56</td><td>10.28</td><td>57.29</td><td>0.61</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>45.57</td><td>74.00</td><td>-28.43</td><td>53.47</td><td>36.66</td><td>12.05</td><td>57.26</td><td>0.65</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	41.77	74.00	-32.23	55.61	32.56	10.28	57.29	0.61	--	Peak	2	7320.00	45.57	74.00	-28.43	53.47	36.66	12.05	57.26	0.65	--	Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>42.17</td><td>74.00</td><td>-31.83</td><td>56.01</td><td>32.56</td><td>10.28</td><td>57.29</td><td>0.61</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>46.13</td><td>74.00</td><td>-27.87</td><td>54.03</td><td>36.66</td><td>12.05</td><td>57.26</td><td>0.65</td><td>--</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	42.17	74.00	-31.83	56.01	32.56	10.28	57.29	0.61	--	Peak	2	7320.00	46.13	74.00	-27.87	54.03	36.66	12.05	57.26	0.65	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4880.00	41.77	74.00	-32.23	55.61	32.56	10.28	57.29	0.61	--	Peak																																																																																																														
2	7320.00	45.57	74.00	-28.43	53.47	36.66	12.05	57.26	0.65	--	Peak																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4880.00	42.17	74.00	-31.83	56.01	32.56	10.28	57.29	0.61	--	Peak																																																																																																														
2	7320.00	46.13	74.00	-27.87	54.03	36.66	12.05	57.26	0.65	--	Peak																																																																																																														



Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL
	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL



Mode	2																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																									
ANT	1																																																																																									
Pol.	Horizontal						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2328.14</td><td>51.85</td><td>74.00</td><td>-22.15</td><td>45.06</td><td>27.20</td><td>6.59</td><td>36.93</td><td>9.93</td><td>154</td><td>182</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2328.14	51.85	74.00	-22.15	45.06	27.20	6.59	36.93	9.93	154	182	Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>103.46</td><td>-----</td><td>-----</td><td>96.44</td><td>27.32</td><td>6.71</td><td>36.94</td><td>9.93</td><td>154</td><td>182</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	103.46	-----	-----	96.44	27.32	6.71	36.94	9.93	154	182	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2328.14	51.85	74.00	-22.15	45.06	27.20	6.59	36.93	9.93	154	182	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2402.00	103.46	-----	-----	96.44	27.32	6.71	36.94	9.93	154	182	Peak																																																																														
Avg	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.98</td><td>40.64</td><td>54.00</td><td>-13.36</td><td>33.66</td><td>27.30</td><td>6.69</td><td>36.94</td><td>9.93</td><td>154</td><td>182</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.98	40.64	54.00	-13.36	33.66	27.30	6.69	36.94	9.93	154	182	Average	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>101.98</td><td>-----</td><td>-----</td><td>94.96</td><td>27.32</td><td>6.71</td><td>36.94</td><td>9.93</td><td>154</td><td>182</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	101.98	-----	-----	94.96	27.32	6.71	36.94	9.93	154	182	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2389.98	40.64	54.00	-13.36	33.66	27.30	6.69	36.94	9.93	154	182	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2402.00	101.98	-----	-----	94.96	27.32	6.71	36.94	9.93	154	182	Average																																																																														







Mode	2																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2359.94</td><td>52.27</td><td>74.00</td><td>-21.73</td><td>45.43</td><td>27.20</td><td>6.65</td><td>36.94</td><td>9.93</td><td>100</td><td>103</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2359.94	52.27	74.00	-21.73	45.43	27.20	6.65	36.94	9.93	100	103	Peak	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>100.61</td><td>-----</td><td>-----</td><td>93.59</td><td>27.32</td><td>6.71</td><td>36.94</td><td>9.93</td><td>100</td><td>103</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	100.61	-----	-----	93.59	27.32	6.71	36.94	9.93	100	103	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2359.94	52.27	74.00	-21.73	45.43	27.20	6.65	36.94	9.93	100	103	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	100.61	-----	-----	93.59	27.32	6.71	36.94	9.93	100	103	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2359.98</td><td>40.57</td><td>54.00</td><td>-13.43</td><td>33.59</td><td>27.30</td><td>6.69</td><td>36.94</td><td>9.93</td><td>100</td><td>103</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2359.98	40.57	54.00	-13.43	33.59	27.30	6.69	36.94	9.93	100	103	Average	Level (dBuV/m) Date: 2026-06-23 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>99.18</td><td>-----</td><td>-----</td><td>92.16</td><td>27.32</td><td>6.71</td><td>36.94</td><td>9.93</td><td>100</td><td>103</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	99.18	-----	-----	92.16	27.32	6.71	36.94	9.93	100	103	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2359.98	40.57	54.00	-13.43	33.59	27.30	6.69	36.94	9.93	100	103	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	99.18	-----	-----	92.16	27.32	6.71	36.94	9.93	100	103	Average																																																																																								







Mode	2																																																																																					
	Harmonic																																																																																					
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																					
ANT	1																																																																																					
Pol.	Horizontal	Vertical																																																																																				
Peak Avg	Level (dBuV/m) Date: 2026-07-03 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>42.00</td><td>74.00</td><td>-32.00</td><td>56.41</td><td>32.22</td><td>10.31</td><td>57.52</td><td>0.58</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	4804.00	42.00	74.00	-32.00	56.41	32.22	10.31	57.52	0.58	--	--	--	Peak	Level (dBuV/m) Date: 2026-07-03 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>41.16</td><td>74.00</td><td>-32.84</td><td>55.57</td><td>32.22</td><td>10.31</td><td>57.52</td><td>0.58</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	4804.00	41.16	74.00	-32.84	55.57	32.22	10.31	57.52	0.58	--	--	--	Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																										
1	4804.00	42.00	74.00	-32.00	56.41	32.22	10.31	57.52	0.58	--	--	--	Peak																																																																									
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																										
1	4804.00	41.16	74.00	-32.84	55.57	32.22	10.31	57.52	0.58	--	--	--	Peak																																																																									







Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-07-03  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-07-03  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	Level (dBuV/m) Date: 2026-07-03  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-07-03  Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL



Mode	3																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-06-23  PEAK_BE_74 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>55.46</td><td>74.00</td><td>-18.54</td><td>47.93</td><td>27.74</td><td>6.81</td><td>36.95</td><td>9.93</td><td>104</td><td>164</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	55.46	74.00	-18.54	47.93	27.74	6.81	36.95	9.93	104	164	Peak	Level (dBuV/m) Date: 2026-06-23  PEAK_74 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.00</td><td>106.15</td><td>-----</td><td>-----</td><td>98.66</td><td>27.70</td><td>6.81</td><td>36.95</td><td>9.93</td><td>104</td><td>164</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2488.00	106.15	-----	-----	98.66	27.70	6.81	36.95	9.93	104	164	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.52	55.46	74.00	-18.54	47.93	27.74	6.81	36.95	9.93	104	164	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2488.00	106.15	-----	-----	98.66	27.70	6.81	36.95	9.93	104	164	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-06-23  AVG_BE_54 Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>45.55</td><td>54.00</td><td>-8.45</td><td>38.02</td><td>27.74</td><td>6.81</td><td>36.95</td><td>9.93</td><td>104</td><td>164</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	45.55	54.00	-8.45	38.02	27.74	6.81	36.95	9.93	104	164	Average	Level (dBuV/m) Date: 2026-06-23  AVG_54 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.00</td><td>104.73</td><td>-----</td><td>-----</td><td>97.24</td><td>27.70</td><td>6.81</td><td>36.95</td><td>9.93</td><td>104</td><td>164</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2488.00	104.73	-----	-----	97.24	27.70	6.81	36.95	9.93	104	164	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.52	45.55	54.00	-8.45	38.02	27.74	6.81	36.95	9.93	104	164	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2488.00	104.73	-----	-----	97.24	27.70	6.81	36.95	9.93	104	164	Average																																																																																								



Mode	3																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>54.57</td><td>74.00</td><td>-19.43</td><td>47.04</td><td>27.74</td><td>6.81</td><td>36.95</td><td>9.93</td><td>318</td><td>130</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	54.57	74.00	-19.43	47.04	27.74	6.81	36.95	9.93	318	130	Peak	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>103.83</td><td>-----</td><td>-----</td><td>96.34</td><td>27.70</td><td>6.81</td><td>36.95</td><td>9.93</td><td>318</td><td>130</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	103.83	-----	-----	96.34	27.70	6.81	36.95	9.93	318	130	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.52	54.57	74.00	-19.43	47.04	27.74	6.81	36.95	9.93	318	130	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	103.83	-----	-----	96.34	27.70	6.81	36.95	9.93	318	130	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_BE_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>44.26</td><td>54.00</td><td>-9.74</td><td>36.73</td><td>27.74</td><td>6.81</td><td>36.95</td><td>9.93</td><td>318</td><td>130</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	44.26	54.00	-9.74	36.73	27.74	6.81	36.95	9.93	318	130	Average	Level (dBuV/m) Date: 2026-06-23  Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.42</td><td>-----</td><td>-----</td><td>94.93</td><td>27.70</td><td>6.81</td><td>36.95</td><td>9.93</td><td>318</td><td>130</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	102.42	-----	-----	94.93	27.70	6.81	36.95	9.93	318	130	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.52	44.26	54.00	-9.74	36.73	27.74	6.81	36.95	9.93	318	130	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	102.42	-----	-----	94.93	27.70	6.81	36.95	9.93	318	130	Average																																																																																								



Mode	3																																																																																																															
	Harmonic																																																																																																															
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																															
ANT	1																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>41.55</td><td>74.00</td><td>-32.45</td><td>54.05</td><td>32.06</td><td>10.25</td><td>57.05</td><td>0.64</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7440.00</td><td>44.60</td><td>74.00</td><td>-29.40</td><td>53.10</td><td>36.24</td><td>12.12</td><td>57.50</td><td>0.64</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	41.55	74.00	-32.45	54.05	32.06	10.25	57.05	0.64	--	Peak	2	7440.00	44.60	74.00	-29.40	53.10	36.24	12.12	57.50	0.64	--	Peak	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>41.15</td><td>74.00</td><td>-32.85</td><td>54.45</td><td>32.86</td><td>10.25</td><td>57.05</td><td>0.64</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7440.00</td><td>44.58</td><td>74.00</td><td>-29.42</td><td>53.08</td><td>36.24</td><td>12.12</td><td>57.50</td><td>0.64</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	41.15	74.00	-32.85	54.45	32.86	10.25	57.05	0.64	--	Peak	2	7440.00	44.58	74.00	-29.42	53.08	36.24	12.12	57.50	0.64	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	4960.00	41.55	74.00	-32.45	54.05	32.06	10.25	57.05	0.64	--	Peak																																																																																																					
2	7440.00	44.60	74.00	-29.40	53.10	36.24	12.12	57.50	0.64	--	Peak																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	4960.00	41.15	74.00	-32.85	54.45	32.86	10.25	57.05	0.64	--	Peak																																																																																																					
2	7440.00	44.58	74.00	-29.42	53.08	36.24	12.12	57.50	0.64	--	Peak																																																																																																					



Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL
	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 HORIZONTAL	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: AVG_54 3m HORN_91280_1326 VERTICAL



Mode	4																																																																																																																																																																																																																									
	LF																																																																																																																																																																																																																									
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																																																																																																																																									
ANT	1																																																																																																																																																																																																																									
Pol.	Horizontal						Vertical																																																																																																																																																																																																																			
QP/ Peak	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: QP 3m B1L06_40103 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>30.97</td><td>23.18</td><td>40.00</td><td>-16.82</td><td>30.50</td><td>23.94</td><td>0.77</td><td>32.16</td><td>0.05</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>94.02</td><td>35.77</td><td>43.50</td><td>-7.73</td><td>51.35</td><td>15.09</td><td>1.38</td><td>32.12</td><td>0.07</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>261.83</td><td>20.16</td><td>46.00</td><td>-25.84</td><td>29.70</td><td>20.04</td><td>2.27</td><td>31.97</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>288.02</td><td>30.10</td><td>46.00</td><td>-15.90</td><td>40.71</td><td>18.89</td><td>2.36</td><td>31.98</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>731.31</td><td>36.07</td><td>46.00</td><td>-9.93</td><td>36.45</td><td>27.67</td><td>3.74</td><td>31.93</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>898.15</td><td>34.53</td><td>46.00</td><td>-11.47</td><td>32.72</td><td>28.83</td><td>4.11</td><td>31.31</td><td>0.18</td><td>--</td><td>Peak</td></tr></tbody></table> Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: QP 3m B1L06_40103 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>30.97</td><td>27.85</td><td>40.00</td><td>-12.15</td><td>35.25</td><td>23.94</td><td>0.77</td><td>32.16</td><td>0.05</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>94.99</td><td>33.88</td><td>43.50</td><td>-9.62</td><td>49.33</td><td>15.21</td><td>1.39</td><td>32.12</td><td>0.07</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>262.80</td><td>21.27</td><td>46.00</td><td>-24.73</td><td>30.81</td><td>20.04</td><td>2.27</td><td>31.97</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>288.02</td><td>28.14</td><td>46.00</td><td>-17.86</td><td>38.75</td><td>18.89</td><td>2.36</td><td>31.98</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>731.31</td><td>36.08</td><td>46.00</td><td>-9.92</td><td>36.46</td><td>27.67</td><td>3.74</td><td>31.93</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>898.15</td><td>36.11</td><td>46.00</td><td>-9.89</td><td>34.30</td><td>28.83</td><td>4.11</td><td>31.31</td><td>0.18</td><td>--</td><td>Peak</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	30.97	23.18	40.00	-16.82	30.50	23.94	0.77	32.16	0.05	--	Peak	2	94.02	35.77	43.50	-7.73	51.35	15.09	1.38	32.12	0.07	--	Peak	3	261.83	20.16	46.00	-25.84	29.70	20.04	2.27	31.97	0.12	--	Peak	4	288.02	30.10	46.00	-15.90	40.71	18.89	2.36	31.98	0.12	--	Peak	5	731.31	36.07	46.00	-9.93	36.45	27.67	3.74	31.93	0.14	--	Peak	6	898.15	34.53	46.00	-11.47	32.72	28.83	4.11	31.31	0.18	--	Peak		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	30.97	27.85	40.00	-12.15	35.25	23.94	0.77	32.16	0.05	--	Peak	2	94.99	33.88	43.50	-9.62	49.33	15.21	1.39	32.12	0.07	--	Peak	3	262.80	21.27	46.00	-24.73	30.81	20.04	2.27	31.97	0.12	--	Peak	4	288.02	28.14	46.00	-17.86	38.75	18.89	2.36	31.98	0.12	--	Peak	5	731.31	36.08	46.00	-9.92	36.46	27.67	3.74	31.93	0.14	--	Peak	6	898.15	36.11	46.00	-9.89	34.30	28.83	4.11	31.31	0.18	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																
1	30.97	23.18	40.00	-16.82	30.50	23.94	0.77	32.16	0.05	--	Peak																																																																																																																																																																																																															
2	94.02	35.77	43.50	-7.73	51.35	15.09	1.38	32.12	0.07	--	Peak																																																																																																																																																																																																															
3	261.83	20.16	46.00	-25.84	29.70	20.04	2.27	31.97	0.12	--	Peak																																																																																																																																																																																																															
4	288.02	30.10	46.00	-15.90	40.71	18.89	2.36	31.98	0.12	--	Peak																																																																																																																																																																																																															
5	731.31	36.07	46.00	-9.93	36.45	27.67	3.74	31.93	0.14	--	Peak																																																																																																																																																																																																															
6	898.15	34.53	46.00	-11.47	32.72	28.83	4.11	31.31	0.18	--	Peak																																																																																																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																
1	30.97	27.85	40.00	-12.15	35.25	23.94	0.77	32.16	0.05	--	Peak																																																																																																																																																																																																															
2	94.99	33.88	43.50	-9.62	49.33	15.21	1.39	32.12	0.07	--	Peak																																																																																																																																																																																																															
3	262.80	21.27	46.00	-24.73	30.81	20.04	2.27	31.97	0.12	--	Peak																																																																																																																																																																																																															
4	288.02	28.14	46.00	-17.86	38.75	18.89	2.36	31.98	0.12	--	Peak																																																																																																																																																																																																															
5	731.31	36.08	46.00	-9.92	36.46	27.67	3.74	31.93	0.14	--	Peak																																																																																																																																																																																																															
6	898.15	36.11	46.00	-9.89	34.30	28.83	4.11	31.31	0.18	--	Peak																																																																																																																																																																																																															



Mode	5																																																																																							
	SHF																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																							
ANT	1																																																																																							
Pol.	Horizontal						Vertical																																																																																	
Peak	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: PEAK_74 1m SHF_BBHA9170_1230 HORIZONTAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 23201.00</td><td>51.31</td><td>74.00</td><td>-22.69</td><td>43.31</td><td>38.80</td><td>26.71</td><td>54.38</td><td>-9.54</td><td>150</td><td>56</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1 23201.00	51.31	74.00	-22.69	43.31	38.80	26.71	54.38	-9.54	150	56	Peak	Level (dBuV/m) Date: 2026-07-06 Site : 03CH13-HY Condition: PEAK_74 1m SHF_BBHA9170_1230 VERTICAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 24909.00</td><td>51.40</td><td>74.00</td><td>-22.60</td><td>41.40</td><td>39.24</td><td>27.13</td><td>53.25</td><td>-9.54</td><td>150</td><td>244</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1 24909.00	51.40	74.00	-22.60	41.40	39.24	27.13	53.25	-9.54	150	244	Peak
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																												
1 23201.00	51.31	74.00	-22.69	43.31	38.80	26.71	54.38	-9.54	150	56	Peak																																																																													
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																												
1 24909.00	51.40	74.00	-22.60	41.40	39.24	27.13	53.25	-9.54	150	244	Peak																																																																													



Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	100	-	-	10Hz
Bluetooth - LE for 2Mbps	100	-	-	10Hz

