

FCC TEST REPORT

Report No.....: AB25120393FW02

FCC ID.....: **2BSS9-HP008**

Applicant.....: Hangzhou Chenzezhian Maoyiyouxiangongsi

Address.....: Room 443 Building 3, NO.5 Lvtai Road, Zhongtai Street, Yuhang District, Hangzhou

Manufacturer.....: Hangzhou Chenzezhian Maoyiyouxiangongsi

Address.....: Room 443 Building 3, NO.5 Lvtai Road, Zhongtai Street, Yuhang District, Hangzhou

Product Name.....: Wireless Vehicle Exit Wand Sensor

Trade Mark.....: Haupowfo

Test Model.....: HP008

Additional Model(s).....: /

Standard.....: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

Date of Receipt.....: 2025.12.30

Date of Issue.....: 2026.01.12

Test Result.....: Pass

Compiled by:
(Printed Name + Signature) Huaijie Li

Huaijie Li

Supervised by:
(Printed Name + Signature) David Huang

David Huang

Approved by:
(Printed Name + Signature) Jay Liu

Jay Liu

Testing Laboratory Name.....: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address.....: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC TEST REPORT

EUT.....	: Wireless Vehicle Exit Wand Sensor
Test Model.....	: HP008
Applicant.....	: Hangzhou Chenzezhian Maoyiyouxiangongsi
Address.....	: Room 443 Building 3, NO.5 Lvtai Road, Zhongtai Street, Yuhang District, Hangzhou
Manufacturer.....	: Hangzhou Chenzezhian Maoyiyouxiangongsi
Address.....	: Room 443 Building 3, NO.5 Lvtai Road, Zhongtai Street, Yuhang District, Hangzhou

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

REPORT VERSION

Version No.	Issue Date	Description
01	2026.01.12	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. GENERAL DESCRIPTION OF EUT	5
1.2. DESCRIPTION OF TEST FACILITY	6
2. RF EXPOSURE EVALUATION	7
2.1 LIMIT	7
2.2 EVALUATION RESULT	8

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	Wireless Vehicle Exit Wand Sensor
Trade Mark:	Haupowfo
Test Model:	HP008
Additional Model(s):	/
Model Difference:	/
Hardware Version:	/
Software Version:	/
Battery:	DC 4.5V Powered By Battery(2600mAh)
Test Sample(s) Number:	AB25120393-01 (Engineer Sample)
Radio Specification Subject to this Report	
Operating Frequency:	433.92MHz
Modulation Type:	ASK
Channel Number(s):	1
Antenna Type:	Integral Antenna
Antenna Gain:	3 dBi

1.2. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +86 755 85250797

E-mail: aibo@aibonorm.com

Website: www.aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

Company Number: 33924

CAB identifier: CN0185

2. RF EXPOSURE EVALUATION

2.1 Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale, $\pi = 3.1416$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.2 Evaluation Result

Mode	Power (dBuV/m)	Antenna Gain	Max EIRP(dBm)	Max EIRP(mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
433.92MHz	73.74	3	-18.460	0.014	0.000003	0.28928	PASS

So a SAR test is not required

*****THE END*****