





F. 3D Image



6# System check at 2600 MHz
Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	2600.00
Relative permittivity (real part)	39.74
Relative permittivity (imaginary part)	13.71
Conductivity (S/m)	1.98

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=1.00 ; SAR Peak: 10.43 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.340
SAR 1g (W/Kg)	5.544
Variation (%)	0.30
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	48.54

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	10.109	5.904	2.866	1.411	0.734	0.381	0.184



F. 3D Image



12. Appendix C. Plots of High SAR Measurement

- 1# SAR Measurement at GPRS850 (Body, Validation Plane)**
- 2# SAR Measurement at GPRS850 (Body, Validation Plane)**
- 3# SAR Measurement at GPRS1900 (Body, Validation Plane)**
- 4# SAR Measurement at GPRS1900 (Body, Validation Plane)**
- 5# SAR Measurement at Band 2 (1900) (Body, Validation Plane)**
- 6# SAR Measurement at Band 2 (1900) (Body, Validation Plane)**
- 7# SAR Measurement at Band 4 (1700) (Body, Validation Plane)**
- 8# SAR Measurement at Band 4 (1700) (Body, Validation Plane)**
- 9# SAR Measurement at Band 5 (850) (Body, Validation Plane)**
- 10# SAR Measurement at Band 5 (850) (Body, Validation Plane)**
- 11# SAR Measurement at ISM (Body, Validation Plane)**
- 12# SAR Measurement at ISM (Body, Validation Plane)**
- 13# SAR Measurement at LTE band 2 (Body, Validation Plane)**
- 14# SAR Measurement at LTE band 2 (Body, Validation Plane)**
- 15# SAR Measurement at LTE band 4 (Body, Validation Plane)**
- 16# SAR Measurement at LTE band 4 (Body, Validation Plane)**
- 17# SAR Measurement at LTE band 5 (Body, Validation Plane)**
- 18# SAR Measurement at LTE band 5 (Body, Validation Plane)**
- 19# SAR Measurement at LTE band 7 (Body, Validation Plane)**
- 20# SAR Measurement at LTE band 7 (Body, Validation Plane)**
- 21# SAR Measurement at LTE band 12 (Body, Validation Plane)**
- 22# SAR Measurement at LTE band 12 (Body, Validation Plane)**
- 23# SAR Measurement at LTE band 13 (Body, Validation Plane)**
- 24# SAR Measurement at LTE band 13 (Body, Validation Plane)**
- 25# SAR Measurement at LTE band 17 (Body, Validation Plane)**
- 26# SAR Measurement at LTE band 17 (Body, Validation Plane)**
- 27# SAR Measurement at LTE band 26 (Body, Validation Plane)**
- 28# SAR Measurement at LTE band 26 (Body, Validation Plane)**
- 29# SAR Measurement at LTE band 26 (Body, Validation Plane)**
- 30# SAR Measurement at LTE band 26 (Body, Validation Plane)**
- 31# SAR Measurement at LTE band 41 (Body, Validation Plane)**
- 32# SAR Measurement at LTE band 41 (Body, Validation Plane)**
- 33# SAR Measurement at LTE band 66 (Body, Validation Plane)**
- 34# SAR Measurement at LTE band 66 (Body, Validation Plane)**

1# SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Signal	TDMA (GPRS)
Channels/Frequency	Middle (189)/ frequency 836.40 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-12.00 ; SAR Peak: 1.64 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.567
SAR 1g (W/Kg)	1.005
Variation (%)	-2.10
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	58.68

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.623	1.060	0.622	0.377	0.242	0.153	0.099



F. 3D Image



2# SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Signal	TDMA (GPRS)
Channels/Frequency	Middle (189)/ frequency 836.40 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=-10.00, Y=-12.00 ; SAR Peak: 0.56 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.196
SAR 1g (W/Kg)	0.338
Variation (%)	-2.41
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	59.85

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.519	0.345	0.206	0.132	0.086	0.054	0.038



F. 3D Image



3# SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Signal	TDMA (GPRS)
Channels/Frequency	Middle (661)/ frequency 1880.00 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-6.00 ; SAR Peak: 0.58 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.231
SAR 1g (W/Kg)	0.401
Variation (%)	-0.77
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	67.69

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.539	0.417	0.282	0.188	0.116	0.073	0.048



F. 3D Image



4# SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Signal	TDMA (GPRS)
Channels/Frequency	Middle (661)/ frequency 1880.00 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-11.00 ; SAR Peak: 4.64 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.573
SAR 1g (W/Kg)	3.038
Variation (%)	4.34
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	66.61

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	4.256	3.217	2.126	1.206	0.687	0.416	0.230



F. 3D Image



5# SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Signal	WCDMA
Channels/Frequency	Middle (9400)/ frequency 1880.00 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-12.00 ; SAR Peak: 2.12 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.806
SAR 1g (W/Kg)	1.455
Variation (%)	0.91
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	63.76

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.067	1.475	0.941	0.591	0.361	0.222	0.143



F. 3D Image



6# SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Signal	WCDMA
Channels/Frequency	Middle (9400)/ frequency 1880.00 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=1.00, Y=-5.00 ; SAR Peak: 0.85 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.346
SAR 1g (W/Kg)	0.588
Variation (%)	1.77
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	65.06

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.843	0.605	0.394	0.262	0.166	0.114	0.075



F. 3D Image



7# SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 4 (1700)
Signal	WCDMA
Channels/Frequency	Middle (1413)/ frequency 1732.60 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.60
Relative permittivity (real part)	40.35
Relative permittivity (imaginary part)	13.89
Conductivity (S/m)	1.34

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-23.00 ; SAR Peak: 1.04 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.353
SAR 1g (W/Kg)	0.656
Variation (%)	-0.04
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	60.41

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.036	0.696	0.420	0.261	0.163	0.109	0.069



F. 3D Image



8# SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 4 (1700)
Signal	WCDMA
Channels/Frequency	Middle (1413)/ frequency 1732.60 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.60
Relative permittivity (real part)	40.35
Relative permittivity (imaginary part)	13.89
Conductivity (S/m)	1.34

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-16.00 ; SAR Peak: 1.79 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.679
SAR 1g (W/Kg)	1.187
Variation (%)	-0.26
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	64.39

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.722	1.229	0.791	0.506	0.316	0.203	0.127



F. 3D Image



9# SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Signal	WCDMA
Channels/Frequency	Middle (4182)/ frequency 836.40 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=-11.00, Y=-12.00 ; SAR Peak: 1.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.519
SAR 1g (W/Kg)	0.883
Variation (%)	-0.22
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	61.37

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.390	0.928	0.557	0.352	0.218	0.146	0.092



F. 3D Image



10# SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Signal	WCDMA
Channels/Frequency	Middle (4182)/ frequency 836.40 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-12.00 ; SAR Peak: 3.81 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.405
SAR 1g (W/Kg)	2.452
Variation (%)	-0.58
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	61.38

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.791	2.540	1.538	0.975	0.624	0.400	0.258



F. 3D Image



11# SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 30/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.63
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Signal	IEEE 802.11 b
Channels/Frequency	Middle (6)/ frequency 2437.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	2437.00
Relative permittivity (real part)	37.70
Relative permittivity (imaginary part)	13.45
Conductivity (S/m)	1.82

C. SAR Surface and Volume




Maximum location: X=-5.00, Y=-1.00 ; SAR Peak: 0.86 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.279
SAR 1g (W/Kg)	0.529
Variation (%)	1.25
Horizontal validation criteria: minimum distance (mm)	18.03
Vertical validation criteria: SAR ratio M2/M1 (%)	56.62

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.870	0.555	0.314	0.176	0.103	0.060	0.026



F. 3D Image



12# SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 30/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.63
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Signal	IEEE 802.11 b
Channels/Frequency	Middle (6)/ frequency 2437.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	2437.00
Relative permittivity (real part)	37.70
Relative permittivity (imaginary part)	13.45
Conductivity (S/m)	1.82

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=1.00 ; SAR Peak: 1.77 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.516
SAR 1g (W/Kg)	1.049
Variation (%)	-0.31
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	55.80

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.921	1.095	0.504	0.322	0.136	0.082	0.031



F. 3D Image



13# SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (18900)/ frequency 1880.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1880.00

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-1.00 ; SAR Peak: 1.10 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.465
SAR 1g (W/Kg)	0.770
Variation (%)	-0.48
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	65.79

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.069	0.781	0.514	0.335	0.216	0.145	0.102



F. 3D Image



14# SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 7/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (18900)/ frequency 1880.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1880.00

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.47
Relative permittivity (imaginary part)	13.77
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-12.00 ; SAR Peak: 3.53 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.298
SAR 1g (W/Kg)	2.382
Variation (%)	0.13
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	63.21

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.395	2.394	1.513	0.959	0.584	0.363	0.224



F. 3D Image



15# SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20175)/ frequency 1732.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1732.50

B. Permittivity

Middle TX Frequency (MHz)	1732.50
Relative permittivity (real part)	39.46
Relative permittivity (imaginary part)	13.53
Conductivity (S/m)	1.30

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-16.00 ; SAR Peak: 2.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.777
SAR 1g (W/Kg)	1.365
Variation (%)	-3.87
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	61.39

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.872	1.410	0.830	1.062	0.349	0.221	0.141



F. 3D Image



16# SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20175)/ frequency 1732.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1732.50

B. Permittivity

Middle TX Frequency (MHz)	1732.50
Relative permittivity (real part)	39.46
Relative permittivity (imaginary part)	13.53
Conductivity (S/m)	1.30

C. SAR Surface and Volume




Maximum location: X=6.00, Y=-16.00 ; SAR Peak: 0.55 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.208
SAR 1g (W/Kg)	0.361
Variation (%)	-1.80
Horizontal validation criteria: minimum distance (mm)	28.84
Vertical validation criteria: SAR ratio M2/M1 (%)	68.62

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.543	0.374	0.236	0.170	0.102	0.079	0.049



F. 3D Image



17# SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20525)/ frequency 836.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	836.50

B. Permittivity

Middle TX Frequency (MHz)	836.50
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=7.00, Y=-9.00 ; SAR Peak: 3.73 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.427
SAR 1g (W/Kg)	2.433
Variation (%)	-0.56
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	62.86

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.716	2.552	1.584	0.995	0.639	0.410	0.270



F. 3D Image



18# SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 5/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20525)/ frequency 836.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	836.50

B. Permittivity

Middle TX Frequency (MHz)	836.50
Relative permittivity (real part)	41.05
Relative permittivity (imaginary part)	19.17
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-11.00 ; SAR Peak: 0.93 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.353
SAR 1g (W/Kg)	0.596
Variation (%)	-0.23
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	65.22

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.849	0.602	0.389	0.249	0.161	0.106	0.067



F. 3D Image



19# SAR Measurement at LTE band 7 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (21100)/ frequency 2535.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2535.00

B. Permittivity

Middle TX Frequency (MHz)	2535.00
Relative permittivity (real part)	40.07
Relative permittivity (imaginary part)	13.57
Conductivity (S/m)	1.91

C. SAR Surface and Volume




Maximum location: X=-6.00, Y=-32.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.263
SAR 1g (W/Kg)	0.555
Variation (%)	3.69
Horizontal validation criteria: minimum distance (mm)	11.18
Vertical validation criteria: SAR ratio M2/M1 (%)	54.87

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.935	0.598	0.328	0.189	0.106	0.057	0.044



F. 3D Image



20# SAR Measurement at LTE band 7 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (21100)/ frequency 2535.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2535.00

B. Permittivity

Middle TX Frequency (MHz)	2535.00
Relative permittivity (real part)	40.07
Relative permittivity (imaginary part)	13.57
Conductivity (S/m)	1.91

C. SAR Surface and Volume




Maximum location: X=-15.00, Y=-11.00 ; SAR Peak: 3.77 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.978
SAR 1g (W/Kg)	2.230
Variation (%)	-0.20
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	59.81

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	5.268	2.469	0.699	0.793	0.184	0.230	0.062



F. 3D Image



21# SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23095)/ frequency 707.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	707.50

B. Permittivity

Middle TX Frequency (MHz)	707.50
Relative permittivity (real part)	40.94
Relative permittivity (imaginary part)	21.71
Conductivity (S/m)	0.85

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-10.00 ; SAR Peak: 0.29 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.118
SAR 1g (W/Kg)	0.193
Variation (%)	2.48
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	66.15

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.270	0.197	0.130	0.088	0.057	0.040	0.027



F. 3D Image



22# SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23095)/ frequency 707.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	707.50

B. Permittivity

Middle TX Frequency (MHz)	707.50
Relative permittivity (real part)	40.94
Relative permittivity (imaginary part)	21.71
Conductivity (S/m)	0.85

C. SAR Surface and Volume




Maximum location: X=7.00, Y=-9.00 ; SAR Peak: 1.27 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.507
SAR 1g (W/Kg)	0.845
Variation (%)	-0.15
Horizontal validation criteria: minimum distance (mm)	22.63
Vertical validation criteria: SAR ratio M2/M1 (%)	63.08

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.279	0.884	0.557	0.362	0.236	0.154	0.100



F. 3D Image



23# SAR Measurement at LTE band 13 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 13
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23230)/ frequency 782.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	782.00

B. Permittivity

Middle TX Frequency (MHz)	782.00
Relative permittivity (real part)	40.06
Relative permittivity (imaginary part)	20.96
Conductivity (S/m)	0.91

C. SAR Surface and Volume




Maximum location: X=7.00, Y=-9.00 ; SAR Peak: 2.74 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.081
SAR 1g (W/Kg)	1.839
Variation (%)	-0.83
Horizontal validation criteria: minimum distance (mm)	22.63
Vertical validation criteria: SAR ratio M2/M1 (%)	62.62

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.727	1.877	1.171	0.747	0.482	0.313	0.206



F. 3D Image



24# SAR Measurement at LTE band 13 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 13
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23230)/ frequency 782.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	782.00

B. Permittivity

Middle TX Frequency (MHz)	782.00
Relative permittivity (real part)	40.06
Relative permittivity (imaginary part)	20.96
Conductivity (S/m)	0.91

C. SAR Surface and Volume




Maximum location: X=-10.00, Y=-12.00 ; SAR Peak: 0.84 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.316
SAR 1g (W/Kg)	0.541
Variation (%)	-1.30
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	62.64

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.782	0.542	0.340	0.217	0.139	0.091	0.061



F. 3D Image



25# SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23790)/ frequency 710.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	710.00

B. Permittivity

Middle TX Frequency (MHz)	710.00
Relative permittivity (real part)	40.93
Relative permittivity (imaginary part)	21.65
Conductivity (S/m)	0.85

C. SAR Surface and Volume




Maximum location: X=-9.00, Y=-12.00 ; SAR Peak: 0.42 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.161
SAR 1g (W/Kg)	0.269
Variation (%)	1.36
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	63.69

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.398	0.278	0.177	0.113	0.075	0.050	0.034



F. 3D Image



26# SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 27/12/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23790)/ frequency 710.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	710.00

B. Permittivity

Middle TX Frequency (MHz)	710.00
Relative permittivity (real part)	40.93
Relative permittivity (imaginary part)	21.65
Conductivity (S/m)	0.85

C. SAR Surface and Volume




Maximum location: X=-6.00, Y=-13.00 ; SAR Peak: 0.64 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.255
SAR 1g (W/Kg)	0.421
Variation (%)	-1.19
Horizontal validation criteria: minimum distance (mm)	22.63
Vertical validation criteria: SAR ratio M2/M1 (%)	63.80

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.619	0.432	0.276	0.178	0.122	0.084	0.060



F. 3D Image



27# SAR Measurement at LTE band 38 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 38
Signal	LTE TDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (38000)/ frequency 2595.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2595.00

B. Permittivity

Middle TX Frequency (MHz)	2595.00
Relative permittivity (real part)	39.71
Relative permittivity (imaginary part)	13.79
Conductivity (S/m)	1.99

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=-11.00 ; SAR Peak: 1.80 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.454
SAR 1g (W/Kg)	1.023
Variation (%)	0.38
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	57.26

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.204	1.142	0.434	0.379	0.127	0.125	0.048



F. 3D Image



28# SAR Measurement at LTE band 38 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 38
Signal	LTE TDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (38000)/ frequency 2595.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2595.00

B. Permittivity

Middle TX Frequency (MHz)	2595.00
Relative permittivity (real part)	39.71
Relative permittivity (imaginary part)	13.79
Conductivity (S/m)	1.99

C. SAR Surface and Volume




Maximum location: X=-5.00, Y=-32.00 ; SAR Peak: 0.50 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.133
SAR 1g (W/Kg)	0.277
Variation (%)	-1.39
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	57.14

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.526	0.300	0.140	0.081	0.050	0.032	0.030



F. 3D Image



29# SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Signal	LTE TDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (40620)/ frequency 2593.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2593.00

B. Permittivity

Middle TX Frequency (MHz)	2593.00
Relative permittivity (real part)	39.79
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.98

C. SAR Surface and Volume




Maximum location: X=-5.00, Y=-11.00 ; SAR Peak: 1.79 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.452
SAR 1g (W/Kg)	1.030
Variation (%)	-2.49
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	56.65

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.164	1.136	0.447	0.348	0.129	0.109	0.047



F. 3D Image



30# SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 4/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Signal	LTE TDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (40620)/ frequency 2593.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2593.00

B. Permittivity

Middle TX Frequency (MHz)	2593.00
Relative permittivity (real part)	39.79
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.98

C. SAR Surface and Volume




Maximum location: X=-6.00, Y=-32.00 ; SAR Peak: 0.54 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.132
SAR 1g (W/Kg)	0.283
Variation (%)	-3.18
Horizontal validation criteria: minimum distance (mm)	7.07
Vertical validation criteria: SAR ratio M2/M1 (%)	55.51

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.599	0.317	0.131	0.080	0.048	0.036	0.031



F. 3D Image



31# SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (132322)/ frequency 1745.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1745.00

B. Permittivity

Middle TX Frequency (MHz)	1745.00
Relative permittivity (real part)	40.28
Relative permittivity (imaginary part)	13.89
Conductivity (S/m)	1.35

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-5.00 ; SAR Peak: 0.92 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.367
SAR 1g (W/Kg)	0.622
Variation (%)	-1.23
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	65.01

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.919	0.658	0.427	0.273	0.176	0.116	0.075



F. 3D Image



32# SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 6/1/2026


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (132322)/ frequency 1745.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1745.00

B. Permittivity

Middle TX Frequency (MHz)	1745.00
Relative permittivity (real part)	40.28
Relative permittivity (imaginary part)	13.89
Conductivity (S/m)	1.35

C. SAR Surface and Volume




Maximum location: X=-10.00, Y=-12.00 ; SAR Peak: 3.80 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.394
SAR 1g (W/Kg)	2.515
Variation (%)	2.26
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	64.41

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.738	2.699	1.738	1.085	0.664	0.393	0.251



F. 3D Image



13. Appendix D. Calibration Certificate

Table of contents
E Field Probe - 0725-EPGO-448
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
Justification of the extended calibration

DocuSign Envelope ID: 8D8CB647-C2B4-4414-A550-C6E3F74EB7AD

**COMOSAR E-Field Probe Calibration Report**

Ref : ACR.108.1.25.BES.A

**SHENZHEN NTEK TESTING TECHNOLOGY
CO., LTD.**

**BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: 0725-EPGO-448**

Calibrated at MVG**Z.I. de la pointe du diable****Technopôle Brest Iroise – 295 avenue Alexis de Rochon****29280 PLOUZANE - FRANCE****Calibration date: 04/15/2025**

Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).

DocuSign Envelope ID: 8D8CB647-C2B4-4414-A550-C6E3F74EB7AD



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.108.1.25.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Pedro Ruiz	Technical Manager	4/18/2025	
<i>Checked & approved by:</i>	Pedro Ruiz	Technical Manager	4/18/2025	
<i>Authorized by:</i>	Kim Rutkowski	Quality Manager	4/23/2025	Signed by: 2B98B547AD1743* ...

	<i>Customer Name</i>
<i>Distribution :</i>	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Pedro Ruiz	4/18/2025	Initial release

DocuSign Envelope ID: 8D8CB647-C2B4-4414-A550-C6E3F74EB7AD



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.108.1.25.BES.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Sensitivity	4
3.2	Linearity	5
3.3	Isotropy	5
3.4	Boundary Effect	5
3.5	Probe Modulation Response	6
4	Measurement Uncertainty	6
5	Calibration Results	6
5.1	Calibration in air	6
5.2	Calibration in liquid	7
6	Verification Results	8
7	List of Equipment	10

DocuSign Envelope ID: 8D8CB647-C2B4-4414-A550-C6E3F74EB7AD



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.108.1.25.BES.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	0725-EPGO-448
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-7.5GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.191 MΩ Dipole 2: R2=0.212 MΩ Dipole 3: R3=0.208 MΩ

2 PRODUCT DESCRIPTION**2.1 GENERAL INFORMATION**

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their effect. All calibrations / measurements performed meet the fore-mentioned standards.

3.1 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards for frequency range 600-7500MHz and using the calorimeter cell method (transfer method) as outlined in the standards for frequency 150-450 MHz.

DocuSign Envelope ID: 8D8CB647-C2B4-4414-A550-C6E3F74EB7AD



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.108.1.25.BES.A

3.2 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

3.3 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.4 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta})}{\delta/2} \text{ for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14 \text{ mm}$ at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect $SAR_{uncertainty}[\%]$ for scanning distances larger than 4mm is 1.0% Limit, 2%).