

# EMC Test Report

**Report No.:** JYTSZ-R01-2600092

**Applicant:** Otolift Trapliften B.V.

**Address of Applicant:** Lekdijk-Oost 27 a, 2861 GB,Bergambacht, The Netherlands

**Equipment Under Test (EUT)**

Product Name: Armrest display

Model No.: 270300100

Trade Mark: Otolift

**FCC ID:** 2BSTUOTO00100


**Applicable Standards:** FCC CFR Title 47 Part 15B

**Date of Sample Receipt:** 02 Apr., 2026

**Date of Test:** 03 Apr., to 15 May, 2026

**Date of report Issued:** 15 May, 2026

**Test Result:** PASS

|                     |                                                                                     |              |                     |
|---------------------|-------------------------------------------------------------------------------------|--------------|---------------------|
| <b>Project by:</b>  | <u>Robin Gu</u>                                                                     | <b>Date:</b> | <u>15 May, 2026</u> |
|                     |  |              |                     |
| <b>Reviewed by:</b> | <u>Yeto Lang</u>                                                                    | <b>Date:</b> | <u>15 May, 2026</u> |
|                     |  |              |                     |
| <b>Approved by:</b> | <u>James Wei</u>                                                                    | <b>Date:</b> | <u>15 May, 2026</u> |
|                     | <b>Manager</b>                                                                      |              |                     |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

| Version No. | Date         | Description |
|-------------|--------------|-------------|
| 00          | 15 May, 2026 | Original    |
|             |              |             |
|             |              |             |
|             |              |             |
|             |              |             |

## 2 Contents

Page

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>Cover Page .....</b>                                           | <b>1</b>  |
| <b>1 Version .....</b>                                            | <b>2</b>  |
| <b>2 Contents.....</b>                                            | <b>3</b>  |
| <b>3 General Information.....</b>                                 | <b>4</b>  |
| 3.1 Client Information .....                                      | 4         |
| 3.2 General Description of E.U.T. ....                            | 4         |
| 3.3 Disclaimer.....                                               | 4         |
| 3.4 Test Mode .....                                               | 4         |
| 3.5 Description of Test Auxiliary Equipment .....                 | 5         |
| 3.6 Description of Cable Used.....                                | 5         |
| 3.7 Measurement Uncertainty .....                                 | 5         |
| 3.8 Additions to, Deviations, or Exclusions from the Method ..... | 5         |
| 3.9 Laboratory Facility .....                                     | 5         |
| 3.10 Laboratory Location.....                                     | 6         |
| 3.11 Test Instruments List.....                                   | 6         |
| <b>4 Measurement Setup and Procedure .....</b>                    | <b>8</b>  |
| 4.1 Test Setup .....                                              | 8         |
| 4.2 Test Procedure .....                                          | 9         |
| <b>5 Test Results.....</b>                                        | <b>10</b> |
| 5.1 Summary .....                                                 | 10        |
| 5.1.1 Clause and data summary .....                               | 10        |
| 5.1.2 Test Limit.....                                             | 10        |
| 5.2 Radiated Emission .....                                       | 11        |

### 3 General Information

#### 3.1 Client Information

|               |                                                                                                    |
|---------------|----------------------------------------------------------------------------------------------------|
| Applicant:    | Otolift Trapliften B.V.                                                                            |
| Address:      | Lekdijk-Oost 27 a, 2861 GB, Bergambacht, The Netherlands                                           |
| Manufacturer: | Betronic BV                                                                                        |
| Address:      | Zekeringstraat 32-F, 1014 BS, Amsterdam, The Netherlands                                           |
| Factory:      | Betronic China (Suzhou)                                                                            |
| Address:      | Building 3, Room 3201, South Xincheng Road, Yushan Town, 215300<br>Kunshan Jiangsu Province, China |

#### 3.2 General Description of E.U.T.

|                        |                                                                               |
|------------------------|-------------------------------------------------------------------------------|
| Product Name:          | Armrest display                                                               |
| Model No.:             | 270300100                                                                     |
| Power Supply:          | DC 24V                                                                        |
| Test Sample Condition: | The test samples were provided in good working order with no visible defects. |

#### 3.3 Disclaimer

|                                                                                                                                                                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Disclaimer:                                                                                                                                                                                                                                                                  |
| For the information or data provided by the client in this report, the relevant results or conclusions of this report are only made for these data or information. The testing laboratory is not responsible for the authenticity and accuracy of these data or information. |

#### 3.4 Test Mode

| Operating Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Detail Description                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| Working mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Keep the EUT in Working mode(Worst case) |
| The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. |                                          |

### 3.5 Description of Test Auxiliary Equipment

| Manufacturer | Description | Model              | S/N        | FCC ID/DoC |
|--------------|-------------|--------------------|------------|------------|
| Lenovo       | Laptop      | ThinkPad T14 Gen 1 | SL10Z47277 | DoC        |

### 3.6 Description of Cable Used

| Cable Type | Description | Length | From | To |
|------------|-------------|--------|------|----|
| /          | /           | /      | /    | /  |

### 3.7 Measurement Uncertainty

| Parameter                                     | Expanded Uncertainty<br>(Confidence of 95%(U = 2Uc(y))) |
|-----------------------------------------------|---------------------------------------------------------|
| Radiated Emission (30MHz ~ 200MHz) (3m SAC)   | 4.7 dB                                                  |
| Radiated Emission (200MHz ~ 1000MHz) (3m SAC) | 5.8 dB                                                  |
| Radiated Emission (1GHz ~ 6GHz) (3m SAC)      | 4.5 dB                                                  |
| Radiated Emission (6GHz ~ 18GHz) (3m SAC)     | 4.5 dB                                                  |
| Radiated Emission (30MHz ~ 1000MHz) (10m SAC) | 4.3 dB                                                  |

**Note:** All the measurement uncertainty value were shown with a coverage  $k=2$  to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### 3.8 Additions to, Deviations, or Exclusions from the Method

|    |
|----|
| No |
|----|

### 3.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

### 3.10 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

### 3.11 Test Instruments List

| Radiated Emission(3m SAC):   |                 |                 |                  |                      |                          |
|------------------------------|-----------------|-----------------|------------------|----------------------|--------------------------|
| Test Equipment               | Manufacturer    | Model No.       | Manage No.       | Cal. Date (mm-dd-yy) | Cal. Due date (mm-dd-yy) |
| 3m SAC                       | ETS             | 9m*6m*6m        | WXJ001-1         | 04-14-2021           | 04-13-2026               |
|                              |                 |                 |                  | 12-09-2025           | 12-08-2030               |
| BiConiLog Antenna            | Schwarzbeck     | VULB9163        | WXJ002           | 08-09-2025           | 08-08-2026               |
| Horn Antenna                 | Schwarzbeck     | BBHA9120D       | WXJ002-2         | 12-07-2025           | 12-06-2026               |
| Pre-amplifier (30MHz ~ 1GHz) | Schwarzbeck     | BBV9743B        | WXJ001-2         | 12-04-2025           | 12-03-2026               |
| Pre-amplifier (1GHz ~ 18GHz) | SKET            | LNPA_0118G-50   | WXJ001-3         | 12-04-2025           | 12-03-2026               |
| EMI Test Receiver            | Rohde & Schwarz | ESRP7           | WXJ003-1         | 12-04-2025           | 12-03-2026               |
| Spectrum Analyzer            | Rohde & Schwarz | FSP 30          | WXJ004           | 12-04-2025           | 12-03-2026               |
| Coaxial Cable (30MHz ~ 1GHz) | JYTSZ           | JYT3M-1G-NN-8M  | WXG001-4         | 01-14-2026           | 01-13-2027               |
| Coaxial Cable (1GHz ~ 18GHz) | JYTSZ           | JYT3M-18G-NN-8M | WXG001-5         | 01-14-2026           | 01-13-2027               |
| Band Reject Filter Group     | Tonscend        | JS0806-F        | WXJ089           | N/A                  |                          |
| Test Software                | Tonscend        | TS+             | Version: 3.0.0.1 |                      |                          |


| Radiated Emission(3m FAR):       |                 |                 |                |                         |                             |
|----------------------------------|-----------------|-----------------|----------------|-------------------------|-----------------------------|
| Test Equipment                   | Manufacturer    | Model No.       | Manage No.     | Cal. Date<br>(mm-dd-yy) | Cal. Due date<br>(mm-dd-yy) |
| 3m FAR                           | YUNYI           | 9m*6m*6m        | WXJ097         | 06-15-2023              | 06-14-2028                  |
| BiConiLog Antenna                | Schwarzbeck     | VULB9163        | WXJ097-2       | 04-24-2025              | 04-23-2026                  |
|                                  |                 |                 |                | 04-13-2026              | 04-12-2027                  |
| Biconical Antenna                | Schwarzbeck     | VUBA9117        | WXJ002-1       | 07-01-2024              | 06-30-2027                  |
| Horn Antenna                     | Schwarzbeck     | BBHA9120D       | WXJ097-3       | 05-23-2025              | 05-22-2026                  |
| Horn Antenna                     | Schwarzbeck     | BBHA9120D       | WXJ002-3       | 12-07-2025              | 12-06-2026                  |
| Horn Antenna                     | Schwarzbeck     | BBHA9170        | WXJ002-5       | 12-07-2025              | 12-06-2026                  |
| Horn Antenna                     | Schwarzbeck     | BBHA9170        | WXJ002-6       | 12-07-2025              | 12-06-2026                  |
| Pre-amplifier<br>(30MHz ~ 1GHz)  | YUNYI           | PAM-310N        | WXJ097-5       | 04-21-2025              | 04-20-2026                  |
|                                  |                 |                 |                | 03-30-2026              | 03-29-2027                  |
| Pre-amplifier<br>(1GHz ~ 18GHz)  | YUNYI           | PAM-118N        | WXJ097-6       | 04-21-2025              | 04-20-2026                  |
|                                  |                 |                 |                | 03-30-2026              | 34-29-2027                  |
| Pre-amplifier<br>(18GHz ~ 40GHz) | RF System       | TRLA-180400G45B | WXJ002-7       | 12-05-2025              | 12-04-2026                  |
| EMI Test Receiver                | Rohde & Schwarz | ESCI3           | WXJ003         | 12-04-2025              | 12-03-2026                  |
| Spectrum Analyzer                | Rohde & Schwarz | FSP 30          | WXJ004         | 12-04-2025              | 12-03-2026                  |
| Spectrum Analyzer                | KEYSIGHT        | N9020B          | WXJ081-1       | 05-08-2025              | 05-07-2026                  |
|                                  |                 |                 |                | 04-13-2026              | 04-12-2027                  |
| Coaxial Cable<br>(30MHz ~ 1GHz)  | JYTSZ           | JYT3M-1G-NN-13M | WXG097-1       | 07-28-2025              | 07-27-2026                  |
| Coaxial Cable<br>(1GHz ~ 18GHz)  | JYTSZ           | JYT3M-18G-NN-8M | WXG097-2       | 07-28-2025              | 07-27-2026                  |
| Coaxial Cable<br>(18GHz ~ 40GHz) | JYTSZ           | JYT3M-40G-SS-8M | WXG097-3       | 07-28-2025              | 07-27-2026                  |
| High Band Reject Filter<br>Group | Tonscend        | JS0806-F        | WXJ089         | N/A                     |                             |
| Low Band Reject Filter<br>Group  | Tonscend        | JS0806-F        | WXJ097-4       | N/A                     |                             |
| Test Software                    | Tonscend        | TS+             | Version: 5.0.0 |                         |                             |

## 4 Measurement Setup and Procedure


### 4.1 Test Setup

#### 1) Radiated emission measurement:

Below 1GHz (3m SAC)



Above 1GHz (3m SAC)



## 4.2 Test Procedure

| Test method       | Test step                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Radiated emission | <p><b>For below 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> <p><b>For above 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> |

## 5 Test Results

### 5.1 Summary

#### 5.1.1 Clause and data summary

| Test items                                                                                                                                                                | Standard clause | Test data       | Result |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|--------|
| Conducted Emission                                                                                                                                                        | Part 15.107     | N/A             | N/A    |
| Radiated Emission                                                                                                                                                         | Part 15.109     | See Section 5.2 | Pass   |
| <b>Remark:</b><br>1. The EUT is a <b>Class B</b> digital device.<br>2. Pass: The EUT complies with the essential requirements in the standard.<br>3. N/A: Not Applicable. |                 |                 |        |
| <b>Test Method:</b>                                                                                                                                                       | ANSI C63.4:2014 |                 |        |


#### 5.1.2 Test Limit

| Test items        | Limit                                                             |                             |                  |                             |                  |
|-------------------|-------------------------------------------------------------------|-----------------------------|------------------|-----------------------------|------------------|
| Radiated Emission | Frequency (MHz)                                                   | Class A Limit (dBµV/m)      |                  | Class B Limit (dBµV/m)      |                  |
|                   |                                                                   | Quasi-Peak @ 3m             | Quasi-Peak @ 10m | Quasi-Peak @ 3m             | Quasi-Peak @ 10m |
|                   | 30 – 88                                                           | 49.0                        | 39.0             | 40.0                        | 30.0             |
|                   | 88 – 216                                                          | 53.5                        | 43.5             | 43.5                        | 33.5             |
|                   | 216 – 960                                                         | 56.0                        | 46.0             | 46.0                        | 36.0             |
|                   | 960 – 1000                                                        | 60.0                        | 50.0             | 54.0                        | 44.0             |
|                   | Note: The more stringent limit applies at transition frequencies. |                             |                  |                             |                  |
|                   | Frequency                                                         | Class A Limit (dBµV/m) @ 3m |                  | Class B Limit (dBµV/m) @ 3m |                  |
|                   |                                                                   | Average                     | Peake            | Average                     | Peake            |
|                   | Above 1 GHz                                                       | 60.0                        | 80.0             | 54.0                        | 74.0             |
|                   | Note: The measurement bandwidth shall be 1 MHz or greater.        |                             |                  |                             |                  |

## 5.2 Radiated Emission

Below 1GHz:

|                 |                 |                |              |
|-----------------|-----------------|----------------|--------------|
| Product Name:   | Armrest display | Product Model: | 270300100    |
| Test By:        | Kiran Zeng      | Test mode:     | Working mode |
| Test Frequency: | 30 MHz ~ 1 GHz  | Polarization:  | Vertical     |
| Test Voltage:   | DC 24V          |                |              |



### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Trace | Polarity |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------|----------|
| 1   | 49.4980     | 48.02            | -12.68      | 35.34          | 40.00          | 4.66        | PK    | Vertical |
| 2   | 114.200     | 45.81            | -15.25      | 30.56          | 43.50          | 12.94       | PK    | Vertical |
| 3   | 148.491     | 48.44            | -18.19      | 30.25          | 43.50          | 13.25       | PK    | Vertical |
| 4   | 247.484     | 47.85            | -13.66      | 34.19          | 46.00          | 11.81       | PK    | Vertical |
| 5   | 742.500     | 38.86            | -2.54       | 36.32          | 46.00          | 9.68        | PK    | Vertical |
| 6   | 841.494     | 46.56            | -1.07       | 45.49          | 46.00          | 0.51        | PK    | Vertical |


### Final Data List

| NO. | Freq. [MHz] | QP Reading [dBμV/m] | Factor [dB] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] | Angle [°] | Verdict |
|-----|-------------|---------------------|-------------|-------------------|-------------------|----------------|-----------|---------|
| 1   | 841.488     | 46.13               | -1.07       | 45.06             | 46.00             | 0.94           | 13.7      | PASS    |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                 |                 |                |              |
|-----------------|-----------------|----------------|--------------|
| Product Name:   | Armrest display | Product Model: | 270300100    |
| Test By:        | Kiran Zeng      | Test mode:     | Working mode |
| Test Frequency: | 30 MHz ~ 1 GHz  | Polarization:  | Horizontal   |
| Test Voltage:   | DC 24V          |                |              |



### Suspected Data List


| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Trace | Polarity   |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------|------------|
| 1   | 148.491     | 38.98            | -18.19      | 20.79          | 43.50          | 22.71       | PK    | Horizontal |
| 2   | 247.484     | 41.87            | -13.66      | 28.21          | 46.00          | 17.79       | PK    | Horizontal |
| 3   | 544.465     | 38.03            | -6.07       | 31.96          | 46.00          | 14.04       | PK    | Horizontal |
| 4   | 742.500     | 37.98            | -2.54       | 35.44          | 46.00          | 10.56       | PK    | Horizontal |
| 5   | 841.494     | 44.49            | -1.07       | 43.42          | 46.00          | 2.58        | PK    | Horizontal |
| 6   | 940.536     | 37.16            | 0.63        | 37.79          | 46.00          | 8.21        | PK    | Horizontal |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

## Above 1GHz:

|                 |                      |                |              |
|-----------------|----------------------|----------------|--------------|
| Product Name:   | Armrest display      | Product Model: | 270300100    |
| Test By:        | Robin Gu             | Test mode:     | Working mode |
| Test Frequency: | 1000 MHz ~ 12000 MHz | Polarization:  | Vertical     |
| Test Voltage:   | DC 24V               |                |              |




### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV/m] | Level [dBμV/m] | Factor [dB] | Limit [dBμV/m] | Margin [dB] | Trace | Polarity |
|-----|-------------|------------------|----------------|-------------|----------------|-------------|-------|----------|
| 1   | 4577.75     | 56.83            | 45.19          | -11.64      | 74.00          | 28.81       | PK    | Vertical |
| 2   | 4613.50     | 45.58            | 34.08          | -11.50      | 54.00          | 19.92       | AV    | Vertical |
| 3   | 5596.62     | 55.43            | 50.36          | -5.07       | 74.00          | 23.64       | PK    | Vertical |
| 4   | 5609.00     | 44.04            | 38.95          | -5.09       | 54.00          | 15.05       | AV    | Vertical |
| 5   | 9325.62     | 44.58            | 45.67          | 1.09        | 54.00          | 8.33        | AV    | Vertical |
| 6   | 9518.12     | 56.23            | 57.70          | 1.47        | 74.00          | 16.30       | PK    | Vertical |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
2. Test Frequency up to 18GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.

|                 |                      |                |              |
|-----------------|----------------------|----------------|--------------|
| Product Name:   | Armrest display      | Product Model: | 270300100    |
| Test By:        | Robin Gu             | Test mode:     | Working mode |
| Test Frequency: | 1000 MHz ~ 12000 MHz | Polarization:  | Horizontal   |
| Test Voltage:   | DC 24V               |                |              |



### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV/m] | Level [dBμV/m] | Factor [dB] | Limit [dBμV/m] | Margin [dB] | Trace | Polarity   |
|-----|-------------|------------------|----------------|-------------|----------------|-------------|-------|------------|
| 1   | 4613.50     | 45.35            | 33.85          | -11.50      | 54.00          | 20.15       | AV    | Horizontal |
| 2   | 4619.00     | 57.24            | 45.75          | -11.49      | 74.00          | 28.25       | PK    | Horizontal |
| 3   | 5593.87     | 43.73            | 38.61          | -5.12       | 54.00          | 15.39       | AV    | Horizontal |
| 4   | 5614.50     | 55.50            | 50.36          | -5.14       | 74.00          | 23.64       | PK    | Horizontal |
| 5   | 9317.37     | 44.84            | 45.91          | 1.07        | 54.00          | 8.09        | AV    | Horizontal |
| 6   | 9461.75     | 56.34            | 57.68          | 1.34        | 74.00          | 16.32       | PK    | Horizontal |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
2. Test Frequency up to 18GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.

-----End of report-----