

Test Report

Product: 915M data transmission

Trade Mark: N/A

Model Number: LR900-F

FCC ID: 2BSUN-LR900-F

Prepared for

DH Research, LLC.

440 Wyoming Avenue Millburn, NJ 7041 United State

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd.

Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China

Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110

Website: <http://www.sz-hongbiao.com>

Table of Contents

1 GENERAL DESCRIPTION	6
1.1 DESCRIPTION OF EUT	6
1.2 TEST MODE	6
1.3 OPERATION CHANNEL LIST	7
1.4 TEST SETUP	7
1.5 POWER SETTING CONFIGURATION PARAMETERS	7
1.6 ANCILLARY EQUIPMENT	7
2 SUMMARY OF TEST RESULT	8
3 TEST FACILITIES AND ACCREDITATIONS	9
3.1 TEST LABORATORY	9
3.2 ENVIRONMENTAL CONDITIONS	9
3.3 MEASUREMENT UNCERTAINTY	9
3.4 TEST SOFTWARE	10
4 LIST OF TEST EQUIPMENT	11
5 TEST ITEM AND RESULTS	13
5.1 ANTENNA REQUIREMENT	13
5.1.1 <i>Standard Requirement</i>	13
5.1.2 <i>Test Result</i>	13
5.2 CONDUCTED EMISSION	14
5.2.1 <i>Limits</i>	14
5.2.2 <i>Test Procedures</i>	14
5.2.3 <i>Test Setup</i>	15
5.2.4 <i>Test Result</i>	15
5.3 RADIATED EMISSION	18
5.3.1 <i>Limits</i>	18
5.3.2 <i>Test Procedures</i>	18
5.3.3 <i>Test Setup</i>	18
5.3.4 <i>Test Result</i>	19
5.3.5 <i>Band Edge - Radiated</i>	23
5.3.6 <i>Spurious emission in restricted band 1000MHz-25000MHz</i>	24
5.4 PEAK OUTPUT POWER	25
5.4.1 <i>Limit</i>	25
5.4.2 <i>Test Procedure</i>	25
5.4.3 <i>Test Setup</i>	25
5.4.4 <i>Test Results</i>	25
5.5 POWER SPECTRAL DENSITY	27
5.5.1 <i>Limit</i>	27
5.5.2 <i>Test Procedure</i>	27
5.5.3 <i>Test Setup</i>	27
5.5.4 <i>Test Results</i>	27
5.6 6DB BANDWIDTH	29
5.6.1 <i>Limit</i>	29
5.6.2 <i>Test Procedure</i>	29
5.6.3 <i>Test Setup</i>	29
5.6.4 <i>Test Results</i>	29
5.7 CONDUCTED BAND EDGE	31
5.7.1 <i>Limit</i>	31
5.7.2 <i>Test Procedure</i>	31
5.7.3 <i>Test Setup</i>	31
5.7.4 <i>Test Results</i>	31
5.8 SPURIOUS RF CONDUCTED EMISSIONS	33

5.8.1 Limit	33
5.8.2 Measuring Instruments	33
5.8.3 Test Procedure	33
5.8.4 Test Setup	33
5.8.5 Test Results	33
6 PHOTOGRAPHS OF THE TEST SETUP	35
7 PHOTOGRAPHS OF THE EUT	36

TEST RESULT CERTIFICATION

Applicant's Name.....: DH Research, LLC
Address.....: 440 Wyoming Avenue Millburn, NJ 7041 United State
Manufacturer's Name.....: DH Research, LLC
Address.....: 440 Wyoming Avenue Millburn, NJ 7041 United State

Product description

Product name.....: 915M data transmission

Model Number.....: LR900-F

Standards.....: FCC Part 15.247

Test procedure.....: IEEE/ANSI C63.10-2020

KDB 558074 D01 15.247 Meas Guidance v05r02

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test

Date (s) of performance of tests.....: Dec. 05 2025~Jan. 30.2026

Test Result.....: **Pass**

Testing Engineer :

Zoe Su

(Z o e S u)

Technical Manager :

Ming Liu

(M i n g L i u)

Authorized Signatory :

Leo Su

(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	915M data transmission
Model name:	LR900-F
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	915MHz
Modulation type:	LoRa
Bit Rate of transmitter:	125 kHz
Antenna type:	SMA Antenna
Antenna gain:	2.5dBi
Max. output power:	25.449dBm
Hardware version:	V1.0
Software version:	V1.0
Battery:	N/A
Power supply:	DC 5V from adapter AC 120V/60Hz
Adapter information:	N/A

1.2 Test Mode

Test Mode	Channel	Frequency (MHz)
TX	01	915

1.3 Operation Channel list

Channel No.	Frequency (MHz)
1	915

1.4 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Power setting configuration parameters

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Test software Version			
Frequency	915 MHz		
Parameters	Default		
RF cable			
Description	Connector	Length	Supplied by
Antenna Cable	SMA	10cm	Applicant

Note: Disclaimer: the loss of RF cable is too small and can be ignored.

1.6 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	MDY-12-EF	N/A	Xiaomi

Note: The laptop is used to assist the RF test. In order to prevent the laptop from causing unnecessary impact on the test, the laptop will be removed from the test environment after the EUT successfully transmits at a fixed frequency using the laptop.

2 Summary of Test Result

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(9kHz-30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Occupied Bandwidth	$\pm 3\%$	
Temperature	± 1 degree	
Humidity	± 5 %	

3.4 Test Software

Software name	Manufacturer	Model	Version
Conducted Emission test Software	Farad	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission test Software	Farad	EZ-EMC	FA-03A2
RF Test System	MWRF	MTS 8310	2.0.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2024-05-18	2026-05-17
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2024-05-18	2026-05-17
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 9170	01193	2024-05-18	2026-05-17
4	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2025-05-07	2026-05-06
5	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2025-05-07	2026-05-06
6	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2025-05-07	2026-05-06
7	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
8	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
9	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2025-05-13	2026-05-12
10	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2024-05-18	2026-05-17
11	HB-E076	Preamplifier	Hewlett Packard	8447D	1937A02278	2025-05-07	2026-05-06
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2025-05-07	2026-05-06
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2025-05-07	2026-05-06
3	HB-E016	Absorb clamp	ZHINAN	ZN23201	N/A	2025-05-10	2026-05-09
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2025-05-10	2026-05-09
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2025-05-07	2026-05-06
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaioq Signal Generator	Agilent	N5181A	MY47070421	2025-05-07	2026-05-06
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2025-05-08	2026-05-07

3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2025-05-08	2026-05-07
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2025-05-07	2026-05-06
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2025-05-08	2026-05-07
6	HB-E058	Thermometer Clock Humidity 915M data transmission	N/A	HTC-1S	N/A	2025-05-09	2026-05-08
7	HB-E081	PXA Signal Analyzer	Agilent	N9030A	N/A	2025-05-07	2026-05-06

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is SMA Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission

5.2.1 Limits

Limits – Class B		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

Note:

- the tighter limit applies at the band edges.
- the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.2.2 Test Procedures

a) EUT Operating Conditions


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup




5.2.4 Test Result

EUT:	915M data transmission	Model Name:	LR900-F
Test Mode:	TX	Phase:	L
Test Voltage:	DC 5V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1770	29.66	11.03	40.69	64.63	-23.94	QP
2	0.1770	25.11	11.03	36.14	54.63	-18.49	AVG
3	0.2670	28.58	11.03	39.61	61.21	-21.60	QP
4	0.2670	25.50	11.03	36.53	51.21	-14.68	AVG
5*	0.4830	27.25	11.03	38.28	56.29	-18.01	QP
6	0.4830	23.95	11.03	34.98	46.29	-11.31	AVG
7	1.1805	17.88	11.04	28.92	56.00	-27.08	QP
8	1.1805	14.80	11.04	25.84	46.00	-20.16	AVG
9	1.6485	15.37	11.05	26.42	56.00	-29.58	QP
10	1.6485	11.89	11.05	22.94	46.00	-23.06	AVG
11	2.8365	12.26	11.06	23.32	56.00	-32.68	QP
12	2.8365	4.45	11.06	15.51	46.00	-30.49	AVG

EUT:	915M data transmission	Model Name:	LR900-F
Test Mode:	TX	Phase:	N
Test Voltage:	DC 5V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1770	30.49	11.03	41.52	64.63	-23.11	QP
2	0.1770	24.58	11.03	35.61	54.63	-19.02	AVG
3*	0.2354	29.43	11.03	40.46	62.26	-21.80	QP
4	0.2354	23.04	11.03	34.07	52.26	-18.19	AVG
5	0.2940	27.90	11.03	38.93	60.41	-21.48	QP
6	0.2940	24.91	11.03	35.94	50.41	-14.47	AVG
7	0.3524	26.50	11.03	37.53	58.91	-21.38	QP
8	0.3524	20.06	11.03	31.09	48.91	-17.82	AVG
9	0.4874	25.23	11.03	36.26	56.21	-19.95	QP
10	0.4874	18.52	11.03	29.55	46.21	-16.66	AVG
11	1.0320	19.71	11.04	30.75	56.00	-25.25	QP
12	1.0320	15.61	11.04	26.65	46.00	-19.35	AVG

5.3 Radiated Emission

5.3.1 Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures


- The radiated emission tests were performed in the 3 meters.
- The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup


Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.3.4 Test Result

Below 30MHz

EUT:	915M data transmission	Model Name:	LR900-F
Pressure:	1010 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX	Polarization:	--


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.


Frequency range (30MHz – 1GHz)

EUT:	915M data transmission	Model Name:	LR900-F
Test Mode:	TX	Phase:	Vertical
Test Voltage:	DC 5V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.0244	33.83	-12.65	21.18	40.00	-18.82	QP
2	287.9904	46.61	-11.96	34.65	46.00	-11.35	QP
3	343.1800	40.75	-10.42	30.33	46.00	-15.67	QP
4	360.4476	40.58	-9.99	30.59	46.00	-15.41	QP
5	763.3757	37.86	-1.59	36.27	46.00	-9.73	QP
6*	824.5968	41.54	-1.00	40.54	46.00	-5.46	QP

EUT:	915M data transmission	Model Name:	LR900-F
Test Mode:	TX	Phase:	Horizontal
Test Voltage:	DC 5V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.5591	35.93	-12.63	23.30	40.00	-16.70	QP
2	48.5015	38.89	-13.02	25.87	40.00	-14.13	QP
3	57.3923	37.15	-13.52	23.63	40.00	-16.37	QP
4	143.8295	34.84	-11.88	22.96	43.50	-20.54	QP
5	239.9873	36.34	-13.41	22.93	46.00	-23.07	QP
6*	830.4001	35.70	-0.99	34.71	46.00	-11.29	QP

5.3.5 Band Edge - Radiated

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Channel (915 MHz)(LoRa									
970.640	53.69	2.40	27.70	40.40	43.39	54	-10.61	Pk	Horizontal
980.440	52.81	2.40	27.70	40.40	42.51	54	-11.49	AV	Horizontal
995.360	52.56	2.40	27.70	40.40	42.26	54	-11.74	Pk	Horizontal
962.440	51.40	2.40	27.70	40.40	41.10	54	-12.90	AV	Vertical
980.160	54.78	2.44	28.30	40.10	45.42	54	-8.58	Pk	Vertical
991.920	52.81	2.44	28.30	40.10	43.45	54	-10.55	AV	Vertical
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									

5.3.6 Spurious emission in restricted band 1000MHz-25000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Channel (915 MHz)(LoRa)--Above 1G									
1830.25	65.21	4.36	32.92	45.53	56.96	74.00	-17.04	Pk	Vertical
2744.88	41.70	4.36	32.92	45.53	33.45	54.00	-20.55	AV	Vertical
3660.00	61.85	5.02	37.63	45.56	58.94	74.00	-15.06	Pk	Horizontal
4575.00	40.94	5.02	37.63	45.56	38.03	54.00	-15.97	AV	Horizontal
5490.00	62.74	4.36	32.92	45.53	54.49	74.00	-19.51	Pk	Vertical
6405.00	42.92	4.36	32.92	45.53	34.67	54.00	-19.33	AV	Vertical
7320.00	62.52	5.02	37.63	45.56	59.61	74.00	-14.39	Pk	Horizontal
8235.00	41.46	5.02	37.63	45.56	38.55	54.00	-15.45	AV	Horizontal
Channel (915 MHz)(LoRa)--Above 1G									
1830.25	65.65	4.41	33.01	45.76	65.65	74.00	-16.69	Pk	Vertical
2744.88	43.29	4.41	33.01	45.76	43.29	54.00	-19.05	AV	Vertical
3660.00	64.37	5.02	37.68	45.59	64.37	74.00	-12.52	Pk	Horizontal
4575.00	41.02	5.02	37.68	45.59	41.02	54.00	-15.87	AV	Horizontal
5490.00	62.96	4.41	33.01	45.76	62.96	74.00	-19.38	Pk	Vertical
6405.00	40.76	4.41	33.01	45.76	40.76	54.00	-21.58	AV	Vertical
7320.00	61.3	5.02	37.68	45.59	61.3	74.00	-15.59	Pk	Horizontal
8235.00	44.44	5.02	37.68	45.59	44.44	54.00	-12.45	AV	Horizontal

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.4 Peak Output Power


5.4.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.4.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=2MHz, VBW=10MHz, Detector=Peak
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.4.3 Test Setup



5.4.4 Test Results

EUT:	915M data transmission	Model Name:	LR900-F
Test Mode:	TX Mode	Test Voltage:	DC 5V

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	915	25.449	30



5.5 Power Spectral Density


5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.5.2 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test Setup



5.5.4 Test Results

EUT:	915M data transmission	Model Name:	LR900-F
Pressure:	1015 hPa	Test Voltage:	DC 5V
Test Mode:	TX Mode		

Frequency	Power Density (dBm/30kHz)	Limit (dBm/3kHz)	Result
915 MHz	2.0	8	Pass



5.6 6dB Bandwidth


5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{kHz}$ (6dB bandwidth)	2400-2483.5

5.6.2 Test Procedure

1. Set RBW= shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = No faster than coupled (auto) time.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Test Setup




5.6.4 Test Results

EUT:	915M data transmission	Model Name:	LR900-F
Pressure:	1012 hPa	Test Voltage:	DC 5V
Test Mode:	LoRa/ CH01		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (MHz)	Result
Low	915	0.619	0.5	Pass

Test plots



5.7 Conducted Band Edge


5.7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.7.2 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.


5.7.3 Test Setup



5.7.4 Test Results

EUT:	915M data transmission	Model Name:	LR900-F
Pressure:	1012 hPa	Test Voltage:	DC 5V
Test Mode:	TX Mode /CH01		

Band Edge, Left Side



5.8 Spurious RF Conducted Emissions

5.8.1 Limit

Below -20dB of the highest emission level in operating band.


5.8.2 Measuring Instruments

The Measuring equipment is listed in the section 4 of this test report.

5.8.3 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW=300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.8.4 Test Setup




5.8.5 Test Results

Note:

1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test plots



6 Photographs of the Test Setup

Note: Refer to the attached test photos

7 Photographs of the EUT

Note: Refer to the attached exterior and interior photos

******* END OF REPORT *******