



SAR Test Report

Report No.: STS2512122H01

Issued for

Shenzhen Linklan Technology Co., Ltd.

No. 1203, Xintang Road, Xintian Community, Fuhai
Subdistrict, Bao'an District, Shenzhen City, China

Product Name: Portable Wi-Fi

Brand Name: N/A

Model Name: LA7

Series Model(s): N/A

FCC ID: 2BSWD-LA7

Test Standard: ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

Max. Report Limbs : 0.975 W/kg(10g)
SAR (10&1g) Body: 0.942 W/kg(1g)

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT CERTIFICATION**

Applicant's name : Shenzhen Linklan Technology Co., Ltd.
Address : No. 1203, Xintang Road, Xintian Community, Fuhai Subdistrict,
Bao'an District, Shenzhen City, China
Manufacturer's Name : Dongguan Jintaiyi Electronics Co., Ltd.
Address : Room 1301, Building 1, Oufei Photoelectric Imaging Industry
Research Center, No.2 Huahai Road, marina bay New District,
Dongguan City, Guangdong Province

Product description

Product name : Portable Wi-Fi
Brand name : N/A
Model name : LA7
Series Model(s) : N/A

Standards : ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test..... :

Date (s) of performance of tests..... : 16 Dec. 2025 ~ 18 Dec. 2025

Date of Issue..... : 06 Jan. 2026

Test Result..... : **Pass**

Testing Engineer :

Xin Liu

(Xin.Liu)

Technical Manager :

Shi fan-long

(Shifan. Long)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	15
5.1 Validation System	15
5.2 Validation Result	16
6. SAR Evaluation Procedures	17
7. EUT Antenna Location Sketch	18
7.1 SAR test exclusion consider table	19
8. EUT Test Position	22
8.1 Body-worn Position Conditions	22
9. Uncertainty	23
9.1 Measurement Uncertainty	23
10. Conducted Power Measurement	26
10.1 Test Result	26
11. EUT and Test Setup Photo	31
11.1 EUT Photo	31
11.2 Setup Photo	34
12. SAR Result Summary	41
12.1 Limbs SAR	41
12.2 Body SAR	42
12.3 Repeated SAR	43
12.4 Repeated SAR measurement	43
12.5 Simultaneous Multi-band Transmission Evaluation	44
13. Equipment List	45
Appendix A. System Validation Plots	46
Appendix B. SAR Test Plots	54
Appendix C. Probe Calibration and Dipole Calibration Report	74



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	06 Jan. 2026	STS2512122H01	ALL	Initial Issue



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Portable Wi-Fi			
Brand Name	N/A			
Model Name	LA7			
Series Model	N/A			
Model Difference	N/A			
Sample number	251216012-1			
Battery	DC 3.85V			
Device Category	Portable			
Product stage	Production unit			
RF Exposure Environment	General Population / Uncontrolled			
Hardware Version	N/A			
Software Version	N/A			
Frequency Range	WCDMA Band 2: 1850 MHz ~ 1910 MHz LTE Band 12: 699 MHz ~ 716 MHz WLAN802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz BLE: 2402 MHz to 2480 MHz			
Max. Reported SAR(1g): (Limit:1.6&4.0W/kg) Test distance: Limbs:0mm Body:5mm	Band	Mode	Body Worn and hotspot(W/kg)	Limbs and Hotspot(W/Kg)
	PCB	WCDMA Band 2	0.942	0.975
	PCB	LTE Band 12	0.464	0.261
	DTS	2.4G WLAN	0.268	0.328
	DTS	BLE	0.029	0.091
	NII	5.2G WLAN	0.350	0.388
1-g Sum SAR			1.292	N/A
10-g Sum SAR			N/A	1.363
Limit			1.6W/kg	4.0W/kg
FCC Equipment Class	Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX(NII) Licensed Transmitter (PCB)			
Operating Mode:	WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 5G WLAN:			



	802.11a(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM):BPSK,QPSK,16-QAM,64-QAM,256-QAM BLE: GFSK
Antenna Specification:	WCDMA/LTE: PIFA Antenna WLAN/BLE: PIFA Antenna
Hotspot Mode	Support
DTM Mode	Not Support
Note: 1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power	



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	IEEE Std C95.1, 2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
10	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 08/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



Figure-SN 21/21 ELLI48



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

4. Tissue Simulating Liquids



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability. For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

**LIQUID MEASUREMENT RESULTS**


Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2025-12-16	21.0	41	707	20.6	Permittivity	42.13	42.61	1.14	±5
					Conductivity	0.89	0.85	-4.49	±5
2025-12-16	21.1	41	750	20.7	Permittivity	41.90	42.52	1.48	±5
					Conductivity	0.89	0.90	1.12	±5
2025-12-16	21.0	41	1852.4	20.6	Permittivity	40.00	41.10	2.75	±5
					Conductivity	1.40	1.41	0.71	±5
2025-12-16	21.1	41	1880	20.8	Permittivity	40.00	40.32	0.80	±5
					Conductivity	1.40	1.37	-2.14	±5
2025-12-16	21.1	41	1900	20.8	Permittivity	40.00	40.19	0.47	±5
					Conductivity	1.40	1.39	-0.71	±5
2025-12-16	21.0	41	1907.6	20.7	Permittivity	40.00	40.88	2.20	±5
					Conductivity	1.40	1.41	0.71	±5
2025-12-18	22.2	45	2437	21.9	Permittivity	39.22	39.34	0.31	±5
					Conductivity	1.79	1.77	-1.12	±5
2025-12-18	22.3	45	2450	22.0	Permittivity	39.20	39.44	0.61	±5
					Conductivity	1.80	1.81	0.56	±5
2025-12-18	22.3	45	2480	22.0	Permittivity	39.15	38.83	-0.82	±5
					Conductivity	1.83	1.86	1.64	±5
2025-12-18	22.2	45	5200	21.9	Permittivity	36.00	36.54	1.50	±5
					Conductivity	4.66	4.64	-0.43	±5
2025-12-18	22.2	45	5240	21.9	Permittivity	35.96	37.14	3.28	±5
					Conductivity	4.70	4.69	-0.21	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Date	Frequency (MHz)	Power	SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	Drift (%)	1W Target		Difference percentage		Limited %
						SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	1g	10g	
2025-12-16	750	100 mW	0.909	0.571	-0.73	8.49	5.53	7.07%	3.25%	10
		Normalize to 1 Watt	9.09	5.71						
2025-12-16	1900	100 mW	4.007	2.069	1.24	39.84	20.20	0.58%	2.43%	10
		Normalize to 1 Watt	40.07	20.69						
2025-12-18	2450	100 mW	5.472	2.435	-3.76	54.70	24.11	0.04%	1.00%	10
		Normalize to 1 Watt	54.72	24.35						
2025-12-18	5200	10 mW	1.562	0.531	-0.02	163.88	57.29	-4.67%	-7.31%	10
		Normalize to 1 Watt	156.23	53.10						

Note:

(1) We use a CW signal of 20dBm(750/1900/2450MHz) and 10dBm(5000-6000MHz) for system check, and then all SAR values are normalized to 1W forward power. The result must be within $\pm 10\%$ of target value.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position


- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Portable Wi-Fi, support WCDMA/LTE/WLAN mode.



- WLAN Antenna
- WCDMA Antenna
- LTE Antenna

Antenna Separation Distance(cm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	≤0.5	3.5	≤0.5	9.5	≤0.5
WCDMA	≤0.5	≤0.5	3.5	≤0.5	≤0.5	9.5
LTE	≤0.5	≤0.5	≤0.5	3.2	9.5	≤0.5

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WLAN/WWAN SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	WCDMA II	LTE Band 12	BT	2.4G WLAN	5.2G WLAN
	Calculated Frequency(GHz)	1.9076	0.704	2.48	2.442	2.442
	Maximum Turn-up power (dBm)	22	24	6	12.5	12.5
	Maximum rated power(mW)	158.49	251.19	3.98	17.78	17.78
Back Side	Separation distance (cm)	0.5	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	3.35	11.75	2.72	2.75	2.75
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (cm)	0.5	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	3.35	11.75	2.72	2.75	2.75
	Testing required?	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	3.5	0.5	3.5	3.5	3.5
	exclusion threshold(mW)	122.18	11.75	110.63	111.28	111.28
	Testing required?	YES	YES	NO	NO	NO
Right Side	Separation distance (cm)	0.5	3.2	0.5	0.5	0.5
	exclusion threshold(mW)	3.35	131.92	2.72	2.75	2.75
	Testing required?	YES	YES	YES	YES	YES
Top Side	Separation distance (cm)	0.5	9.5	9.5	9.5	9.5
	exclusion threshold(mW)	3.35	544.49	741.12	742.97	742.97
	Testing required?	YES	NO	NO	NO	NO
Bottom Side	Separation distance (cm)	9.5	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	773.23	11.75	2.72	2.75	2.75
	Testing required?	NO	YES	YES	YES	YES

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, if the maximum time-averaged power available does not exceed 1 mW. This stand-alone SAR exemption test.



4. Per KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5. Per KDB 447498 D04, An alternative to the SAR-based exemption is using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in below table to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.



6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.
8. Per KDB 248227, as maximum rated power for U-NII-1 > U-NII-2A, U-NII-1 was chosen for SAR evaluation. Based on the measurements obtained, SAR measurements on U-NII-2A are not required as highest reported SAR from U-NII-1 band is $\leq 1.2\text{W/Kg}$.


8. EUT Test Position

This EUT was tested in Back Side, Front Side, Left Side, Right Side, Top Side and Bottom Side.

8.1 Body-worn Position Conditions

Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D04 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

SATIMO Uncertainty- SN 08/21 EPG0352									
Measurement uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ %)	10g Ui (+ %)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.71	0.71	0.07	0.07	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.71	0.71	0.42	0.42	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	1.00	1.00	1.97	1.97	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	1.00	1.00	0.10	0.10	∞
Integration Time	E.2.8	1.43	R	1.73	1.00	1.00	0.83	0.83	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
Test sample Related									
Test sample positioning	E.4.2	3.10	N	1.00	1.00	1.00	3.10	3.10	∞
Device holder uncertainty	E.4.1	3.80	N	1.00	1.00	1.00	3.80	3.80	∞
Output power variation— SAR drift measurement	E.2.9	4.50	R	1.73	1.00	1.00	2.60	2.60	∞
SAR scaling	E.6.5	1.80	R	1.73	1.00	1.00	1.04	1.04	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	M
Liquid permittivity measurement	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	∞
Combined Standard Uncertainty			RSS				10.08	9.59	
Expanded Uncertainty (95% Confidence interval)			K=2				19.58	19.18	



SATIMO Uncertainty- SN 08/21 EPG0352									
System Validation uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	1.00	1.00	0.10	0.10	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
System validation source									
Deviation of experimental dipole from numerical dipole	E.6.4	4.80	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.10	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.40	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and set-up									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid conductivity (measured)	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid permittivity (temperature uncertainty)	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity (measured)	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				9.72	9.52	
Expanded Uncertainty (95% Confidence interval)			K=2				19.44	19.03	



SATIMO Uncertainty- SN 08/21 EPG0352									
• System Check uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ -%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration drift	E.2.1.3	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.00	0.00	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.8	R	1.73	0.00	0.00	0.00	0.00	∞
Linearity	E.2.4	1.25	R	1.73	0.00	0.00	0.00	0.00	∞
System detection limits	E.2.4	1.20	R	1.73	0.00	0.00	0.00	0.00	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	0.00	0.00	0.00	0.00	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions- Noise	E.6.1	3.51	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	0.00	0.00	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.2	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	3.9	R	1.73	0.00	0.00	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	4.8	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.1	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.4	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.7	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.4	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid permittivity measurement	E.3.3	4.1	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.7	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.8	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				5.56	5.20	
Expanded Uncertainty (95% Confidence interval)			K=2				11.12	10.41	



10. Conducted Power Measurement

10.1 Test Result

WCDMA

Band	WCDMA Band 2		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880	1907.6
RMC 12.2Kbps	24.06	23.84	23.54
HSDPA Subtest-1	24.81	25.07	25.17
HSDPA Subtest-2	24.37	24.82	24.77
HSDPA Subtest-3	23.36	23.41	23.74
HSDPA Subtest-4	23.14	23.74	23.82
HSUPA Subtest-1	23.61	25.02	25.14
HSUPA Subtest-2	24.85	25.19	25.22
HSUPA Subtest-3	23.29	24.05	23.88
HSUPA Subtest-4	24.86	25.21	25.28
HSUPA Subtest-5	23.54	24.44	24.45

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
 2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
 3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
 4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
 5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
 7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.
 8. According to April 2015 TCB workshop, SAR test exclusion can be applied for testing overlapping LTE bands as follows:
 - a) The maximum output power, including tolerance, for the smaller band must be $\leq$ the larger band to qualify for the SAR test exclusion.
 - b) The channel bandwidth and other operating parameters for the smaller band must be fully supported by the larger band.
- LTE Band 2 (1850-1910 MHz) is covered by LTE Band 25(1850-1915 MHz)
 - LTE Band 4 (1710-1755 MHz) is covered by LTE Band 66 (1710-1780MHz)
 - LTE Band 17 (704-716 MHz) is covered by LTE Band 12(699-716MHz)



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.26	22.40	22.24
1.4	1	2		22.23	22.32	22.14
1.4	1	5		22.34	22.42	22.18
1.4	3	0		22.32	22.36	22.31
1.4	3	1		22.30	22.36	22.21
1.4	3	2		22.33	22.48	22.21
1.4	6	0		21.28	21.48	21.19
1.4	1	0	16-QAM	21.22	21.51	21.35
1.4	1	2		21.21	21.47	21.30
1.4	1	5		21.30	21.50	21.33
1.4	3	0		21.61	21.73	21.54
1.4	3	1		21.58	21.81	21.67
1.4	3	2		21.67	21.75	21.73
1.4	6	0		20.50	20.65	20.34
3	1	0	QPSK	22.30	22.41	22.35
3	1	7		22.40	22.58	22.40
3	1	14		22.45	22.53	22.30
3	8	0		21.26	21.43	21.45
3	8	4		21.30	21.45	21.44
3	8	7		21.36	21.46	21.42
3	15	0		21.33	21.46	21.45
3	1	0	16-QAM	21.38	21.30	21.59
3	1	7		21.51	21.31	21.63
3	1	14		21.55	21.24	21.54
3	8	0		20.40	20.44	20.46
3	8	4		20.39	20.43	20.48
3	8	7		20.51	20.46	20.47
3	15	0		20.28	20.52	20.44



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.22	22.36	22.36
5	1	12		22.41	22.43	22.42
5	1	24		22.38	22.24	22.18
5	12	0		21.3	21.39	21.27
5	12	6		21.39	21.36	21.3
5	12	11		21.36	21.35	21.19
5	25	0		21.22	21.35	21.26
5	1	0	16-QAM	21.76	21.62	21.8
5	1	12		21.98	21.68	21.89
5	1	24		21.97	21.69	21.74
5	12	0		20.32	20.51	20.3
5	12	6		20.41	20.51	20.32
5	12	11		20.4	20.39	20.23
5	25	0		20.31	20.35	20.22
10	1	0	QPSK	22.3	22.49	22.41
10	1	24		21.26	22.57	22.43
10	1	49		22.48	22.48	22.38
10	25	0		21.43	21.47	21.3
10	25	12		21.45	21.45	21.33
10	25	24		21.42	21.38	21.23
10	50	0		21.43	21.4	21.22
10	1	0	16-QAM	21.5	21.27	21.83
10	1	24		21.65	21.27	21.76
10	1	49		21.66	21.25	21.71
10	25	0		20.43	20.4	20.33
10	25	12		20.47	20.5	20.33
10	25	24		20.42	20.51	20.27
10	50	0		20.47	20.4	20.31

**2.4G WLAN**

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
802.11b	1	2412	11.82	15.21
	7	2437	12.08	16.14
	11	2462	12.02	15.92
802.11g	1	2412	10.70	11.75
	7	2437	10.83	12.11
	11	2462	10.80	12.02
802.11 n-HT20	1	2412	9.64	9.20
	7	2437	9.80	9.55
	11	2462	9.70	9.33
802.11 n-HT40	3	2422	8.66	7.35
	6	2437	8.76	7.52
	9	2452	8.74	7.48

5.2G WLAN

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
802.11a	36	5180	11.12	12.94
	40	5200	10.68	11.69
	48	5240	11.60	14.45
802.11 n-HT20	36	5180	9.71	9.35
	40	5200	9.84	9.64
	48	5240	10.28	10.67
802.11 n-HT40	38	5190	8.71	7.43
	46	5230	9.00	7.94
802.11ac-VHT20	36	5180	9.72	9.38
	40	5200	9.78	9.51
	48	5240	9.72	9.38
802.11ac-VHT40	38	5190	8.56	7.18
	46	5230	9.02	7.98
802.11ac-VHT80	42	5210	8.49	7.06

2.4G WLAN

BLE				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	5.48	3.53
	19	2440	5.26	3.36
	39	2480	5.57	3.61


11. EUT and Test Setup Photo

11.1 EUT Photo


Front side




Back side




Top side




Bottom side



Left side



Right side






11.2 Setup Photo

Limbs Front side(separation distance is 0mm)



Limbs Back Side (separation distance is 0mm)




Limbs Left side(separation distance is 0mm)



Limbs Right Side (separation distance is 0mm)



Limbs Top side(separation distance is 0mm)



Limbs Bottom Side (separation distance is 0mm)



Body Front side(separation distance is 5mm)



Body Back Side (separation distance is 5mm)



Body Left side(separation distance is 5mm)



Body Right Side (separation distance is 5mm)



Body Top side(separation distance is 5mm)




Body Bottom Side (separation distance is 5mm)





Liquid depth (15 cm)





12. SAR Result Summary

12.1 Limbs SAR

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 10g (W/Kg)	Power Drift(%)	Max Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
WCDMA Band II	N/A	RMC	N/A	N/A	Front Side	1852.4	0.881	-2.71	24.50	24.06	1.107	0.975	1
					Front Side	1880	0.815	-3.65	24.50	23.84	1.164	0.949	/
					Front Side	1907.6	0.759	-2.33	24.50	23.54	1.247	0.947	/
					Back Side	1852.4	0.814	2.65	24.50	24.06	1.107	0.901	/
					Top Side	1852.4	0.631	-3.58	24.50	24.06	1.107	0.698	/
					Right Side	1852.4	0.705	-0.11	24.50	24.06	1.107	0.780	/
2.4GHz WLAN	N/A	802.11b	N/A	N/A	Left Side	1852.4	0.201	-0.43	24.50	24.06	1.107	0.222	/
					Front Side	2437	0.298	-2.72	12.50	12.08	1.102	0.328	3
					Back Side	2437	0.162	0.25	12.50	12.08	1.102	0.178	/
					Right Side	2437	0.141	-2.57	12.50	12.08	1.102	0.155	/
					Bottom Side	2437	0.175	0.38	12.50	12.08	1.102	0.193	/
					Front Side	2480	0.082	-0.36	6.00	5.57	1.104	0.091	5
BT	N/A	GFSK	N/A	N/A	Back Side	2480	0.065	-0.55	6.00	5.57	1.104	0.072	/
					Right Side	2480	0.05	-0.46	6.00	5.57	1.104	0.055	/
					Bottom Side	2480	0.071	-0.68	6.00	5.57	1.104	0.078	/
					Front Side	5240	0.354	-2.08	12.00	11.60	1.096	0.388	7
5.2GHz WLAN	N/A	802.11a	N/A	N/A	Back Side	5240	0.236	1.76	12.00	11.60	1.096	0.259	/
					Right Side	5240	0.240	-0.21	12.00	11.60	1.096	0.263	/
					Bottom Side	5240	0.269	0.50	12.00	11.60	1.096	0.295	/
					Front side	707.5	0.236	3.96	23.00	22.57	1.104	0.261	9
LTE Band 12	10M	QPSK	1	24	Front side	707.5	0.221	1.56	21.50	21.47	1.007	0.223	/
			25	0	Front side	707.5	0.221	1.56	21.50	21.47	1.007	0.223	/
			1	24	Back Side	707.5	0.169	3.46	23.00	22.57	1.104	0.187	/
			25	0	Back Side	707.5	0.152	-1.20	21.50	21.47	1.007	0.153	/
			1	24	Left Side	707.5	0.147	-0.42	23.00	22.57	1.104	0.162	/
			25	0	Left Side	707.5	0.168	-1.66	21.50	21.47	1.007	0.169	/
			1	24	Right Side	707.5	0.056	3.43	23.00	22.57	1.104	0.062	/
			25	0	Right Side	707.5	0.041	-0.25	21.50	21.47	1.007	0.041	/
			1	24	Bottom Side	707.5	0.155	-3.93	23.00	22.57	1.104	0.171	/
			25	0	Bottom Side	707.5	0.151	1.22	21.50	21.47	1.007	0.152	/

Note:

- The test separation of all above table is 0mm.
- Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

**12.2 Body SAR**

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
WCDMA Band II	N/A	RMC	N/A	N/A	Front Side	1852.4	0.851	-3.81	24.50	24.06	1.107	0.942	2
					Front Side	1880	0.785	3.14	24.50	23.84	1.164	0.914	/
					Front Side	1907.6	0.741	0.03	24.50	23.54	1.247	0.924	/
					Back Side	1852.4	0.614	1.19	24.50	24.06	1.107	0.679	/
					Top Side	1852.4	0.485	2.47	24.50	24.06	1.107	0.537	/
					Right Side	1852.4	0.685	-3.84	24.50	24.06	1.107	0.758	/
2.4GHz WLAN	N/A	802.11b	N/A	N/A	Left Side	1852.4	0.102	-1.11	24.50	24.06	1.107	0.113	/
					Front Side	2437	0.243	-2.97	12.50	12.08	1.102	0.268	4
					Back Side	2437	0.195	3.57	12.50	12.08	1.102	0.215	/
					Front Side	2437	0.175	-0.61	12.50	12.08	1.102	0.193	/
					Bottom Side	2437	0.185	2.60	12.50	12.08	1.102	0.204	/
					Front Side	2480	0.026	0.14	6.00	5.57	1.104	0.029	6
BT	N/A	GFSK	N/A	N/A	Back Side	2480	0.018	1.91	6.00	5.57	1.104	0.020	/
					Front Side	2480	0.015	-2.10	6.00	5.57	1.104	0.017	/
					Bottom Side	2480	0.019	3.49	6.00	5.57	1.104	0.021	/
					Front Side	5240	0.319	-3.78	12.00	11.60	1.096	0.350	8
5.2GHz WLAN	N/A	802.11a	N/A	N/A	Back Side	5240	0.231	0.71	12.00	11.60	1.096	0.253	/
					Front Side	5240	0.252	-3.11	12.00	11.60	1.096	0.276	/
					Bottom Side	5240	0.198	-3.87	12.00	11.60	1.096	0.217	/
					Front Side	5240	0.198	-3.87	12.00	11.60	1.096	0.217	/
LTE Band 12	10M	QPSK	1	24	Front side	707.5	0.420	-3.81	23.00	22.57	1.104	0.464	10
			25	0	Front side	707.5	0.415	-1.13	21.50	21.47	1.007	0.418	/
			1	24	Back Side	707.5	0.310	-1.63	23.00	22.57	1.104	0.342	/
			25	0	Back Side	707.5	0.285	1.49	21.50	21.47	1.007	0.287	/
			1	24	Left Side	707.5	0.331	0.44	23.00	22.57	1.104	0.365	/
			25	0	Left Side	707.5	0.301	3.63	21.50	21.47	1.007	0.303	/
			1	24	Right Side	707.5	0.096	-3.29	23.00	22.57	1.104	0.106	/
			25	0	Right Side	707.5	0.088	-2.71	21.50	21.47	1.007	0.089	/
			1	24	Bottom Side	707.5	0.221	-1.71	23.00	22.57	1.104	0.244	/
			25	0	Bottom Side	707.5	0.210	0.70	21.50	21.47	1.007	0.211	/

Note:

- The test separation of all above table is 5mm.
- Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



12.3 Repeated SAR

Band	Mode	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR(W/Kg)	Meas. No.
WCDMA Band II	RMC	Front Side	1852.4	0.845	-0.02	24.50	24.06	0.935	-
		Front Side	1880	0.755	3.28	24.50	23.84	0.879	-
		Front Side	1907.6	0.705	-2.48	24.50	23.54	0.879	-

12.4 Repeated SAR measurement

Band	Mode	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(W/kg)	2nd Repeated SAR 1g	Ratio
WCDMA Band II	RMC	Front Side	1852.4	0.851	0.845	1.007	-	-	-
		Front Side	1880	0.785	0.755	1.040	-	-	-
		Front Side	1907.6	0.741	0.705	1.051	-	-	-

Note:

1. Per KDB 865664 D01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$.
4. The ratio is the difference in percentage between original and repeated measured SAR.

**12.5 Simultaneous Multi-band Transmission Evaluation**

Application Simultaneous Transmission information:

Position	Simultaneous State
Limbs	1. WCDMA + 2.4/5GHz WLAN
	2. WCDMA + BLE
	3. LTE + 2.4/5GHz WLAN
	4. LTE + BLE
Body	1. WCDMA + 2.4/5GHz WLAN
	2. WCDMA + BLE
	3. LTE + 2.4/5GHz WLAN
	4. LTE + BLE

NOTE:

1. For simultaneous transmission at limbs and body exposure position, 2 transmitters simultaneous transmission was the worst state.
2. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.

Simultaneous Mode	Position	Mode	Max. 1&10-g	1&10-g Sum SAR
			(W/kg)	(W/kg)
WCDMA + 2.4G WLAN	Limbs	GSM	0.975	1.066
		2.4G WLAN	0.091	
	Body	GSM	0.942	0.971
		2.4G WLAN	0.029	
WCDMA + Bluetooth	Limbs	GSM	0.975	1.066
		Bluetooth	0.091	
	Body	GSM	0.942	0.971
		Bluetooth	0.029	
WCDMA + 5G WLAN	Limbs	GSM	0.975	1.363
		5G WLAN	0.388	
	Body	GSM	0.942	1.292
		5G WLAN	0.350	
LTE + 2.4G WLAN	Limbs	LTE	0.261	0.352
		2.4G WLAN	0.091	
	Body	LTE	0.464	0.493
		2.4G WLAN	0.029	
LTE + Bluetooth	Limbs	LTE	0.261	0.352
		Bluetooth	0.091	
	Body	LTE	0.464	0.493
		Bluetooth	0.029	
LTE + 5G WLAN	Limbs	LTE	0.261	0.649
		5G WLAN	0.388	
	Body	LTE	0.464	0.814
		5G WLAN	0.350	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
SAR Test System	SATIMO	N/A	V5.3.15.11	N/A	N/A
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2023.07.04	2026.07.03
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2023.09.14	2026.09.13
Waveguide	MVG	SWG5500	SN 13/14 WGA32	2023.07.04	2026.07.03
E-Field Probe	MVG	SSE2	SN 08/21 EPG0352	2025.09.15	2026.09.14
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2025.09.15	2026.09.14
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom3	MVG	SAM	SN 21/21 ELLI48	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	HXT-10-8-SMA	240327017	2025-02-22	2026-02-21
Directional coupler	Xi'an Xingbo	XBOH-OA08-20dB	211123-4-3	2025-02-22	2026-02-21
Network Analyzer	Agilent	E5071C	MY46520378	2025-09-26	2026-09-24
Multi Meter	Keithley	Multi Meter 2000	4050073	2025-09-22	2026-09-21
Signal Generator	Agilent	N5182A	MY50140530	2025-09-26	2026-09-25
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2025-02-22	2026-02-21
Wireless Communication Test Set	R&S	CMW500	156324	2025-09-25	2026-09-24
Power Amplifier	DESAY	WCS-DLNA50M8G50G1	CSKJLNA231227A	2025-09-29	2026-09-28
Power Meter	R&S	NRP	100510	2025-09-25	2026-09-24
Power Sensor	R&S	NRP-Z11	101919	2025-09-25	2026-09-24
Power Sensor	Keysight	U2021XA	MY56280002	2025-09-25	2026-09-24
Temperature hygrometer	TOPRIE	TP502V4-P	6700000124198	2025.10.09	2026.10.08
Thermograph	Elitech	RC-4	S/N EF7176501537	2025.10.17	2026.10.16



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-16

Experimental conditions.

Device Position	Validation plane
Band	750 MHz
Channels	-
Signal	CW
Frequency (MHz)	750
Relative permittivity	42.52
Conductivity (S/m)	0.90
Probe	SN 08/21 EPGO352
ConvF	1.51
Crest factor:	1:1




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 1.20 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	0.571
SAR 1g (W/Kg)	0.909
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	54.221014

E. Z Axis Scan



F. 3D Image



**System Performance Check Data (1900MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-16

Experimental conditions.

Device Position	Validation plane
Band	1900 MHz
Channels	-
Signal	CW
Frequency (MHz)	1900
Relative permittivity	40.19
Conductivity (S/m)	1.39
Probe	SN 08/21 EPGO352
ConvF	1.73
Crest factor:	1:1




Maximum location: X=2.00, Y=-3.00 ; SAR Peak: 6.43 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	2.069
SAR 1g (W/Kg)	4.007
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.365210

E. Z Axis Scan



F. 3D Image



**System Performance Check Data (2450MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-18

Experimental conditions.

Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	39.44
Conductivity (S/m)	1.81
Probe	SN 08/21 EPGO352
ConvF	1.82
Crest factor:	1:1




Maximum location: X=2.00, Y=-2.00 ; SAR Peak: 10.29 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	2.435
SAR 1g (W/Kg)	5.472
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.545439

E. Z Axis Scan



F. 3D Image



**System Performance Check Data (5200MHz)**

Type: Dipole measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-12-18

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	5200MHz
Channels	Middle
Signal	CW
Frequency (MHz)	5200
Relative permittivity	36.54
Conductivity (S/m)	4.64
Probe	SN 08/21 EPGO352
ConvF	1.37
Crest factor:	1:1




Maximum location: X=14.00, Y=-7.00 ; SAR Peak: 5.05 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.531
SAR 1g (W/Kg)	1.562
Horizontal validation criteria: minimum distance (mm)	8.944272
Vertical validation criteria: SAR ratio M2/M1 (%)	58.163250

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	4.889	3.081	1.792	1.025	0.608	0.354	0.206	0.120	0.070	0.041	0.024	0.014



F. 3D Image






Appendix B. SAR Test Plots

Plot 1: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-16
ConvF	1.73
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Limbs
Device Position	Front side
Band	WCDMA 2
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1852.4
Relative permittivity (real part)	41.10
Conductivity (S/m)	1.41




Maximum location: X=9.00, Y=-16.00 ; SAR Peak: 3.45 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.881
SAR 1g (W/Kg)	1.883
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	47.684908

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.487	2.019	0.963	0.505	0.255	0.128	0.065




F. 3D Image





Plot 2: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-16
ConvF	1.73
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Front side
Band	WCDMA 2
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1852.4
Relative permittivity (real part)	41.10
Conductivity (S/m)	1.41





Maximum location: X=-24.00, Y=55.00 ; SAR Peak: 1.46 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.414
SAR 1g (W/Kg)	0.851
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.312850

**E. Z Axis Scan**


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.461	0.899	0.475	0.267	0.146	0.080	0.044

**F. 3D Image**



Plot 3: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Limbs
Device Position	Front side
Band	2.4GHz WLAN
Signal	802.11b (Crest factor: 1.0)
Frequency (MHz)	2437
Relative permittivity (real part)	39.34
Conductivity (S/m)	1.77




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.298
SAR 1g (W/Kg)	0.644
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	46.069746

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.197	0.681	0.314	0.157	0.076	0.037	0.018




F. 3D Image





Plot 4: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Front side
Band	2.4GHz WLAN
Signal	802.11b (Crest factor: 1.0)
Frequency (MHz)	2437
Relative permittivity (real part)	39.34
Conductivity (S/m)	1.77




Maximum location: X=-5.00, Y=22.00 ; SAR Peak: 0.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.137
SAR 1g (W/Kg)	0.243
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	58.375894

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.385	0.254	0.148	0.083	0.050	0.029	0.017




F. 3D Image





Plot 5: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Limbs
Device Position	Front side
Band	BT
Signal	GFSK (Crest factor: 1.0)
Frequency (MHz)	2480
Relative permittivity (real part)	38.83
Conductivity (S/m)	1.86




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.082
SAR 1g (W/Kg)	0.262
Horizontal validation criteria: minimum distance (mm)	5.656854
Vertical validation criteria: SAR ratio M2/M1 (%)	69.796354

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00	24.00
SAR (W/Kg)	0.760	0.355	0.192	0.174	0.106	0.082	0.059	0.036	0.033	0.017	0.018	0.011




F. 3D Image





Plot 6: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Front side
Band	BT
Signal	GFSK (Crest factor: 1.0)
Frequency (MHz)	2480
Relative permittivity (real part)	38.83
Conductivity (S/m)	1.86




Maximum location: X=15.00, Y=-10.00 ; SAR Peak: 0.05 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.014
SAR 1g (W/Kg)	0.026
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	55.273335

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.045	0.027	0.014	0.010	0.006	0.004	0.002




F. 3D Image





Plot 7: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.37
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Limbs
Device Position	Front side
Band	5.2GHz WLAN
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5240
Relative permittivity (real part)	37.14
Conductivity (S/m)	4.69




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.354
SAR 1g (W/Kg)	1.227
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	55.553277

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	3.668	2.259	1.255	0.686	0.397	0.223	0.125	0.070	0.040	0.022	0.013	0.007




F. 3D Image





Plot 8: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-18
ConvF	1.37
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Front side
Band	5.2GHz WLAN
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5240
Relative permittivity (real part)	37.14
Conductivity (S/m)	4.69




Maximum location: X=-15.00, Y=37.00 ; SAR Peak: 0.88 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.122
SAR 1g (W/Kg)	0.319
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	57.484340

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.795	0.505	0.290	0.171	0.123	0.078	0.050	0.032	0.020	0.013	0.008	0.005




F. 3D Image





Plot 9: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-16
ConvF	1.51
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Limbs
Device Position	Front side
Band	LTE band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	42.61
Conductivity (S/m)	0.85




Maximum location: X=8.00, Y=-10.00 ; SAR Peak: 1.25 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.236
SAR 1g (W/Kg)	0.485
Horizontal validation criteria: minimum distance (mm)	20.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	83.999437

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.198	0.592	0.213	0.231	0.147	0.100	0.101




F. 3D Image





Plot 10: DUT: Portable Wi-Fi; EUT Model: LA7

Test Date	2025-12-16
ConvF	1.51
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Front side
Band	LTE band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	42.61
Conductivity (S/m)	0.85




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.214
SAR 1g (W/Kg)	0.420
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	71.146989

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.923	0.476	0.188	0.209	0.090	0.085	0.043



F. 3D Image





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※