

TEST REPORT

Product Name : MIC WIRELESS
Model Number : N1, N2, N3, N5, N7, A1, F11, F15, K11
FCC ID : 2BSXZ-YIMIDA-MIC

Prepared for : Dongguan Yimida Electronic Technology Co.,Ltd
Address : 7th Floor, Building 2, Huanjin Industrial Zone, Youganpu Village, Fenggang Town, Dongguan City, Guangdong Province, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2511190031W00202R
Date of sample receipt : Nov 19, 2025
Date(s) of Tests : Nov 19, 2025 to Dec 05, 2025
Date of issue : Dec 06, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Dongguan Yimida Electronic Technology Co.,Ltd
Address : 7th Floor, Building 2, Huanjin Industrial Zone, Youganpu Village, Fenggang Town, Dongguan City, Guangdong Province, China
Manufacturer : Dongguan Yimida Electronic Technology Co.,Ltd
Address : 7th Floor, Building 2, Huanjin Industrial Zone, Youganpu Village, Fenggang Town, Dongguan City, Guangdong Province, China
Factory : Dongguan Yimida Electronic Technology Co.,Ltd
Address : 7th Floor, Building 2, Huanjin Industrial Zone, Youganpu Village, Fenggang Town, Dongguan City, Guangdong Province, China
EUT : MIC WIRELESS
Model Name : N1, N2, N3, N5, N7, A1, F11, F15, K11
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Nov 19, 2025 to Dec 05, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2511190031W00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	MIC WIRELESS
Model Number:	N1, N2, N3, N5, N7, A1, F11, F15, K11 (Note: These models are the same, except for the model names;N1 was selected for full test.)
Sample:	2#
Device Type:	BLE
Data Rate:	1Mbps for GFSK modulation 2Mbps for GFSK modulation
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	40 channels
Transmit Power Max:	0.38 dBm(0.001091 W)
Antenna Type:	Chip Antenna
Antenna Gain:	2.67 dBi
Power supply:	DC 3.7V from battery DC 5V from USB
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement:

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain:2.67 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	EIRP (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	Calculation threshold(1-g SAR)
2402	GFSK(1M)	0.15	2.82	3±1	4	0.7786	3
2440	GFSK(1M)	-0.44	2.23	2±1	3	0.6233	3
2480	GFSK(1M)	-0.24	2.43	2±1	3	0.6284	3
2402	GFSK(2M)	0.38	3.05	3±1	4	0.7786	3
2440	GFSK(2M)	-0.42	2.25	2±1	3	0.6233	3
2480	GFSK(2M)	-0.1	2.57	2±1	3	0.6284	3

According to KDB 447498, no stand-alone required for BLE antenna, and no simultaneous SAR measurement is required.

*** End of Report ***