



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-Mail: ctl@ctl-lab.com

RF Exposure evaluation

Report Reference No. : CTL2510142091-WFH

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Tested by:
(position+printed name+signature)

Lydia Ou
(Test Engineer)

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)



Product Name : Smart Cat Nest

Model/Type reference : JMCH-004

List Model(s) : JMCH-001, JMCH-002, JMCH-003, JMCH-005, JMCH-006,
JMCH-007, JMCH-008, JMCH-009, HCCN-002, HCCN-004

Trade Mark : N/A

FCC ID : 2BSY5-JMCH

Applicant's name : Dongguan Gimi Electric Appliance Co., Ltd.

Address of applicant : No. 5, Lane 2, Jincheng Road, Golden Phoenix Industrial Zone,
Fenggang Town, Dongguan City, Guangdong Province, China

Test Firm : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test specification :

47CFR §1.1310

Standard : **47CFR §2.1091**

KDB447498 D01 General RF Exposure Guidance v06

TRF Originator : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF : Dated 2017-01

Date of receipt of test item : Oct 31, 2025

Date of Test : Oct 31, 2025 - Nov 19, 2025

Date of Issue : Nov 19, 2025

Result : Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2510142091-WFH	Nov 19, 2025
		Date of issue

Product Name : Smart Cat Nest

Sample No : CTL251014209001, CTL251014209002,
CTL251014209003

Model /Type : JMCH-004

Listed Models : JMCH-001, JMCH-002, JMCH-003, JMCH-005, JMCH-006,
JMCH-007, JMCH-008, JMCH-009, HCCN-002, HCCN-004

Applicant : **Dongguan Gimi Electric Appliance Co., Ltd.**

Address : No. 5, Lane 2, Jincheng Road, Golden Phoenix Industrial
Zone, Fenggang Town, Dongguan City, Guangdong
Province, China

Manufacturer : **Dongguan Gimi Electric Appliance Co., Ltd.**

Address : No. 5, Lane 2, Jincheng Road, Golden Phoenix Industrial
Zone, Fenggang Town, Dongguan City, Guangdong
Province, China

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

[illegible]

Contents

1	GENERAL INFORMATION	5
1.1	ENVIRONMENTAL CONDITIONS	5
1.2	PRODUCT DESCRIPTION	5
1.3	TEST FACILITY	7
1.4	STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
2	METHOD OF MEASUREMENT	8
2.1	APPLICABLE STANDARD	8
2.2	EVALUATION METHOD AND LIMIT	8
3	CONDUCTED POWER RESULTS	10
4	MANUFACTURING TOLERANCE	12
5	EVALUATION RESULTS.....	14
5.1	STANDALONE EVALUATION	14
6	CONCLUSION.....	16

1 GENERAL INFORMATION

1.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C -35°C
Relative Humidity:	35%-55 %
Air Pressure:	101 KPa

1.2 Product Description

Product Name:	Smart Cat Nest		
Model/Type reference:	JMCH-004		
Power supply:	DC 9V from adapter		
Adapter information	Mode: HA036A-900300UH Input:100-240V~50/60Hz 1.0A MAX Output:9V $\overline{\text{---}}$ 3.0A		
Test Voltage:	AC 110V/60Hz		
Bluetooth Low Energy			
Supported type:	Bluetooth Low Energy		
Modulation:	GFSK		
Operation frequency:	2402MHz~2480MHz		
Channel number:	40		
Channel separation:	2MHz		
Antenna type:	PCB Antenna		
Antenna gain:	1.95 dBi		
Wi-Fi 2.4GHz			
Supported type:	IEEE 802.11 b/g/n		
Modulation:	IEEE 802.11 b: DSSS IEEE 802.11 g/IEEE 802.11 n(HT20)/IEEE 802.11 n(HT40): OFDM		
Operation frequency:	IEEE 802.11 b/IEEE 802.11 g/IEEE 802.11 n(HT20): 2412MHz~2462MHz IEEE 802.11 n(HT40): 2422MHz~2452MHz		
Channel number:	IEEE 802.11 b/IEEE 802.11 g/IEEE 802.11 n(HT20)/ : 11 IEEE 802.11 n(HT40):7		
Channel separation:	5MHz		
MIMO:	Not Support		
Antenna type:	PCB Antenna		
Antenna gain:	1.95 dBi		
Wi-Fi 5GHz			
Supported type:	20MHz system	40MHz system	80MHz system
	802.11a 802.11n	802.11n	/

Operation frequency:	5180-5240MHz 5260-5320MHz 5500-5700MHz 5745-5825MHz	5190-5230MHz 5270-5310MHz 5510-5670MHz 5755-5795MHz	/
Modulation:	OFDM	OFDM	/
Channel number:	24	11	/
Channel separation:	20MHz	40MHz	/
MIMO:	Not Support		
DFS Operational mode:	Support		
Antenna type:	PCB Antenna		
Antenna gain:	5180MHz-5240MHz: 1.97 dBi 5260MHz-5320MHz: 1.97dBi 5500MHz-5700MHz: 1.60dBi 5745MHz-5825MHz: -0.76 dBi		

Note 1: For more details, refer to the user's manual of the EUT.

Note 2: Antenna gain and cable loss provided by the applicant.

1.3 Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832.

1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	± 1.18 dB	(1)

Note 1: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

2 METHOD OF MEASUREMENT

2.1 Applicable Standard

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

2.2 Evaluation Method and Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3 Conducted Power Results

Bluetooth Low Energy

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
1M	2402	4.99
	2440	5.63
	2480	5.53
2M	2402	5.79
	2440	6.46
	2480	5.79

2.4G Wi-Fi

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	2412	13.90
	2437	14.67
	2462	14.59
802.11g	2412	15.60
	2437	16.39
	2462	16.31
802.11n (HT20)	2412	15.57
	2437	16.24
	2462	16.27
802.11n (HT40)	2422	16.65
	2437	16.25
	2452	16.37

5G Wi-Fi Band 1

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11a	5180	11.34
	5200	12.04
	5240	11.21
802.11n (HT20)	5180	11.25
	5200	11.14
	5240	11.21
802.11n (HT40)	5190	12.08
	5230	11.14

5G Wi-Fi Band 2A

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11a	5260	12.51
	5300	11.73
	5320	11.37
802.11n (HT20)	5260	12.18
	5300	11.40
	5320	11.26
802.11n (HT40)	5270	12.72
	5310	11.53

5G Wi-Fi Band 2C

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11a	5500	12.42
	5580	12.49
	5700	12.39
802.11n (HT20)	5500	12.84
	5580	12.42
	5700	12.14
802.11n (HT40)	5510	12.76
	5550	12.52
	5670	12.87

5G Wi-Fi Band 3

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11a	5745	14.00
	5785	13.00
	5825	13.84
802.11n (HT20)	5745	13.91
	5785	13.31
	5825	13.79
802.11n (HT40)	5755	13.99
	5795	13.70

4 Manufacturing Tolerance

Note: Tolerance $\pm(\text{dB}):1.0$

Bluetooth Low Energy

Mode	Frequency (MHz)	Target (dBm)
1M	2402	5.0
	2440	6.0
	2480	6.0
2M	2402	6.0
	2440	6.0
	2480	6.0

2.4G Wi-Fi

Mode	Frequency (MHz)	Target (dBm)
802.11b	2412	14
	2437	15
	2462	15
802.11g	2412	16
	2437	16
	2462	16
802.11n (HT20)	2412	16
	2437	16
	2462	16
802.11n (HT40)	2422	17
	2437	16
	2452	16

5G Wi-Fi Band 1

Mode	Frequency (MHz)	Target (dBm)
802.11a	5180	11
	5200	12
	5240	11
802.11n (HT20)	5180	11
	5200	11
	5240	11
802.11n (HT40)	5190	12
	5230	11

5G Wi-Fi Band 2A

Mode	Frequency (MHz)	Target (dBm)
802.11a	5260	13
	5300	12
	5320	11
802.11n (HT20)	5260	12
	5300	11
	5320	11
802.11n (HT40)	5270	13
	5310	12

5G Wi-Fi Band 2C

Mode	Frequency (MHz)	Target (dBm)
802.11a	5500	12
	5580	12
	5700	12
802.11n (HT20)	5500	13
	5580	12
	5700	12
802.11n (HT40)	5510	13
	5550	13
	5670	13

5G Wi-Fi Band 3

Mode	Frequency (MHz)	Target (dBm)
802.11a	5745	14
	5785	13
	5825	14
802.11n (HT20)	5745	14
	5785	13
	5825	14
802.11n (HT40)	5755	14
	5795	14

5 Evaluation Results

5.1 Standalone Evaluation

Bluetooth Low Energy

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
1M	2.402	20	6	3.98	1.5668	0.0012	1.0000
	2.440	20	7	5.01	1.5668	0.0016	1.0000
	2.480	20	7	5.01	1.5668	0.0016	1.0000
2M	2.402	20	7	5.01	1.5668	0.0016	1.0000
	2.440	20	7	5.01	1.5668	0.0016	1.0000
	2.480	20	7	5.01	1.5668	0.0016	1.0000

2.4G Wi-Fi

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
802.11b	2412	20	15	31.62	1.5668	0.0099	1.0000
	2437	20	16	39.81	1.5668	0.0124	1.0000
	2462	20	16	39.81	1.5668	0.0124	1.0000
802.11g	2412	20	17	50.12	1.5668	0.0156	1.0000
	2437	20	17	50.12	1.5668	0.0156	1.0000
	2462	20	17	50.12	1.5668	0.0156	1.0000
802.11n (HT20)	2412	20	17	50.12	1.5668	0.0156	1.0000
	2437	20	17	50.12	1.5668	0.0156	1.0000
	2462	20	17	50.12	1.5668	0.0156	1.0000
802.11n (HT40)	2422	20	18	63.10	1.5668	0.0197	1.0000
	2437	20	17	50.12	1.5668	0.0156	1.0000
	2452	20	17	50.12	1.5668	0.0156	1.0000

5G Wi-Fi Band 1

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
802.11a	5180	20	12	15.85	1.5740	0.0050	1.0000
	5200	20	13	19.95	1.5740	0.0062	1.0000
	5240	20	12	15.85	1.5740	0.0050	1.0000
802.11n (HT20)	5180	20	12	15.85	1.5740	0.0050	1.0000
	5200	20	12	15.85	1.5740	0.0050	1.0000
	5240	20	12	15.85	1.5740	0.0050	1.0000
802.11n (HT40)	5190	20	13	19.95	1.5740	0.0062	1.0000
	5230	20	12	15.85	1.5740	0.0050	1.0000

5G Wi-Fi Band 2A

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
802.11a	5260	20	14	25.12	1.5740	0.0079	1.0000
	5300	20	13	19.95	1.5740	0.0062	1.0000
	5320	20	12	15.85	1.5740	0.0050	1.0000
802.11n (HT20)	5260	20	13	19.95	1.5740	0.0062	1.0000
	5300	20	12	15.85	1.5740	0.0050	1.0000
	5320	20	12	15.85	1.5740	0.0050	1.0000
802.11n (HT40)	5270	20	14	25.12	1.5740	0.0079	1.0000
	5310	20	13	19.95	1.5740	0.0062	1.0000

5G Wi-Fi Band 2C

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
802.11a	5500	20	13	19.95	1.4454	0.0057	1.0000
	5580	20	13	19.95	1.4454	0.0057	1.0000
	5700	20	13	19.95	1.4454	0.0057	1.0000
802.11n (HT20)	5500	20	14	25.12	1.4454	0.0072	1.0000
	5580	20	13	19.95	1.4454	0.0057	1.0000
	5700	20	13	19.95	1.4454	0.0057	1.0000
802.11n (HT40)	5510	20	14	25.12	1.4454	0.0072	1.0000
	5550	20	14	25.12	1.4454	0.0072	1.0000
	5670	20	14	25.12	1.4454	0.0072	1.0000

5G Wi-Fi Band 3

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)
			dBm	mW			
802.11a	5745	20	15	31.62	0.8395	0.0053	1.0000
	5785	20	14	25.12	0.8395	0.0042	1.0000
	5825	20	15	31.62	0.8395	0.0053	1.0000
802.11n (HT20)	5745	20	15	31.62	0.8395	0.0053	1.0000
	5785	20	14	25.12	0.8395	0.0042	1.0000
	5825	20	15	31.62	0.8395	0.0053	1.0000
802.11n (HT40)	5755	20	15	31.62	0.8395	0.0053	1.0000
	5795	20	15	31.62	0.8395	0.0053	1.0000

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is $\geq 20\text{cm}$, In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091

6 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

*****THE END*****