

**FCC 47 CFR PART 15 SUBPART C**

**TEST REPORT**

*For*

**Intel BE200**

**MODEL NUMBER: BE200NGW**

**REPORT NUMBER: 4792146700.1-RF-3**

**ISSUE DATE: Feb 25, 2026**

**FCC ID: 2BSYS-A2515**

*Prepared for*

**Financial Future(Beijing) Information Technology Co., Ltd.  
Room 12-01, 10th Floor, Building 38, Haidian Street, Haidian District, Beijing**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,  
Guangdong, China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

## Revision History

| Rev. | Issue Date | Revisions     | Revised By |
|------|------------|---------------|------------|
| V0   | 2/25/2026  | Initial Issue |            |

### Summary of Test Results

| Test Item                                 | Clause                                         | Limit/Requirement                             | Result |
|-------------------------------------------|------------------------------------------------|-----------------------------------------------|--------|
| Antenna Requirement                       | N/A                                            | FCC Part 15.203/15.247 (c)                    | Pass   |
| AC Power Line Conducted Emission          | ANSI C63.10-2020+Cor 1-2023, Clause 6.2        | FCC Part 15.207                               | Pass   |
| Conducted Peak Output Power               | ANSI C63.10-2020+Cor 1-2023, Clause 11.9.1.2   | FCC Part 15.247 (b)(3)                        | Pass   |
| Conducted Average Output Power            | ANSI C63.10-2020+Cor 1-2023, Clause 11.9.2.3.1 | FCC Part 15.247 (b)(3)                        | Pass   |
| 6dB Bandwidth and 99% Occupied Bandwidth  | ANSI C63.10-2020+Cor 1-2023, Clause 11.8.1     | FCC Part 15.247 (a)(2)                        | Pass   |
| Power Spectral Density                    | ANSI C63.10-2020+Cor 1-2023, Clause 11.10.2    | FCC Part 15.247 (e)                           | Pass   |
| Conducted Band edge and spurious emission | ANSI C63.10-2020+Cor 1-2023, Clause 11.11      | FCC Part 15.247(d)                            | Pass   |
| Radiated Band edge and Spurious Emission  | ANSI C63.10-2020+Cor 1-2023, Clause 11.12      | FCC Part 15.247 (d)<br>FCC Part 15.205/15.209 | Pass   |
| Duty Cycle                                | ANSI C63.10-2020+Cor 1-2023, Clause 11.6       | None; for reporting purposes only.            | Pass   |

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <FCC 47 CFR PART 15 SUBPART C

Note: The antenna gain of EUT is smaller than that of the RF module(FCC ID: 2BSYS-A2515 ). So in this report the Radiated Spurious Emission were evaluated and recorded in the report, and output power items were recorded in the report. For the test results of all other test items please refer to module test reports.

## CONTENTS

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. ATTESTATION OF TEST RESULTS.....</b>                  | <b>5</b>  |
| <b>2. TEST METHODOLOGY.....</b>                             | <b>7</b>  |
| <b>3. FACILITIES AND ACCREDITATION.....</b>                 | <b>7</b>  |
| <b>4. CALIBRATION AND UNCERTAINTY .....</b>                 | <b>8</b>  |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>          | <i>8</i>  |
| 4.2. <i>MEASUREMENT UNCERTAINTY .....</i>                   | <i>8</i>  |
| <b>5. EQUIPMENT UNDER TEST .....</b>                        | <b>9</b>  |
| 5.1. <i>DESCRIPTION OF EUT .....</i>                        | <i>9</i>  |
| 5.2. <i>CHANNEL LIST .....</i>                              | <i>9</i>  |
| 5.3. <i>MAXIMUM POWER .....</i>                             | <i>9</i>  |
| 5.4. <i>TEST CHANNEL CONFIGURATION .....</i>                | <i>10</i> |
| 5.5. <i>THE WORSE CASE POWER SETTING PARAMETER .....</i>    | <i>10</i> |
| 5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>         | <i>10</i> |
| 5.7. <i>SUPPORT UNITS FOR SYSTEM TEST .....</i>             | <i>11</i> |
| <b>6. MEASURING EQUIPMENT AND SOFTWARE USED.....</b>        | <b>12</b> |
| <b>7. ANTENNA PORT TEST RESULTS .....</b>                   | <b>15</b> |
| 7.1. <i>CONDUCTED OUTPUT POWER .....</i>                    | <i>15</i> |
| <b>8. RADIATED TEST RESULTS .....</b>                       | <b>16</b> |
| 8.1. <i>RESTRICTED BANDEDGE-ANT BT0 .....</i>               | <i>24</i> |
| 8.2. <i>SPURIOUS EMISSIONS-ANT BT0 (30 MHZ~1 GHZ) .....</i> | <i>28</i> |
| 8.3. <i>SPURIOUS EMISSIONS-ANT BT0.....</i>                 | <i>30</i> |
| <b>9. ANTENNA REQUIREMENT .....</b>                         | <b>36</b> |
| 9.1. <i>APPENDIX A: MAXIMUM CONDUCTED OUTPUT POWER.....</i> | <i>37</i> |
| 9.1.1. <i>Test Result-Ant BT0.....</i>                      | <i>37</i> |

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

**Company Name:** Financial Future(Beijing) Information Technology Co., Ltd.  
**Address:** Room 12-01, 10th Floor, Building 38, Haidian Street, Haidian District, Beijing

### Manufacturer Information

**Company Name:** Financial Future(Beijing) Information Technology Co., Ltd.  
**Address:** Room 12-01, 10th Floor, Building 38, Haidian Street, Haidian District, Beijing

### EUT Information

**EUT Name:** Intel BE200  
**Model:** BE200NGW  
**Sample Received Date:** Feb 10, 2026  
**Sample Status:** Normal  
**Sample ID:** 9445241  
**Date of Tested:** Feb 10, 2026- Feb 25, 2026

| APPLICABLE STANDARDS                                 |              |
|------------------------------------------------------|--------------|
| STANDARD                                             | TEST RESULTS |
| FCC 47 CFR PART 15 SUBPART C<br>ISED RSS-247 Issue 4 | Pass         |


Prepared By:



Johnson Liu

Laboratory Engineer


Checked By:



Fanny Huang

Project Engineer

Approved By:



Kebo Zhang

Operations Leader

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC 47 CFR PART 15 SUBPART C , KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, ANSI C63.10-2020+Cor 1-2023

## 3. FACILITIES AND ACCREDITATION

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 4102.01)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p><b>ISED (Company No.: 21320)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.<br/>Facility Name:<br/>Chamber E, the VCCI registration No. is G-20240 and R-20248<br/>Shielding Room F, the VCCI registration No. is C-20202 and T-20202</p> |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item                                                                                                                                     | Uncertainty               |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Conduction emission                                                                                                                           | 3.62 dB                   |
| Radiated Emission<br>(Included Fundamental Emission) (9 kHz ~ 30 MHz)                                                                         | 2.2 dB                    |
| Radiated Emission<br>(Included Fundamental Emission) (30 MHz ~ 1 GHz)                                                                         | 4.00 dB                   |
| Radiated Emission<br>(Included Fundamental Emission) (1 GHz to 26 GHz)                                                                        | 5.78 dB (1 GHz ~ 18 GHz)  |
|                                                                                                                                               | 5.23 dB (18 GHz ~ 26 GHz) |
| Duty Cycle                                                                                                                                    | ±0.028%                   |
| DTS and 99% Occupied Bandwidth                                                                                                                | ±0.0196%                  |
| Maximum Conducted Output Power                                                                                                                | ±0.686 dB                 |
| Maximum Power Spectral Density Level                                                                                                          | ±0.743 dB                 |
| Conducted Band-edge Compliance                                                                                                                | ±1.328 dB                 |
| Conducted Unwanted Emissions In Non-restricted<br>Frequency Bands                                                                             | ±0.746 dB (9 kHz ~ 1 GHz) |
|                                                                                                                                               | ±1.328dB (1 GHz ~ 26 GHz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                           |

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

|          |             |
|----------|-------------|
| EUT Name | Intel BE200 |
| Model    | BE200NGW    |

|                      |                                       |
|----------------------|---------------------------------------|
| Frequency Range:     | 2402 MHz to 2480 MHz                  |
| Type of Modulation:  | GFSK                                  |
| Data Rates:          | 1Mbps                                 |
| Normal Test Voltage: | DC 20V powered by an external adapter |

### 5.2. CHANNEL LIST

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 2402            | 11      | 2424            | 22      | 2446            | 33      | 2468            |
| 1       | 2404            | 12      | 2426            | 23      | 2448            | 34      | 2470            |
| 2       | 2406            | 13      | 2428            | 24      | 2450            | 35      | 2472            |
| 3       | 2408            | 14      | 2430            | 25      | 2452            | 36      | 2474            |
| 4       | 2410            | 15      | 2432            | 26      | 2454            | 37      | 2476            |
| 5       | 2412            | 16      | 2434            | 27      | 2456            | 38      | 2478            |
| 6       | 2414            | 17      | 2436            | 28      | 2458            | 39      | 2480            |
| 7       | 2416            | 18      | 2438            | 29      | 2460            | /       | /               |
| 8       | 2418            | 19      | 2440            | 30      | 2462            | /       | /               |
| 9       | 2420            | 20      | 2442            | 31      | 2464            | /       | /               |
| 10      | 2422            | 21      | 2444            | 32      | 2466            | /       | /               |

### 5.3. MAXIMUM POWER

For BT0:

| Test Mode | Frequency (MHz) | Channel Number | Maximum Peak Output Power (dBm) |
|-----------|-----------------|----------------|---------------------------------|
| LE 1M     | 2402 ~ 2480     | 0-39[40]       | 14.45                           |

#### 5.4. TEST CHANNEL CONFIGURATION

| Test Mode | Test Channel                                                  | Frequency                    |
|-----------|---------------------------------------------------------------|------------------------------|
| LE 1M     | CH 0(Low Channel), CH 19(MID Channel),<br>CH 39(High Channel) | 2402 MHz, 2440 MHz, 2480 MHz |

#### 5.5. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band |                         |                             |         |         |
|--------------------------------------------------------------------|-------------------------|-----------------------------|---------|---------|
| Test Software Version                                              |                         | DRTU                        |         |         |
| Modulation Type                                                    | Transmit Antenna Number | Test Software setting value |         |         |
|                                                                    |                         | CH 0                        | CH 19   | CH 39   |
| GFSK(1Mbps)                                                        | BT0                     | default                     | default | default |

#### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

| Antenna | Frequency (MHz) | Antenna Type | MAX Antenna Gain (dBi) |
|---------|-----------------|--------------|------------------------|
| BT0     | 2402-2480       | PIFA Antenna | 2.79                   |

Note: Equipment with two diversity BT antennas but only one antenna active at any moment in time.

| Test Mode | Transmit and Receive Mode                   | Description                                                |
|-----------|---------------------------------------------|------------------------------------------------------------|
| LE 1M     | <input checked="" type="checkbox"/> 1TX,1RX | Antenna BT0 can be used as transmitting/receiving antenna. |

Note: 1. The value of the antenna gain was declared by customers.

2. The antenna can not transmit simultaneously.

## 5.7. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

| Item | Equipment | Brand Name | Model Name | Remark |
|------|-----------|------------|------------|--------|
| /    | /         | /          | /          | /      |


### I/O CABLES

| Cable No | Port | Connector Type | Cable Type | Cable Length(m) | Remarks |
|----------|------|----------------|------------|-----------------|---------|
| /        | /    | /              | /          | /               | /       |

### ACCESSORIES

| Item | Accessory | Brand Name | Model Name | Description |
|------|-----------|------------|------------|-------------|
| /    | /         | /          | /          | /           |

### SETUP DIAGRAM FOR TESTS



Note: AC Adaptor only use for AC POWER LINE CONDUCTED EMISSION test

## 6. MEASURING EQUIPMENT AND SOFTWARE USED

| R&S TS 8997 Test System        |              |                         |                  |              |              |
|--------------------------------|--------------|-------------------------|------------------|--------------|--------------|
| Equipment                      | Manufacturer | Model No.               | Serial No.       | Last Cal.    | Due. Date    |
| Power sensor, Power Meter      | R&S          | OSP120                  | 100921           | Dec.26,2025  | Dec.25,2026  |
| Vector Signal Generator        | R&S          | SMBV100A                | 261637           | Sep.12, 2025 | Sep.11, 2026 |
| Signal Generator               | R&S          | SMB100A                 | 178553           | Sep.12, 2025 | Sep.11, 2026 |
| Signal Analyzer                | R&S          | FSV40                   | 101118           | Sep.12, 2025 | Sep.11, 2026 |
| Software                       |              |                         |                  |              |              |
| Description                    |              | Manufacturer            | Name             |              | Version      |
| For R&S TS 8997 Test System    |              | Rohde & Schwarz         | EMC 32           |              | 10.60.10     |
| Tonsend RF Test System         |              |                         |                  |              |              |
| Equipment                      | Manufacturer | Model No.               | Serial No.       | Last Cal.    | Due. Date    |
| Wireless Connectivity Tester   | R&S          | CMW270                  | 1201.0002N75-102 | Sep.12, 2025 | Sep.11, 2026 |
| PXA Signal Analyzer            | Keysight     | N9030A                  | MY55410512       | Sep.12, 2025 | Sep.11, 2026 |
| MXG Vector Signal Generator    | Keysight     | N5182B                  | MY56200284       | Sep.12, 2025 | Sep.11, 2026 |
| MXG Vector Signal Generator    | Keysight     | N5172B                  | MY56200301       | Sep.12, 2025 | Sep.11, 2026 |
| DC power supply                | TSSTAKASAGO  | ZX-400L                 | 409150160137     | Sep.12, 2025 | Sep.11, 2026 |
| Temperature & Humidity Chamber | SANMOOD      | SG-80-CC-2              | 2088             | Sep.12, 2025 | Sep.11, 2026 |
| Attenuator                     | Aglient      | 8495B                   | 2814a12853       | Sep.12, 2025 | Sep.11, 2026 |
| RF Control Unit                | Tonscend     | JS0806-2                | 23B80620666      | Dec.26,2025  | Dec.25,2026  |
| Software                       |              |                         |                  |              |              |
| Description                    | Manufacturer | Name                    |                  |              | Version      |
| Tonsend SRD Test System        | Tonsend      | JS1120-3 RF Test System |                  |              | V3.2.22      |

| Conducted Emissions                   |              |           |              |              |              |
|---------------------------------------|--------------|-----------|--------------|--------------|--------------|
| Equipment                             | Manufacturer | Model No. | Serial No.   | Last Cal.    | Due Date     |
| EMI Test Receiver                     | R&S          | ESR3      | 101961       | Sep.12, 2025 | Sep.11, 2026 |
| Two-Line V-Network                    | R&S          | ENV216    | 101983       | Sep.12, 2025 | Sep.11, 2026 |
| Software                              |              |           |              |              |              |
| Description                           |              |           | Manufacturer | Name         | Version      |
| Test Software for Conducted Emissions |              |           | Farad        | EZ-EMC       | Ver. UL-3A1  |

| Radiated Emissions                   |              |                                     |               |               |              |
|--------------------------------------|--------------|-------------------------------------|---------------|---------------|--------------|
| Equipment                            | Manufacturer | Model No.                           | Serial No.    | Last Cal.     | Due Date     |
| MXE EMI Receiver                     | KESIGHT      | N9038A                              | MY56400036    | Sep.12, 2025  | Sep.11, 2026 |
| Hybrid Log Periodic Antenna          | TDK          | HLP-3003C                           | 130960        | June 28, 2024 | June.27 2027 |
| Preamplifier                         | HP           | 8447D                               | 2944A09099    | Sep.12, 2025  | Sep.11, 2026 |
| EMI Measurement Receiver             | R&S          | ESR26                               | 101377        | Sep.12, 2025  | Sep.11, 2026 |
| Horn Antenna                         | TDK          | HRN-0118                            | 130940        | Dec.10, 2024  | Dec.11, 2027 |
| Preamplifier                         | TDK          | PA-02-0118                          | TRS-305-00067 | Sep.12, 2025  | Sep.11, 2026 |
| Horn Antenna                         | Schwarzbeck  | BBHA9170                            | 697           | Jun 30, 2024  | Jun 29, 2027 |
| Preamplifier                         | TDK          | PA-02-2                             | TRS-307-00003 | Sep.12, 2025  | Sep.11, 2026 |
| Preamplifier                         | TDK          | PA-02-3                             | TRS-308-00002 | Sep.12, 2025  | Sep.11, 2026 |
| Loop antenna                         | Schwarzbeck  | 1519B                               | 00008         | Dec.09, 2024  | Dec.08, 2027 |
| High Pass Filter                     | Wi           | WHKX10-2700-3000-18000-40SS         | 23            | Sep.12, 2025  | Sep.11, 2026 |
| Band Reject Filter                   | Wainwright   | WRCJV8-2350-2400-2483.5-2533.5-40SS | 4             | Sep.12, 2025  | Sep.11, 2026 |
| Software                             |              |                                     |               |               |              |
| Description                          |              |                                     | Manufacturer  | Name          | Version      |
| Test Software for Radiated Emissions |              |                                     | Farad         | EZ-EMC        | Ver. UL-3A1  |

| Other Instrument           |              |           |            |              |              |
|----------------------------|--------------|-----------|------------|--------------|--------------|
| Equipment                  | Manufacturer | Model No. | Serial No. | Last Cal.    | Due Date     |
| Temperature humidity probe | OMEGA        | ITHX-SD-5 | 18470007   | Sep.16, 2025 | Sep.15, 2026 |
| Barometer                  | Yiyi         | Baro      | N/A        | Sep.19, 2025 | Sep.18, 2026 |
| Attenuator                 | Agilent      | 8495B     | 2814a12853 | Sep.12, 2025 | Sep.11, 2026 |

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

| FCC 47 CFR Part15 (15.247) Subpart C |                           |                  |                       |
|--------------------------------------|---------------------------|------------------|-----------------------|
| Section                              | Test Item                 | Limit            | Frequency Range (MHz) |
| FCC 47 CFR 15.247(b)(3)              | Peak Conduct Output Power | 1 watt or 30 dBm | 2400-2483.5           |

#### TEST PROCEDURE

##### **Refer to ANSI C63.10-2020+Cor 1-2023 clause 11.9.1.2:**

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.


##### **Refer to ANSI C63.10-2020+Cor 1-2023 clause 11.9.2.3.1:**

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |        |                   |        |
|---------------------|--------|-------------------|--------|
| Temperature         | 24.5°C | Relative Humidity | 59.6%  |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 20V |

#### TEST DATE / ENGINEER

|           |              |         |             |
|-----------|--------------|---------|-------------|
| Test Date | Feb 25, 2026 | Test By | Bairong Liu |
|-----------|--------------|---------|-------------|

#### TEST RESULTS

Please refer to section "Test Data" - Appendix A

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to FCC 47 CFR §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz |                                    |                                      |         |
|--------------------------------------------------------------------------|------------------------------------|--------------------------------------|---------|
| Frequency Range (MHz)                                                    | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m |         |
|                                                                          |                                    | Quasi-Peak                           |         |
| 30 - 88                                                                  | 100                                | 40                                   |         |
| 88 - 216                                                                 | 150                                | 43.5                                 |         |
| 216 - 960                                                                | 200                                | 46                                   |         |
| Above 960                                                                | 500                                | 54                                   |         |
| Above 1000                                                               | 500                                | Peak                                 | Average |
|                                                                          |                                    | 74                                   | 54      |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz |                                   |                               |
|------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Frequency (MHz)                                                              | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490                                                                  | 2400/F(kHz)                       | 300                           |
| 0.490-1.705                                                                  | 24000/F(kHz)                      | 30                            |
| 1.705-30.0                                                                   | 30                                | 30                            |

ISED General field strength limits at frequencies below 30 MHz

| Table 6 – General field strength limits at frequencies below 30 MHz |                                          |                          |
|---------------------------------------------------------------------|------------------------------------------|--------------------------|
| Frequency                                                           | Magnetic field strength (H-Field) (uA/m) | Measurement distance (m) |
| 9 - 490 kHz <sup>Note 1</sup>                                       | 6.37/F (F in kHz)                        | 300                      |
| 490 - 1705 kHz                                                      | 63.7/F (F in kHz)                        | 30                       |
| 1.705 - 30 MHz                                                      | 0.08                                     | 30                       |

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

| MHz                 | MHz                   | GHz           |
|---------------------|-----------------------|---------------|
| 0.090 - 0.110       | 149.9 - 150.05        | 9.0 - 9.2     |
| 0.495 - 0.505       | 156.52475 - 156.52525 | 9.3 - 9.5     |
| 2.1735 - 2.1905     | 156.7 - 156.9         | 10.6 - 12.7   |
| 3.020 - 3.026       | 162.0125 - 167.17     | 13.25 - 13.4  |
| 4.125 - 4.128       | 167.72 - 173.2        | 14.47 - 14.6  |
| 4.17725 - 4.17775   | 240 - 285             | 15.35 - 16.2  |
| 4.20725 - 4.20775   | 322 - 335.4           | 17.7 - 21.4   |
| 5.677 - 5.683       | 399.9 - 410           | 22.01 - 23.12 |
| 6.215 - 6.218       | 608 - 614             | 23.6 - 24.0   |
| 6.26775 - 6.26825   | 960 - 1427            | 31.2 - 31.8   |
| 6.31175 - 6.31225   | 1435 - 1626.5         | 36.43 - 36.5  |
| 8.291 - 8.294       | 1645.5 - 1646.5       | Above 38.6    |
| 8.362 - 8.366       | 1660 - 1710           |               |
| 8.37625 - 8.38675   | 1718.8 - 1722.2       |               |
| 8.41425 - 8.41475   | 2200 - 2300           |               |
| 12.29 - 12.293      | 2310 - 2390           |               |
| 12.51975 - 12.52025 | 2483.5 - 2500         |               |
| 12.57675 - 12.57725 | 2655 - 2900           |               |
| 13.36 - 13.41       | 3260 - 3267           |               |
| 16.42 - 16.423      | 3332 - 3339           |               |
| 16.69475 - 16.69525 | 3345.8 - 3358         |               |
| 16.80425 - 16.80475 | 3500 - 4400           |               |
| 25.5 - 25.67        | 4500 - 5150           |               |
| 37.5 - 38.25        | 5350 - 5460           |               |
| 73 - 74.6           | 7250 - 7750           |               |
| 74.8 - 75.2         | 8025 - 8500           |               |
| 108 - 138           |                       |               |

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

| MHz                      | MHz                 | MHz           | GHz              |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110              | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| <sup>1</sup> 0.495-0.505 | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905            | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128              | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.17725-4.17775          | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.20725-4.20775          | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218              | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825          | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225          | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294              | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366              | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675          | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475          | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293             | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025        | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725        | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41              |                     |               |                  |

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

**TEST PROCEDURE**

Below 30 MHz

The setting of the spectrum analyzer

|       |                                                                  |
|-------|------------------------------------------------------------------|
| RBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto                                                             |

1. The testing follows the guidelines in ANSI C63.10-2020+Cor 1-2023 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

|          |          |
|----------|----------|
| RBW      | 120 kHz  |
| VBW      | 300 kHz  |
| Sweep    | Auto     |
| Detector | Peak/QP  |
| Trace    | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2020+Cor 1-2023 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

|          |                                |
|----------|--------------------------------|
| RBW      | 1 MHz                          |
| VBW      | PEAK: 3 MHz<br>AVG: see note 6 |
| Sweep    | Auto                           |
| Detector | Peak                           |
| Trace    | Max hold                       |

1. The testing follows the guidelines in ANSI C63.10-2020+Cor 1-2023 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All antennas and modes have been tested, but only the worst data was recorded in the report.
5.  $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All antennas and have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All antennas and modes have been tested, but only the worst data was recorded in the report.


## **TEST SETUP**



Below 1 GHz and above 30 MHz



Above 1GHz



#### **TEST ENVIRONMENT**

|                     |        |                   |        |
|---------------------|--------|-------------------|--------|
| Temperature         | 22.3℃  | Relative Humidity | 58.6%  |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 20V |


#### **TEST DATE / ENGINEER**

|           |              |         |             |
|-----------|--------------|---------|-------------|
| Test Date | Feb 10, 2026 | Test By | Stipe Zheng |
|-----------|--------------|---------|-------------|

## TEST RESULTS


### 8.1. RESTRICTED BANDEDGE-ANT BT0

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2402   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2374.850        | 12.36          | 31.31          | 43.67           | 74.00          | 30.33       | peak   |
| 2   | 2390.000        | 10.31          | 31.24          | 41.55           | 74.00          | 32.45       | peak   |

|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2402   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2356.540        | 12.87          | 31.4           | 44.27           | 74.00          | 29.73       | peak   |
| 2   | 2390.000        | 10.02          | 31.24          | 41.26           | 74.00          | 32.74       | peak   |

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2480   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 10.89          | 31.42          | 42.31           | 74.00          | 31.69       | peak   |
| 2   | 2492.722        | 13.11          | 31.52          | 44.63           | 74.00          | 29.37       | peak   |


|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2480   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 9.49           | 31.42          | 40.91           | 74.00          | 33.09       | peak   |
| 2   | 2491.522        | 13.01          | 31.51          | 44.52           | 74.00          | 29.48       | peak   |


## 8.2. SPURIOUS EMISSIONS-ANT BT0 (30 MHZ~1 GHZ)

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2402   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 35.300          | 40.44          | -16.97         | 23.47           | 40.00          | 16.53       | QP     |
| 2   | 51.367          | 31.68          | -15.24         | 16.44           | 40.00          | 23.56       | QP     |
| 3   | 61.510          | 31.49          | -15.72         | 15.77           | 40.00          | 24.23       | QP     |
| 4   | 110.462         | 31.43          | -16.05         | 15.38           | 43.50          | 28.12       | QP     |
| 5   | 191.405         | 32.98          | -17.68         | 15.30           | 43.50          | 28.20       | QP     |
| 6   | 287.457         | 32.17          | -14.07         | 18.10           | 46.00          | 27.90       | QP     |


|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2402   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 40.671          | 45.72          | -15.88         | 29.84           | 40.00          | 10.16       | QP     |
| 2   | 62.994          | 40.92          | -15.81         | 25.11           | 40.00          | 14.89       | QP     |
| 3   | 91.474          | 39.27          | -18.25         | 21.02           | 43.50          | 22.48       | QP     |
| 4   | 283.852         | 30.56          | -14.08         | 16.48           | 46.00          | 29.52       | QP     |
| 5   | 355.501         | 31.94          | -11.75         | 20.19           | 46.00          | 25.81       | QP     |
| 6   | 635.746         | 28.65          | -7.36          | 21.29           | 46.00          | 24.71       | QP     |


### 8.3. SPURIOUS EMISSIONS-ANT BT0

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2402   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4134.800        | 46.12          | -3.67          | 42.45           | 74.00          | 31.55       | peak   |
| 2   | 4859.000        | 45.67          | -1.7           | 43.97           | 74.00          | 30.03       | peak   |
| 3   | 8993.400        | 42.01          | 6.57           | 48.58           | -              | -           | peak   |
| 4   | 11438.000       | 42.22          | 7.41           | 49.63           | 74.00          | 24.37       | peak   |
| 5   | 12311.800       | 42.15          | 7.82           | 49.97           | 74.00          | 24.03       | peak   |
| 6   | 15546.900       | 40.95          | 8.05           | 49.00           | 74.00          | 25.00       | peak   |

|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2402   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4121.200        | 46.86          | -3.79          | 43.07           | 74.00          | 30.93       | peak   |
| 2   | 4830.100        | 46.26          | -2.07          | 44.19           | 74.00          | 29.81       | peak   |
| 3   | 7380.100        | 43.79          | 2.71           | 46.50           | 74.00          | 27.50       | peak   |
| 4   | 9156.600        | 42.12          | 6.93           | 49.05           | 74.00          | 24.95       | peak   |
| 5   | 11417.600       | 41.10          | 7.6            | 48.70           | 74.00          | 25.30       | peak   |
| 6   | 12131.600       | 40.95          | 7.73           | 48.68           | 74.00          | 25.32       | peak   |

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2440   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4315.000        | 46.12          | -3.16          | 42.96           | 74.00          | 31.04       | peak   |
| 2   | 5000.100        | 45.29          | -1.55          | 43.74           | 74.00          | 30.26       | peak   |
| 3   | 7414.100        | 44.29          | 2.57           | 46.86           | 74.00          | 27.14       | peak   |
| 4   | 9408.200        | 42.12          | 6.32           | 48.44           | 74.00          | 25.56       | peak   |
| 5   | 11449.900       | 42.75          | 7.29           | 50.04           | 74.00          | 23.96       | peak   |
| 6   | 12107.800       | 42.20          | 7.78           | 49.98           | 74.00          | 24.02       | peak   |

|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2440   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 3788.000        | 46.89          | 30.64          | 42.45           | 74.00          | 31.55       | peak   |
| 2   | 4558.100        | 46.70          | 31.99          | 43.88           | 74.00          | 30.12       | peak   |
| 3   | 7594.300        | 44.50          | 36.20          | 46.69           | 74.00          | 27.31       | peak   |
| 4   | 9044.400        | 41.92          | 38.86          | 48.92           | 74.00          | 25.08       | peak   |
| 5   | 11783.100       | 43.34          | 38.58          | 50.04           | 74.00          | 23.96       | peak   |
| 6   | 15601.300       | 39.43          | 38.99          | 47.70           | 74.00          | 26.30       | peak   |

|            |            |                 |        |
|------------|------------|-----------------|--------|
| Test Mode: | BLE 1M     | Frequency(MHz): | 2480   |
| Polarity:  | Horizontal | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4085.500        | 46.72          | -3.95          | 42.77           | 74.00          | 31.23       | peak   |
| 2   | 4843.700        | 45.83          | -1.84          | 43.99           | 74.00          | 30.01       | peak   |
| 3   | 7463.400        | 43.91          | 2.61           | 46.52           | 74.00          | 27.48       | peak   |
| 4   | 9381.000        | 42.26          | 6.47           | 48.73           | 74.00          | 25.27       | peak   |
| 5   | 11150.700       | 42.74          | 6.72           | 49.46           | 74.00          | 24.54       | peak   |
| 6   | 12685.800       | 41.88          | 8.02           | 49.90           | 74.00          | 24.10       | peak   |

|            |          |                 |        |
|------------|----------|-----------------|--------|
| Test Mode: | BLE 1M   | Frequency(MHz): | 2480   |
| Polarity:  | Vertical | Test Voltage:   | DC 20V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 3975.000        | 46.55          | -4.52          | 42.03           | 74.00          | 31.97       | peak   |
| 2   | 4911.700        | 44.56          | -1.5           | 43.06           | 74.00          | 30.94       | peak   |
| 3   | 7517.800        | 43.85          | 2.6            | 46.45           | 74.00          | 27.55       | peak   |
| 4   | 9404.800        | 42.18          | 6.35           | 48.53           | 74.00          | 25.47       | peak   |
| 5   | 11174.500       | 42.09          | 6.71           | 48.80           | 74.00          | 25.20       | peak   |
| 6   | 12527.700       | 41.20          | 8.15           | 49.35           | 74.00          | 24.65       | peak   |

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass

## 9.1. APPENDIX A: MAXIMUM CONDUCTED OUTPUT POWER

### 9.1.1. Test Result-Ant BT0

| Test Mode | Antenna | Frequency [MHz] | Conducted Peak Power[dBm] | Conducted Limit[dBm] | EIRP[dBm] | EIRP Limit[dBm] | Verdict |
|-----------|---------|-----------------|---------------------------|----------------------|-----------|-----------------|---------|
| BLE_1M    | Ant1    | 2402            | 14.27                     | ≤30                  | 17.06     | ≤36             | PASS    |
|           |         | 2440            | 14.30                     | ≤30                  | 17.09     | ≤36             | PASS    |
|           |         | 2480            | 14.45                     | ≤30                  | 17.24     | ≤36             | PASS    |

**END OF REPORT**