

Test Report Number:	LCZE25110045	Total Page(s):
Applicant Name:	Guangdong Shenlizhuo Technology Co., LTD.	
Applicant Address:	Building A, No. 5 Dongdi Road, Yuxiang Industrial Zone, Henglan Town, ZHONGSHAN CITY Guangdong	
Product Name:	Remote Controller	
Model / Type Reference:	SLZ-FS2.4G-H19	
FCC ID:	2BSZT-SLZ-FS-H19	
Date of Issue:	2025-11-13	
Testing Laboratory:	LCTECH Guangdong Testing Services Co., Ltd. 2/F., Technology and Enterprise Development Center, Guangyuan Road, Xiaolan, Zhongshan, Guangdong, China	
Test Specification:	KDB 447498 D04 Interim General RF Exposure Guidance v01	
Test Result:	Passed	
Compiled by:	Reviewed by:	
2025-11-13 Rex He		2025-11-13 Tension Li
<i>Date</i>	<i>Name</i>	<i>Signature</i>
		<i>Date</i>
		<i>Name</i>
		<i>Signature</i>
Remark:		
N/A		
The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore.		

RF Exposure evaluation

According to 447498 D04 Interim General RF Exposure Guidance v01

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$e_{irp} = p_t \times g_t = (E \cdot d)^2 / 30$$

where: p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((dBuV/m)/20)/10}$

d = measurement distance in meters (m)---3m $S_{opt} = (E \cdot d)^2 / 30 \times g_t$

Frequency(MHz)	Field Strength (dBuV/m)	eirp(mW)	limit (mW)	min. distance (cm)
2402	91.13	0.389	3	0.50

Then SAR evaluation is not required