

RF Exposure Evaluation

FCC ID:2BT2L-PB68

Report No..... : ZHT-250812137W01-2

Product..... : ZENS GLASSIA POWER BANK

Trademark..... : ZENS

Model(s)..... : PB68-5K

Model Difference..... : The product has different colored and patterns shells, and this test used
: EUT with white shells. the test data of EUT with white shell can represent
the remaining colors.

Applicant..... : ZENSBUDS LIMITED

Address..... : FLAT/RM 15 7/F FABRICO INDUSTRIAL BLDG.78-84 KWAI CHEONG
RD. KWAI CHUNG NEW TERRITORIES, Hong Kong, China

Manufacturer..... : ZENSBUDS LIMITED

Address..... : FLAT/RM 15 7/F FABRICO INDUSTRIAL BLDG.78-84 KWAI CHEONG
RD. KWAI CHUNG NEW TERRITORIES, Hong Kong, China

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai
Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Aug. 12, 2025

Date of Test(s)..... : Aug. 12, 2025 to Sept. 1, 2025

Date of Issue..... : Jan. 8, 2026

Test Standard(s)..... : KDB 680106 D01 Wireless Power Transfer v04

In the configuration tested, the EUT complied with the standards specified above.

Prepared by

Leon Li

Leon Li/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director

Approved by:

Levi Lee

Levi Lee/ Manager

Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.

Table of Contents

	Page
1. GENERAL INFORMATION	3
1.1. GENERAL DESCRIPTION OF EUT	3
1.2. Test Modes	4
1.3. Auxiliary equipment	4
2. RF EXPOSURE TEST	5
2.1. Measuring Standard	5
2.2. Requirements	5
2.3. Limits	5
2.4. Test Setup	6
2.5. Test Procedure	7
2.6. MEASUREMENT UNCERTAINTY	7
2.7. Test Instruments list	8
2.8. Test Result	8
2.9. Test Photos	11



1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	ZENS GLASSIA POWER BANK
Test Model No.:	PB68-5K
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	111-205kHz, 360kHz
Modulation type:	ASK
Antenna Type:	Coil Antenna
Antenna gain:	0dBi
Ratings	USB-C Input: 5 V---3 A, 9 V---2 A, 12 V---1.5 A (18W Max) USB-C Output: 5 V---3 A, 9 V---2.22 A, 12 V---1.67 A (20W Max) Battery capacity: 5000mAh/ 3.85V/ 19.25Wh Wireless Output: 5W/7.5W/10W/15W Charge and Discharge Simultaneously: USB-C Input 5 V---3 A + Wireless Output:5W USB-C Input 9 V---2 A + Wireless Output:5W USB-C Input 9 V---2 A + Wireless Output:7.5W USB-C Input 9 V---2 A + Wireless Output:10W USB-C Input: 9 V---2 A + Wireless Output:15W
Sample Number:	250812137YP001
Remark:The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	



1.2. TEST MODES

Test Modes:

Mode 1	Mobile phone charging (111-205kHz: Battery Status:≤1%)
Mode 2	Mobile phone charging (111-205kHz: Battery Status:50%)
Mode 3	Mobile phone charging (111-205kHz: Battery Status:≥98%)
Mode 4	Mobile phone charging (360kHz: Battery Status:≤1%)
Mode 5	Mobile phone charging (360kHz: Battery Status:50%)
Mode 6	Mobile phone charging (360kHz: Battery Status:≥98%)
Mode 7	Standby

Note: All modes were tested, only the worst-case was recorded in the report. Mode 1 is the worst mode.

1.3. AUXILIARY EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	AC Adapter	Huizhou Jinhu Industrial Development Co., Ltd.	VCBAJACH	/	AE
E-2	Mobile phone	Xiaomi Communications Co., Ltd.	Xiaomi 13	/	AE
E-3	Mobile phone	Apple Inc.	iPhone 15 Pro	/	AE

2. RF EXPOSURE TEST

2.1. MEASURING STANDARD

KDB 680106 D01 Wireless Power Transfer v04

2.2. REQUIREMENTS

According to the item 5 of KDB 680106 D01 v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

Requirements of section 3 of KDB 680106 D01	Yes/ No	Description
Mobile Device and Portable Device Configurations	Yes	Portable Device
Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz	Yes	The device operate in the frequency range Cellphone: 111-205kHz, 360kHz
RF Exposure compliance may be ensured only for a minimum conditions at smaller distances can still be considered unlikely.separation distance that is greater than 20 cm, while use	Yes	The EUT H-field and E-field strengths at 0-20 cm surrounding the device.

2.3. LIMITS

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)


Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30


F=frequency in MHz
 * =Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.4. TEST SETUP

For mobile exposure conditions:



For portable exposure conditions:



2.5. TEST PROCEDURE

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (0-20 cm from all sides and 0-20 cm from the top) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

Remark: The EUT's test position A, B, C, D, E and F is valid for the E and H field measurements.

2.6. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	E-field	14.72%
2	H-field	15.48%
3	Temperature	$\pm 0.5^{\circ}\text{C}$
4	Humidity	$\pm 2\%$

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is included

2.7. TEST INSTRUMENTS LIST

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-8H3D+E3D V2	3127	September 09, 2025	September 08, 2026
				September 10, 2024	September 09, 2025
Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-DASV2	3121	September 09, 2025	September 08, 2026
				September 10, 2024	September 09, 2025



2.8. TEST RESULT

According to the formula:

Assessed Distance (cm)	Test Mode	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)	Test Position F (A/m)	50% Limits (A/m)	Limits (A/m)	test result
0	Mode 1	0.46	0.39	0.42	0.39	0.42	0.45	0.815	1.63	PASS
Measured Distance (cm)	Test Mode	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)	Test Position F (A/m)	50% Limits (A/m)	Limits (A/m)	test result
2	Mode 1	0.35	0.38	0.30	0.37	0.35	0.36	0.815	1.63	PASS
4	Mode 1	0.28	0.28	0.26	0.27	0.29	0.28	0.815	1.63	PASS
6	Mode 1	0.22	0.24	0.22	0.16	0.20	0.26	0.815	1.63	PASS
8	Mode 1	0.18	0.16	0.17	0.13	0.16	0.21	0.815	1.63	PASS
10	Mode 1	0.13	0.06	0.15	0.11	0.09	0.15	0.815	1.63	PASS
12	Mode 1	0.12	0.05	0.04	0.11	0.1	0.14	0.815	1.63	PASS
14	Mode 1	0.12	0.13	0.13	0.14	0.04	0.08	0.815	1.63	PASS
16	Mode 1	0.08	0.14	0.09	0.1	0.1	0.06	0.815	1.63	PASS
18	Mode 1	0.1	0.03	0.05	0.1	0.14	0.13	0.815	1.63	PASS
20	Mode 1	0.08	0.06	0.09	0.13	0.09	0.09	0.815	1.63	PASS

The formula for the magnetic field strength at a distance r from the coil is

$$H = I / (2\pi r) * \mu$$

H is A/m

I is the current intensity


μ is the permeability, and its value depends on the medium.

The other parameters are fixed, so H is inversely proportional to r.

X is the distance from the test point to the center of the coil circle.


$$B = \frac{\mu_0 I R^2}{2(R^2 + X^2)^{3/2}}$$

Top & Bottom Side:




$$B = \frac{\mu_0 * I * N * R^2}{2 * (R^2 + x^2)^{3/2}}$$

Front, Left, Right & Rear Side:



$$B = \frac{\mu_0 * I * N}{2 * x}$$

Symbol	Definition
B	means H-field value. (Unit: A/m)
μ_0	is space permeability, $\mu_0=4\pi*10^{-7}$.
I	a current element passing through a coil. (Unit: A)
R	the distance from the center point of the wireless charging device to other edges. $R=39/2=19.5\text{mm}=0.0195\text{m}$
X	means the evaluated point to the coil center. (For top & bottom side: $x=\text{test distance}$; For other side: $x=\text{test distance}+R$)
N	Number of turns, according to provided "Antenna specification" files: $N=11$



2.9 Test Photos







***** END OF REPORT *****