FCC TEST REPORT

FCC ID: 2BT6B-B12

On Behalf of

HONGKONG BAOYITONG LIMITED

Open-Ear Headphones

Model No.: B12

Prepared for	:	HONGKONG BAOYITONG LIMITED
Address	:	RM 4C, 12/F TUNG LEE IND BLDG, 9 LAI YIP ST, KWUN TONG, HONG KONG

Prepared By	:	Shenzhen PSI Testing Co., Ltd.
Address	:	1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number	:	psi2606095-C01-R02
Date of Receipt	:	June 11, 2026
Date of Test	:	June 11, 2026–June 25, 2026
Date of Report	:	June 25, 2026
Version Number	:	V0

TABLE OF CONTENTS

Description **Page**

1. Summary Of Standards And Results ---------- 6
1.1. Description of Standards and Results ---------- 6
2. General Information ---------- 7
2.1. Description of Device (EUT) ---------- 7
2.2. Accessories of Device (EUT) ---------- 8
2.3. Tested Supporting System Details ---------- 8
2.4. Block Diagram of Connection Between EUT and Simulators ---------- 8
2.5. Test Mode Description ---------- 9
2.6. Software test version and power setting information ---------- 9
2.7. Test Conditions ---------- 9
2.8. Test Facility ---------- 10
2.9. Measurement Uncertainty ---------- 10
2.10. Test Equipment List ---------- 11
3. Spurious Emission ---------- 12
3.1. Test Limits ---------- 12
3.2. Block Diagram of Test setup ---------- 13
3.3. Test Procedure ---------- 14
3.4. Test Results ---------- 15
4. Power Line Conducted Emission ---------- 21
4.1. Test Limits ---------- 21
4.2. Test Procedure ---------- 21
4.3. Test Setup ---------- 21
4.4. Test Results ---------- 22
5. Out-of-band Emissions ---------- 25
5.1. Test Limits ---------- 25
5.2. Test Procedure ---------- 25
5.3. Test Setup ---------- 25
5.4. Test Results ---------- 25
6. Conducted Maximum Output Power ---------- 36
6.1. Test limits ---------- 36
6.2. Test Procedure ---------- 36
6.3. Test Setup ---------- 36
6.4. Test Results ---------- 36
7. Peak Power Spectral Density ---------- 43
7.1. Test limits ---------- 43
7.2. Test Procedure ---------- 43
7.3. Test Setup ---------- 43
7.4. Test Results ---------- 43
8. Occupied Bandwidth ---------- 47
8.1. Test limits ---------- 47
8.2. Test Procedure ---------- 47
8.3. Test Setup ---------- 47
8.4. Test Results ---------- 47
9. Band Edge Test ---------- 54
9.1. Test Limit ---------- 54
9.2. Block Diagram of Test Setup ---------- 54
9.3. Test Procedure ---------- 54
9.4. Test Results ---------- 55
10. Antenna Requirement ---------- 57

10.1. Standard Requirement ----------57
10.2. Results ----------57
11. Photos of test setup----------58
12. Photos of EUT----------58

TEST REPORT DECLARATION

Applicant	:	HONGKONG BAOYITONG LIMITED
Address	:	RM 4C, 12/F TUNG LEE IND BLDG, 9 LAI YIP ST, KWUN TONG, HONG KONG
Manufacturer	:	HONGKONG BAOYITONG LIMITED
Address	:	RM 4C, 12/F TUNG LEE IND BLDG, 9 LAI YIP ST, KWUN TONG, HONG KONG
EUT Description	:	Open-Ear Headphones
		(A) Model No. : B12
		(B) Trademark : TuneFlux

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2020+Cor.1-2023

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....…..:	Felix Pang Test Engineer	Felix Pang
Approved by (name + signature)…....:	Simple Guan Project Manager	Simple Guan
Date of issue……..:	June 25, 2026	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 25, 2026	Initial released Issue	Felix Pang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2020+Cor.1-2023	P
6dB Bandwidth	FCC PART 15:15.247(a)(2), ANSI C63.10:2020+Cor.1-2023	P
Output Power	FCC Part 15: 15.247(b)(3), ANSI C63.10:2020+Cor.1-2023	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d), ANSI C63.10:2020+Cor.1-2023	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10:2020+Cor.1-2023	P
Power Spectral Density	FCC PART 15:15.247(e), ANSI C63.10:2020+Cor.1-2023	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10:2020+Cor.1-2023	P
Antenna Requirement	FCC Part 15: 15.203	P

Note:
1. P is an abbreviation for Pass.
2. F is an abbreviation for Fail.
3. N/A is an abbreviation for Not Applicable.
4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.
5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.

2. General Information

2.1. Description of Device (EUT)

EUT Name	:	Open-Ear Headphones
Model No.	:	B12
Diff	:	N/A
Power supply	:	DC 5V from adapter, DC 3.7V from battery.
Radio Technology	:	Bluetooth V5.0 LE
Operation frequency	:	2402-2480MHz
Channel No.	:	40 channels
Channel Separation	:	2MHz
Data rate	:	1Mbps/2Mbps
Modulation	:	GFSK
Antenna Type	:	Internal antenna, Maximum Gain is 2.78dBi.
PMN	:	N/A
HVIN	:	N/A
Software version	:	N/A
Hardware version/FVIN	:	N/A
Note	:	Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.

2.2. Accessories of Device (EUT)

Accessories 1 : N/A

Manufacturer : N/A

Model : N/A

Rating : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	Adapter	Baseus	CCXFK65CC	AJ250501
2	Notebook PC	Dell	Latitude 3490	N/A

2.4. Block Diagram of Connection Between EUT and Simulators

Spurious Emission

Power Line Conducted Emission



RF



2.5. Test Mode Description

Keeping TX			
Mode	Data rate (Mbps)	Channel	Frequency(MHz)
GFSK Tx Mode	1	CH0	2402
	1	CH19	2440
	1	CH39	2480
GFSK Tx Mode	2	CH0	2402
	2	CH19	2440
	2	CH39	2480
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
CH0	2402	CH14	2430	CH28	2458
CH1	2404	CH15	2432	CH29	2460
CH2	2406	CH16	2434	CH30	2462
CH3	2408	CH17	2436	CH31	2464
CH4	2410	CH18	2438	CH32	2466
CH5	2412	CH19	2440	CH33	2468
CH6	2414	CH20	2442	CH34	2470
CH7	2416	CH21	2444	CH35	2472
CH8	2418	CH22	2446	CH36	2474
CH9	2420	CH23	2448	CH37	2476
CH10	2422	CH24	2450	CH38	2478
CH11	2424	CH25	2452	CH39	2480
CH12	2426	CH26	2454	--	--
CH13	2428	CH27	2456	--	--

2.6. Software test version and power setting information

Software testing version	FS381_PB3_1.5M.exe
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:

Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK Tx Mode 1Mbps/2Mpbs	CH0	2402	TX level is set as defaults value.
	CH19	2440	TX level is set as defaults value.
	CH39	2480	TX level is set as defaults value.

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission
Registration Number: 916281
Designation Number: CN1362

September 21, 2023 Certificated by IC
Registration Number: 31123
CAB identifier: CN0158

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Power Line Conducted Emissions Test	2.13dB
Radiation Emission test in 3m chamber(below 30MHz)	4.07dB
Radiation Emission test in 3m chamber(30MHz to 1GHz)	4.51dB
Radiation Emission test in 3m chamber(1GHz to 18GHz)	5.07dB
Radiation Emission test in 3m chamber(18GHz to 40GHz)	5.21dB
Radio Frequency	48.24KHz
Conducted RF Power	0.41dB
Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Duty Cycle	1%
Conducted-Spurious Emission	1.26dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.18	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV 216	102282	/	2025.12.18	1 Year
4.	L.I.S.N.#2	EMCO	3810-2	00094944	/	2025.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV40-N	101648	3.70	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LNPA_0118 G-50	SK2022032901	/	2025.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_1840 G-50	SK2019040302	/	2025.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2025.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P008	/	2025.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638	/	2025.12.18	1 Year
17.	Cable	SKET	Cable-RE-1	#02/#03	/	2025.12.18	1 Year
18.	Cable	SKET	Cable-RE-2	#01	/	2025.12.18	1 Year
19.	Cable	SKET	Cable-RE-3	#04	/	2025.12.18	1 Year
20.	Cable	SKET	Cable-CE-1	A-E-24	/	2025.12.18	1 Year
21.	6dB Attenuator	Schwarzbeck	DGA 9552N 6dB	CK4186	/	2025.12.18	1 Year
22.	Power meter	Agilent	E4419B	GB40202121	/	2025.12.18	1 Year
23.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.18	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EZ_EMC	Farad	PSI-3A1
CE	EZ_EMC	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

3. Spurious Emission

3.1. Test Limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

Note: The peak limit is 20 dB higher than the average limit.

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

3.2. Block Diagram of Test setup

a. In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



b. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



c. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2020+Cor.1-2023 on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

3.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz:					
Test Date	:	2026.06.19	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	GFSK mode			
Test Voltage	:	AC 120V/60Hz			
Test Results	:	**PASS**			
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.				

From 30MHz to 1000MHz:					
Test Date	:	2026.06.19	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	GFSK mode			
Test Voltage	:	AC 120V/60Hz			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of 1Mbps GFSK 2402MHz mode was listed in this report.				

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.5479	13.36	13.93	27.29	40.00	-12.71	QP
2 *	49.4460	14.49	13.76	28.25	40.00	-11.75	QP
3	58.3819	14.34	13.34	27.68	40.00	-12.32	QP
4	107.9823	16.18	11.80	27.98	43.50	-15.52	QP
5	145.4143	12.42	14.88	27.30	43.50	-16.20	QP
6	364.0999	14.86	16.85	31.71	46.00	-14.29	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	59.4405	12.94	13.28	26.22	40.00	-13.78	QP
2	121.4421	14.00	13.26	27.26	43.50	-16.24	QP
3	164.5465	12.27	14.79	27.06	43.50	-16.44	QP
4	250.6305	15.61	13.51	29.12	46.00	-16.88	QP
5	365.6993	12.82	16.88	29.70	46.00	-16.30	QP
6	487.7425	12.27	19.63	31.90	46.00	-14.10	QP

Note: Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:					
Test Date	:	2026.06.19	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	GFSK mode			
Test Voltage	:	AC 120V/60Hz			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.				

1Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	56.44	-13.25	43.19	74.00	-30.81	Peak
2	4804	V	49.10	-13.25	35.85	54.00	-18.15	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	58.17	-13.25	44.92	74.00	-29.08	Peak
6	4804	H	45.66	-13.25	32.41	54.00	-21.59	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	57.87	-12.98	44.89	74.00	-29.11	Peak
2	4880	V	50.20	-12.98	37.22	54.00	-16.78	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	58.20	-12.98	45.22	74.00	-28.78	Peak
6	4880	H	44.73	-12.98	31.75	54.00	-22.25	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	58.17	-12.70	45.47	74.00	-28.53	Peak
2	4960	V	49.60	-12.70	36.90	54.00	-17.10	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	54.74	-12.70	42.04	74.00	-31.96	Peak
6	4960	H	45.63	-12.70	32.93	54.00	-21.07	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit.							

2Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	57.48	-13.25	44.23	74.00	-29.77	Peak
2	4804	V	49.55	-13.25	36.30	54.00	-17.70	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	54.48	-13.25	41.23	74.00	-32.77	Peak
6	4804	H	48.07	-13.25	34.82	54.00	-19.18	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	60.27	-12.98	47.29	74.00	-26.71	Peak
2	4880	V	50.57	-12.98	37.59	54.00	-16.41	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	57.46	-12.98	44.48	74.00	-29.52	Peak
6	4880	H	46.94	-12.98	33.96	54.00	-20.04	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	59.62	-12.70	46.92	74.00	-27.08	Peak
2	4960	V	49.44	-12.70	36.74	54.00	-17.26	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	56.85	-12.70	44.15	74.00	-29.85	Peak
6	4960	H	44.85	-12.70	32.15	54.00	-21.85	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit.							

4. Power Line Conducted Emission

4.1. Test Limits

Frequency	Limits dB(μV)	
MHz	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2020+Cor.1-2023 on Conducted Emission Measurement.
The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup



4.4. Test Results

Test Date	:	2026.06.16	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	GFSK mode			
Test Voltage	:	AC 120V/60Hz			
Test Results	:	**PASS**			
Note:		1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of 1Mbps GFSK 2402MHz mode was listed in this report.			

Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1740	30.39	9.56	39.95	64.77	-24.82	QP
2	0.1740	20.51	9.56	30.07	54.77	-24.70	AVG
3	0.2260	31.35	9.40	40.75	62.60	-21.85	QP
4	0.2260	20.18	9.40	29.58	52.60	-23.02	AVG
5	0.2779	30.37	9.40	39.77	60.88	-21.11	QP
6	0.2779	19.44	9.40	28.84	50.88	-22.04	AVG
7	0.4660	29.33	9.60	38.93	56.58	-17.65	QP
8	0.4660	18.03	9.60	27.63	46.58	-18.95	AVG
9	0.7820	29.47	9.51	38.98	56.00	-17.02	QP
10	0.7820	18.69	9.51	28.20	46.00	-17.80	AVG
11 *	1.0140	29.21	9.80	39.01	56.00	-16.99	QP
12	1.0140	18.12	9.80	27.92	46.00	-18.08	AVG

Note: Level = Reading + Factor, Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2540	31.34	9.40	40.74	61.63	-20.89	QP
2	0.2540	20.54	9.40	29.94	51.63	-21.69	AVG
3	0.4620	29.18	9.59	38.77	56.66	-17.89	QP
4	0.4620	18.11	9.59	27.70	46.66	-18.96	AVG
5	0.5540	30.21	9.75	39.96	56.00	-16.04	QP
6	0.5540	18.59	9.75	28.34	46.00	-17.66	AVG
7	0.7780	29.83	9.82	39.65	56.00	-16.35	QP
8 *	0.7780	21.86	9.82	31.68	46.00	-14.32	AVG
9	0.8700	29.20	9.73	38.93	56.00	-17.07	QP
10	0.8700	18.35	9.73	28.08	46.00	-17.92	AVG
11	1.1300	29.38	9.57	38.95	56.00	-17.05	QP
12	1.1300	18.75	9.57	28.32	46.00	-17.68	AVG

Note: Level = Reading + Factor, Margin = Level - Limit

5. Out-of-band Emissions

5.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.

5.2. Test Procedure

ANSI C63.10:2020+Cor.1-2023 Section 11.11.1, Section 11.11.2, Section 11.11.3
Connect the transmitter ouput to spectrum analvzer using a low loss RF cable, and set the spectrum analvzerto RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting aremade of the in-band reference level, bandedge and out-of-band emissions.

5.3. Test Setup



5.4. Test Results

PASS.

The test results are listed in next pages.

Bandedge: Pass

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402.00	2399.015	-0.010	-46.143	-20.010	Pass
NVNT	ANT1	1Mbps	2480.00	2483.575	-0.945	-53.454	-20.945	Pass
NVNT	ANT1	2Mbps	2402.00	2399.965	-0.284	-33.427	-20.284	Pass
NVNT	ANT1	2Mbps	2480.00	2484.025	-1.176	-55.224	-21.176	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402



2_Bandedge_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Bandedge_NVNT_ANT1_1Mbps_2480



1_Reference_Level_NVNT_ANT1_2Mbps_2402

2_Bandedge_NVNT_ANT1_2Mbps_2402



1_Reference_Level_NVNT_ANT1_2Mbps_2480

2_Bandedge_NVNT_ANT1_2Mbps_2480



Spurious Emission: Pass

Condition	Antenna	Modulation	TX_Frequency (MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402.00	-0.010	-44.988	-20.010	Pass
NVNT	ANT1	1Mbps	2440.00	-0.537	-45.658	-20.537	Pass
NVNT	ANT1	1Mbps	2480.00	-0.945	-42.968	-20.945	Pass
NVNT	ANT1	2Mbps	2402.00	-0.284	-45.915	-20.284	Pass
NVNT	ANT1	2Mbps	2440.00	-0.771	-46.135	-20.771	Pass
NVNT	ANT1	2Mbps	2480.00	-1.176	-47.900	-21.176	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402



2_Spurious_Emission_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2440

2_Spurious_Emission_NVNT_ANT1_1Mbps_2440



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Spurious_Emission_NVNT_ANT1_1Mbps_2480



1_Reference_Level_NVNT_ANT1_2Mbps_2402

2_Spurious_Emission_NVNT_ANT1_2Mbps_2402



1_Reference_Level_NVNT_ANT1_2Mbps_2440

2_Spurious_Emission_NVNT_ANT1_2Mbps_2440



1_Reference_Level_NVNT_ANT1_2Mbps_2480

2_Spurious_Emission_NVNT_ANT1_2Mbps_2480



6. Conducted Maximum Output Power

6.1. Test limits

Please refer RSS-247 & FCC PART 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm).

6.2. Test Procedure

ANSI C63.10-2020+Cor.1-2023, section 11.9.1 Maximum peak conducted output power.

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

a) Set the RBW ≥ DTS bandwidth.

b) Set VBW ≥ [3 × RBW].

c) Set span ≥ [3 × RBW].

d) Sweep time = auto couple.

e) Detector = peak.

f) Trace mode = max hold.

g) Allow trace to fully stabilize.

h) Use peak marker function to determine the peak amplitude level.

6.3. Test Setup



6.4. Test Results

Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402.00	0.10	1.02	1000	Pass
NVNT	ANT1	1Mbps	2440.00	-0.30	0.93	1000	Pass
NVNT	ANT1	1Mbps	2480.00	-0.83	0.83	1000	Pass
NVNT	ANT1	2Mbps	2402.00	**0.21**	**1.05**	1000	Pass
NVNT	ANT1	2Mbps	2440.00	-0.22	0.95	1000	Pass
NVNT	ANT1	2Mbps	2480.00	-0.71	0.85	1000	Pass

Peak_Output_Power_NVNT_ANT1_1Mbps_2402



Peak_Output_Power_NVNT_ANT1_1Mbps_2440



Peak_Output_Power_NVNT_ANT1_1Mbps_2480



Peak_Output_Power_NVNT_ANT1_2Mbps_2402

Peak_Output_Power_NVNT_ANT1_2Mbps_2440



Peak_Output_Power_NVNT_ANT1_2Mbps_2480



Condition	Antenna	Rate	Frequency (MHz)	Dutycycle(%)	Duty_factor
NVNT	ANT1	1Mbps	2402.00	15.62	8.06
NVNT	ANT1	1Mbps	2440.00	12.90	8.89
NVNT	ANT1	1Mbps	2480.00	16.13	7.92
NVNT	ANT1	2Mbps	2402.00	12.50	9.03
NVNT	ANT1	2Mbps	2440.00	9.38	10.28
NVNT	ANT1	2Mbps	2480.00	9.68	10.14

Duty_Cycle_NVNT_ANT1_1Mbps_2402



Duty_Cycle_NVNT_ANT1_1Mbps_2440



Duty_Cycle_NVNT_ANT1_1Mbps_2480



Duty_Cycle_NVNT_ANT1_2Mbps_2402



Duty_Cycle_NVNT_ANT1_2Mbps_2440



Duty_Cycle_NVNT_ANT1_2Mbps_2480



7. Peak Power Spectral Density

7.1. Test limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz(Set the RBW to: 3 kHz≤RBW≤100 kHz.), VBW = 10kHz(Set the VBW≥3×RBW), span≥1.5×DTS bandwidth., detail see the test plot.
4. Record the max reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

7.3. Test Setup



7.4. Test Results

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm/3kHz)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402.00	-19.01	8	Pass
NVNT	ANT1	1Mbps	2440.00	-19.31	8	Pass
NVNT	ANT1	1Mbps	2480.00	-19.39	8	Pass
NVNT	ANT1	2Mbps	2402.00	-20.97	8	Pass
NVNT	ANT1	2Mbps	2440.00	-21.60	8	Pass
NVNT	ANT1	2Mbps	2480.00	-21.91	8	Pass

Power_Spectral_Density_NVNT_ANT1_1Mbps_2402



Power_Spectral_Density_NVNT_ANT1_1Mbps_2440



Power_Spectral_Density_NVNT_ANT1_1Mbps_2480



Power_Spectral_Density_NVNT_ANT1_2Mbps_2402



Power_Spectral_Density_NVNT_ANT1_2Mbps_2440



Power_Spectral_Density_NVNT_ANT1_2Mbps_2480



8. Occupied Bandwidth

8.1. Test limits

Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2. Test Procedure

Details see the ANSI C63.10:2020+Cor.1-2023 section 6.9.3 and section 11.8.1
DTS bandwidth

a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
b) The test receiver set RBW = 100kHz, VBW≥3*RBW =300kHz, Peak Detector, Sweep time set auto, detail see the test plot.

Occupied bandwidth-power bandwidth (99%) measurement procedure

c) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1 .5 times and 5.0 times the OBW.
d) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
e) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than 10 log (0BW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.

8.3. Test Setup



8.4. Test Results

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402.00	507.37	500	Pass
NVNT	ANT1	1Mbps	2440.00	506.14	500	Pass
NVNT	ANT1	1Mbps	2480.00	508.59	500	Pass
NVNT	ANT1	2Mbps	2402.00	855.35	500	Pass
NVNT	ANT1	2Mbps	2440.00	852.03	500	Pass
NVNT	ANT1	2Mbps	2480.00	852.35	500	Pass

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2402



-6dB_Bandwidth_NVNT_ANT1_1Mbps_2440

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2480

-6dB_Bandwidth_NVNT_ANT1_2Mbps_2402



-6dB_Bandwidth_NVNT_ANT1_2Mbps_2440



-6dB_Bandwidth_NVNT_ANT1_2Mbps_2480



Condition	Antenna	Rate	Frequency (MHz)	99%%BW(MHz)
NVNT	ANT1	1Mbps	2402.00	1.018
NVNT	ANT1	1Mbps	2440.00	1.019
NVNT	ANT1	1Mbps	2480.00	1.019
NVNT	ANT1	2Mbps	2402.00	2.030
NVNT	ANT1	2Mbps	2440.00	2.032
NVNT	ANT1	2Mbps	2480.00	2.033

99%_Occupied_Bandwidth_NVNT_ANT1_1Mbps_2402

99%_Occupied_Bandwidth_NVNT_ANT1_1Mbps_2440

99%_Occupied_Bandwidth_NVNT_ANT1_1Mbps_2480

99%_Occupied_Bandwidth_NVNT_ANT1_2Mbps_2402



99%_Occupied_Bandwidth_NVNT_ANT1_2Mbps_2440



99%_Occupied_Bandwidth_NVNT_ANT1_2Mbps_2480



9. Band Edge Test

9.1. Test Limit

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

9.2. Block Diagram of Test Setup



9.3. Test Procedure

ANSI C63.10:2020+Cor.1-2023 section 6.10.5.2
All restriction band and non- restriction band have been tested, only worse case is reported.
Details see the KDB558074 D01 Meas Guidance v05r02

1. Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
2. Check the spurious emissions out of band.
3. RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

9.4. Test Results

Test Date	:	2026.06.09	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Results	:	**PASS**			

Frequency Range : **2310MHz~2410MHz**								
Test Mode : 1Mbps: GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	61.68	-20.45	41.23	74.00	-32.77	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	64.34	-20.41	43.93	74.00	-30.07	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	61.79	-20.45	41.34	74.00	-32.66	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	63.57	-20.41	43.16	74.00	-30.84	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : **2450MHz~2550MHz**								
Test Mode : 1Mbps: GFSK TX 2480MHz								
1	2483.5	H	60.74	-20.15	40.59	74.00	-33.41	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	64.81	-20.15	44.66	74.00	-29.34	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor, Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Frequency Range : **2310MHz~2410MHz**								
Test Mode : 2Mbps: GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	59.55	-20.45	39.10	74.00	-34.90	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	63.82	-20.41	43.41	74.00	-30.59	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	62.80	-20.45	42.35	74.00	-31.65	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	63.10	-20.41	42.69	74.00	-31.31	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : **2450MHz~2550MHz**								
Test Mode : 2Mbps: GFSK TX 2480MHz								
1	2483.5	H	61.89	-20.15	41.74	74.00	-32.26	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	65.32	-20.15	45.17	74.00	-28.83	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor, Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

10. Antenna Requirement

10.1.Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2.Results

The EUT antenna is internal antenna. It complies with the standard requirement.

11. Photos of test setup

Reference to the **psi2606095-C01-R01 appendix I Test Setup Photo** for details.

12. Photos of EUT

Reference to the **psi2606095-C01-R01 appendix II external photos** and **appendix III internal photos** for details.

------ END OF REPORT------