



FCC RF Exposure

EUT Description: JS108 PRO Membrane Keyboard

Model No.: JS108 PRO

Series Model: JS108, IP108, IP108 PRO

FCC ID: 2BTAA-JS108PRO

Equipment type: Portable Device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz. The result is rounded to one decimal place for comparison

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min test separation Distance, mm})] [\sqrt{f(\text{GHz})}]}{< 3.0 \text{ for 1-g SAR, and } < 7.5 \text{ for 10-g extremity SAR, where}}$$

Power and distance are rounded to the nearest mW and mm before calculation

Limits for Maximum Permissible Exposure (MPE)

$$\text{EIRP} = \text{EMeas} + 20 \log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas is the field strength of the emission at the measurement distance, in dB uV/m

dMeas is the measurement distance, in m

Test Result of RF Exposure Evaluation**2.4G SRD**

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
82.20	-13.03	0.0498	2402	5.00	0.0154	3.0000
81.98	-13.25	0.0473	2440	5.00	0.0148	3.0000
83.68	-11.55	0.0700	2480	5.00	0.0220	3.0000

BLE

Frequency(MHz)	Output power(dBm)	Max tune-up(mW)	Min. distance(mm)	Calc. thresholds	limit
2402	-2.95	0.5070	5.00	0.1572	3.0000
2440	-1.79	0.6622	5.00	0.2069	3.0000
2480	-2.46	0.5675	5.00	0.1788	3.0000

Conclusion: No SAR is required