FCC Test Report

Report No: FCS202609265W02

Issued for

Applicant:	FURYCUBE LIMITED
Address:	KAISER ESTATE NO.41 MAN YUE STREET HUNGHOM KL, Hong Kong
Product Name:	JS108 PRO Membrane Keyboard
Brand Name:	FURYCUBE
Model Name:	JS108 PRO
Series Model:	JS108,IP108,IP108 PRO
FCC ID:	2BTAA-JS108PRO

Issued By: Flux Compliance Service Laboratory
Add: Room 105, 1/F., Baohao Technology Building 1, NO.15, Gongye West Road, Songshan Lake Hi-Tech Industrial Area, Dongguan,Guangdong,China
Tel: 0769-27280901 Fax:0769-27280901 http://www.FCS-lab.com

TEST RESULT CERTIFICATION	
Applicant's Name..... :	FURYCUBE LIMITED
Address..... :	KAISER ESTATE NO.41 MAN YUE STREET HUNGHOM KL, Hong Kong
Manufacture's Name..... :	FURYCUBE LIMITED
Address..... :	KAISER ESTATE NO.41 MAN YUE STREET HUNGHOM KL, Hong Kong
Product Description	
Product Name..... :	JS108 PRO Membrane Keyboard
Brand Name.....:	FURYCUBE
Model Name..... :	JS108 PRO
Series Model.....:	please refer to the first page of the report
Test Standards..... :	FCC Rules and Regulations Part 15 Subpart C, Section 247
Test Procedure..... :	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document..	
Date of Test..... :	
Date (s) of performance of tests. :	Sep. 23, 2026~Sep. 29, 2026
Date of Issue.....:	Sep. 29, 2026
Test Result.....:	Pass

Tested by : orange OuYang

(orange OuYang)

Reviewed by : Aron Zhang

(Aron Zhang)

Approved by : Jack Wang

(Jack Wang)

Table of Contents Page

1. SUMMARY OF TEST RESULTS 6
1.1 TEST FACTORY 7
1.2 MEASUREMENT UNCERTAINTY 7
2. GENERAL INFORMATION 8
2.1 GENERAL DESCRIPTION OF THE EUT 8
2.2 BLOCK ADIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS 11
2.4 EQUIPMENTS LIST 12
3. CONDUCTED EMISSION MEASUREMENT 13
4. 6DB BANDWIDTH 17
4.1 LIMIT 17
4.2 TEST PROCEDURE 17
4.3 TEST SETUP 17
4.4 TEST RESULTS 17
4.5 ORIGINAL TEST DATA 18
5. CONDUCTED OUTPUT POWER 19
5.1 LIMIT 19
5.2 SPECTRUM ANALYZER SETTING 19
5.3 TEST PROCEDURE 19
5.4 TEST SETUP 19
5.5 TEST RESULTS 19
6. BAND EDGE AND SPURIOUS(CONDUCTED) 21
6.1 LIMIT 21
6.2 TEST PROCEDURE 21
6.3 TEST SETUP 21
6.4 TEST RESULTS 22
6.5 ORIGINAL TEST DATA 22
7. POWER SPECTRAL DENSITY 24
7.1 LIMIT 24
7.2 TEST PROCEDURE 24

Table of Contents **Page**

7.3 TEST SETUP 24
7.4 TEST RESULTS 24
7.5 ORIGINAL TEST DATA 25
8. RADIATED EMISSION MEASUREMENT 26
8.1 RADIATED EMISSION LIMITS 26
8.2 TEST PROCEDURE 27
8.3 TESTSETUP 28
8.4 TEST RESULTS 29
9. RADIATED EMISSION (30MHZ-1000MHZ) 30
9.1 RADIATED EMISSION ABOVE 1GHZ 32
9.2 RADIATED BAND EDGE DATA 34
10. ANTENNA REQUIREMENT 35
10.1 STANDARD REQUIREMENT 35
10.2 RESULT 35

Revision History

Rev.	Issue Date	Effect Page	Contents
00	Sep. 29, 2026	N/A	N/A

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.247(a)(2)	6dB Bandwidth	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105, 1/F., Baohao Technology Building 1, No.15, Gongye West Road, Songshan Lake Hi-Tech Industrial Area, Dongguan, Guangdong, China
Telephone:	+86-0769-27280901
Fax:	+86-0769-27280901
Laboratory Accreditations	
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number：5545.01 ISED Number：25801 CAB ID ：CN0097	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ±U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.70dB
2	Unwanted Emissions, conducted	±2.988 dB
3	Conducted Emission (9KHz-150KHz)	±3.17 dB
4	All emissions radiated (9KHz -30MHz)	±4.12 dB
5	Conducted Emission (150KHz-30MHz)	±2.25 dB
6	All emissions,radiated(<1G) 30MHz-1000MHz	±4.60 dB
7	All emissions,radiated 1GHz -18GHz	±5.31 dB
8	All emissions,radiated 18GHz -40GHz	±4.31 dB
9	Occupied bandwidth	±5.8 dB
10	Power Spectral Density	±0.748 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	JS108 PRO Membrane Keyboard
Trade Name	FURYCUBE
Model Name	JS108 PRO
Series Model	please refer to the first page of the report
Model Difference	The PCB board, structure, and internal components of these models are the same. Only the model names and colors are different;therefore, no additional models were tested.
Product Description	Operation Frequency: 2402-2480 MHz Modulation Type: GFSK Radio Technology: BLE Bluetooth Configuration: LE Number Of Channel: 40 CH Antenna Gain (dBi) 5.37 Transmitter rate: 1Mbps
Channel List	Please refer to the Note 2.
Power Supply	DC 5V
Battery	DC 3.7V
Hardware version number	N/A
Software version number	N/A
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed description of the product features, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List

Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	NA	N/A	PCB Antenna	N/A	5.37	Antenna

4. Table for RF Cable

Ant.	Cable Loss(dB)	Provided by
1	1.0	FURYCUBE LIMITED

Note:
1. The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.
2. The laboratory is not responsible for the accuracy of the cable loss.

2.2 BLOCK ADIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test

Radiation:



Conduction



Test software: FCC_assist_1.0.2.2

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

No.	Test model description
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Charging

Note:

1. All the test modes can be supply by battery, only the result of the worst case recorded in the report. GFSK mode is worst mode.
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The EUT used fully charge battery when tested.
4. During the test, the duty cycle>98%, the test voltage was tuned from 85% to 115% of the Nominal rate supply voltage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Adapter	vivo	V2323A-CN	N/A	this adapter is for testing only in report
C-1	USB Cable	FURYCUBE LIMITED	N/A	N/A	0.5m

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	FCS-E014	2026/8/20	2027/8/19
Spectrum Analyzer	Agilent	E4407B	FCS-E032	2026/8/20	2027/8/19
Spectrum Analyzer	R&S	FSV40	FCS-E012	2026/8/22	2027/8/21
Loop Antenna	HCT	6505	FCS-E030	2026/8/22	2027/8/21
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2026/8/22	2027/8/21
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2026/8/22	2027/8/21
Pre-amplifier (1G-18G)	Agilent	8449B	FCS-E013	2026/8/20	2027/8/19
Pre-amplifier (0.1M-3GHz)	EMC INSTRUMENTS CORPORATION	EMC330N	FCS-E004	2026/8/20	2027/8/19
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2026/8/22	2027/8/21
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2026/8/22	2027/8/21
Temperature & Humidity	Yuhuaze	N/A	FCS-E009	2026/8/24	2027/8/23
Testing Software	EZ-EMC(Ver.FA-03A2 RE+)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP3	FCS-E001	2026/8/20	2027/8/19
LISN	R&S	ENV216	FCS-E007	2026/8/20	2027/8/19
CE Cable	N/A	N/A	N/A	2026/8/20	2027/8/19
Temperature & Humidity	HTC-1	victor	FCS-E008	2026/8/24	2027/8/23
Testing Software	EZ-EMC(EMC-COM 3A1.1)				

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
MXA SIGNAL Analyzer	Keysight	N9020A	FCS-W005	2026/8/20	2027/8/19
Open Switch and Control Unit	EZLZ	Ezlzrfp	FCS-W007	2026/08/25	2027/08/24
Temperature & Humidity	Yuhuaze	N/A	FCS-E009	2026/8/24	2027/8/23
Testing Software	LZ-RF(Ver.LzRf-3A3)				

3. CONDUCTED EMISSION MEASUREMENT

3.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 TEST RESULTS

Temperature:	25℃	Relative Humidity:	60%
Test Mode:	Low CH (GFSK)	Phase:	L
Test Voltage:	DC 5V From Adapter With AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4335	36.31	9.61	45.92	57.19	11.27	QP
2	0.4335	22.68	9.61	32.29	47.19	14.90	AVG
3	0.5144	27.54	9.61	37.15	56.00	18.85	QP
4	0.5144	16.44	9.61	26.05	46.00	19.95	AVG
5	0.6140	27.81	9.62	37.43	56.00	18.57	QP
6	0.6140	13.04	9.62	22.66	46.00	23.34	AVG
7	1.4415	27.47	9.62	37.09	56.00	18.91	QP
8	1.4415	13.50	9.62	23.12	46.00	22.88	AVG
9	3.1560	27.55	9.63	37.18	56.00	18.82	QP
10	3.1560	12.19	9.63	21.82	46.00	24.18	AVG
11	4.2720	29.04	9.64	38.68	56.00	17.32	QP
12	4.2720	14.52	9.64	24.16	46.00	21.84	AVG

Temperature:	25℃	Relative Humidity:	60%
Test Mode:	Low CH (GFSK)	Phase:	N
Test Voltage:	DC 5V From Adapter With AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1635	29.09	9.63	38.72	65.28	26.56	QP
2	0.1635	11.30	9.63	20.93	55.28	34.35	AVG
3	0.1905	27.61	9.62	37.23	64.01	26.78	QP
4	0.1905	10.49	9.62	20.11	54.01	33.90	AVG
5	0.2175	26.55	9.62	36.17	62.91	26.74	QP
6	0.2175	9.52	9.62	19.14	52.91	33.77	AVG
7	0.4335	32.79	9.61	42.40	57.19	14.79	QP
8	0.4335	17.87	9.61	27.48	47.19	19.71	AVG
9	2.1344	25.24	9.64	34.88	56.00	21.12	QP
10	2.1344	10.09	9.64	19.73	46.00	26.27	AVG
11	5.4870	26.80	9.66	36.46	60.00	23.54	QP
12	5.4870	12.51	9.66	22.17	50.00	27.83	AVG

Remark:1.All readings are Quasi-Peak and Average values
2.During the test, pre-scan all modes, only the worst case is recorded in the report.

4. 6DB BANDWIDTH

4.1 LIMIT

FCC Part 15.247,Subpart C RSS-Gen Clause 6.7				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	6dB Bandwidth	>= 500KHz	2400-2483.5	PASS
RSS-Gen Clause 6.7	99% Bandwidth	For reporting purposes only.	2400-2483.5	PASS

4.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth :100KHz For 99% Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : ≥3 × RBW For 99% Bandwidth : approximately 3×RBW
Trace	Max hold
Sweep	Auto

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3 TEST SETUP

4.4 TEST RESULTS

TestMode	Channel (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Limit [MHz]	Verdict
Lowest	2402MHz	0.512	0.5	Pass
Middle	2440MHz	0.514	0.5	Pass
Highest	2480MHz	0.512	0.5	Pass

Note:6dB Bandwidth Result(MHz)=mark2-mark1

4.5 ORIGINAL TEST DATA

6BW,1M_PHY,Lowest

6BW,1M_PHY,Middle



6BW,1M_PHY,Highest

5. CONDUCTED OUTPUT POWER

5.1 LIMIT

FCC Part 15 Subpart C			
Section	Test Item	Limit	Frequency Range
15.247(b)(3)	Peak output power	Power <1W(30dBm)	2400-2483.5

5.2 SPECTRUM ANALYZER SETTING

Spectrum Parameters	Setting
RBW	≥DTS Bandwidth
VBW	3*RBW
Span	≥3*DTS Bandwidth
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.3 TEST PROCEDURE

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 5.2.
c. Set the EUT transmit continuously with maximum output power.
d. Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
e. Repeat above procedures until all channels were measured.
f. Record the results in the test report.

5.4 TEST SETUP

5.5 TEST RESULTS

TestMode	Channel (MHz)	Result（dBm）	Limit（dBm）	Verdict
Lowest	2402MHz	-2.95	30	Pass
Middle	2440MHz	-1.79	30	Pass
Highest	2480MHz	-2.46	30	Pass

conducted output power-peak

Low channel



Middle, channel



High channel



6. BAND EDGE AND SPURIOUS(CONDUCTED)

6.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

6.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

6.3 TEST SETUP

6.4 TEST RESULTS

Eut set mode	CH or Frequency	Result
GFSK	CH0	Pass
	CH39	Pass

6.5 ORIGINAL TEST DATA

Reference level measurement

Low channel



Middle, channel



High channel



Band edge

Low channel



High channel



Spurious emissions

Low 2402MHz 0.3GHz-25GHz



Middle 2440MHz 0.3GHz-25GHz



High 2480MHz 0.3GHz-25GHz



7. POWER SPECTRAL DENSITY

7.1 LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

7.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.3 TEST SETUP

7.4 TEST RESULTS

TestMode	Channel (MHz)	Result (dBm/3KHz)	Limit (dBm/3KHz)	Verdict
GFSK	2402MHz	-22.37	8	Pass
GFSK	2440MHz	-21.28	8	Pass
GFSK	2480MHz	-21.75	8	Pass

7.5 ORIGINAL TEST DATA

GFSK-2402MHz



GFSK-2440MHz



GFSK-2480MH



8. RADIATED EMISSION MEASUREMENT

8.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz

Receiver Parameter	**Setting**
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

8.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz,and above 1GHz.
b. The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

8.3 TESTSETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



8.4 TEST RESULTS

(9KHz-30MHz)

Temperature:	22.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Test Mode:	GFSK(Worst mode)

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits (dBuv) + distance extrapolation factor.

9. RADIATED EMISSION (30MHZ-1000MHZ)

Temperature:	24.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	Low channel GFSK(Worst mode)		



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	36.6375	26.25	-11.55	14.70	40.00	-25.30	QP
2	76.5121	27.29	-15.13	12.16	40.00	-27.84	QP
3	146.8877	25.96	-11.99	13.97	43.50	-29.53	QP
4	303.5437	26.43	-11.61	14.82	46.00	-31.18	QP
5	517.2480	26.52	-6.61	19.91	46.00	-26.09	QP
6	909.6667	27.04	0.12	27.16	46.00	-18.84	QP

Note: 1. Margin = Result (Result =Reading + Factor)–Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Temperature:	22.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	Low channel GFSK(Worst mode)		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.1795	25.96	-12.20	13.76	40.00	-26.24	QP
2	68.1514	27.33	-14.55	12.78	40.00	-27.22	QP
3	135.9822	26.78	-12.45	14.33	43.50	-29.17	QP
4	275.1570	26.93	-12.25	14.68	46.00	-31.32	QP
5	539.4775	26.62	-5.96	20.66	46.00	-25.34	QP
6	972.3374	26.88	0.86	27.74	54.00	-26.26	QP

Note: 1. Margin = Result (Result =Reading + Factor)–Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

9.1 RADIATED EMISSION ABOVE 1GHZ

Low CH (GFSK)
Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804.00	47.35	32.11	6.366	43.88	41.95	74	-32.05	Vertical
7206.00	44.63	35.71	7.265	43.06	44.54	74	-29.46	Vertical
9608.00	39.65	37.60	8.625	43.28	42.59	74	-31.41	Vertical
12010.00	*					74		Vertical
14412.00	*					74		Vertical
4804.00	53.28	32.11	6.366	43.88	47.88	74	-26.12	Horizontal
7206.00	44.27	35.71	7.265	43.06	44.18	74	-29.82	Horizontal
9608.00	41.16	37.60	8.625	43.28	44.10	74	-29.90	Horizontal
12010.00	*					74		Horizontal
14412.00	*					74		Horizontal

Middle CH (GFSK)

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4880	48.26	32.38	6.437	43.81	43.27	74	-30.73	Vertical
7320	43.53	35.86	7.246	43.16	43.48	74	-30.52	Vertical
9760	39.72	37.82	8.716	43.33	42.93	74	-31.07	Vertical
12200	*					74		Vertical
14640	*					74		Vertical
4880	54.37	32.38	6.437	43.81	49.38	74	-24.62	Horizontal
7320	43.29	35.86	7.246	43.16	43.24	74	-30.76	Horizontal
9760	42.68	37.82	8.716	43.33	45.89	74	-28.11	Horizontal
12200	*					74		Horizontal
14640	*					74		Horizontal

Remark:
1. Final Level =Receiver Read level + Antenna Factor + Cable Loss- Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. "*", means this data is the too weak instrument of signal is unable to test.
4. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

High CH (GFSK)
Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960	49.31	32.78	6.512	43.74	44.87	74	-29.13	Vertical
7440	43.16	35.92	7.225	43.25	43.05	74	-30.95	Vertical
9920	39.27	37.72	8.812	43.38	42.43	74	-31.57	Vertical
12400	*					74		Vertical
14880	*					74		Vertical
4960	53.26	32.78	6.512	43.74	48.82	74	-25.18	Horizontal
7440	44.89	35.92	7.225	43.25	44.78	74	-29.22	Horizontal
9920	40.37	37.72	8.812	43.38	43.53	74	-30.47	Horizontal
12400	*					74		Horizontal
14880	*					74		Horizontal

Remark:
1. Final Level =Receiver Read level + Antenna Factor + Cable Loss- Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. "*", means this data is the too weak instrument of signal is unable to test
4. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

9.2 RADIATED BAND EDGE DATA

Low CH (GFSK)

Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	58.47	27.62	3.70	47.84	41.95	74	-32.05	Horizontal
2390	58.35	27.14	3.79	47.72	41.56	74	-32.44	Horizontal
2400	59.16	27.10	3.80	47.70	42.36	74	-31.64	Horizontal
2310	59.45	27.62	3.70	47.84	42.93	74	-31.07	Vertical
2390	58.34	27.14	3.79	47.72	41.55	74	-32.45	Vertical
2400	59.27	27.10	3.80	47.70	42.47	74	-31.53	Vertical

High CH(GFSK)

Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	58.44	27.60	3.89	47.57	42.36	74	-31.64	Horizontal
2500	58.71	27.70	3.91	47.55	42.77	74	-31.23	Horizontal
2483.5	59.19	27.60	3.89	47.57	43.11	74	-30.89	Vertical
2500	58.26	27.70	3.91	47.55	42.32	74	-31.68	Vertical

Remark.
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
2.The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
3.All restriction band have been tested, and only the worst case is shown in report
4.For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2 RESULT

The antennas used for this product are PCB antenna and no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 5.37dBi.

※※※※※END OF THE REPORT※※※※※