

TEST REPORT

Applicant: Hankook Technology Commerce Limited

Address of Applicant: FLAT E, 23/F GOLDEN SUN CENTRE 56-67 BONHAM STRAND WEST SHEUNG WAN HK

Manufacturer Hankook Technology Commerce Limited

Address of Manufacturer: FLAT E, 23/F GOLDEN SUN CENTRE 56-67 BONHAM STRAND WEST SHEUNG WAN HK

Equipment Under Test (EUT)

Product Name: 5G Mobile Phone

Model No.: NX809J

FCC ID: 2BTCR-NX809J

Applicable standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22
FCC CFR Title 47 Part 24
FCC CFR Title 47 Part 27

Date of sample receipt: November 18, 2025

Date of Test: November 19, 2025-December 25, 2025

Date of report issued: December 25, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	December 25, 2025	Original

Tested By:

Jauch. Cai

Date:

December 25, 2025

Test Engineer

Prepared By:

Jessie Lu

Date:

December 25, 2025

Project Engineer

Check By:

Robinson Lu

Date:

December 25, 2025

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 CHANNEL LIST.....	6
5.3 MAXIMUM ERP/EIRP, FREQUENCY TOLERANCE AND EMISSION DESIGNATOR.....	6
5.4 RELATED SUBMITTAL(S) / GRANT (S)	7
5.5 TEST METHODOLOGY	7
5.6 DEVIATION FROM STANDARDS	7
5.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.8 TEST FACILITY	7
5.9 TEST LOCATION.....	7
6 TEST INSTRUMENTS LIST.....	8
7 SYSTEM TEST CONFIGURATION	10
7.1 TEST MODE	10
7.2 CONFIGURATION OF TESTED SYSTEM	10
7.3 CONDUCTED AVERAGE OUTPUT POWER AND ERP/EIRP	11
7.4 PEAK-TO-AVERAGE RATIO	12
7.5 99% OCCUPIED BANDWIDTH & 26dB EMISSIONS BANDWIDTH	13
7.6 MODULATION CHARACTERISTIC	14
7.7 OUT OF BAND EMISSION AT ANTENNA TERMINALS	14
7.8 SPURIOUS RADIATION EMISSIONS.....	15
7.9 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	18
7.10 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	19
8 TEST SETUP PHOTO.....	20
9 EUT CONSTRUCTIONAL DETAILS	20

4 Test Summary

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 22.913(a)(5) Part 24.232 (c) Part 27.50(d)(4)	Pass
Peak-to-Average Ratio	Part 2.1046 Part 22.913(d) Part 24.232(d) Part 27.50(d)(5)	Pass
99% Occupied Bandwidth & 26dB Emissions Bandwidth	Part 2.1049	Pass
Modulation Characteristics	Part 2.1047	N/A
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass
Spurious Radiation Emissions	Part 2.1053 Part 22.917 Part 24.238	Pass
Out of band emission, Band Edge	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass
Frequency stability vs. temperature	Part 2.1055 Part 22.355 Part 24.235 Part 27.54	Pass
Frequency stability vs. voltage	Part 2.1055 Part 22.355 Part 24.235 Part 27.54	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: Not applicable.

5 General Information

5.1 General Description of EUT

Product Name:	5G Mobile Phone	
Model No.:	NX809J	
Test sample(s) ID:	GTSL2025120078F-2, GTSL2025120078F-3	
Sample(s) Status:	Engineer sample	
Support Bands:	WCDMA Band II, WCDMA Band IV, WCDMA Band V	
TX Frequency:	WCDMA Band II: 1850MHz~1910MHz WCDMA Band IV: 1710MHz~1755MHz WCDMA Band V: 824MHz~849MHz	
Modulation type:	WCDMA Band II/IV/V: QPSK 16QAM	
Antenna type:	Internal Antenna	
Antenna gain:	WCDMA Band II:	Ant1: -0.65dBi, Ant4: -4.6dBi
	WCDMA Band IV:	Ant1: -1.5dBi, Ant4: -4.4dBi
	WCDMA Band V:	Ant3: -3.2dBi, Ant5: -3.6dBi
Power supply:	Rechargeable Li-ion Polymer Battery DC 3.79V/7500mAh	

Disclaimer statement:

1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

5.2 Channel List

Operation Frequency List:

WCDMA Band II		WCDMA Band IV		WCDMA Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
9262	1852.40	1312	1712.40	4132	826.40
9263	1852.60	1313	1712.60	4133	826.60
⋮	⋮			⋮	⋮
9399	1879.80	1412	1732.40	4181	836.20
9400	1880.00	1413	1732.60	4182	836.40
9401	1880.20	1414	1732.80	4183	836.60
⋮	⋮	...	...	⋮	⋮
9537	1907.40	1512	1752.40	4232	846.40
9538	1907.60	1513	1752.60	4233	846.60

Final test channel:

WCDMA Band II		WCDMA Band IV		WCDMA Band V	
Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
9262	1852.40	1312	1712.40	4132	826.40
9400	1880.00	1413	1732.60	4183	836.60
9538	1907.60	1513	1752.60	4233	846.60

5.3 Maximum ERP/EIRP, Frequency Tolerance and Emission Designator

System	Type of Modulation	Emission Designator	Frequency Tolerance (ppm)	Maximum ERP (W)
WCDMA 850	QPSK	4M14F9W	0.000191	0.067

System	Type of Modulation	Emission Designator	Frequency Tolerance (ppm)	Maximum EIRP (W)
WCDMA 1900	QPSK	4M18F9W	-0.000931	0.188
WCDMA 1700	QPSK	4M16F9W	-0.001633	0.160

5.4 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 /24 of the FCC CFR 47 Rules.

5.5 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on ANSI C63.26:2015 and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.9 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 01, 2025	Jun. 30, 2026
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.15, 2025	Nov.14, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 12, 2025	Nov. 11, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 11, 2025	Jul. 10, 2026
17	RE cable 2	GTS	N/A	GTS676	Jul. 11, 2025	Jul. 10, 2026
18	RE cable 3	GTS	N/A	GTS677	Jul. 11, 2025	Jul. 10, 2026
19	RE cable 4	GTS	N/A	GTS678	Jul. 11, 2025	Jul. 10, 2026
20	RE cable 5	GTS	N/A	GTS679	Jul. 11, 2025	Jul. 10, 2026
21	RE cable 6	GTS	N/A	GTS680	Jul. 11, 2025	Jul. 10, 2026
22	RE cable 7	GTS	N/A	GTS681	Jul. 11, 2025	Jul. 10, 2026
23	RE cable 8	GTS	N/A	GTS682	Jul. 11, 2025	Jul. 10, 2026
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 11, 2025	Apr. 10, 2026
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 11, 2025	Apr. 10, 2026
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 11, 2025	Apr. 10, 2026
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 11, 2025	Apr. 10, 2026
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 11, 2025	Apr. 10, 2026
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 11, 2025	Apr. 10, 2026
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 16, 2025	Jul. 15, 2026

7 System test configuration

7.1 Test mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three(X: flat, Y: portrait, Z: landscape) different orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for WCDMA Band V.
2. 30 MHz to 20000 MHz for WCDMA Band II.
3. 30 MHz to 18000 MHz for WCDMA Band IV.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V (Ant3)	RMC 12.2kbps Link	RMC 12.2kbps Link
WCDMA Band II (Ant1)	RMC 12.2kbps Link	RMC 12.2kbps Link
WCDMA Band IV (Ant1)	RMC 12.2kbps Link	RMC 12.2kbps Link


Note: The maximum power levels are chosen to test as the worst case configuration as follows:

RMC 12.2kbps mode for WCDMA band V,


RMC 12.2kbps mode for WCDMA band II,

RMC 12.2kbps mode for WCDMA band IV, only these modes were used for all tests.

7.2 Configuration of Tested System




7.3 Conducted Average Output Power and ERP/EIRP

Test Requirement:	FCC part 22.913 & FCC part 24.232 & FCC part2.1046
Test Method:	FCC KDB 971168 D01 V03r01 Section
Limit:	WCDMA Band V: 7W(38.45dBm) WCDMA Band II: 2W(33.01dBm)
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The transmitter output port was connected to base station. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement. 3. Set EUT at maximum power through base station. 4. Select lowest, middle, and highest channels for each band and different modulation. 5. Measure the maximum burst power. 6. EIRP=measured power+ antenna gain ERP=EIRP-2.15
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 7.1 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix

7.4 Peak-to-Average Ratio

Test Requirement:	FCC part 24.232 & FCC part2.1046
Test Method:	FCC KDB 971168 D01 V03r01 Section
Limit:	13db
Test setup:	 <pre> graph LR CC[Control Computer] --> EUT[EUT] PS[Power Supply] --> EUT subgraph EUT direction TB CP[Control port(s)] AP[Antenna port(s)] PP[Power port] end AP <--> PD[Power Divider] PD --> WC[Wireless Communication] PD --> SA[Spectrum Analyzer] </pre>
Test Procedure:	A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode. Test Settings 1. The signal analyzer's CCDF measurement profile enabled 2. Frequency= carrier center frequency 3. Measurement BW > EBW of signal 4. for continuous transmissions, set to 1ms 5. Record the maximum PAPR level associated with a probability of 0.1%.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WCDMA.

7.5 99% Occupied Bandwidth & 26dB Emissions Bandwidth


Test Requirement:	FCC part2.1049
Test Method:	FCC KDB 971168 D01 V03r01 Section
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WCDMA.

7.6 MODULATION CHARACTERISTIC




According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

7.7 Out of band emission at antenna terminals

Test Requirement:	FCC part 22.917 and FCC part 24.238 & FCC part 2.1051
Test Method:	FCC KDB 971168 D01 V03r01 Section
Limit:	-13dBm
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WCDMA.

7.8 Spurious Radiation Emissions

Test Requirement:	FCC part 2.1053 & FCC part 22.917 & FCC part 24.238
Test Method:	FCC KDB 971168 D01 V03r01 Section & ANSI C63.26:2015
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 7.1 for details
Test results:	Pass

Measurement Data:

All condition were test, only report worst case.

30MHz~9GHz: WCDMA 850 Middle Channel							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	38.23	-89.08	-67.08	-13.00	54.08	22.00	Horizontal
2	52.06	-93.89	-74.64	-13.00	61.64	19.25	Horizontal
3	110.90	-96.05	-76.47	-13.00	63.47	19.58	Horizontal
4	1948.53	-53.39	-52.29	-13.00	39.29	1.10	Horizontal
5	7479.76	-60.67	-41.00	-13.00	28.00	19.67	Horizontal
6	17304.44	-66.05	-37.23	-13.00	24.23	28.82	Horizontal
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	50.97	-90.58	-71.59	-13.00	58.59	18.99	Vertical
2	104.20	-93.37	-69.33	-13.00	56.33	24.04	Vertical
3	442.85	-101.28	-72.09	-13.00	59.09	29.19	Vertical
4	2406.23	-48.37	-45.13	-13.00	32.13	3.24	Vertical
5	5113.51	-58.78	-44.20	-13.00	31.20	14.58	Vertical
6	10790.13	-61.78	-39.14	-13.00	26.14	22.64	Vertical


30MHz~20GHz: WCDMA 1900 Middle Channel							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	38.28	-90.65	-68.65	-13.00	55.65	22.00	Horizontal
2	104.60	-93.56	-74.20	-13.00	61.20	19.36	Horizontal
3	505.36	-105.22	-72.60	-13.00	59.60	32.62	Horizontal
4	4889.62	-59.01	-44.26	-13.00	31.26	14.75	Horizontal
5	7418.75	-59.49	-39.79	-13.00	26.79	19.70	Horizontal
6	13113.80	-62.69	-39.47	-13.00	26.47	23.22	Horizontal
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	38.26	-90.65	-70.26	-13.00	57.26	20.39	Vertical
2	51.43	-93.16	-74.17	-13.00	61.17	18.99	Vertical
3	104.01	-94.57	-70.53	-13.00	57.53	24.04	Vertical
4	4662.34	-59.50	-46.43	-13.00	33.43	13.07	Vertical
5	11049.20	-61.41	-38.63	-13.00	25.63	22.78	Vertical
6	17436.01	-66.11	-37.33	-13.00	24.33	28.78	Vertical

30MHz~18GHz: WCDMA 1700 Middle Channel							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	38.01	-83.78	-61.78	-13.00	48.78	22.00	Horizontal
2	63.34	-87.02	-67.68	-13.00	54.68	19.34	Horizontal
3	312.47	-96.26	-69.60	-13.00	56.60	26.66	Horizontal
4	5089.22	-58.33	-43.76	-13.00	30.76	14.57	Horizontal
5	7741.66	-59.55	-40.28	-13.00	27.28	19.27	Horizontal
6	17160.04	-65.86	-37.77	-13.00	24.77	28.09	Horizontal
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	39.44	-85.31	-65.06	-13.00	52.06	20.25	Vertical
2	99.92	-88.94	-64.54	-13.00	51.54	24.40	Vertical
3	302.22	-94.40	-69.02	-13.00	56.02	25.38	Vertical
4	1053.47	-54.05	-55.72	-13.00	42.72	-1.67	Vertical
5	7757.63	-60.36	-41.09	-13.00	28.09	19.27	Vertical
6	12279.06	-61.38	-38.66	-13.00	25.66	22.72	Vertical

Notes:


1. Level = Reading Level + Factor.
2. Margin = Limit - Level.

7.9 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC part 22.355 and FCC part 24.235 and Part 27.54
Test Method:	FCC Part2.1055
Limit:	WCDMA 850: $\pm 2.5\text{ppm}$ WCDMA 1700/1900: Stay within the authorized frequency band
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of $+50^{\circ}\text{C}$ reached.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WCDMA.

7.10 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC part 22.355 and FCC part 24.235
Test Method:	FCC Part2.1055
Limit:	$\pm 2.5\text{ppm}$
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WCDMA.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----