



REPORT No.: SZ25090117S01

## Annex C Plots of System Performance Check

## Measurement Report for Device, FRONT, Validation band, CW, Channel 10000 (10000.0 MHz)

## Device Under Test Properties

| Model, Manufacturer | Dimensions [mm]       | IMEI | DUT Type |
|---------------------|-----------------------|------|----------|
| Device,             | 100.0 x 100.0 x 100.0 |      | Phone    |

## Exposure Conditions

| Phantom Section | Position, Test Distance [mm] | Band            | Group, UID | Frequency [MHz], Channel Number | Conversion Factor |
|-----------------|------------------------------|-----------------|------------|---------------------------------|-------------------|
| 5G              | FRONT, 10.0                  | Validation band | CW, 0--    | 10000.0, 10000                  | 1.0               |

## Hardware Setup

| Phantom       | Medium | Probe, Calibration Date               | DAE, Calibration Date   |
|---------------|--------|---------------------------------------|-------------------------|
| mmWave – xxxx | Air –  | EUmmWV4 – SN9602_F1–55GHz, 2025–03–19 | DAE4 Sn1643, 2025–03–21 |

## Scans Setup

| Scan Type           | 5G Scan       |
|---------------------|---------------|
| Grid Extents [mm]   | 120.0 x 120.0 |
| Grid Steps [lambda] | 0.25 x 0.25   |
| Sensor Surface [mm] | 10.0          |
| MAIA                | N/A           |

## Measurement Results

| Scan Type                    | 5G Scan           |
|------------------------------|-------------------|
| Date                         | 2025–12–04, 12:49 |
| Avg. Area [cm <sup>2</sup> ] | 4.00              |
| psPDn+ [W/m <sup>2</sup> ]   | 41.9              |
| psPDtot+ [W/m <sup>2</sup> ] | 42.6              |
| psPDmod+ [W/m <sup>2</sup> ] | 42.3              |
| E <sub>max</sub> [V/m]       | 114               |
| Power Drift [dB]             | 0.06              |

