

TEST REPORT

Applicant: TENG INTERNACIONAL TRADING LIMITED
Address: 4f 299 QRC NOS 287 299 QUEENS RD CENTRAL,
HONG KONG
Equipment Type: Pos Terminal
Model Name: K8
Brand Name: TENG INTERNACIONAL
FCC ID: 2BTGQ-K8
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Dec. 01, 2025
Test Date: Dec. 09, 2025 - Jan. 21, 2026
Date of Issue: Jan. 26, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Yang Panxia*Yang Panxia***Checked by:** Xiong Chong*Xiong Chong***Approved by:** Tolan Tu
(Technical Director)*Tolan Tu*

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jan. 26, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	General Description for Equipment under Test (EUT).....	4
2.4	Ancillary Equipment.....	5
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict.....	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List.....	7
4.2	Test Configurations	7
4.3	Test Setups	8
5	TEST ITEMS	10
5.1	Emission Tests	10
ANNEX A	TEST RESULTS.....	15
A.1	Radiated Emission.....	15
A.2	Conducted Emission, AC Ports.....	25
ANNEX B	TEST SETUP PHOTOS	30
ANNEX C	EUT EXTERNAL PHOTOS.....	30
ANNEX D	EUT INTERNAL PHOTOS.....	30

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No. 55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	TENG INTERNACIONAL TRADING LIMITED
Address	4f 299 QRC NOS 287 299 QUEENS RD CENTRAL, HONG KONG

2.2 Manufacturer Information

Manufacturer	TENG INTERNACIONAL TRADING LIMITED
Address	4f 299 QRC NOS 287 299 QUEENS RD CENTRAL, HONG KONG

2.3 General Description for Equipment under Test (EUT)

EUT Name	Pos Terminal
Model Name Under Test	K8
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V3
Software Version	SP7997A_V022_20251112_debug
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	SP7997A
	Serial No.	N/A
	Capacity	5100 mAh
	Rated Voltage	3.6 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	Adapter 1	
	Brand Name	N/A
	Model No.	F10L1-050200SPAE-U
	Serial No.	N/A
	Rated Input	100-240V~, 50/60Hz, 0.3A
	Rated Output	5.0V= 2.0A
Ancillary Equipment 3	Adapter 2	
	Brand Name	N/A
	Model No.	GLH50R2000HW
	Serial No.	N/A
	Rated Input	100-240V~, 50/60Hz, 0.4A
	Rated Output	5.0V= 2.0A
Ancillary Equipment 4	USB Cable	
	Length (Approx.)	1.51 m

2.5 Technical Information

Network and Wireless connectivity	2G Network GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/5 4G Network LTE FDD Band 5/7 Bluetooth, WIFI, NFC
Classification of equipment	Class B
The highest internal frequency of EUT	5850 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.4 dB
Radiated emissions (30 MHz-1 GHz)-C8-966	4.2 dB
Radiated emissions (1 GHz-18 GHz)-C8-966	5.3 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Type-C Cable	OPPO	N/A	N/A	1m	Unshielded with core	☒
Laptop Computer	HONOR	KPRC-W10	N/A	N/A	N/A	☒

4.2 Test Configurations


All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	<u>The Print Test Mode</u> EUT + Battery + Adapter + USB Cable
Mode 2	<u>The Data transmission Test Mode</u> EUT + Battery + Type-C Cable + Laptop Computer


Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 2	1
Conducted Emission, AC Ports	Mode 1~Mode 2	1
Note: All operation modes were tested, but only test data of the worst mode was presented in this report.		

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \times \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \times \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \times \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report

Sample No.	S01+A03+A09	Temperature	21.2℃
Humidity	42%RH	Pressure	101.3kPa
Test Engineer	Liao Ziyang	Test Date	2025.12.17


Test Mode 1

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.049	24.70	-28.76	40.0	15.30	Peak	360.00	100	Vertical	Pass
2	33.589	20.17	-28.50	40.0	19.83	Peak	106.20	100	Vertical	Pass
3	61.428	20.02	-25.72	40.0	19.98	Peak	95.20	100	Vertical	Pass
4	129.716	20.82	-28.16	43.5	22.68	Peak	360.00	100	Vertical	Pass
5	178.410	25.74	-26.60	43.5	17.76	Peak	264.60	100	Vertical	Pass
6	309.748	23.61	-21.25	46.0	22.39	Peak	291.70	100	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	179.089	21.85	-26.50	43.5	21.65	Peak	344.50	100	Horizontal	Pass
2	272.306	23.05	-22.30	46.0	22.95	Peak	170.00	100	Horizontal	Pass
3	309.942	25.99	-21.25	46.0	20.01	Peak	227.30	100	Horizontal	Pass
4	373.332	25.25	-19.41	46.0	20.75	Peak	131.30	100	Horizontal	Pass
5	518.589	30.36	-15.41	46.0	15.64	Peak	8.30	100	Horizontal	Pass
6	768.024	34.16	-8.89	46.0	11.84	Peak	0.00	100	Horizontal	Pass


Sample No.	S01+A03+A09	Temperature	22.6℃
Humidity	43%RH	Pressure	100.9kPa
Test Engineer	Liao Ziyang	Test Date	2025.12.15

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1279.200	42.70	-13.55	74.0	31.30	Peak	0.00	100	Vertical	Pass
1**	1279.200	32.88	-13.55	54.0	21.12	AV	0.00	100	Vertical	Pass
2	2916.900	50.10	-4.49	74.0	23.90	Peak	360.00	200	Vertical	Pass
2**	2916.900	40.79	-4.49	54.0	13.21	AV	360.00	200	Vertical	Pass
3	3494.800	47.57	-6.29	74.0	26.43	Peak	97.40	200	Vertical	Pass
3**	3494.800	37.77	-6.29	54.0	16.23	AV	97.40	200	Vertical	Pass
4	4498.400	48.93	-0.86	74.0	25.07	Peak	307.20	100	Vertical	Pass
4**	4498.400	38.98	-0.86	54.0	15.02	AV	307.20	100	Vertical	Pass
5	7091.713	52.07	19.65	74.0	21.93	Peak	186.60	100	Vertical	Pass
5**	7091.713	42.23	19.65	54.0	11.77	AV	186.60	100	Vertical	Pass
6	12606.825	54.15	22.60	74.0	19.85	Peak	52.70	100	Vertical	Pass
6**	12606.825	45.79	22.60	54.0	8.21	AV	52.70	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1367.900	42.84	-13.45	74.0	31.16	Peak	236.80	100	Horizontal	Pass
1**	1367.900	32.27	-13.45	54.0	21.73	AV	236.80	100	Horizontal	Pass
2	1777.800	44.45	-12.56	74.0	29.55	Peak	248.40	100	Horizontal	Pass
2**	1777.800	34.29	-12.56	54.0	19.71	AV	248.40	100	Horizontal	Pass
3	2914.300	50.08	-4.58	74.0	23.92	Peak	225.30	100	Horizontal	Pass
3**	2914.300	40.14	-4.58	54.0	13.86	AV	225.30	100	Horizontal	Pass
4	4375.000	48.65	-0.45	74.0	25.35	Peak	25.90	200	Horizontal	Pass
4**	4375.000	40.98	-0.45	54.0	13.02	AV	25.90	200	Horizontal	Pass
5	7544.237	52.58	20.19	74.0	21.42	Peak	323.70	200	Horizontal	Pass
5**	7544.237	42.45	20.19	54.0	11.55	AV	323.70	200	Horizontal	Pass
6	12613.151	54.96	22.51	74.0	19.04	Peak	306.30	100	Horizontal	Pass
6**	12613.151	44.41	22.51	54.0	9.59	AV	306.30	100	Horizontal	Pass

Sample No.	S02+A13+A15	Temperature	20.9℃
Humidity	38%RH	Pressure	101.6kPa
Test Engineer	Liao Ziyang	Test Date	2026.01.21


Test Mode 1

5) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	49.352	21.62	-24.16	40.0	18.38	Peak	122.60	100	Vertical	Pass
2	67.054	23.58	-27.31	40.0	16.42	Peak	270.60	100	Vertical	Pass
3	139.513	28.63	-28.65	43.5	14.87	Peak	118.10	200	Vertical	Pass
4	261.005	25.29	-22.41	46.0	20.71	Peak	177.90	100	Vertical	Pass
5	872.687	33.66	-6.58	46.0	12.34	Peak	166.30	100	Vertical	Pass
6	967.311	34.84	-4.98	54.0	19.16	Peak	13.20	100	Vertical	Pass


6) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	198.877	17.89	-24.27	43.5	25.61	Peak	120.20	100	Horizontal	Pass
2	300.630	28.46	-21.29	46.0	17.54	Peak	128.00	100	Horizontal	Pass
3	384.050	26.55	-18.93	46.0	19.45	Peak	70.70	100	Horizontal	Pass
4	585.471	26.34	-13.05	46.0	19.66	Peak	259.90	100	Horizontal	Pass
5	759.101	30.48	-8.71	46.0	15.52	Peak	360.00	100	Horizontal	Pass
6	922.060	33.08	-5.86	46.0	12.92	Peak	19.80	100	Horizontal	Pass


Sample No.	S02+A13+A15	Temperature	22.2℃
Humidity	57%RH	Pressure	101.0kPa
Test Engineer	Ya Jingtang	Test Date	2026.01.20

7) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2225.300	41.51	-10.92	74.0	32.49	Peak	106.00	100	Vertical	Pass
1**	2225.300	31.78	-10.92	54.0	22.22	AV	106.00	100	Vertical	Pass
2	3120.000	44.92	-8.13	74.0	29.08	Peak	216.00	100	Vertical	Pass
2**	3120.000	35.33	-8.13	54.0	18.67	AV	216.00	100	Vertical	Pass
3	3659.800	45.12	-6.57	74.0	28.88	Peak	43.00	200	Vertical	Pass
3**	3659.800	35.98	-6.57	54.0	18.02	AV	43.00	200	Vertical	Pass
4	4433.600	46.68	-4.10	74.0	27.32	Peak	81.00	100	Vertical	Pass
4**	4433.600	37.48	-4.10	54.0	16.52	AV	81.00	100	Vertical	Pass
5	6230.600	51.75	1.81	74.0	22.25	Peak	297.00	100	Vertical	Pass
5**	6230.600	40.72	1.81	54.0	13.28	AV	297.00	100	Vertical	Pass
6	17659.275	55.06	22.09	74.0	18.94	Peak	263.00	200	Vertical	Pass
6**	17659.275	42.89	22.09	54.0	11.11	AV	263.00	200	Vertical	Pass

8) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2225.100	41.85	-10.91	74.0	32.15	Peak	189.00	200	Horizontal	Pass
1**	2225.100	32.09	-10.91	54.0	21.91	AV	189.00	200	Horizontal	Pass
2	3109.800	44.44	-7.86	74.0	29.56	Peak	28.00	100	Horizontal	Pass
2**	3109.800	34.32	-7.86	54.0	19.68	AV	28.00	100	Horizontal	Pass
3	4468.600	47.00	-4.99	74.0	27.00	Peak	152.00	100	Horizontal	Pass
3**	4468.600	35.56	-4.99	54.0	18.44	AV	152.00	100	Horizontal	Pass
4	5762.800	50.22	-0.41	74.0	23.78	Peak	67.00	100	Horizontal	Pass
4**	5762.800	40.23	-0.41	54.0	13.77	AV	67.00	100	Horizontal	Pass
5	6745.600	51.40	1.86	74.0	22.60	Peak	243.00	200	Horizontal	Pass
5**	6745.600	40.47	1.86	54.0	13.53	AV	243.00	200	Horizontal	Pass
6	17648.775	55.39	22.42	74.0	18.61	Peak	30.00	100	Horizontal	Pass
6**	17648.775	42.70	22.42	54.0	11.30	AV	30.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330121	2025.04.16	2026.04.15	☒
Test Antenna-Bi-Log	SCHWARZB ECK	VULB 9163	01414	2023.11.03	2026.11.02	☒
Anechoic Chamber	EMC Electronic Co., Ltd	C8-966	107	2024.05.12	2027.05.11	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.4 en	/		☒
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330121	2025.04.16	2026.04.15	☒
EMI Receiver	R&S	FSV-40	101544	2025.10.30	2026.10.29	☒
Test Antenna-Horn	SCHWARZB ECK	BBHA 9120D	02459	2023.10.26	2026.10.25	☒
Test Antenna-Horn	A-INFOMW	LB-180400KF	J211060273	2024.06.15	2027.06.14	☒
Anechoic Chamber	EMC Electronic Co., Ltd	C8-966	107	2024.05.12	2027.05.11	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.4 en	/		☒

A.2 Conducted Emission, AC Ports

Sample No.	S01+A03+A09	Temperature	25.6℃
Humidity	40%RH	Pressure	101kPa
Test Engineer	Huang Penghui	Test Date	2025.12.09


Test Mode 1

1) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.610	48.27	10.23	56.00	7.73	Peak	L	Pass
1**	0.610	38.82	10.23	46.00	7.18	AV	L	Pass
2	1.114	41.61	10.17	56.00	14.39	Peak	L	Pass
2**	1.114	29.64	10.17	46.00	16.36	AV	L	Pass
3	1.698	41.56	10.25	56.00	14.44	Peak	L	Pass
3**	1.698	29.14	10.25	46.00	16.86	AV	L	Pass
4	2.254	41.01	10.17	56.00	14.99	Peak	L	Pass
4**	2.254	28.83	10.17	46.00	17.17	AV	L	Pass
5	2.634	41.29	10.13	56.00	14.71	Peak	L	Pass
5**	2.634	28.77	10.13	46.00	17.23	AV	L	Pass
6	3.706	40.60	10.34	56.00	15.40	Peak	L	Pass
6**	3.706	29.13	10.34	46.00	16.87	AV	L	Pass

2) AC Ports - N Phase




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.150	48.53	9.86	66.00	17.47	Peak	N	Pass
1**	0.150	31.31	9.86	56.00	24.69	AV	N	Pass
2	0.356	41.88	10.79	58.82	16.94	Peak	N	Pass
2**	0.356	27.46	10.79	48.82	21.36	AV	N	Pass
3	0.612	43.00	10.23	56.00	13.00	Peak	N	Pass
3**	0.612	34.39	10.23	46.00	11.61	AV	N	Pass
4	1.776	37.53	10.23	56.00	18.47	Peak	N	Pass
4**	1.776	27.19	10.23	46.00	18.81	AV	N	Pass
5	5.036	37.37	10.40	60.00	22.63	Peak	N	Pass
5**	5.036	26.08	10.40	50.00	23.92	AV	N	Pass
6	10.828	37.62	10.63	60.00	22.38	Peak	N	Pass
6**	10.828	24.31	10.63	50.00	25.69	AV	N	Pass

Sample No.	S02+A13+A15	Temperature	24.3℃
Humidity	55%RH	Pressure	101.6kPa
Test Engineer	Huang Penghui	Test Date	2026.01.21


Test Mode 1

3) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.150	56.91	9.86	66.00	9.09	Peak	L	Pass
1**	0.150	36.05	9.86	56.00	19.95	AV	L	Pass
2	0.308	49.03	9.98	60.02	10.99	Peak	L	Pass
2**	0.308	29.31	9.98	50.02	20.71	AV	L	Pass
3	0.556	44.39	10.11	56.00	11.61	Peak	L	Pass
3**	0.556	29.65	10.11	46.00	16.35	AV	L	Pass
4	1.910	35.92	10.67	56.00	20.08	Peak	L	Pass
4**	1.910	23.87	10.67	46.00	22.13	AV	L	Pass
5	4.888	35.79	10.24	56.00	20.21	Peak	L	Pass
5**	4.888	24.81	10.24	46.00	21.19	AV	L	Pass
6	18.374	36.54	11.15	60.00	23.46	Peak	L	Pass
6**	18.374	24.79	11.15	50.00	25.21	AV	L	Pass

4) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.154	56.21	9.86	65.78	9.57	Peak	N	Pass
1**	0.154	34.23	9.86	55.78	21.55	AV	N	Pass
2	0.278	50.40	9.82	60.88	10.48	Peak	N	Pass
2**	0.278	30.09	9.82	50.88	20.79	AV	N	Pass
3	0.552	44.55	10.10	56.00	11.45	Peak	N	Pass
3**	0.552	29.97	10.10	46.00	16.03	AV	N	Pass
4	1.904	36.68	10.74	56.00	19.32	Peak	N	Pass
4**	1.904	24.79	10.74	46.00	21.21	AV	N	Pass
5	5.074	36.73	10.36	60.00	23.27	Peak	N	Pass
5**	5.074	24.19	10.36	50.00	25.81	AV	N	Pass
6	20.232	37.27	11.14	60.00	22.73	Peak	N	Pass
6**	20.232	25.25	11.14	50.00	24.75	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038B	MY61380132	2025.04.01	2026.03.31	☒
LISN	SCHWARZBECK	NSLK 8127	01009	2025.07.15	2026.07.14	☒
Shielded Room	YiHeng Electronic Co., Ltd	/	235	2024.11.05	2027.11.04	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.4 en	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ25B1341-AE-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ25B1341-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ25B1341-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--