

TEST REPORT

Applicant: TENG INTERNACIONAL TRADING LIMITED
Address: 4f 299 QRC NOS 287 299 QUEENS RD CENTRAL,
HONG KONG
Equipment Type: Pos Terminal
Model Name: S9
Brand Name: TENG INTERNACIONAL
FCC ID: 2BTGQ-S9
Test Standard: 47 CFR Part 15 Subpart C
ANSI C63.10-2020
Sample Arrival Date: Mar. 30, 2026
Test Date: Apr. 11, 2026 - Apr. 15, 2026
Date of Issue: Jun. 30, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** He Shichang**Checked by:** Xiong Chong**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jun. 30, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Environments.....	7
4.2	Test Setups	7
5	TEST ITEMS	9
5.1	Antenna Requirements	9
5.2	Emission Bandwidth	10
5.3	Field Strength of Fundamental Emissions and Radiated Emissions.....	12
5.4	Frequency Tolerance.....	14
5.5	Conducted Emission.....	15
ANNEX A	TEST RESULT	16
A.1	Emission Bandwidth	16
A.2	Field Strength of Fundamental Emissions.....	19
A.3	Radiated Emissions	21

A.4	Frequency Stability	26
A.5	Conducted Emissions	28
ANNEX B	TEST SETUP PHOTOS	32
ANNEX C	EUT EXTERNAL PHOTOS.....	32
ANNEX D	EUT INTERNAL PHOTOS.....	32

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	601, Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong
	☒ 1/F., Building B, Ganghongji High-Tech Intelligent Industrial Park, No.1008, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	TENG INTERNACIONAL TRADING LIMITED
Address	4f 299 QRC NOS 287 299 QUEENS RD CENTRAL, HONG KONG

2.2 Manufacturer Information

Manufacturer	TENG INTERNACIONAL TRADING LIMITED
Address	4f 299 QRC NOS 287 299 QUEENS RD CENTRAL, HONG KONG

2.3 General Description for Equipment under Test (EUT)

EUT Name	Pos Terminal
Model Name Under Test	S9
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth, WIFI, NFC, GSM, WCDMA, HSDPA, HSUPA, LTE
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	ASK
Frequency Range	13.56 MHz
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Receiver Categorization	3
Number of channel	1
Tested Channel	1
Antenna Type	PIFA Antenna

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional Radiators
2	ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Verdict
1	Antenna Requirement	15.203	Pass ^{Note}
2	Emissions Bandwidth	15.215	Pass
3	Field Strength of Fundamental Emissions	15.225(a)	Pass
4	Radiated Emissions	15.225(d) / 15.209	Pass
5	Frequency Stability	15.225(e)	Pass
6	Conducted Emission	15.207	Pass
Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203			

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)-AMN	3.2 dB
Radiated emissions (30 MHz-1 GHz)-966	5.36 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments


During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.6 V

4.2 Test Setups

Test Setup 1


Radiated Test (Below 30 MHz)



(Diagram 1)

Test Setup 2


Radiated Test (30 MHz-1 GHz)



(Diagram 2)

Test Setup 3

AC Power Supply Port Test



(Diagram 3)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer EUT internal photos.

5.2 Emission Bandwidth

5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

5.2.2 Test Setup

See section 4.2(Diagram 1) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW

RBW = 1% to 5% the OBW

VBW $\geq$ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 1.5 to 5 times the OBW

RBW = 1% to 5% OBW

VBW $\geq$ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

5.3 Field Strength of Fundamental Emissions and Radiated Emissions

5.3.1 Limit

FCC §15.225(a), (b), (c)

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated spurious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBμV/m) = $20\log(X) + 40\log(30/3) = 20\log(15848) + 40\log(30/3) = 124\text{dB}\mu\text{V}$

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency range (MHz)	Field Strength@30m		Field Strength@10m	Field Strength@3m
	μV/m	dBμV/m	dBμV/m	dBμV/m
Below 13.110	30	29.5	48.58	69.5
13.110 ~ 13.410	106	40.5	59.58	80.5
13.410 ~ 13.553	334	50.5	69.58	90.5
13.553 ~13.567	15848	84	103.08	124
13.567 ~ 13.710	334	50.5	69.58	90.5
13.710 ~14.010	106	40.5	59.58	80.5
Above 14.010	30	29.5	48.58	69.5

NOTE:

1. Field Strength (dBμV/m) = $20*\log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dB μ V/m@3m (AV) and 74dB μ V/m@3m (PK).

5.3.2 Test Setup

See section 4.2(Diagram 1 and Diagram 2) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $30 \text{ MHz} < f < 1 \text{ GHz}$, 10 kHz for $150 \text{ kHz} < f < 30 \text{ MHz}$, 300 Hz for $f < 150 \text{ kHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.3.4 Test Result and Test Equipment List

Please refer to ANNEX A.2 and A.3.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit – Results

5.4 Frequency Tolerance

5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.4.2 Test Setup

See section 4.2(Diagram 1) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The test is performed in a Temperature Chamber.
2. The EUT is configured as MS + DC Power Supply.

5.4.4 Test Result and Test Equipment List

Please refer to ANNEX A.4.

5.5 Conducted Emission

5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Setup

See section 4.2(Diagram 3) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.5.4 Test Result and Test Equipment List

Please refer to ANNEX A.5.

NOTE:

1. Results (dBμV) = Reading (dBμV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit – Results

ANNEX A TEST RESULT

A.1 Emission Bandwidth

Note: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.


Sample No.	EE26030471-002-S01 SC-SZ25B0425-A09 SC-SZ25B0425-A03	Temperature	20.4℃
Humidity	65%RH	Pressure	100.7kPa
Test Engineer	Zhou Haonan	Test Date	2026.04.11

Test Data


Frequency (MHz)	Emission Bandwidth (20dB down) (kHz)	Occupied Bandwidth (99%) (kHz)
13.56	25.169	23.344

Test Plots

Emission Bandwidth



99% Occupied Bandwidth



Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	Keysight	N9020A	MY56060127	2025.12.25	2026.12.24	☒
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	01414	2023.11.03	2026.11.02	☒
Anechoic Chamber	EMC Electronic Co., Ltd	966-C13	/	2024.11.25	2027.08.25	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.2 Field Strength of Fundamental Emissions

Note: Field Strength of Fundamental Emissions tests were performed in X, Y, Z axis direction of EUT.
And only the worst axis test condition was recorded in this test report.


Sample No.	EE26030471-002-S01 SC-SZ25B0425-A09 SC-SZ25B0425-A03	Temperature	20.4℃
Humidity	65%RH	Pressure	100.7kPa
Test Engineer	Zhou Haonan	Test Date	2026.04.11

Test Data

Field Strength of Fundamental Emissions Value					
Frequency (MHz)	Detector	Field Strength (dBμV/m)	Limit @10m (dBμV/m)	EUT	Margin (dB)
13.560	PEAK	69.90	124.0	Horizontal	54.10

Test Plots

Test Antenna-LOOP, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	13.560	69.90	20.97	124.0	54.10	Peak	258.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	Keysight	N9020A	MY56060127	2025.12.25	2026.12.24	☒
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	01414	2023.11.03	2026.11.02	☒
Anechoic Chamber	EMC Electronic Co., Ltd	966-C13	/	2024.11.25	2027.08.25	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.3 Radiated Emissions

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.


Note 2: All Radiated Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

(9 kHz ~ 30 MHz)

Sample No.	EE26030471-002-S01 SC-SZ25B0425-A09 SC-SZ25B0425-A03	Temperature	20.4℃
Humidity	65%RH	Pressure	100.7kPa
Test Engineer	Zhou Haonan	Test Date	2026.04.11

The Data and Plots

Below 30 MHz, Test Antenna LOOP, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	0.012	56.99	19.74	126.0	69.01	Peak	360.00	100	Horizontal	Pass
2	0.020	50.65	19.78	121.6	70.95	Peak	360.00	100	Horizontal	Pass
3	0.165	43.61	19.84	103.3	59.69	Peak	254.00	100	Horizontal	Pass
4	0.956	35.19	20.00	68.0	32.81	Peak	176.00	100	Horizontal	Pass
5	6.747	31.99	20.64	69.5	37.51	Peak	62.00	100	Horizontal	Pass
6	13.560	70.44	20.97	69.5	-0.94	Peak	2.00	100	Horizontal	N/A


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 30 MHz						
EMI Receiver	Keysight	N9020A	MY56060127	2025.12.25	2026.12.24	☒
Test Antenna-Loop	SCHWARZBECK	FMZB 1513-60	00015	2024.05.07	2026.05.06	☒
Anechoic Chamber	EMC Electronic Co., Ltd	966-C13	/	2024.11.25	2027.08.25	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

(30 MHz ~ 10th Harmonic)

Sample No.	EE26030471-001-S03 SC-SZ25B0424-A09 SC-SZ25B0424-A03	Temperature	23.3℃
Humidity	57%RH	Pressure	100.2kPa
Test Engineer	Ya Jingtang	Test Date	2026.04.15


The Data and Plots

30 MHz to 1 GHz, Test Antenna Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	31.988	30.18	-26.75	40.0	9.82	Peak	235.00	100	Vertical	Pass
2	52.795	29.34	-24.89	40.0	10.66	Peak	217.00	100	Vertical	Pass
3	58.227	28.33	-25.26	40.0	11.67	Peak	96.00	100	Vertical	Pass
4	132.189	27.17	-25.29	43.5	16.33	Peak	300.00	100	Vertical	Pass
5	284.770	28.79	-22.68	46.0	17.21	Peak	251.00	100	Vertical	Pass
6	393.265	30.02	-19.10	46.0	15.98	Peak	176.00	100	Vertical	Pass

30 MHz to 1 GHz, Test Antenna Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	230.499	28.51	-25.89	46.0	17.49	Peak	169.00	100	Horizontal	Pass
2	257.659	31.65	-24.16	46.0	14.35	Peak	178.00	100	Horizontal	Pass
3	284.770	31.43	-22.68	46.0	14.57	Peak	203.00	100	Horizontal	Pass
4	420.328	31.07	-18.41	46.0	14.93	Peak	360.00	100	Horizontal	Pass
5	447.488	33.76	-17.05	46.0	12.24	Peak	146.00	200	Horizontal	Pass
6	474.599	32.32	-16.69	46.0	13.68	Peak	138.00	200	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 30 MHz						
EMI Receiver	Keysight	N9020A	MY56060127	2025.12.25	2026.12.24	☒
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	01414	2023.11.03	2026.11.02	☒
Anechoic Chamber	EMC Electronic Co., Ltd	966-C13	/	2024.11.25	2027.08.25	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.4 Frequency Stability

Note 1: Because the 85% (3.06V) of the rated supply voltage value lower than (3.30V) limit of the manufacturer, the cut-off voltage of EUT is test here.

Note 2: Because the 115% (4.14V) of the rated supply voltage value lower than (4.20V) limit of the manufacturer, the 115% (4.14V) of the rated supply voltage of EUT is test here.

Sample No.	EE26030471-002-S01 SC-SZ25B0425-A09 SC-SZ25B0425-A03	Temperature	20.4℃
Humidity	65%RH	Pressure	100.7kPa
Test Engineer	Zhou Haonan	Test Date	2026.04.11

OPERATING FREQUENCY:	13560000 Hz
REFERENCE VOLTAGE:	3.60 V
DEVIATION LIMIT:	±0.01%

Test Data

VOLTAGE (%)	Test Conditions		Frequency (Hz)	Deviation (%)	Verdict
	Power (VDC)	Temperature (℃)			
100	3.60	-30	13560025	0.000002	Pass
100		-20	13560050	0.000004	Pass
100		-10	13560075	-0.000002	Pass
100		0	13560100	0.000737	Pass
100		+10	13559975	-0.000002	Pass
100		+20	13559950	-0.000004	Pass
100		+25	13559925	-0.000006	Pass
100		+30	13559900	-0.000007	Pass
100		+40	13559950	-0.000004	Pass
100		+50	13560000	0.000000	Pass
MAX(Battery End Point, 85)	3.30	+20	13560100	0.000007	Pass
MIN(Battery End Point, 115)	4.14	+20	13560150	0.000011	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	Keysight	N9020A	MY56060127	2025.12.25	2026.12.24	☒
Test Antenna-Loop	SCHWARZBECK	FMZB 1513-60	00015	2024.05.07	2026.05.06	☒
Temperature Chamber	AHK	SP20	1412	2025.07.28	2026.07.27	☒
DC Power Supply	ITECH	IT6522D	80064901177 7310013	2025.07.18	2026.07.17	☒
Anechoic Chamber	EMC Electronic Co., Ltd	966-C13	/	2024.11.25	2027.08.25	☒
Description	Supplier	Name	Version	/		Use
Test Software	/	/	/	/		☒


A.5 Conducted Emissions

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Sample No.	EE26030471-002-S01 SC-SZ25B0425-A09 SC-SZ25B0425-A03	Temperature	24.2℃
Humidity	46%RH	Pressure	100.2kPa
Test Engineer	Ya Jingtang	Test Date	2026.04.15


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.156	43.85	9.86	65.67	21.82	Peak	L	Pass
1**	0.156	28.91	9.86	55.67	26.76	AV	L	Pass
2	0.268	41.11	9.82	61.18	20.07	Peak	L	Pass
2**	0.268	25.48	9.82	51.18	25.70	AV	L	Pass
3	0.404	42.70	10.57	57.77	15.07	Peak	L	Pass
3**	0.404	28.97	10.57	47.77	18.80	AV	L	Pass
4	0.578	45.59	10.16	56.00	10.41	Peak	L	Pass
4**	0.578	28.32	10.16	46.00	17.68	AV	L	Pass
5	0.842	43.55	10.67	56.00	12.45	Peak	L	Pass
5**	0.842	28.10	10.67	46.00	17.90	AV	L	Pass
6	1.054	42.89	10.21	56.00	13.11	Peak	L	Pass
6**	1.054	29.36	10.21	46.00	16.64	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.200	44.42	9.84	63.61	19.19	Peak	N	Pass
1**	0.200	28.60	9.84	53.61	25.01	AV	N	Pass
2	0.308	43.06	9.98	60.02	16.96	Peak	N	Pass
2**	0.308	29.54	9.98	50.02	20.48	AV	N	Pass
3	0.538	48.51	10.08	56.00	7.49	Peak	N	Pass
3**	0.538	32.11	10.08	46.00	13.89	AV	N	Pass
4	0.600	47.70	10.22	56.00	8.30	Peak	N	Pass
4**	0.600	31.29	10.22	46.00	14.71	AV	N	Pass
5	0.754	43.85	10.27	56.00	12.15	Peak	N	Pass
5**	0.754	31.98	10.27	46.00	14.02	AV	N	Pass
6	1.172	41.98	10.23	56.00	14.02	Peak	N	Pass
6**	1.172	27.20	10.23	46.00	18.80	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038B	MY61380132	2025.12.26	2026.12.25	☒
LISN	SCHWARZBECK	NSLK 8127	01009	2025.07.15	2026.07.14	☒
Shielded Room	YiHeng Electronic Co., Ltd	/	235	2024.11.05	2027.11.04	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “Ti-EE26040134-AE-2.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26040134-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “Ti-EE26040134-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--