FCC TEST REPORT

FCC ID: 2BTH4-F120

Product	:	quadcopter
Model Name	:	F120, F8620, F220, F320, F420, F716, F720, F8620A, F8620B
Brand	:	N/A
Report No.	:	NCT25039854E1-1

Prepared for

Wuhan Tongpai Technology Co., Ltd.
Room (1), 20th Floor, Unit 1, Building 1, Tianhui Longcheng (Longxinyuan Area B), Panlongcheng, Huangpi District, Wuhan, Hubei China

Prepared by

Shenzhen NCT Testing Technology Co., Ltd.
A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China
TEL: 400-8868-419

1 TEST RESULT CERTIFICATION

Applicant's name	:	Wuhan Tongpai Technology Co., Ltd.
Address	:	Room (1), 20th Floor, Unit 1, Building 1, Tianhui Longcheng (Longxinyuan Area B), Panlongcheng, Huangpi District, Wuhan, Hubei China
Manufacture's name	:	Wuhan Tongpai Technology Co., Ltd.
Address	:	Room (1), 20th Floor, Unit 1, Building 1, Tianhui Longcheng (Longxinyuan Area B), Panlongcheng, Huangpi District, Wuhan, Hubei China
Product name	:	quadcopter
Model name	:	F120, F8620, F220, F320, F420, F716, F720, F8620A, F8620B
Standards	:	FCC CFR47 Part 15 Section 15.247
Test procedure	:	ANSI C63.10:2020
Date of test	:	Sep. 28, 2025-Dec. 12, 2025
Date of Issue	:	Dec. 12, 2025

This device described above has been tested by NCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NCT, this document may be altered or revised by NCT, personal only, and shall be noted in the revision of the document.

Test Engineer:

Keven Wu / Engineer

Technical Manager:

Henry Wang / Manager

Contents

Page

1 TEST RESULT CERTIFICATION 2
2 TEST SUMMARY 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF E.U.T. 6
3.2 CHANNEL LIST 7
3.3 TEST SITE 8
3.4 TEST SETUP CONFIGURATION 8
3.5 TEST MODE 9
4 EQUIPMENT DURING TEST 10
4.1 EQUIPMENTS LIST 10
4.2 MEASUREMENT UNCERTAINTY 12
4.3 DESCRIPTION OF SUPPORT UNITS 12
5 CONDUCTED EMISSION 13
5.1 E.U.T. OPERATION 13
5.2 EUT SETUP 13
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14
5.4 MEASUREMENT PROCEDURE 14
5.5 CONDUCTED EMISSION LIMIT 14
5.6 MEASUREMENT DESCRIPTION 14
5.7 CONDUCTED EMISSION TEST RESULT 14
6 RADIATED SPURIOUS EMISSIONS 15
6.1 EUT OPERATION 15
6.2 TEST SETUP 16
6.3 SPECTRUM ANALYZER SETUP 17
6.4 TEST PROCEDURE 18
6.5 SUMMARY OF TEST RESULTS 19
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT 28
7.1 TEST PROCEDURE 28
7.2 TEST SETUP BLOCKING 28

7.3 TEST RESULT 28
8 6DB&99% BANDWIDTH MEASUREMENT 29
8.1 TEST PROCEDURE 29
8.2 TEST SETUP BLOCKING 29
8.3 TEST RESULT 29
9 MAXIMUM OUTPUT POWER 30
9.1 TEST PROCEDURE 30
9.2 TEST SETUP BLOCKING 30
9.3 TEST RESULT 30
10 POWER SPECTRAL DENSITY 31
10.1 TEST PROCEDURE 31
10.2 TEST SETUP BLOCKING 31
10.3 TEST RESULT 31
11 ANTENNA APPLICATION 32
11.1 ANTENNA REQUIREMENT 32
11.2 RESULT 32
12 TEST SETUP AND EUT PHOTOS 33

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	FCC part 15.207	PASS
Radiated Spurious Emissions	FCC part 15.205/15.209	PASS
Conducted Spurious Emission	FCC part 15. 247(d)	PASS
Band edge	FCC part 15.247(d)	PASS
6dB&99% Bandwidth	FCC part 15.247 (a)(2)	PASS
Maximum Peak Output Power	FCC part 15.247 (b)(3)	PASS
Power Spectral Density	FCC part 15.247 (e)	PASS
Antenna Requirement	FCC part 15.203/15.247 (b)(4)	PASS

Remark:

"N/A" denotes test is not applicable in this Test Report.

3 General Information

3.1 General Description of E.U.T.

Product Name	:	quadcopter
Model Name	:	F120
Sample ID	:	20250928A-001#
Sample(s) Status:	:	Engineer sample
Series Model	:	F8620, F220, F320, F420, F716, F720, F8620A, F8620B
Model Different.:	:	All the same except the model number.
Specification	:	802.11b/g/n HT20
Operation Frequency	:	2412-2462MHz for 802.11b/g/n20;
Number of Channel	:	11 channels for 802.11b/g/n20
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	External Antenna
Antenna Gain	:	4.6 dBi
Power supply	:	DC 3.7V from battery
Hardware Version	:	N/A
Software Version	:	N/A
Remark：the Antenna gain is provided by customer from Antenna spec. and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.		

3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

3.3 Test Site

Site Description

EMC Lab. : Accredited by CNAS, 2022-09-27

The certificate is valid until 2028.01.07

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)

The Certificate Registration Number is L8251

Designation Number: CN1347

Test Firm Registration Number: 894804

Accredited by A2LA, June 14, 2023

The Certificate Registration Number is 6837.01

Accredited by Industry Canada, November 09, 2018

The Conformity Assessment Body Identifier is CN0150

Company Number: 30806

Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.

Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

3.4 Test Setup Configuration

Radiated Emission (30MHz-1GHz)

EUT

Radiated Emission(above 1GHz)

EUT

Conducted Spurious



Note:The test diagram has integrated cable loss to Offset Settings. The cable loss is compensated in the test data.

EIRP=RF Conducted Power+ ANT Gain

3.5 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	WiFiTestTool V1.1.7
Power level setup	0 dBm

4 Equipment During Test

4.1 Equipments List

Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	944 Room	/	EMToni	2025/1/17	2028/1/16
EMI Test Receiver	ESPI	101604	Rohde & Schwarz	2025/6/10	2026/6/09
limitator	ESH3-Z2	NA	Ronde&Schwaz	2025/6/10	2026/6/09
Attenuation	PCL-10dB	221126	HTEC	2025/6/10	2026/6/09
LISN	ENV 216	102796	Rohde & Schwarz	2025/6/10	2026/6/09
LISN	VN1-13S	004023	CRANAGE	2025/6/10	2026/6/09
Cable	RG223-1500MM	NA	RG	2025/6/10	2026/6/09

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2025/1/17	2028/1/16
EMI Test Receiver	ESCI	101178	Rohde & Schwarz	2025/6/10	2026/6/09
Amplifi（30MHz-1GHz）	BBV 9743 B	00374	SCHNWARZBECK	2025/6/10	2026/6/09
Power Meter	ML2495A	10084	Anritu	2025/6/10	2026/6/09
Bilog Antenna（30MHz-1GHz）	VULB9162	00473	SCHNWARZBECK	2025/3/08	2026/3/07
Horn antenna（1GHz-18GHz）	BBHA 9120 D	02622	SCHNWARZBECK	2025/3/10	2026/3/09
Pream plifier（1GHz-18GHz）	BBV 9718D	0024	SCHNWARZBECK	2025/6/10	2026/6/09
Spectrum Analyze（10Hz-40GHz）	FSV 40	100952	Rohde & Schwarz	2025/6/10	2026/6/09
Pream plifier（18GHz-40GHz）	BBV 9721	0056	SCHNWARZBECK	2025/6/10	2026/6/09

Double Ridge Guide Horn Antenna（18GHz-40GHz）	SAS-574	588	A.H.System	2025/3/10	2026/3/09
Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHNWARZBECK	2025/6/10	2026/6/09
Comprehensive tester	CWM500	104995	Rohde & Schwarz	2025/6/10	2026/6/09
Amplifier (9KHz-30MHz)	BBV 9745	00109	CHNWARZBECK	2025/6/10	2026/6/09
MXG Signal Analyzer	N9020A	MY50510202	Agilent	2025/6/10	2026/6/09
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2025/6/10	2026/6/09
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2025/6/10	2026/6/09
Power Sensor	TR1029-2	512364	Techoy	2025/6/10	2026/6/09
RF Swith	TR1029-1	512364	Techoy	2025/6/10	2026/6/09
Cable	DA800-4000MM	NA	DA	2025/6/10	2026/6/09
Cable	DA800-11000MM	NA	DA	2025/6/10	2026/6/09

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ-EMC	Ver.EMC-CON 3A1.1+
2	EMC radiation test system	FALA	EZ-EMC	Ver.FA-03A2 RE+
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10^{-6}
Bandwidth	± 1.5 x 10^{-6}
Time	±2%
Duty Cycle	±2%
Temperature	±1° C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9KHz~30MHz)	±4.51dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Radiated Emission(25GHz~40GHz)	±3.38dB

4.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	quadcopter	N/A	F120	N/A	EUT

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

5 Conducted Emission

Test Requirement:	:	FCC CFR 47 Part 15 Section 15.207
Test Method	:	ANSI C63.10: 2020
Test Result	:	PASS
Frequency Range	:	150kHz to 30MHz
Class/Severity	:	Class B

5.1 E.U.T. Operation

Operating Environment :

Temperature	:	24.5 °C
Humidity	:	51.3 % RH
Atmospheric Pressure	:	101.1kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2020.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:
1. The lower limit shall apply at the transition frequencies
2.The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

The EUT is powered by the Battery, so this test item is not applicable for the EUT.

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method : ANSI C63.10:2020

Test Result : PASS

Measurement Distance : 3m

Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation

Operating Environment :

Temperature: : 24.5°C

Humidity: : 52 % RH

Atmospheric Pressure: : 101.1kPa

Test Voltage : DC 3.6V

6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site

The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz

6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.

5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

6. Repeat above procedures until the measurements for all frequencies are complete.

7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room

6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:

Temperature:	24.5°C	Relative Humidity:	52%
Pressure:	101.1 kPa	Polarization:	Horizontal
Test Voltage:	DC3.7V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	280.0237	52.84	-13.92	38.92	46.00	-7.08	QP
2	319.9370	51.26	-13.37	37.89	46.00	-8.11	QP
3	336.0350	50.88	-13.04	37.84	46.00	-8.16	QP
4	400.4318	50.54	-11.56	38.98	46.00	-7.02	QP
5	480.5276	47.01	-9.95	37.06	46.00	-8.94	QP
6	744.8660	44.99	-5.50	39.49	46.00	-6.51	QP

Temperature:	24.5°C	Relative Humidity:	52%
Pressure:	101.1kPa	Polarization:	Vertical
Test Voltage:	DC3.7V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	159.7844	44.97	-18.62	26.35	43.50	-17.15	QP
2	239.9873	46.55	-15.08	31.47	46.00	-14.53	QP
3	280.0237	50.94	-13.92	37.02	46.00	-8.98	QP
4	601.4265	47.27	-8.82	38.45	46.00	-7.55	QP
5	696.8567	43.97	-6.39	37.58	46.00	-8.42	QP
6	793.3960	43.91	-4.53	39.38	46.00	-6.62	QP

Remark:Emission Level=Reading+Cable Loss+ANT Factor

Test Frequency: From 1GHz to 18GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	45.94	34.11	5.04	32.44	49.31	74.00	-24.69	PK
V	4824.00	35.32	34.11	5.04	32.44	38.69	54.00	-15.31	AV
V	7236.00	43.64	32.57	6.30	35.89	53.26	74.00	-20.74	PK
V	7236.00	30	32.57	6.30	35.89	39.62	54.00	-14.38	AV
V	9648.00	35.78	32.96	7.56	38.40	48.78	74.00	-25.22	PK
V	9648.00	23.36	32.96	7.56	38.40	36.36	54.00	-17.64	AV
V	12060.00	34.95	32.06	8.92	39.01	50.82	74.00	-23.18	PK
V	12060.00	23.04	32.06	8.92	39.01	38.91	54.00	-15.09	AV
H	4824.00	45.05	34.11	5.04	32.44	48.42	74.00	-25.58	PK
H	4824.00	37.04	34.11	5.04	32.44	40.41	54.00	-13.59	AV
H	7236.00	42.06	32.57	6.30	35.89	51.68	74.00	-22.32	PK
H	7236.00	29.89	32.57	6.30	35.89	39.51	54.00	-14.49	AV
H	9648.00	35.33	32.96	7.56	38.40	48.33	74.00	-25.67	PK
H	9648.00	25.94	32.96	7.56	38.40	38.94	54.00	-15.06	AV
H	12060.00	34.71	32.06	8.92	39.01	50.58	74.00	-23.42	PK
H	12060.00	25.26	32.06	8.92	39.01	41.13	54.00	-12.87	AV

Radiated Band Emission Measuremen:

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	47.09	34.08	5.08	32.57	50.66	74.00	-23.34	PK
V	4874.00	38.86	34.08	5.08	32.57	42.43	54.00	-11.57	AV
V	7311.00	45.00	32.62	6.34	35.95	54.67	74.00	-19.33	PK
V	7311.00	34.01	32.62	6.34	35.95	43.68	54.00	-10.32	AV
V	9748.00	42.49	32.93	7.58	38.40	55.54	74.00	-18.46	PK
V	9748.00	31.98	32.93	7.58	38.40	45.03	54.00	-8.97	AV
V	12185.00	40.25	31.97	8.89	39.04	56.21	74.00	-17.79	PK
V	12185.00	27.09	31.97	8.89	39.04	43.05	54.00	-10.95	AV
H	4874.00	43.65	34.08	5.08	32.57	47.22	74.00	-26.78	PK
H	4874.00	33.87	34.08	5.08	32.57	37.44	54.00	-16.56	AV
H	7311.00	43.52	32.62	6.34	35.95	53.19	74.00	-20.81	PK
H	7311.00	33.40	32.62	6.34	35.95	43.07	54.00	-10.93	AV
H	9748.00	42.71	32.93	7.58	38.40	55.76	74.00	-18.24	PK
H	9748.00	30.15	32.93	7.58	38.40	43.20	54.00	-10.80	AV
H	12185.00	36.64	31.97	8.89	39.04	52.60	74.00	-21.40	PK
H	12185.00	26.38	31.97	8.89	39.04	42.34	54.00	-11.66	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	47.05	34.05	5.14	32.79	50.93	74.00	-23.07	PK
V	4924.00	35.07	34.05	5.14	32.79	38.95	54.00	-15.05	AV
V	7386.00	40.24	32.67	6.36	35.99	49.92	74.00	-24.08	PK
V	7386.00	28.91	32.67	6.36	35.99	38.59	54.00	-15.41	AV
V	9848.00	41.71	32.89	7.59	38.37	54.78	74.00	-19.22	PK
V	9848.00	28.58	32.89	7.59	38.37	41.65	54.00	-12.35	AV
V	12310.00	34.70	31.88	8.82	39.06	50.70	74.00	-23.30	PK
V	12310.00	22.34	31.88	8.82	39.06	38.34	54.00	-15.66	AV
H	4924.00	44.26	34.05	5.14	32.79	48.14	74.00	-25.86	PK
H	4924.00	36.84	34.05	5.14	32.79	40.72	54.00	-13.28	AV
H	7386.00	45.45	32.67	6.36	35.99	55.13	74.00	-18.87	PK
H	7386.00	28.12	32.67	6.36	35.99	37.80	54.00	-16.20	AV
H	9848.00	37.38	32.89	7.59	38.37	50.45	74.00	-23.55	PK
H	9848.00	25.76	32.89	7.59	38.37	38.83	54.00	-15.17	AV
H	12310.00	38.01	31.88	8.82	39.06	54.01	74.00	-19.99	PK
H	12310.00	26.46	31.88	8.82	39.06	42.46	54.00	-11.54	AV

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. We test all the mode and recorded the worst mode (802.11b) in the report.

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Detector Type	Result
802.11b	Low Channel 2412MHz										
	H	2390.00	57.80	35.17	3.48	27.49	53.60	74.00	-20.4	PK	PASS
	H	2390.00	49.49	35.17	3.48	27.49	45.29	54.00	-8.71	AV	PASS
	H	2400.00	60.55	35.16	3.49	27.52	56.40	74.00	-17.6	PK	PASS
	H	2400.00	49.82	35.16	3.49	27.52	45.67	54.00	-8.33	AV	PASS
	V	2390.00	57.51	35.17	3.48	27.49	53.31	74.00	-20.69	PK	PASS
	V	2390.00	50.07	35.17	3.48	27.49	45.87	54.00	-8.13	AV	PASS
	V	2400.00	59.84	35.16	3.49	27.52	55.69	74.00	-18.31	PK	PASS
	V	2400.00	49.93	35.16	3.49	27.52	45.78	54.00	-8.22	AV	PASS
	High Channel 2462MHz										
	H	2483.50	58.23	35.11	3.56	27.75	54.43	74.00	-19.57	PK	PASS
	H	2483.50	48.54	35.11	3.56	27.75	44.74	54.00	-9.26	AV	PASS
	H	2500.00	59.42	35.10	3.57	27.80	55.69	74.00	-18.31	PK	PASS
	H	2500.00	50.02	35.10	3.57	27.80	46.29	54.00	-7.71	AV	PASS
	V	2483.50	58.40	35.11	3.56	27.75	54.60	74.00	-19.4	PK	PASS
	V	2483.50	49.77	35.11	3.56	27.75	45.97	54.00	-8.03	AV	PASS
	V	2500.00	58.73	35.10	3.57	27.80	55.00	74.00	-19	PK	PASS
	V	2500.00	49.97	35.10	3.57	27.80	46.24	54.00	-7.76	AV	PASS
802.11g	Low Channel 2412MHz										
	H	2390.00	57.80	35.17	3.48	27.49	53.60	74.00	-20.4	PK	PASS
	H	2390.00	49.63	35.17	3.48	27.49	45.43	54.00	-8.57	AV	PASS
	H	2400.00	60.32	35.16	3.49	27.52	56.17	74.00	-17.83	PK	PASS

	H	2400.00	49.86	35.16	3.49	27.52	45.71	54.00	-8.29	AV	PASS
	V	2390.00	57.31	35.17	3.48	27.49	53.11	74.00	-20.89	PK	PASS
	V	2390.00	49.93	35.17	3.48	27.49	45.73	54.00	-8.27	AV	PASS
	V	2400.00	59.63	35.16	3.49	27.52	55.48	74.00	-18.52	PK	PASS
	V	2400.00	49.88	35.16	3.49	27.52	45.73	54.00	-8.27	AV	PASS
	High Channel 2462MHz										
	H	2483.50	58.13	35.11	3.56	27.75	54.33	74.00	-19.67	PK	PASS
	H	2483.50	48.53	35.11	3.56	27.75	44.73	54.00	-9.27	AV	PASS
	H	2500.00	59.68	35.10	3.57	27.80	55.95	74.00	-18.05	PK	PASS
	H	2500.00	50.08	35.10	3.57	27.80	46.35	54.00	-7.65	AV	PASS
	V	2483.50	58.63	35.11	3.56	27.75	54.83	74.00	-19.17	PK	PASS
	V	2483.50	49.92	35.11	3.56	27.75	46.12	54.00	-7.88	AV	PASS
	V	2500.00	58.28	35.10	3.57	27.80	54.55	74.00	-19.45	PK	PASS
	V	2500.00	50.47	35.10	3.57	27.80	46.74	54.00	-7.26	AV	PASS
802.11 n20	Low Channel 2412MHz										
	H	2390.00	57.53	35.17	3.48	27.49	53.33	74.00	-20.67	PK	PASS
	H	2390.00	49.68	35.17	3.48	27.49	45.48	54.00	-8.52	AV	PASS
	H	2400.00	60.37	35.16	3.49	27.52	56.22	74.00	-17.78	PK	PASS
	H	2400.00	49.34	35.16	3.49	27.52	45.19	54.00	-8.81	AV	PASS
	V	2390.00	57.64	35.17	3.48	27.49	53.44	74.00	-20.56	PK	PASS
	V	2390.00	50.44	35.17	3.48	27.49	46.24	54.00	-7.76	AV	PASS
	V	2400.00	59.45	35.16	3.49	27.52	55.30	74.00	-18.7	PK	PASS
	V	2400.00	49.86	35.16	3.49	27.52	45.71	54.00	-8.29	AV	PASS
	High Channel 2462MHz										
	H	2483.50	58.02	35.11	3.56	27.75	54.22	74.00	-19.78	PK	PASS
	H	2483.50	48.99	35.11	3.56	27.75	45.19	54.00	-8.81	AV	PASS

	H	2500.00	59.21	35.10	3.57	27.80	55.48	74.00	-18.52	PK	PASS
	H	2500.00	49.98	35.10	3.57	27.80	46.25	54.00	-7.75	AV	PASS
	V	2483.50	58.49	35.11	3.56	27.75	54.69	74.00	-19.31	PK	PASS
	V	2483.50	49.91	35.11	3.56	27.75	46.11	54.00	-7.89	AV	PASS
	V	2500.00	58.59	35.10	3.57	27.80	54.86	74.00	-19.14	PK	PASS
	V	2500.00	50.12	35.10	3.57	27.80	46.39	54.00	-7.61	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

Shenzhen NCT Testing Technology Co., Ltd. 2008

7 Conduct Band Edge And Spurious Emissions Measurement

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2020
Test Limit	:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Setup Blocking



7.3 Test Result

Please see the Appendix for the data

8 6dB&99% Bandwidth Measurement

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2020
Test Limit		Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW = 3*RBW for 6dB bandwidth
3. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW = 3*RBW for 99% bandwidth

8.2 Test Setup Blocking

EUT — spectrum analyzer

8.3 Test Result

Please see the Appendix for the data

9 Maximum Output Power

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2020
Test Limit	:	Regulation 15.247 (b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

9.1 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

9.2 Test Setup Blocking



9.3 Test Result

Please see the Appendix for the data

10 Power Spectral density

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2020
Test Limit	:	Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz, Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

10.2 Test Setup Blocking



10.3 Test Result

Please see the Appendix for the data

11 Antenna Application

11.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 Result

The EUT'S antenna, permanent attached antenna, is External Antenna. The antenna's gain is 4.6 dBi and meets the requirement.

12 Test Setup and EUT Photos

Reference to the attachment for details.

******THE END REPORT******