



RADIO TEST REPORT

Applicant	:	Shenzhen Arzopa Technology Incorporated Company
Address of Applicant	:	1602, Xingtong Building, No. 88, Baoxing Road, Haiwang Community, Xin 'an Sub-district, Bao 'an District, Shenzhen, Guangdong, China
Manufacturer	:	Shenzhen Arzopa Technology Incorporated Company
Address of Manufacturer	:	1602, Xingtong Building, No. 88, Baoxing Road, Haiwang Community, Xin 'an Sub-district, Bao 'an District, Shenzhen, Guangdong, China
Equipment under Test	:	C1Pro Smart Calendar (17.35-inch)
Model No.	:	C03HR01C1
FCC ID	:	2BTIM-C03HR01C1
IC	:	34917-C03HR01C1
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63.10-2020+Cor.1-2023+C63.10a- 2024+Errata to C63.10a-2024
Report No.	:	DDT-RE26061007-1E01
Issue Date	:	2026/08/18
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	8
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result.....	14
4.5.	Test graphs	15
5.	99% Bandwidth	18
5.1.	Block diagram of test setup	18
5.2.	Limits	18
5.3.	Test procedure	18
5.4.	Test result.....	19
5.5.	Test graphs	20
6.	Conducted Output Power	23
6.1.	Block diagram of test setup	23
6.2.	Limits	23
6.3.	Test procedure	23
6.4.	Test result average.....	24
7.	Power Spectral Density	25
7.1.	Block diagram of test setup	25
7.2.	Limits	25
7.3.	Test procedure	25
7.4.	Test result.....	26
7.5.	Test graphs	27
8.	Band Edge Compliance (Conducted Method).....	30
8.1.	Block diagram of test setup	30

8.2.	Limits	30
8.3.	Test procedure	30
8.4.	Test result.....	31
8.5.	Test graphs	32
9.	RF Conducted Spurious Emissions.....	34
9.1.	Block diagram of test setup	34
9.2.	Limits	34
9.3.	Test procedure	34
9.4.	Test result.....	35
9.5.	Test graphs	36
10.	Duty Cycle	45
10.1.	Block diagram of test setup	45
10.2.	Limit.....	45
10.3.	Test procedure	45
10.4.	Test result.....	46
10.5.	Test graphs	47
11.	Antenna Requirements.....	50
11.1.	Limit.....	50
11.2.	Result	50
12.	Radiated Emission	51
12.1.	Test equipment.....	51
12.2.	Block diagram of test setup	52
12.3.	Limits	54
12.4.	Assistant equipment used for test	56
12.5.	Test procedure	56
12.6.	Test result.....	57
12.7.	Test data	58
13.	Band Edge Compliance.....	66
13.1.	Test equipment.....	66
13.2.	Block diagram of test setup	66
13.3.	Limits	67
13.4.	Assistant equipment used for test	67
13.5.	Test procedure	67
13.6.	Test result.....	67
13.7.	Test data	67
14.	Power Line Conducted Emissions.....	80
14.1.	Test equipment.....	80
14.2.	Block diagram of test setup	80

14.3. Limits80

14.4. Assistant equipment used for test81

14.5. Test procedure81

14.6. Test result.....81

14.7. Test data82

15. Test Setup Photograph84

16. Photos of the EUT86

Test Report Declare

Applicant	:	Shenzhen Arzopa Technology Incorporated Company
Address of Applicant	:	1602, Xingtong Building, No. 88, Baoxing Road, Haiwang Community, Xin 'an Sub-district, Bao 'an District, Shenzhen, Guangdong, China
Equipment under Test	:	C1Pro Smart Calendar (17.35-inch)
Model No.	:	C03HR01C1
Manufacturer	:	Shenzhen Arzopa Technology Incorporated Company
Address of Manufacturer	:	1602, Xingtong Building, No. 88, Baoxing Road, Haiwang Community, Xin 'an Sub-district, Bao 'an District, Shenzhen, Guangdong, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020,
RSS-247 Issue 4 July 24, 2025,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26061007-1E01		
Date of Receipt:	2026/06/16	Date of Test:	2026/06/23 - 2026/07/24

Created: Jacky Huang	Reviewed: Tiger Mo	Approved: Damon Hu
		
2026/08/02	2026/08/18	2026/08/18

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/08/18	Damon Hu

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2), RSS-247 clause 6.3.1(a), RSS-Gen clause 6.7	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3), RSS-247 clause 6.3.2	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e), RSS-247 clause 6.3.1(b)	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 4 7 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: C1Pro Smart Calendar (17.35-inch)
Model Number	: C03HR01C1
EUT Function Description	: Please reference user manual of this device
Power Supply	: Input: 12.0V = 2.5A by external adapter
Antenna Type	: FPC
Max Antenna Gain (dBi)	: 2.63
Radio Technology	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412MHz to 2462MHz IEEE 802.11g: 2412MHz to 2462MHz IEEE 802.11n HT20: 2412MHz to 2462MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)


Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
USB C-C cable	/	/	Length: 1.75m, without core
Adapter	SHENZHEN PUSHIDA ELECTRONIC TECHNOLOGY CO.,LTD	PSD16-C-EU	INPUT: 100-240V~50/60Hz 0.8A Max TYPE-C OUTPUT: 5.0V=3.0A/9.0V=3.0A/12.0V=2.5A/15.0V=2.0A/20.0V=1.5A 30.0W PPS: 3.3-11.0V=2.7A

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: adb.exe

The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Data rate, Channel, and Frequency				
Tested mode	Tx Power Setting	Data rate (Mbps) (see Note)	Test Channel	Frequency (MHz)
	ANT1			
IEEE 802.11b	Default	1	LCH: CH1	2412
		1	MCH: CH6	2437
		1	HCH: CH11	2462
IEEE 802.11g	12	6	LCH: CH1	2412
		6	MCH: CH6	2437
		6	HCH: CH11	2462
IEEE 802.11n HT20	14	MCS 0	LCH: CH1	2412
		MCS 0	MCH: CH6	2437
		MCS 0	HCH: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.				

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9\text{ kHz} \leq f < 7\text{ GHz}$);
	3.31 dB ($7\text{ GHz} \leq f < 40\text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
☒ RF Connected Test (RF Measurement System 1#)					
SIGNAL ANALYZER	R&S	FSQ26	101272	2027/02/27	1 Year
Wideband Radio Communication Tester	R&S	CMW500	117491	2027/02/27	1 Year
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2027/02/27	1 Year
MXG Vector Signal Generator	Agilent	N5182A	MY47420658	2027/02/27	1 Year
RF Control Unit	Tonscend	JS0806-2	158060010	2027/02/27	1 Year
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/27	1 Year
Test Software	Tonscend	JS1120-3	V3.6.21	N/A	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW: 100 kHz

VBW: $\geq [3 \times \text{RBW}]$

Detector Mode: peak

Sweep time: auto

Trace mode: max hold


- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.


4.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	7.68	2407.96	2415.64	0.5	PASS
		2437	7.72	2433.32	2441.04	0.5	PASS
		2462	7.76	2457.88	2465.64	0.5	PASS
11G	Ant1	2412	14.68	2404.44	2419.12	0.5	PASS
		2437	14.64	2429.84	2444.48	0.5	PASS
		2462	14.16	2454.56	2468.72	0.5	PASS
11N20SISO	Ant1	2412	12.64	2404.96	2417.60	0.5	PASS
		2437	15.08	2429.84	2444.92	0.5	PASS
		2462	13.72	2454.16	2467.88	0.5	PASS

4.5. Test graphs








5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	peak
Sweep time:	auto
Trace mode:	max hold


- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005

Test Mode	Antenna	Channel Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	11.920	2406.0400	2417.9600	---	---
		2437	12.000	2431.1200	2443.1200	---	---
		2462	12.240	2455.8400	2468.0800	---	---
11G	Ant1	2412	17.160	2403.3200	2420.4800	---	---
		2437	17.240	2428.4000	2445.6400	---	---
		2462	17.080	2453.2800	2470.3600	---	---
11N20SISO	Ant1	2412	18.120	2402.8800	2421.0000	---	---
		2437	18.200	2427.9600	2446.1600	---	---
		2462	18.120	2452.8000	2470.9200	---	---

[illegible]





11N20SISO_Ant1_2462

Ref 20 dBm

Att 20 dB

RBW 500 kHz

VBW 2 MHz

SWF 5 ns

Marker 1 [T1]

11.31 dBm

2.462000000 GHz

CBW/8.120000000 MHz

Temp 1 [T1] -2.18 dBm


2.452800000 GHz

Temp 2 [T1] -1.65 dBm

2.470820000 GHz

6. Conducted Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.2.3.
- (2) Connect EUT's antenna output to RF power meter by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously, If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal.
- (4) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- (5) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.
- (6) Record the RF average power of each antenna port.


6.4. Test result average

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005

Test Mode	Antenna	Frequency [MHz]	Average power [dBm]	Duty Cycle [%]	DC Factor [dB]	Result [dBm]	Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	18.81	98.94	0.00	18.81	≤30.00	21.44	≤36.00	PASS
		2437	18.55	98.95	0.00	18.55	≤30.00	21.18	≤36.00	PASS
		2462	18.15	98.83	0.00	18.15	≤30.00	20.78	≤36.00	PASS
11G	Ant1	2412	14.51	92.72	0.33	14.84	≤30.00	17.47	≤36.00	PASS
		2437	14.34	92.72	0.33	14.67	≤30.00	17.30	≤36.00	PASS
		2462	14.06	93.33	0.30	14.36	≤30.00	16.99	≤36.00	PASS
11N20SISO	Ant1	2412	16.11	92.25	0.35	16.46	≤30.00	19.09	≤36.00	PASS
		2437	15.85	92.25	0.35	16.20	≤30.00	18.83	≤36.00	PASS
		2462	15.62	92.96	0.32	15.94	≤30.00	18.57	≤36.00	PASS

7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency: DTS Channel center frequency

RBW: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$

VBW: $\geq 3\text{RBW}$

Span: 1.5 times the DTS bandwidth

Detector Mode: RMS

Sweep time: auto

Trace mode: max hold

Trace: Employ trace averaging (rms) mode over a minimum of 100 traces.

- (5) Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
- (6) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005




Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-10.17	≤8.00	PASS
		2437	-10.46	≤8.00	PASS
		2462	-11.43	≤8.00	PASS
11G	Ant1	2412	-13.17	≤8.00	PASS
		2437	-13.14	≤8.00	PASS
		2462	-13.68	≤8.00	PASS
11N20SISO	Ant1	2412	-13.75	≤8.00	PASS
		2437	-13.53	≤8.00	PASS
		2462	-13.84	≤8.00	PASS

Note: The Duty Cycle Factor is compensated in the graph.

7.5. Test graphs








8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	auto
Trace mode:	Max hold


- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#		
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17		
Test Power Supply:	AC 120V	Sample Number:	S26061007-005		

EUT Set Mode	CH or Frequency	Result (dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	/	/	/
	CH11	Pass		/	/


8.5. Test graphs





9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency:	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span:	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode:	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:


RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Number of measurement points:	$\geq \text{Span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode:	Max hold
- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


9.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005

EUT Set Mode	CH or Frequency	Result (dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	/	/	/
	CH6	Pass		/	/
	CH11	Pass		/	/

9.5. Test graphs





11B_Ant1_2437_1000~26500

Ref 28.8 dBm

Offset 26.7 dB

Att 20 dB

RBW 100 kHz

VBW 300 kHz

SWF 2.6 s

Marker 2 [T1]

-37.60 dBm

24.819650000 GHz

Marker 1 [T1]


15.36 dBm

2.437301000 GHz

1 R

VB

Start 1 GHz 2.55 GHz/ Stop 26.5 GHz



11B_Ant1_2462_1000~26500

Ref 28.8 dBm

Off set 26.7 dB

Att 20 dB

RBW 100 kHz

VBW 300 kHz

SWF 2.6 s

Marker 2 [T1]

-37.83 dBm

24.522000000 GHz




Marker 1 [T1]

15.17 dBm

2.462500000 GHz

Date: 16. JUL. 2026 11:11:24









11N20SISO_Ant1_2412_1000~26500

Ref 28.8 dBm

Off set 26.7 dB

Att 20 dB

RBW 100 kHz

VBW 300 kHz

SWF 2.6 s

Marker 2 [T1]

-38.01 dBm

24.828050000 GHz

Marker 1 [T1]

12.83 dBm

2.412700000 GHz


Date: 16. JUL. 2026 10: 56: 26





10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset. set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger


- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

10.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 1#
Ambient Condition:	27.7-28.6℃,40.1-45.2%RH	Test Date:	2026.7.16-2026.7.17
Test Power Supply:	AC 120V	Sample Number:	S26061007-005

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2412	8.43	8.52	98.94
		2437	8.45	8.54	98.95
		2462	8.44	8.54	98.83
11G	Ant1	2412	1.40	1.51	92.72
		2437	1.40	1.51	92.72
		2462	1.40	1.50	93.33
11N20SISO	Ant1	2412	1.31	1.42	92.25
		2437	1.31	1.42	92.25
		2462	1.32	1.42	92.96

10.5. Test graphs







11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

11.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

12. Radiated Emission

12.1. Test equipment


Below 1GHz:



Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18	1 Year
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25	1 Year
				2026/07/06	1 Year
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/	/
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2026/10/10	1 Year
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2026/10/10	1 Year
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2026/10/10	1 Year

Above 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/	/
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC05922	2027/01/06	1 Year
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10	1 Year
				2026/07/04	1 Year
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25	1 Year
				2026/07/06	1 Year
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27	1 Year
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10	1 Year
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/	/
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4

8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement distance (m)
9 - 490 kHz ¹	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak)	
		54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Notebook	Lenovo	i5-5300U	Test comptuer	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT through three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

(12) The worst simultaneous case and was recorded.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-23

Tested By:

Li Xiongbin

Test Mode:

TX 11B 2412 MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.3°C;Humi:58.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC Below 1G\7

Memo:

Sample Number:S26061007-004




Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	104.730	47.54	11.33	4.33	30.90	43.50	12.60	QP	Horizontal
2	112.732	45.43	11.49	4.37	28.98	43.50	14.52	QP	Horizontal
3	175.959	44.85	9.76	4.74	26.97	43.50	16.53	QP	Horizontal
4	190.869	49.66	10.16	4.83	32.26	43.50	11.24	QP	Horizontal
5	268.933	52.43	12.40	5.16	37.59	46.00	8.41	QP	Horizontal
6	395.760	45.04	15.08	5.69	33.31	46.00	12.69	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-06-23**Tested By:** Li Xiongbín**Test Mode:** TX 11B 2412 MHz Mode**Power Supply:** AC 120V/60Hz**Condition:** Temp:22.3°C;Humi:58.1%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2026 report data\Q26061007-1E\FCC Below 1G\8**Memo:** Sample Number:S26061007-004**Final Data List**


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	39.214	53.53	12.26	3.91	37.40	40.00	2.60	QP	Vertical
2	99.784	53.75	11.87	4.30	37.62	43.50	5.88	QP	Vertical
3	105.024	56.15	11.58	4.33	39.75	43.50	3.75	QP	Vertical
4	111.630	53.97	11.96	4.37	37.99	43.50	5.51	QP	Vertical
5	136.898	48.01	7.98	4.51	28.16	43.50	15.34	QP	Vertical
6	176.083	47.83	9.76	4.74	29.95	43.50	13.55	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-24 **Tested By:** Cao Jie
Test Mode: TX 11B 2412MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:21.1°C;Humi:47.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\7
Memo: Sample Number:S26061007-004 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4224.000	53.12	31.95	-41.47	43.60	74.00	30.40	PK	Horizontal
2	4752.000	52.53	33.01	-41.72	43.82	74.00	30.18	PK	Horizontal
3	7392.000	50.99	37.23	-40.18	48.04	74.00	25.96	PK	Horizontal
4	8427.000	47.81	38.21	-39.23	46.79	74.00	27.21	PK	Horizontal
5	11073.000	44.30	39.70	-35.94	48.06	74.00	25.94	PK	Horizontal
6	12109.500	41.54	39.90	-34.14	47.30	74.00	26.70	PK	Horizontal

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7392.000	47.84	37.23	-40.18	44.89	54.00	9.11	AV	Horizontal
2	11073.000	32.24	39.70	-35.94	36.00	54.00	18.00	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-24 **Tested By:** Cao Jie
Test Mode: TX 11B 2412MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:21.1°C;Humi:47.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\8
Memo: Sample Number:S26061007-004 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4224.000	54.06	31.95	-41.47	44.54	74.00	29.46	PK	Vertical
2	4752.000	57.07	33.01	-41.72	48.36	74.00	25.64	PK	Vertical
3	7392.000	52.83	37.23	-40.18	49.88	74.00	24.12	PK	Vertical
4	8266.500	47.64	37.93	-39.27	46.30	74.00	27.70	PK	Vertical
5	10731.000	43.74	40.00	-35.72	48.02	74.00	25.98	PK	Vertical
6	12375.000	42.72	39.73	-34.64	47.81	74.00	26.19	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4752.000	53.30	33.01	-41.72	44.59	54.00	9.41	AV	Vertical
2	7392.000	48.48	37.23	-40.18	45.53	54.00	8.47	AV	Vertical
3	10731.000	33.40	40.00	-35.72	37.68	54.00	16.32	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-24

Tested By:

Cao Jie

Test Mode:

TX 11B 2437MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.1°C;Humi:47.3%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\9

Memo:

Sample Number:S26061007-004 Power Setting:NA



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3960.000	52.88	31.68	-41.74	42.82	74.00	31.18	PK	Horizontal
2	4752.000	52.70	33.01	-41.72	43.99	74.00	30.01	PK	Horizontal
3	7309.500	54.41	37.64	-40.36	51.69	74.00	22.31	PK	Horizontal
4	8278.500	47.39	37.96	-39.29	46.06	74.00	27.94	PK	Horizontal
5	10795.500	43.79	40.00	-35.96	47.83	74.00	26.17	PK	Horizontal
6	11566.500	43.63	39.67	-35.31	47.99	74.00	26.01	PK	Horizontal

Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7309.500	50.99	37.64	-40.36	48.27	54.00	5.73	AV	Horizontal


Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-24 **Tested By:** Cao Jie
Test Mode: TX 11B 2437MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:21.1°C;Humi:47.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\10
Memo: Sample Number:S26061007-004 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4224.000	53.75	31.95	-41.47	44.23	74.00	29.77	PK	Vertical
2	4752.000	57.16	33.01	-41.72	48.45	74.00	25.55	PK	Vertical
3	7315.500	52.95	37.61	-40.35	50.21	74.00	23.79	PK	Vertical
4	7392.000	53.75	37.23	-40.18	50.80	74.00	23.20	PK	Vertical
5	8367.000	47.71	38.03	-39.36	46.38	74.00	27.62	PK	Vertical
6	11574.000	42.58	39.65	-35.28	46.95	74.00	27.05	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4752.000	53.68	33.01	-41.72	44.97	54.00	9.03	AV	Vertical
2	7315.500	50.47	37.61	-40.35	47.73	54.00	6.27	AV	Vertical
3	7392.000	50.88	37.23	-40.18	47.93	54.00	6.07	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-24

Tested By:

Cao Jie

Test Mode:

TX 11B 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.1°C;Humi:47.3%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\11

Memo:

Sample Number:S26061007-004 Power Setting:NA



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3696.000	53.33	30.68	-41.58	42.43	74.00	31.57	PK	Horizontal
2	4224.000	52.48	31.95	-41.47	42.96	74.00	31.04	PK	Horizontal
3	4875.000	50.53	33.45	-41.61	42.37	74.00	31.63	PK	Horizontal
4	7389.000	54.80	37.24	-40.18	51.86	74.00	22.14	PK	Horizontal
5	8257.500	47.62	37.92	-39.25	46.29	74.00	27.71	PK	Horizontal
6	11569.500	43.45	39.66	-35.30	47.81	74.00	26.19	PK	Horizontal

Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7389.000	51.56	37.24	-40.18	48.62	54.00	5.38	AV	Horizontal


Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-24 **Tested By:** Cao Jie
Test Mode: TX 11B 2462MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:21.1°C;Humi:47.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061007-1E\FCC ABOVE 1G 2.4G\12
Memo: Sample Number:S26061007-004 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4224.000	55.14	31.95	-41.47	45.62	74.00	28.38	PK	Vertical
2	4752.000	57.45	33.01	-41.72	48.74	74.00	25.26	PK	Vertical
3	7392.000	52.96	37.23	-40.18	50.01	74.00	23.99	PK	Vertical
4	8158.500	47.25	37.90	-39.33	45.82	74.00	28.18	PK	Vertical
5	10695.000	43.52	39.99	-35.61	47.90	74.00	26.10	PK	Vertical
6	11662.500	44.28	39.54	-35.35	48.47	74.00	25.53	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4752.000	53.84	33.01	-41.72	45.13	54.00	8.87	AV	Vertical
2	7392.000	49.93	37.23	-40.18	46.98	54.00	7.02	AV	Vertical
3	11662.500	35.25	39.54	-35.35	39.44	54.00	14.56	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/	/
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC05922	2027/01/06	1 Year
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10 2026/07/04	1 Year 1 Year
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25 2026/07/06	1 Year 1 Year
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27	1 Year
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10	1 Year
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/	/

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Notebook	Lenovo	i5-5300U	Test comptuer	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.


13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-07-15	Tested By:	Cao Jie
Test Mode:	TX 11B 2412MHz Mode	Power Supply:	AC 120V/60Hz
Condition:	Temp:21.0°C;Humi:52.9%	Test Site:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\11		
Memo:	Sample Number:S26061007-004 Power Setting:NA		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.540	20.00	27.47	5.98	0.00	53.45	74.00	20.55	PK	Horizontal
2	2390.000	17.48	27.46	5.98	0.00	50.92	74.00	23.08	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2388.540	13.05	27.47	5.98	46.50	54.00	7.50	AV	Horizontal	
2	2390.000	14.30	27.46	5.98	47.74	54.00	6.26	AV	Horizontal	

- Note:
- 1. Level = Reading + Cable loss + Antenna Factor + AMP
 - 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 - 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11B 2412MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\12

Memo:

Sample Number:S26061007-004 Power Setting:NA



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2382.562	20.30	27.50	5.98	0.00	53.78	74.00	20.22	PK	Vertical
2	2390.000	18.80	27.46	5.98	0.00	52.24	74.00	21.76	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2382.562	13.29	27.50	5.98	46.77	54.00	7.23	AV	Vertical	
2	2390.000	13.84	27.46	5.98	47.28	54.00	6.72	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11B 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\13

Memo:

Sample Number:S26061007-004 Power Setting:NA



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	16.95	27.54	6.02	0.00	50.51	74.00	23.49	PK	Horizontal
2	2486.058	19.84	27.56	6.02	0.00	53.42	74.00	20.58	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	14.32	27.54	6.02	47.88	54.00	6.12	AV	Horizontal	
2	2486.058	13.86	27.56	6.02	47.44	54.00	6.56	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11B 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\14

Memo:

Sample Number:S26061007-004 Power Setting:NA



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	17.33	27.54	6.02	0.00	50.89	74.00	23.11	PK	Vertical
2	2486.875	19.35	27.57	6.02	0.00	52.94	74.00	21.06	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	13.93	27.54	6.02	47.49	54.00	6.51	AV	Vertical	
2	2486.875	13.64	27.57	6.02	47.23	54.00	6.77	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11G 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\15

Memo:

Sample Number:S26061007-004 Power Setting:12



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	23.58	27.54	6.02	0.00	57.14	74.00	16.86	PK	Horizontal
2	2484.595	26.76	27.55	6.02	0.00	60.33	74.00	13.67	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.498	16.30	27.54	6.02	49.86	54.00	4.14	AV	Horizontal	
2	2484.595	16.07	27.55	6.02	49.64	54.00	4.36	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11G 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\16

Memo:

Sample Number:S26061007-004 Power Setting:12



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	20.42	27.54	6.02	0.00	53.98	74.00	20.02	PK	Vertical
2	2484.400	23.23	27.54	6.02	0.00	56.79	74.00	17.21	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	15.48	27.54	6.02	49.04	54.00	4.96	AV	Vertical	
2	2484.400	15.24	27.54	6.02	48.80	54.00	5.20	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11G 2412MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\17

Memo:

Sample Number:S26061007-004 Power Setting:12



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.616	23.66	27.47	5.98	0.00	57.11	74.00	16.89	PK	Horizontal
2	2390.000	22.85	27.46	5.98	0.00	56.29	74.00	17.71	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2387.616	14.86	27.47	5.98	48.31	54.00	5.69	AV	Horizontal	
2	2390.000	15.37	27.46	5.98	48.81	54.00	5.19	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11G 2412MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\18

Memo:

Sample Number:S26061007-004 Power Setting:12



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.392	23.71	27.48	5.98	0.00	57.17	74.00	16.83	PK	Vertical
2	2390.000	22.04	27.46	5.98	0.00	55.48	74.00	18.52	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2387.392	14.38	27.48	5.98	47.84	54.00	6.16	AV	Vertical	
2	2390.000	14.53	27.46	5.98	47.97	54.00	6.03	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11N20 2462MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\19

Memo:

Sample Number:S26061007-004 Power Setting:14



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	23.86	27.54	6.02	0.00	57.42	74.00	16.58	PK	Horizontal
2	2485.623	26.43	27.56	6.02	0.00	60.01	74.00	13.99	PK	Horizontal


Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.499	17.04	27.54	6.02	50.60	54.00	3.40	AV	Horizontal	
2	2485.623	16.74	27.56	6.02	50.32	54.00	3.68	AV	Horizontal	

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-15 **Tested By:** Cao Jie
Test Mode: TX 11N20 2462MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:21.0°C;Humi:52.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\20
Memo: Sample Number:S26061007-004 Power Setting:14



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	21.36	27.54	6.02	0.00	54.92	74.00	19.08	PK	Vertical
2	2483.980	23.70	27.54	6.02	0.00	57.26	74.00	16.74	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	15.59	27.54	6.02	49.15	54.00	4.85	AV	Vertical
2	2483.980	15.42	27.54	6.02	48.98	54.00	5.02	AV	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11N20 2412MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\21

Memo:

Sample Number:S26061007-004 Power Setting:14



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.358	26.87	27.47	5.98	0.00	60.32	74.00	13.68	PK	Horizontal
2	2390.000	24.43	27.46	5.98	0.00	57.87	74.00	16.13	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2388.358	16.63	27.47	5.98	50.08	54.00	3.92	AV	Horizontal	
2	2390.002	17.03	27.46	5.98	50.47	54.00	3.53	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-15

Tested By:

Cao Jie

Test Mode:

TX 11N20 2412MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.0°C;Humi:52.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26061007-1E\FCC ABOVE 1G 2.4G\22

Memo:

Sample Number:S26061007-004 Power Setting:14



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.722	25.28	27.47	5.98	0.00	58.73	74.00	15.27	PK	Vertical
2	2390.000	24.82	27.46	5.98	0.00	58.26	74.00	15.74	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2388.722	15.76	27.47	5.98	49.21	54.00	4.79	AV	Vertical	
2	2390.000	14.94	27.46	5.98	48.38	54.00	5.62	AV	Vertical	

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
EMI Test Receiver	R&S	ESCI 3	DDT-ZC00235	2027/06/10	1 Year
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2027/06/14	1 Year
Pulse Limiter	SCHWARZBECK	ESH3-Z2	DDT-ZC00539	2027/06/10	1 Year
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2027/06/21	1 Year
Conducted & Radiated Software	Audix	e3	DDT-ZC00562	/	/
Two-line V-shaped artificial network	ROHDE&SCHWARZ	ENV216	DDT-ZC05693	2026/11/04	1 Year
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2027/06/09	1 Year

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Notebook	Lenovo	i5-5300U	Test comptuer	/

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “---” means Peak detection; “---” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2026 CE Report Data\Q26061007-1E\0625 CE.EM6

Test Date : 2026-06-25

Tested By : Li Xiongbin

Power Supply : AC 120V/60Hz


Test Mode : 11B 2412MHz TX Mode

Condition : TEMP:26.1°C, RH:65.4%

LISN : 2025 1# 216/LINE

Memo : S26061007-004

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBuV)	Limit Line (dBuV)	Margin (dB)	Detector	Phase
1	0.17	14.03	9.84	0.05	9.89	33.81	65.21	31.40	QP	LINE
2	0.17	3.67	9.84	0.05	9.89	23.45	55.21	31.76	Average	LINE
3	0.32	12.41	9.68	0.06	9.89	32.04	59.62	27.58	QP	LINE
4	0.32	2.21	9.68	0.06	9.89	21.84	49.62	27.78	Average	LINE
5	0.36	15.24	9.66	0.07	9.89	34.86	58.78	23.92	QP	LINE
6	0.36	9.12	9.66	0.07	9.89	28.74	48.78	20.04	Average	LINE
7	0.39	25.45	9.68	0.08	9.89	45.10	58.08	12.98	QP	LINE
8	0.39	18.08	9.68	0.08	9.89	37.73	48.08	10.35	Average	LINE
9	0.68	11.55	9.95	0.12	9.89	31.51	56.00	24.49	QP	LINE
10	0.68	4.78	9.95	0.12	9.89	24.74	46.00	21.26	Average	LINE
11	7.98	18.61	10.02	0.24	9.84	38.71	60.00	21.29	QP	LINE
12	7.98	10.48	10.02	0.24	9.84	30.58	50.00	19.42	Average	LINE

Note:


1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room
Test Date : 2026-06-25
Power Supply : AC 120V/60Hz
Condition : TEMP:26.1°C, RH:65.4%
Memo : S26061007-004

D:\2026 CE Report Data\Q26061007-1E\0625 CE.EM6
Tested By : Li Xiongbín
Test Mode : 11B 2412MHz TX Mode
LISN : 2025 1# 216/NEUTRAL

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.16	13.07	9.71	0.05	9.89	32.72	65.30	32.58	QP	NEUTRAL
2	0.16	0.63	9.71	0.05	9.89	20.28	55.30	35.02	Average	NEUTRAL
3	0.23	11.04	9.84	0.06	9.89	30.83	62.48	31.65	QP	NEUTRAL
4	0.23	0.47	9.84	0.06	9.89	20.26	52.48	32.22	Average	NEUTRAL
5	0.36	11.85	9.90	0.07	9.89	31.71	58.78	27.07	QP	NEUTRAL
6	0.36	5.23	9.90	0.07	9.89	25.09	48.78	23.69	Average	NEUTRAL
7	0.39	21.50	9.83	0.07	9.89	41.29	58.12	16.83	QP	NEUTRAL
8	0.39	14.94	9.83	0.07	9.89	34.73	48.12	13.39	Average	NEUTRAL
9	0.72	7.42	9.91	0.12	9.90	27.35	56.00	28.65	QP	NEUTRAL
10	0.72	-1.35	9.91	0.12	9.90	18.58	46.00	27.42	Average	NEUTRAL
11	7.89	15.42	9.96	0.24	9.84	35.46	60.00	24.54	QP	NEUTRAL
12	7.89	6.14	9.96	0.24	9.84	26.18	50.00	23.82	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

16. Photos of the EUT

Please refer to DDT-Q26061007-2E appendix I

-----End Report-----