

Prüfbericht-Nr.: <i>Test report no.:</i>	CN26J4E3 002	Auftrags-Nr.: <i>Order no.:</i>	168584456	Seite 1 von 25 Page 1 of 25
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-11-17	
Auftraggeber: <i>Client:</i>	Moga Technology Co., Ltd. 6-201 Room, business street, Huashan Road, Longshan district, Economic and Technological Development Area, Wuhu 241000 Anhui, P.R. China			
Prüfgegenstand: <i>Test item:</i>	AiMOGA Mornine			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	M1			
Auftrags-Inhalt: <i>Order content:</i>	Test Report			
Prüfgrundlage: <i>Test specification:</i>	CFR Title 47 FCC Part 15: Subpart E Section 15.407 RSS-247 Issue 4 July 2025 RSS-Gen Issue 5 February 2021			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2026-02-12	Please refer to photo documents		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A004209761-001~009			
Prüfzeitraum: <i>Testing period:</i>	2026-03-19 - 2026-04-01			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>			genehmigt von: <i>authorized by:</i>	
Datum: <i>Date:</i>	2026-06-05	Ausstellungsdatum: <i>Issue date:</i>		2026-06-05
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:		Sachverständige(r)/Expert
Sonstiges / <i>Other:</i>	FCC ID: 2BTJ8MORNINEM1 IC: 34938-MORNINEM1 HVIN: M1 This report is for 5GHz Wi-Fi.			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26J4E3 002
Test report no.:

Seite 2 von 25
Page 2 of 25

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 FREQUENCY STABILITY

RESULT: Pass

5.1.5 26dB BANDWIDTH AND 99% BANDWIDTH

RESULT: Pass

5.1.6 6dB BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	12
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	12
3.5	SUBMITTED DOCUMENTS.....	12
4	TEST SET-UP AND OPERATION MODES	13
4.1	PRINCIPLE OF CONFIGURATION SELECTION	13
4.2	TEST OPERATION AND TEST SOFTWARE.....	13
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	13
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	13
4.5	TEST SETUP DIAGRAM	14
5	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	15
5.1.1	<i>Antenna Requirement</i>	<i>15</i>
5.1.2	<i>Maximum Conducted Output Power</i>	<i>16</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>19</i>
5.1.4	<i>Frequency Stability.....</i>	<i>20</i>
5.1.5	<i>26dB Bandwidth and 99% Bandwidth</i>	<i>21</i>
5.1.6	<i>6dB Bandwidth</i>	<i>22</i>
5.1.7	<i>Radiated Spurious Emission</i>	<i>23</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	24
7	LIST OF TABLES.....	25

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 5GHz Wi-Fi (Transmitter AP6256)

Appendix B: Test Results of 5GHz Wi-Fi (Transmitter RTL8852BE)

Appendix C: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

FCC Accreditation Designation No.: 694916

ISED wireless device testing laboratory: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (SRD-Tonscend)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Wireless Connectivity Tester	R&S	CMW270	102505	2025-09-23	2026-09-22
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2025-09-23	2026-09-22
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2025-09-23	2026-09-22
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2025-09-23	2026-09-22
DC power supply	Keysight	E3642A	MY61276100	2025-09-23	2026-09-22
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2025-09-23	2026-09-22
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2025-09-23	2026-09-22
Test Software	Tonscend	JS1120-3	N/A	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A	N/A
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13
Unwanted Emission Testing (TS9975)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2025-09-22	2026-09-21
Signal Analyzer	R&S	FSV 40	101439	2025-09-22	2026-09-21
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2025-09-22	2026-09-21
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2025-09-22	2026-09-21
Amplifier	R&S	SCU-18F	180070	2025-09-22	2026-09-21
Amplifier	R&S	SCU40A	100475	2025-09-22	2026-09-21
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-09-28	2026-09-27
Double-Ridged	ETS-LINDGREN	3117	00218717	2024-09-28	2026-09-27

Antenna (1-18 GHz)					
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2024-09-28	2026-09-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2024-09-28	2026-09-27
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-09-14	2027-09-13

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. File for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The Product is an AiMOGA Mornine which support 2.4GHz Wi-Fi, 5GHz Wi-Fi and Lora wireless technologies.

For details refer to the User Manual, Technical Description and Circuit Diagram.

Note: The device will be power off when in charging and wireless link will be disabled, thus FCC Part 15.207 AC Conducted emission is not required.

3.2 Ratings and System Details

Table 3: General Information of EUT

General Information of EUT	Value
Kind of Equipment:	AiMOGA Mornine
Type Designation:	M1
FCC ID:	2BTJ8MORNINEM1
IC:	34938-MORNINEM1
HVIN:	M1
Operating Voltage:	46.8Vdc Battery Powered
Test Voltage:	46.8Vdc Battery Powered
Radiofrequency operating mode:	1) 2.4GHz Wi-Fi: operating within 2400-2483.5MHz 2) 5GHz Wi-Fi: operating within 5150-5250MHz, 5745-5825MHz 3) Lora: 902-928MHz

This device has two Wi-Fi transmitters, Transmitter AP6256 and RTL8852BE, both of them are tested respectively.

Table 4: Technical Specification of Transmitter AP6256

Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)
Type of Modulation:	DSSS, OFDM
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0~MCS 7 for 802.11n(HT20) (All data rates considered, only the Worst-cases reported)
Channel Number:	11 channels for 802.11b/g/n(HT20)
Channel Separation:	5 MHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx
Antenna Gain:	2.8 dBi (Provided by the Client)
Technical Specification of 5GHz Wi-Fi	
Operating Frequency:	5180-5240MHz, 5745-5825MHz
Protocol:	802.11 a/n20/n40/ac20/ac40/ac80
Channel Number:	5180-5240MHz, 7CHs 5745-5825MHz, 8CHs
Type of Modulation:	OFDM
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0~MCS7 for 802.11n MCS0~MCS9 for 802.11ac (All data rates considered, only the Worst-cases reported.)
Channel Separation:	20MHz, 40MHz, 80MHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx
Antenna Gain:	3.5 dBi (Provided by the Client)

Table 5: Technical Specification of Transmitter RTL8852BE

Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)/ax(HE20) 2422 - 2452 MHz for 802.11n(HT40)/ax(HE20)
Type of Modulation:	DSSS, OFDM, OFDMA
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0~MCS 7 for 802.11n MCS0~MCS 11 for 802.11ax (All data rates considered, only the Worst-cases reported.)
Channel Number:	11 channels for 802.11b/g/n(HT20)/ax(HE20) 7 channels for 802.11n(HT40)/ax(HE40)
Channel Separation:	5 MHz
Antenna Type:	Internal Antennas (The internal antennas with SMA connector are within the transmitter's enclosure and cannot be accessed.)
Antenna Number:	2Tx2Rx
Antenna Gain:	0.6 dBi for ANT1 / ANT2 (Provided by the Client)
Smart Antenna Systems:	☒ 802.11b ☒ SISO, ☒ 2*2 CDD,

	☒ 802.11n	☒ SISO, ☒ 2*2 CDD,				
	☒ 802.11ax	☒ SISO, ☒ 2*2 MIMO(Beamforming)				
RU Mode for 802.11ax:	☒ Full RU					
Technical Specification of 5GHz Wi-Fi						
Operating Frequency:	5180-5240MHz, 5745-5825MHz					
Protocol:	802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80					
Channel Number:	5180-5240MHz, 7CHs 5745-5825MHz, 8CHs					
Type of Modulation:	OFDM, OFDMA					
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0~MCS7 for 802.11n MCS0~MCS9 for 802.11ac MCS0 ~ MCS11 for 802.11ax (All data rates considered, only the Worst-cases reported.)					
Channel Separation:	20MHz, 40MHz, 80MHz					
Antenna Type:	Internal Antennas (The internal antennas with SMA connector are within the transmitter's enclosure and cannot be accessed.)					
Antenna Number:	2Tx2Rx					
Antenna Gain:	ANT1 / ANT2 (Provided by the Client) 5180-5240MHz: 1.81dBi 5745-5825MHz: 2.02dBi					
Smart Antenna Systems:	☒ 802.11a	☒ SISO, ☒ 2*2 CDD,				
	☒ 802.11n	☒ SISO, ☒ 2*2 CDD,				
	☒ 802.11ac	☒ SISO, ☒ 2*2 MIMO (Beamforming)				
	☒ 802.11ax	☒ SISO, ☒ 2*2 MIMO(Beamforming)				
RU Mode for 802.11ax	☒ Full RU					
Antenna Type	Frequency Band (MHz)	Peak Antenna Gain (dBi)		Beamforming Directional Gain (dBi)	CDD Directional Gain (dBi)	
		Ant 1	Ant 2		For Power	For PSD
Integral Antennas	2400~2483.5MHz	0.6	0.6	3.6	0.6	3.6
	5150~5250MHz	1.81	1.81	4.81	1.81	4.81
	5725~5850MHz	2.02	2.02	5.02	2.02	5.02
1. The device supports CDD Mode and Beamforming mode, details refer to the table as below. 2. CDD signals are correlated, the directional gain as follows, When NSS=1, for power measurements: Array Gain = 0 dB for NANT ≤4, the directional gain = max antenna gain + array gain For power spectral density (PSD) measurements: the max directional gain= 10 log [(10^(G1 /20) + 10^(G2 /20)+ ... + (10^GN) /20)^2 /NANT] 3. Beamforming signals are correlated, the directional gain as follows, the max directional gain = 10 log[(10^(G1 /20) + 10^(G2 /20)+ ... + (10^GN) /20)^2 /NANT] 4. The information as above is from the antenna specifications.						

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 6: RF Channel and Frequency of 5GHz Wi-Fi

U-NII-1					
20MHz Bandwidth		40MHz Bandwidth		80MHz Bandwidth	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

U-NII-3					
20MHz Bandwidth		40MHz Bandwidth		80MHz Bandwidth	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, 5G Wi-Fi wireless transmitting mode
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - User Manual |
| - Operation Description | - FCC/IC Label and Location Info |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024.

According to clause 3.1, all tests were performed in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 7: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Laptop	Lenovo	T480	PF-16A6N8
DC Power Supply	KIKUSUI	PAN35-5A	YM002997

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.203
RSS-247 clause 6.8

The EUT has Internal Antennas, within the transmitter's enclosure and cannot be accessed, no consideration of replacement, refer to section 3.2 for details.

Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: **CN26J4E3 002**
Test Report No.:Seite 16 von 25
Page 16 of 25

5.1.2 Maximum Conducted Output Power

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.407(a)(1)&(2)&(4) RSS-247 clause 7.3
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: FCC: <250mW (24dBm) (5150-5250MHz) <1W (30dBm) (5725-5850MHz) IC: * Max e.i.r.p.<200mW (23dBm) (5150-5250MHz) *200 mW (23dBm) or 10 dBm + 10 logB, where B is the 99% emission bandwidth in MHz, where is lesser. Max conducted output power <1W (30dBm) (5725-5850MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-19 to 2026-03-27
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

Table 8: Test Result of Maximum Output Power, Transmitter AP6256

Test Mode	Channel	Maximum Power		Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Verdict
		(dBm)	(W)				
802.11 a	5180	12.62	0.0183	≤24.00	16.12	≤22.30	PASS
	5200	17.99	0.0630	≤24.00	21.49	≤22.30	PASS
	5240	18.45	0.0700	≤24.00	21.95	≤22.30	PASS
	5745	17.70	0.0589	≤30.00	21.20	≤36.00	PASS
	5785	17.73	0.0593	≤30.00	21.23	≤36.00	PASS
	5825	17.7	0.0589	≤30.00	21.20	≤36.00	PASS
802.11 n20	5180	17.76	0.0597	≤24.00	21.26	≤22.55	PASS
	5200	17.77	0.0598	≤24.00	21.27	≤22.55	PASS
	5240	18.08	0.0643	≤24.00	21.58	≤22.55	PASS
	5745	17.51	0.0564	≤30.00	21.01	≤36.00	PASS
	5785	17.46	0.0557	≤30.00	20.96	≤36.00	PASS
	5825	17.41	0.0551	≤30.00	20.91	≤36.00	PASS
802.11 n40	5190	17.19	0.0524	≤24.00	20.69	≤23.00	PASS
	5230	17.44	0.0555	≤24.00	20.94	≤23.00	PASS
	5755	17.36	0.0545	≤30.00	20.86	≤36.00	PASS
	5795	17.28	0.0535	≤30.00	20.78	≤36.00	PASS
802.11 ac20	5180	12.13	0.0163	≤24.00	15.63	≤22.55	PASS
	5200	17.45	0.0556	≤24.00	20.95	≤22.55	PASS
	5240	17.87	0.0612	≤24.00	21.37	≤22.55	PASS
	5745	17.29	0.0536	≤30.00	20.79	≤36.00	PASS
	5785	17.36	0.0545	≤30.00	20.86	≤36.00	PASS
	5825	17.20	0.0525	≤30.00	20.7	≤36.00	PASS
802.11 ac40	5190	10.01	0.0100	≤24.00	20.59	≤23.00	PASS
	5230	17.30	0.0537	≤24.00	13.51	≤23.00	PASS
	5755	17.28	0.0535	≤30.00	20.78	≤36.00	PASS
	5795	17.24	0.0530	≤30.00	20.74	≤36.00	PASS
802.11 ac80	5210	6.18	0.0041	≤24.00	9.68	≤23.00	PASS
	5775	17.22	0.0527	≤30.00	20.72	≤36.00	PASS

Note:

- 1) The Duty Cycle Factor is compensated in the graph.
- 2) Antenna gain(G): 3.5dBi, e.i.r.p.=P(Conducted power)+ G
- 3) B is the 99% emission bandwidth in MHz

Table 9: Test Result of Maximum Output Power, Transmitter RTL8852BE

Test Mode	Channel	Maximum Power MIMO		Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Verdict
		(dBm)	(W)		MIMO		
802.11 a	5180	17.33	0.0541	≤24.00	19.14	≤22.17	PASS
	5200	17.06	0.0508	≤24.00	18.87	≤22.17	PASS
	5240	17.67	0.0585	≤24.00	19.48	≤22.17	PASS
	5745	18.86	0.0769	≤30.00	20.88	≤36.00	PASS
	5785	18.95	0.0785	≤30.00	20.97	≤36.00	PASS
	5825	18.78	0.0755	≤30.00	20.80	≤36.00	PASS
802.11 n20	5180	17.04	0.0506	≤24.00	18.85	≤22.46	PASS
	5200	17.03	0.0505	≤24.00	18.84	≤22.46	PASS
	5240	17.27	0.0533	≤24.00	19.08	≤22.46	PASS
	5745	18.51	0.0710	≤30.00	20.53	≤36.00	PASS
	5785	19.01	0.0796	≤30.00	21.03	≤36.00	PASS
	5825	19.06	0.0805	≤30.00	21.08	≤36.00	PASS
802.11 n40	5190	17.34	0.0542	≤24.00	19.15	≤23.00	PASS
	5230	17.15	0.0519	≤24.00	18.96	≤23.00	PASS
	5755	18.36	0.0685	≤30.00	20.38	≤36.00	PASS
	5795	18.14	0.0652	≤30.00	20.16	≤36.00	PASS
802.11 ac20	5180	14.72	0.0296	≤24.00	19.53	≤22.48	PASS
	5200	15.21	0.0332	≤24.00	20.02	≤22.48	PASS
	5240	15.29	0.0338	≤24.00	20.10	≤22.48	PASS
	5745	18.83	0.0764	≤30.00	23.85	≤36.00	PASS
	5785	18.80	0.0759	≤30.00	23.82	≤36.00	PASS
	5825	18.68	0.0738	≤30.00	23.70	≤36.00	PASS
802.11 ac40	5190	14.61	0.0289	≤24.00	19.42	≤23.00	PASS
	5230	15.23	0.0333	≤24.00	20.04	≤23.00	PASS
	5755	18.53	0.0713	≤30.00	23.55	≤36.00	PASS
	5795	18.63	0.0729	≤30.00	23.65	≤36.00	PASS
802.11 ac80	5210	14.65	0.0292	≤24.00	19.46	≤23.00	PASS
	5775	18.35	0.0684	≤30.00	23.37	≤36.00	PASS
802.11 ax20	5180	15.22	0.0333	≤24.00	20.03	≤22.78	PASS
	5200	14.86	0.0306	≤24.00	19.67	≤22.78	PASS
	5240	15.07	0.0321	≤24.00	19.88	≤22.78	PASS
	5745	18.53	0.0713	≤30.00	23.55	≤36.00	PASS
	5785	18.30	0.0676	≤30.00	23.32	≤36.00	PASS
	5825	18.23	0.0665	≤30.00	23.25	≤36.00	PASS
802.11 ax40	5190	15.24	0.0334	≤24.00	20.05	≤23.00	PASS
	5230	14.76	0.0299	≤24.00	19.57	≤23.00	PASS
	5755	17.88	0.0614	≤30.00	22.90	≤36.00	PASS
	5795	17.78	0.0600	≤30.00	22.80	≤36.00	PASS
802.11 ax80	5210	14.84	0.0305	≤24.00	19.65	≤23.00	PASS
	5775	17.78	0.0600	≤30.00	22.80	≤36.00	PASS

Note: Both MIMO and SISO tested, only the worst-case MIMO listed.

Note:

1) The Duty Cycle Factor is compensated for in the above tables.

2) Antenna gain(G):

5180-5240MHz: 1.81dBi

5745-5825MHz: 2.02dBi

e.i.r.p.=P(Conducted power)+ G

3) B is the 99% emission bandwidth in MHz

4) Only the worst case was presented in this report.

5.1.3 Conducted Power Spectral Density

RESULT:**Pass****Test Specification**

Test standard	: FCC part 15.407(a) RSS-247 clause 7.3
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024 KDB 789033 D02 v01r03
Limits	: FCC: <11dBm/MHz (5150-5250MHz 5250-5350MHz, 5470- 5725MHz) <30dBm/500kHz (5725-5850MHz) IC: e.i.r.p. spectral density <10dBm/MHz (5150-5250MHz) <30dBm/500kHz (5725-5850MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-19 to 2026-03-27
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN26J4E3 002
Test Report No.:

Seite 20 von 25
Page 20 of 25

5.1.4 Frequency Stability

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.407(g) RSS-Gen Clause 6.11
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Within assigned bands
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-19 to 2026-03-27
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: **CN26J4E3 002**
Test Report No.:Seite 21 von 25
Page 21 of 25**5.1.5 26dB Bandwidth and 99% Bandwidth****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.407 RSS-Gen Clause 6.7
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: N/A
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-19 to 2026-03-27
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: **CN26J4E3 002**
Test Report No.:Seite 22 von 25
Page 22 of 25

5.1.6 6dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.407(e) RSS-247 clause 7.3.4.2
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: At least 500kHz (5725-5850MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-19 to 2026-03-27
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

5.1.7 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.407(b) & FCC Part 15.205 & FCC Part 15.209 RSS-247 clause 7.3 & RSS-GEN clause 8.9 and 8.10
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024 KDB 789033 D02 v01r03
Limits	: • For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. • For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. • Restricted Bands meet the requirement of 15.209 limit and RSS-GEN
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2026-03-29 to 2026-04-01
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

Remark: Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A, B.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix C.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: General Information of EUT	8
Table 4: Technical Specification of Transmitter AP6256.....	9
Table 5: Technical Specification of Transmitter RTL8852BE	9
Table 6: RF Channel and Frequency of 5GHz Wi-Fi.....	11
Table 7: List of Accessories and Auxiliary Equipment.....	13
Table 8: Test Result of Maximum Output Power, Transmitter AP6256	17
Table 9: Test Result of Maximum Output Power, Transmitter RTL8852BE.....	18