

Dates of Tests: Nov 05, 2025 ~ Dec 08, 2025
Test Report S/N: LR500112512F
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2BTK2-B253M-CYE-V1

APPLICANT

YG PLUS, INC.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	OFFICIAL LIGHT STICK
Manufacturer	:	HUIZHOU DELI INDUSTRY CO., LTD.
Model name	:	CLOSE YOUR EYES OFFICIAL LIGHT STICK
Variant Model name	:	-
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2020
Frequency Range	:	2402 ~ 2480 MHz BLE
Max. Output Power	:	Max -2.27 dBm - Conducted
Data of issue	:	Dec 12 ,2025

This test report is issued under the authority of:



Eun-Hwan Jung, Manager

The test was supervised by:



In-Sun Lee, Test Engineer

Revision history

Revision	Date of issue	Description	Revised by
--	Dec 12 ,2025	Initial	-

TABLE OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 RF EXPOSURE EVULATION----- 6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2027-02-27	FCC CAB
VCCI	JAPAN	C-14948	2026-09-10	VCCI registration
VCCI	JAPAN	T-12416	2026-09-10	VCCI registration
VCCI	JAPAN	R-14483	2026-10-15	VCCI registration
VCCI	JAPAN	G-10847	2027-12-13	VCCI registration
IC	CANADA	5799A-1	2026-08-05	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : YG PLUS, INC.
 Address : 19F, Three IFC, 10, Gukjegeumyung-ro, Yeongdeungpo-gu, Seoul, South Korea
 Tel / Fax : +82-10-8942-7990 / +82-70-4405-2111
 Manufacturer : HUIZHOU DELI INDUSTRY CO., LTD.
 Address : NO.13, NO. 6, SONGSHAN INDUSTRIAL ZONE, ZHONGKAI HIGH-TECH DEVELOPMENT ZONE, HUICHENG DISTRICT, HUIZHOU CITY, GUANGDONG, CHINA
 Tel / Fax : +86 752 2508123 / +86 752 2511196

2-2 Equipment Under Test (EUT)

Model name : CLOSE YOUR EYES OFFICIAL LIGHT STICK
 Serial number : Identical prototype
 Date of receipt : Nov 05, 2025
 EUT condition : Pre-production, not damaged
 Antenna type : Pattern Antenna (Gain : 2.1 dBi)
 Frequency Range : 2402 ~ 2480 MHz
 RF output power : Max -2.27 dBm – Conducted
 Type of Modulation : GFSK
 Power Source : DC 4.5 V

*This product includes a voltage regulation circuit, and the testing was conducted at DC 4.5 V among the available supply voltages of DC 4.5 V and DC 5 V

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	2402	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

3.2 RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz
* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (0.59 * 1.62) / (4 * 5^2 * \pi)$ $S = 0.000\ 2\ \text{mW/cm}^2$	Where, S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
---	---

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 3 dBm $\pm$ 0.5dB)

2.4GHz Mode

Max Peak output Power at antenna input terminal	-2.27	dBm
Max Peak output Power at antenna input terminal	0.59	mW
Prediction distance	5	mm
Prediction frequency	2402	MHz
Antenna Gain(typical)	2.1	dBi
Antenna Gain(numeric)	1.62	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance $\leq$ 5 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [0.59 / 5] * [\sqrt{2.402}] = 0.078 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.