



FCC TEST REPORT

FCC ID: 2BTKU-GP-D425

Product	:	Thermal Barcode Printer, Barcode Label Printer, Thermal Label Printer
Model Name	:	GP-D425(Additional Models refer to page 5)
Brand	:	N/A
Report No.	:	PTC26051124401E-FC03
Prepared for		
Zhuhai Howbest Label Printer Co., Ltd		
2/F, NO.168 Yile Road, Pingsha Town, Zhuhai, China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



TEST RESULT CERTIFICATION

Applicant's name : Zhuhai Howbest Label Printer Co., Ltd

Address : 2/F, NO.168 Yile Road, Pingsha Town, Zhuhai, China

Manufacture's name : Zhuhai Howbest Label Printer Co., Ltd

Address : 2/F, NO.168 Yile Road, Pingsha Town, Zhuhai, China

Product name : Thermal Barcode Printer, Barcode Label Printer, Thermal Label Printer

Model name : GP-D425(Additional Models refer to page 5)

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Jun. 02, 2026 to Jun. 15, 2026

Date of Issue : Jun. 15, 2026

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



Report No.: PTC26051124401E-FC03

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC CFR47 Part 1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Thermal Barcode Printer, Barcode Label Printer, Thermal Label Printer
Model Name	:	GP-D425
Additional Models	:	GP-420D,GP-1120D,GP-1121D,GP-1122D,GP-1123D,GP-1126D,GP-1127D,GP-1128D,GP-1129D,GP-1204B,GP-1214B,GP-1224B,GP-1234B,GP-1244B,GP-1254B,GP-1264B,GP-1274B,GP-1284B,GP-1294B,S-4120A,S-4121A,S-4122A,S-4123A,S-4124A,S-4125A,S-4126A,S-4127A,S-4128A,S-4129A,GP-D424,GP-1320D,GP-1321D,GP-1322D,GP-1323D,GP-1326D,GP-1327D,GP-1328D,GP-1329D,GP-1204D,GP-1214D,GP-1234D,GP-1244D,GP-1254D,GP-1264D,GP-1274D,GP-1284D,GP-1294D,S-4120A,S-4121A,S-4122A,S-4123A,S-4124A,S-4125A,S-4126A,S-4127A,S-4128A,S-4129A,GP-428D,GP-1228D,GP-1221D,GP-1227D,GP-1228D,GP-1229D,S-4120E,S-4121E,S-4122E,S-4123E,S-4124E,S-4125E,S-4126E,S-4127E,S-4128E,S-4129E, GP-D425,GP-1226D,GP-1220D,GP-1222D,GP-1223D,GP-1226D,S-4120D,S-4121D,S-4122D,S-4123D,S-4124D,S-4125D,S-4126D,S-4127D,S-4128D,S-4129D
Specification	:	BR+EDR+BLE
Operation Frequency	:	2402-2480MHz
Number of Channel	:	79 channels for BDR+EDR 40 channels For DTS
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK,8DPSK For DSS GFSK, For DTS
Antenna installation	:	PCB antenna
Antenna Gain	:	4.85 dBi
Power supply	:	Input: DC 24V=2.5A Adapter:20202M-240250U Input: AC100-240V 50/60Hz 1.5A MAX Output:+24.0V=2.5A
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(0) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2441_ DH5	3.05	3.96	3.96±1	3.133286	0.001904	1	Pass
2440_ BLE 2M	3.05	3.79	3.79±1	3.013000	0.001831	1	Pass

Note: BT and BLE can't Simultaneous transmission.

*******THE END REPORT*******