

FCC RF EXPOSURE REPORT

FCC ID: 2BTLL-GIT01

Test Report No.....: RF251107008-03-005

Product(s) Name.....: Mini PC

Model(s).....: IT15 Max, IT***** (* Representing numbers 0-9, letters A-Z, a-z, "-" or spaces)

Trade Mark.....: GEEKOM

Applicant.....: Shenzhen Geekom Electronic Technology Co., Ltd

Address.....: B705 No. 1044, Cha Guang Road, Shu Guang Community, Xi Li Street,
Nan Shan District, Shen Zhen, China

Receipt Date.....: 2025.11.13

Test Date.....: 2025.11.16 ~ 2025.12.04

Issued Date.....: 2025.12.08

Standards.....: FCC Guidelines for Human Exposure IEEE C95.1
FCC Title 47 Part 2.1091
KDB 447498 D01 General RF Exposure Guidance v06

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Black Ding	Tim Zhang	
<i>Jason Huang</i>	<i>Black Ding</i>	<i>Tim Zhang</i>	

History of this test report

Original Report Issue Date: 2025.12.08

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. MPE CALCULATION METHOD

Radio Frequency Exposure Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)
300-1,500	--	--	f/1500
1,500-100,000	--	--	1.0

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4GHz_WiFi:

Antenna gain		Antenna Type
ANT1: 2.99dBi	ANT2: 2.90dBi	Integrated Antenna

For 5.2GHz_WiFi:

Antenna gain		Antenna Type
ANT1: 3.72dBi	ANT2: 3.86dBi	Integrated Antenna

For 5.8GHz_WiFi:

Antenna gain		Antenna Type
ANT1: 3.40dBi	ANT2: 3.82dBi	Integrated Antenna

For BDR+EDR/BLE:

Antenna gain		Antenna Type
2.99dBi		Integrated Antenna

2. TEST RESULTS

Worst case as below

Operating Mode	Freq.	Maximum conducted output power	Directional Antenna Gain	Calculated maximum EIRP		MPE Limit	MPE Value
	(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	
BDR+EDR	2402-2480	2.74	2.99	5.73	3.74	1	0.0007
BLE	2402-2480	0.10	2.99	3.09	2.04	1	0.0004
2.4G Wifi	2412-2462	15.72	2.99	18.71	74.30	1	0.0148
5.2G Wifi	5180-5240	12.73	3.86	16.59	45.60	1	0.0091
5.8G Wifi	5745-5825	16.12	3.82	19.94	98.63	1	0.0196

Note: 1. The calculated distance is 20 cm.

2. The 2.4G Wifi function can not transmit at the same time with the 5G Wifi function

3. The Wifi function can transmit at the same time with the BT function.

Simultaneous transmitting consideration(worst case)

The ratio= $MPE_{BDR+EDR}/limit + MPE_{5.8G\ Wifi}/limit = 0.0007/1 + 0.0196/1 = 0.0203 < 1.0$

Result: Complies

Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

(END OF REPORT)