



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104,Building 7 and 8,DCC Cultural and Creative Garden No.98,Pingxin North Road,Shangmugu,Pinghu Street, Longgang District,Shenzhen,Guangdong,China

TEST REPORT

FCC Rules and Regulations Part 15 Subpart C (Section 15.209)

Report Reference No.....: **GTS20260410006-3-01**

FCC ID.....: **2BTLP-HSK20**

Compiled by

(position+printed name+signature)..: File administrators Jinghua Xiao

Supervised by

(position+printed name+signature)..: Test Engineer Evan Ouyang

Approved by

(position+printed name+signature)..: Manager Jason Hu



Date of issue.....: Apr.21, 2026

Representative Laboratory Name. : Shenzhen Global Test Service Co.,Ltd.

Address.....: No.7-101 and 8A-104,Building 7 and 8,DCC Cultural and Creative Garden No.98,Pingxin North Road,Shangmugu,Pinghu Street,Longgang District,Shenzhen,Guangdong,China

Applicant's name.....: Dongguan Xingweiming Electronic Technology Co., Ltd.

Address.....: Room 302, Building 1, No.23, Guest Road, Huangjiang Town, Dongguan City, Guangdong Province, China

Test specification.....:

Standard.....: FCC Rules and Regulations Part 15 Subpart C (Section 15.209)

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: charger

Trade Mark.....: N/A

Manufacturer.....: Dongguan Heshunkang Intelligent Technology Co., Ltd.

Model/Type reference.....: HSK20

List Model.....: N/A

Modulation Type.....: ASK

Operation Frequency.....: 115-205KHz

Ratings.....: Input: DC 5.0V/1A
Output/ Wireless: 2.5W

Result.....: **PASS**

TEST REPORT

Test Report No. :	GTS20260410006-3-01	Apr.21, 2026
		Date of issue

Equipment under Test : charger

Model /Type : HSK20

Listed Models : N/A

Applicant : **Dongguan Xingweiming Electronic Technology Co., Ltd.**

Address : Room 302, Building 1, No.23, Guest Road, Huangjiang Town, Dongguan City, Guangdong Province, China

Manufacturer **Dongguan Heshunkang Intelligent Technology Co., Ltd.**

Address : Room 302, Building 1, No.23, Guest Road, Huangjiang Town, Dongguan City, Guangdong Province, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	5
2.4. EUT Exercise Software	6
2.5. Special Accessories	6
2.6. External I/O Cable	6
2.7. Modifications	6
3. TEST ENVIRONMENT	7
3.1. Address of the test laboratory	7
3.2. Test Facility	7
3.3. Test Description	7
3.4. Statement of the measurement uncertainty	7
3.5. Equipments Used during the Test	8
4. TEST CONDITIONS AND RESULTS	9
4.1. AC Power Conducted Emission	9
4.2. Radiated Emission	11
4.3. Occupied Bandwidth	15
4.4. Antenna Requirement	16
5. TEST SETUP PHOTOS OF THE EUT	17
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	19

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules and Regulations Part 15 Subpart C \(Section 15.209\)](#): Radiated emission limits; general requirements.

[ANSI C63.10: 2020](#): American National Standard for Testing Unlicensed Wireless Devices

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Apr.15, 2026
Testing commenced on	:	Apr.15, 2026
Testing concluded on	:	Apr.21, 2026

2.2. Product Description

Product Name:	charger
Trade Mark:	N/A
Model/Type reference:	HSK20
List Model:	N/A
Model Declaration	N/A
Power supply:	Input: DC 5.0V/1A Output/ Wireless: 2.5W
Hardware version	N/A
Software version	N/A
Sample ID	GTS20260410006-3-S0001-1#>S20260410006-3-S0001-2#
WPT	
Operation frequency	115-205KHz
Modulation Type	ASK
Load Sensing	Contact transmission
Antenna Type	Coil Antenna
Antenna Gain	0.0 dBi

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

Input: DC 5.0V/1A
Output/ Wireless: 2.5W

Description of the test mode

Operation Frequency each of channel	
Channel	Frequency
1	127.352KHz

Mode	AC mode
Mode 1	5W Wireless Charging (No battery, sim load <1%)
	5W Wireless Charging (No battery, sim load 50%)
	5W Wireless Charging (No battery, sim load 99%)

.Note :1.EUT has one port, The supports wireless charging in AC mode.

2. All modes were tested for load states less than 1%, less than 50%, and less than 99%.

2.4. EUT Exercise Software

N/A

2.5. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Perfect Gallant Tec Co.,Ltd.	Adapter	PG241-120200B	--	SDOC
Dongguan Xingweiming Electronic Technology Co., Ltd.	Watch	DR16	--	SDOC

Note: The Adapter is only used for auxiliary testing.

2.6. External I/O Cable

I/O Port Description	Quantity	Cable
DC IN Port	1	1.0M, Unscreened Cable

2.7. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104,Building 7 and 8,DCC Cultural and Creative Garden No.98,Pingxin North Road,Shangmugu,Pinghu Street,Longgang District,Shenzhen,Guangdong,China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

CAB identifier is CN0082.

3.3. Test Description

Description Of Test	Result
Conducted Emissions Test	Compliant
Radiated Emission Test	Compliant
Occupied Bandwidth Measurement	Compliant
Antenna Requirement	Compliant

3.4. Statement of the measurement uncertainty

Measurement Uncertainty		
Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	=	4.06dB, k=2

3.5. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	CYBERTEK	EM5040A	E1850400105	2025/07/07	2026/07/06
LISN	R&S	ESH2-Z5	893606/008	2025/07/07	2026/07/06
EMI Test Receiver	R&S	ESPI3	101841-cd	2025/07/07	2026/07/06
EMI Test Receiver	R&S	ESCI7	101102	2025/07/07	2026/07/06
Spectrum Analyzer	Agilent	N9020A	MY48010425	2025/07/07	2026/07/06
Spectrum Analyzer	R&S	FSV40	100019	2025/07/07	2026/07/06
Vector Signal generator	Agilent	N5181A	MY49060502	2025/07/15	2026/07/14
Signal generator	Agilent	N5182A	3610AO1069	2025/07/07	2026/07/06
Climate Chamber	ESPEC	EL-10KA	A20120523	2025/07/15	2026/07/14
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2025/12/01	2026/11/30
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	15006	2025/07/07	2026/07/06
Bilog Antenna	Schwarzbeck	VULB9163	000976	2025/07/15	2026/07/14
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2025/07/15	2026/07/14
Amplifier	Schwarzbeck	BBV 9743	#202	2025/07/07	2026/07/06
Amplifier	Schwarzbeck	BBV9179	9719-025	2025/12/01	2026/11/30
Amplifier	EMCI	EMC051845B	980355	2025/07/07	2026/07/06
Temperature/Humidity Meter	Gangxing	CTH-608	02	2025/07/07	2026/07/06
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2025/07/07	2026/07/06
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2025/07/07	2026/07/06
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2025/07/15	2026/07/14
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2025/07/15	2026/07/14
Data acquisition card	Agilent	U2531A	TW53323507	2025/07/15	2026/07/14
Power Sensor	Agilent	U2021XA	MY5365004	2025/07/07	2026/07/06
Test Control Unit	Tonscend	JS0806-1	178060067	2025/07/07	2026/07/06
Automated filter bank	Tonscend	JS0806-F	19F8060177	2025/07/07	2026/07/06
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

The calibration interval is 1 year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, The EUT received DC 5V power, the adapter received AC 120V/60Hz or AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

1. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Temperature	25°C	Humidity	60%
Test Engineer	Evan Ouyang	Configurations	WPT
Power supply:	AC 120V/60Hz	Polarization	L




Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.726	35.70	32.48	10.23	45.93	42.71	56.00	46.00	10.07	3.29	L1	PASS
2	0.8925	22.08	12.69	10.23	32.31	22.92	56.00	46.00	23.69	23.08	L1	PASS
3	1.455	39.80	35.18	10.23	50.03	45.41	56.00	46.00	5.97	0.59	L1	PASS
4	2.9085	26.09	21.28	10.33	36.42	31.61	56.00	46.00	19.58	14.39	L1	PASS
5	4.3665	25.90	20.70	10.36	36.26	31.06	56.00	46.00	19.74	14.94	L1	PASS
6	5.82	22.76	17.27	10.46	33.22	27.73	60.00	50.00	26.78	22.27	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---



Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.726	34.57	31.73	10.23	44.80	41.96	56.00	46.00	11.20	4.04	N	PASS
2	1.455	34.32	33.19	10.23	44.55	43.42	56.00	46.00	11.45	2.58	N	PASS
3	2.526	33.47	15.70	10.31	43.78	26.01	56.00	46.00	12.22	19.99	N	PASS
4	3.678	21.59	8.96	10.36	31.95	19.32	56.00	46.00	24.05	26.68	N	PASS
5	6.513	20.45	7.50	10.50	30.95	18.00	60.00	50.00	29.05	32.00	N	PASS
6	9.672	29.81	10.41	10.57	40.38	20.98	60.00	50.00	19.62	29.02	N	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).


2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Note: All the modes have been tested and recorded worst mode in the report.


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

- 1.The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –25GHz.
- 2.Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
- 3.And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4.Repeat above procedures until all frequency measurements have been completed.
- 5.The EUT minimum operation frequency was 115KHz and maximum operation frequency was 205KHz.so radiated emission test frequency band from 9KHz to 1GHz.
- 6.The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- 7.Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power. The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+ 40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+ 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200

Above 960	3	54.0	500
-----------	---	------	-----

TEST RESULTS


Temperature	25°C	Humidity	58%
Test Engineer	Evan Ouyang	Configurations	WPT

For 9 KHz-30MHz**Coplanar**

Suspected List												
NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark	
1	0.127352	75.82	0.34	76.16	105.53	29.37	100	260	PK	Coplanar	PASS	
2	0.254475	52.49	0.44	52.93	99.49	46.56	100	279	PK	Coplanar	PASS	
3	0.47835	53.51	0.58	54.09	94.01	39.92	100	279	PK	Coplanar	PASS	
4	0.9261	52.12	0.85	52.97	68.27	15.30	100	131	PK	Coplanar	PASS	
5	1.7619	52.76	1.34	54.10	69.54	15.44	100	214	PK	Coplanar	PASS	
6	6.134925	49.15	3.91	53.06	69.54	16.48	100	223	PK	Coplanar	PASS	

Note: 1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Coaxial


Suspected List												
NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark	
1	0.127352	81.29	0.34	81.63	105.53	23.90	100	108	PK	Coaxial	PASS	
2	0.2097	54.67	0.42	55.09	101.17	46.08	100	2	PK	Coaxial	PASS	
3	0.463425	52.25	0.57	52.82	94.28	41.46	100	277	PK	Coaxial	PASS	
4	0.8067	51.94	0.77	52.71	69.47	16.76	100	34	PK	Coaxial	PASS	
5	1.627575	51.90	1.26	53.16	63.37	10.21	100	219	PK	Coaxial	PASS	
6	4.5678	51.54	3.00	54.54	69.54	15.00	100	274	PK	Coaxial	PASS	

Note: 1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

For 30MHz-1GHz

Horizontal




Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	46.005	28.48	-3.15	25.33	40.00	14.67	100	164	PK	Horizontal	PASS
2	108.57	27.48	-4.09	23.39	43.50	20.11	100	348	PK	Horizontal	PASS
3	205.57	31.69	-4.08	27.61	43.50	15.89	100	303	PK	Horizontal	PASS
4	255.525	33.59	-2.83	30.76	46.00	15.24	100	288	PK	Horizontal	PASS
5	434.005	26.23	1.43	27.66	46.00	18.34	100	149	PK	Horizontal	PASS
6	809.395	24.03	7.57	31.60	46.00	14.40	100	37	PK	Horizontal	PASS

Note: 1. Result (dBuV/m) = Reading (dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	64.92	33.22	-5.89	27.33	40.00	12.67	100	7	PK	Vertical	PASS
2	110.025	34.87	-4.48	30.39	43.50	13.11	100	85	PK	Vertical	PASS
3	143.975	34.92	-7.58	27.34	43.50	16.16	100	289	PK	Vertical	PASS
4	175.5	33.54	-6.32	27.22	43.50	16.28	100	131	PK	Vertical	PASS
5	240.005	32.46	-3.69	28.77	46.00	17.23	100	349	PK	Vertical	PASS
6	528.58	27.11	2.86	29.97	46.00	16.03	100	357	PK	Vertical	PASS

Note: 1. Result (dBuV/m) = Reading (dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Note: All the modes have been tested and recorded worst mode in the report.

4.3. Occupied Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equip compliance with the 20dB attenuation specification may base on measurement at the intentional radiator’s antenna output terminal unless the intentional radiator uses a permanently attached antenna, in which case compliance shall be demonstrated by measuring the radiated emissions.


LIMIT

/.

TEST RESULTS

Temperature	24.5℃	Humidity	53.9%
Test Engineer	Evan Ouyang	Configurations	WPT

Mode	Freq (KHz)	20dB Bandwidth (KHz)	Limit (kHz)	Conclusion
Tx Mode	127.352	2.590	/	PASS



4.4. Antenna Requirement

Standard Applicable

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Information

The antenna used in this product is a Coil Antenna, The directional gains of antenna used for transmitting is 0dBi.

Reference to the **Internal photos**.

5. Test Setup Photos of the EUT

Photo of Radiated Emissions Measurement




Fig. 1




Fig. 2

Photo of Conducted Emissions Measurement



Fig. 3



Fig. 4

6. External and Internal Photos of the EUT



Fig. 1




Fig. 2




Fig. 3



Fig. 4



Fig. 5



Fig. 6




Fig. 7

Antenna




Fig. 8




Fig. 9




Fig. 10

.....End of Report.....