



TEST REPORT

For RF Expose

Report No..... : CHTW25120040

Project No : SHT2511070402W

FCC ID : 2BTM2-BD-HV2

Applicant's name : L5 ASSISTANT INC.

Address..... : 10 Kent Court, Willowbrook, Illinois 60527,USA

Product Name : Blue Bud

Trade Mark..... : -

Model No..... : 02

Listed Model(s) : -

Standard : **FCC Part 2 (Section 2.1093)**

Date of receipt of test sample.....: 2025/11/28

Date of testing.....: 2025/12/1 – 2025/12/11

Date of issue.....: 2025/12/12

Result.....: **PASS**



Compiled by (Position+Printed name+Signature) :	File administrator	Xiaodong Zhao	<i>Xiaodong Zhao</i>
Supervised by (Position+Printed name+Signature) :	Project Engineer	Caspar Chen	<i>Caspar Chen</i>
Approved by (Position+Printed name+Signature) :	RF Manager	Xu Yang	<i>Xu Yang</i>

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Test Report Form No. : R0066

Test Report Form(s) Originator : Shenzhen Huatongwei International Inspection Co., Ltd.

Master TRF : Dated 2025-07

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample. The authenticity of this Test Report and its contents can be verified by contacting the Laboratory, responsible for this Test Report.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test standards	3
1.2.	Report version information	3
<u>2.</u>	<u>SUMMARY</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Radio Specification Description	4
2.4.	Testing Laboratory Information	4
<u>3.</u>	<u>RF EXPOSURE</u>	<u>5</u>
<u>4.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>6</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test standards

The tests were performed according to following standards:

[FCC Part 2 \(Section 2.1093\)](#)- Radiofrequency radiation exposure evaluation: portable devices.
[KDB 447498 D04 Interim General RF Exposure Guidance v01](#)- RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
[FCC Part 1 \(Section 1.1307\)](#)- Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2025-12-12	Original

2. SUMMARY

2.1. Client Information

Applicant:	L5 ASSISTANT INC.
Address:	10 Kent Court, Willowbrook, Illinois 60527,USA
Manufacturer:	Shenzhen Sun Wealth Technology Co.,Ltd.
Address:	Room 606, Hengqin Building, NO.60 Minzhi Avenue, Longhua District, Shenzhen City, Guangdong Province, China

2.2. Product Description

Product Name:	Blue Bud
Trade Mark:	-
Model No.:	02
Listed Model(s):	-
Power supply:	DC 5V
Hardware version:	V1.1
Software version:	V2.1
RF Exposure Environment:	General Population/Uncontrolled

2.3. Radio Specification Description

Bluetooth	
Supported type:	☒ LE-1Mbps ☒ LE-2Mbps

Note: Please refer to RF report for detailed technical specifications

2.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China
Contact information:	Tel: 400-963-0755 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn

3. RF EXPOSURE

LIMIT:

KDB447498 D04 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Radio Type	Frequency range (MHz)	Conducted Power (dBm)	Maximum Tune-up (dBm)	Calculating data	Limit	Result
Bluetooth	2402-2480	2.77	3.00	0.6284	3.00	Pass

Note:

- 1) The maximum antenna gain is 3.74dBi
- 2) The exposure evaluation safety distance is 5mm.

4. **EXTERNAL AND INTERNAL PHOTOS OF THE EUT**

Reference to the test report No. CHTW25120039

-----End of Report-----