

FCC Test Report

Report No. : 1812C60139912504

Applicant : Guangdong Hanying Photoelectric Technology Co., Ltd

Address : Room 201, Building 3, No. 3 sima Industrial Road, Changping Town, Dongguan City, Guangdong Province, 523000 China

Product Name : Smart Projector

Report Date : 2026-05-11



Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	8
1.4. Operation channel list	9
1.5. Description of Test Modes	9
1.6. Measurement Uncertainty	10
1.7. Additional Instructions	10
1.8. Test Summary	11
1.9. Description of Test Facility	12
1.10. Disclaimer	12
1.11. Test Equipment List	13
2. Conducted Emission at AC power line	15
2.1. EUT Operation	15
2.2. Test Setup	15
2.3. Test Data	16
3. Duty Cycle	20
3.1. EUT Operation	20
3.2. Test Setup	20
3.3. Test Data	20
4. Emission bandwidth and occupied bandwidth	21
4.1. EUT Operation	22
4.2. Test Setup	23
4.3. Test Data	23
5. Maximum conducted output power	24
5.1. EUT Operation	24
5.2. Test Setup	25
5.3. Test Data	25
6. Power spectral density	26
6.1. EUT Operation	26
6.2. Test Setup	27
6.3. Test Data	27
7. Frequency stability	28
7.1. EUT Operation	28
7.2. Test Setup	28
7.3. Test Data	29
8. Band edge emissions (Conducted)	40
8.1. EUT Operation	42
8.2. Test Setup	42
8.3. Test Data	42
9. Band edge emissions (Radiated)	43

9.1. EUT Operation45

9.2. Test Setup46

9.3. Test Data47

10. Undesirable emission limits (below 1GHz)55

10.1. EUT Operation57

10.2. Test Setup58

10.3. Test Data59

11. Undesirable emission limits (above 1GHz).....63

11.1. EUT Operation65

11.2. Test Setup65

11.3. Test Data66

APPENDIX I -- TEST SETUP PHOTOGRAPH68

APPENDIX II -- EXTERNAL PHOTOGRAPH68

APPENDIX III -- INTERNAL PHOTOGRAPH.....68

TEST REPORT

Applicant	:	Guangdong Hanying Photoelectric Technology Co., Ltd
Manufacturer	:	Guangdong Hanying Photoelectric Technology Co., Ltd
Product Name	:	Smart Projector
Model No.	:	HY320F, HY320GT
Trade Mark	:	MAGCUBIC
Rating(s)	:	Input1:45V= 0.95A Input2:12V= 1.1A
Test Standard(s)	:	47 CFR Part 15E KDB 789033 D02 General UNII Test Procedures New Rules v02r01 ANSI C63.10-2020+Cor.1-2023

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with above listed standard(s) requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt: 2026-03-10

Date of Test: 2026-03-10 to 2026-04-17

Polly Mo

Prepared By:

(Polly Mo)

Hugo Chem

Approved & Authorized Signer:

(Hugo Chen)

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2026-05-11

1. General Information

1.1. Client Information

Applicant	:	Guangdong Hanying Photoelectric Technology Co., Ltd
Address	:	Room 201, Building 3, No. 3 sima Industrial Road, Changping Town, Dongguan City, Guangdong Province, 523000 China
Manufacturer	:	Guangdong Hanying Photoelectric Technology Co., Ltd
Address	:	Room 201, Building 3, No. 3 sima Industrial Road, Changping Town, Dongguan City, Guangdong Province, 523000 China
Factory	:	Guangdong Hanying Photoelectric Technology Co., Ltd
Address	:	Room 201, Building 3, No. 3 sima Industrial Road, Changping Town, Dongguan City, Guangdong Province, 523000 China

1.2. Description of Device (EUT)

Product Name	:	Smart Projector
Model No.	:	HY320F, HY320GT (Note: All samples are the same except the model number, so we prepare "HY320F" for test only.)
Trade Mark	:	MAGCUBIC
Test Power Supply	:	120VAC/60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Manufacturer: Guangdong Mingxin Power Technologies Co.,Ltd. MODEL:MX60W-4500950U-1201100U INPUT:100-240V~50/60Hz 1.5A Max OUTPUT1:45.0V=0.95A OUTPUT2:12.0V=1.1A
Remote Control 1	:	Model: HT-HYK-009 Manufacturer: ShenzhenBaoAn Hengtai Electronic Fantoyg
Remote Control 2	:	Model: HYT-HY16C-001 Manufacturer: Shenzhen Haiyitai intelligent Electronic Technology Co., Ltd
RF Specification		
Operation Frequency	:	802.11a/n(HT20)/ac(VHT20)/ax(HEW20): U-NII Band 1: 5180MHz to 5240MHz; U-NII Band 3: 5745MHz to 5825MHz; 802.11n(HT40)/ac(VHT40)/ax(HEW40): U-NII Band 1: 5190MHz to 5230MHz; U-NII Band 3: 5755MHz to 5795MHz
Number of Channel	:	802.11a/n(HT20)/ac(VHT20)/ax(HEW20): U-NII Band 1: 4; U-NII Band 3: 5; 802.11n(HT40)/ac(VHT40)/ax(HEW40): U-NII Band 1: 2;

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

		U-NII Band 3: 2
Modulation Type	:	802.11a: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Device Type	:	Client Devices
Antenna Type	:	FPC Antenna
TPC Function	:	N/A
Antenna Gain(Peak)	:	WiFi 5.2G: 4.45dBi WiFi 5.8G: 2.51dBi
Remark: (1) All of the RF specification are provided by customer. (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. (3) 802.11ax only support SU (full RU) mode.		

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

1.4. Operation channel list

Operation Band: U-NII Band 1

Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	/	/
48	5240	/	/

Operation Band: U-NII Band 3

Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	/	/
161	5805	/	/
165	5825	/	/

1.5. Description of Test Modes

Pretest Modes	Descriptions
TM1	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report.
TM2	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.
TM3	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.
TM4	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.
TM5	Keep the EUT works in normal operating mode and connect to companion device

1.6. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	2.8dB
Dwell Time	2%
Occupied Bandwidth	552Hz
Conducted Output Power	0.84dB
Power Spectral Density	0.84dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.64dB; 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB
Radiated emissions (Below 30MHz)	3.14dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.70dB; Vertical: 4.42dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.7. Additional Instructions

Power level setup in software: adb

Operation Band: U-NII Band 1

Mode	Power level	Transmitting type
802.11a	default	data pack TX
802.11n(HT20)	default	data pack TX
802.11n(HT40)	default	data pack TX
802.11ac(VHT20)	default	data pack TX
802.11ac(VHT40)	default	data pack TX
802.11ax(HEW20)	default	data pack TX
802.11ax(HEW40)	default	data pack TX

Operation Band: U-NII Band 3

Mode	Power level	Transmitting type
802.11a	default	data pack TX
802.11n(HT20)	default	data pack TX
802.11n(HT40)	default	data pack TX
802.11ac(VHT20)	default	data pack TX

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

802.11ac(VHT40)	default	data pack TX
802.11ax(HEW20)	default	data pack TX
802.11ax(HEW40)	default	data pack TX

1.8. Test Summary

Test Items	Test Modes	Status
Conducted Emission at AC power line	Mode1,2,3,4	P
Duty Cycle	Mode1,2,3,4	P
Emission bandwidth and occupied bandwidth	Mode1,2,3,4	P
Maximum conducted output power	Mode1,2,3,4	P
Power spectral density	Mode1,2,3,4	P
Frequency stability	Mode5	P
Band edge emissions (Conducted)	Mode1,2,3,4	P
Band edge emissions (Radiated)	Mode1,2,3,4	P
Undesirable emission limits (below 1GHz)	Mode1,2,3,4	P
Undesirable emission limits (above 1GHz)	Mode1,2,3,4	P
Note: P: Pass N: N/A, not applicable		

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.:279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.10. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

1.11. Test Equipment List

Conducted Emission at AC power line					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	2025-09-05	2026-09-04
2	Software Name EZ-EMC	Farad Technology	ANB-03A	/	/
3	EMI Test Receiver(CE2#)	Rohde & Schwarz	ESCI	2025-12-29	2026-12-28
4	Three Phase V-type Artificial Power Network LISN 200A	EMtrace	PWL-50-3200A	2025-12-29	2026-12-28
5	10dB Attenuator	Emtrace	10dB100W	2025-12-29	2026-12-28
6	Pulse limiter	EMtrace	PL00903-2#	2025-12-30	2026-12-29

Frequency stability Band edge emissions (Conducted) Duty Cycle Emission bandwidth and occupied bandwidth Maximum conducted output power Power spectral density					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	2025-10-10	2026-10-09
2	DC Power Supply	IVYTECH	IV3605	2025-09-05	2026-09-04
3	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	2025-12-29	2026-12-28
4	MXA Spectrum Analysis	KEYSIGHT	N9020A	2025-12-29	2026-12-28
5	Oscilloscope	Tektronix	MDO3012	2025-09-30	2026-09-29
6	MXG RF Vector Signal Generator	Agilent	N5182A	2025-12-29	2026-12-28
7	RF Test software	Toscend	JS1120-3	/	/

Band edge emissions (Radiated)					
Undesirable emission limits (above 1GHz)					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	2025-12-30	2026-12-29
2	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	2025-12-30	2026-12-29
3	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	2025-10-27	2028-10-26
4	EMI Test Software EZ-EMC	SHURPLE	N/A	/	/
5	Horn Antenna	A-INFO	LB-180400-KF	2024-01-22	2027-01-21
6	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	2025-12-29	2026-12-28
7	Amplifier	Talent Microwave	TLLA18G40G-53-30	2026-01-05	2027-01-04

Undesirable emission limits (below 1GHz)					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	2025-12-30	2026-12-29
2	Pre-amplifier	SONOMA	310N	2025-12-30	2026-12-29
3	Bilog Broadband Antenna	Schwarzbeck	VULB9163	2025-10-26	2028-10-25
4	Loop Antenna (9K-30M)	Schwarzbeck	FMZB1519B	2025-09-05	2026-09-04
5	EMI Test Software EZ-EMC	SHURPLE	N/A	/	/


2. Conducted Emission at AC power line

Test Requirement:	47 CFR Part 15.207(a)		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020+Cor.1-2023 section 6.2 Remark: $\text{Result(dBuV)} = \text{Reading(dBuV)} + \text{Factor(dB)}$ $\text{Over Limit(dB)} = \text{Result(dBuV)} - \text{Limit(dBuV)}$		

2.1. EUT Operation


Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

2.2. Test Setup



2.3. Test Data

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------




Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



Shenzhen Anbotek Compliance Laboratory Limited


Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------

TM1 / Line: Line / Band: 5725-5850 MHz / BW: 20 / CH: L

Test Power Supply: 120VAC/60Hz for Adapter




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1940	29.59	18.08	47.67	63.86	-16.19	QP	
2	0.2060	35.65	18.08	53.73	63.36	-9.63	QP	
3	0.2060	18.54	18.08	36.62	53.36	-16.74	AVG	
4	0.2260	21.29	18.09	39.38	52.59	-13.21	AVG	
5	0.2740	26.51	18.10	44.61	60.99	-16.38	QP	
6	0.2940	24.10	18.10	42.20	60.41	-18.21	QP	
7	0.5700	19.31	18.11	37.42	56.00	-18.58	QP	
8	0.5700	7.44	18.11	25.55	46.00	-20.45	AVG	
9	1.1260	5.03	18.11	23.14	46.00	-22.86	AVG	
10	3.9980	5.76	18.02	23.78	46.00	-22.22	AVG	
11	20.2860	30.87	18.07	48.94	60.00	-11.06	QP	
12	20.2860	21.83	18.07	39.90	50.00	-10.10	AVG	

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



Note: Only record the worst data in the report.


3. Duty Cycle

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2020+Cor.1-2023 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

3.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

3.2. Test Setup



3.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.

4. Emission bandwidth and occupied bandwidth


Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: 47 CFR Part 15.407(e)
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 6.9 & 12.5 KDB 789033 D02, Clause C.2
Procedure:	Emission bandwidth: a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth. b) Set the VBW > RBW. c) Detector = peak. d) Trace mode = max-hold. e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%. Occupied bandwidth: a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are

	recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies. h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s). 6 dB emission bandwidth: a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
--	--

4.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

4.2. Test Setup



4.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.


5. Maximum conducted output power

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.4
Procedure:	Refer to ANSI C63.10-2020+Cor.1-2023 section 12.4

5.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

5.2. Test Setup



5.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.


6. Power spectral density

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.6
Procedure:	Refer to ANSI C63.10-2020+Cor.1-2023, section 12.6

6.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

6.2. Test Setup



6.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.


7. Frequency stability

Test Requirement:	47 CFR Part 15.407(g)
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 6.8
Procedure:	Refer to ANSI C63.10-2020+Cor.1-2023 section 6.8

7.1. EUT Operation

Operating Environment:	
Test mode:	5: Normal Operating: Keep the EUT works in normal operating mode and connect to companion device

7.2. Test Setup



7.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Test Mode: 5.2G							
Mode	TX Type	Frequency (MHz)	Temperature (°C)	Voltage (VAC)	Measured Frequency (MHz)	Limit	Verdict
802.11a	SISO	5180	20	102.00	5180.09	5172 to 5188	Pass
				120.00	5180.00	5172 to 5188	Pass
				138.00	5180.02	5172 to 5188	Pass
			-30	120.00	5180.03	5172 to 5188	Pass
			-20	120.00	5180.12	5150 to 5250	Pass
			-10	120.00	5180.02	5150 to 5250	Pass
			0	120.00	5180.05	5150 to 5250	Pass
			10	120.00	5180.12	5150 to 5250	Pass
			30	120.00	5180.05	5150 to 5250	Pass
			40	120.00	5180.08	5150 to 5250	Pass
			50	120.00	5180.01	5172 to 5188	Pass
		5200	20	102.00	5200.02	5192 to 5208	Pass
				120.00	5200.03	5192 to 5208	Pass
				138.00	5200.04	5192 to 5208	Pass
			-30	120.00	5200.10	5192 to 5208	Pass
			-20	120.00	5200.11	5150 to 5250	Pass
			-10	120.00	5200.05	5150 to 5250	Pass
			0	120.00	5200.04	5150 to 5250	Pass
			10	120.00	5200.10	5150 to 5250	Pass
			30	120.00	5200.13	5150 to 5250	Pass
			40	120.00	5200.03	5150 to 5250	Pass
			50	120.00	5200.05	5192 to 5208	Pass
		5240	20	102.00	5240.08	5232 to 5248	Pass
				120.00	5240.09	5232 to 5248	Pass
				138.00	5240.11	5232 to 5248	Pass
			-30	120.00	5240.08	5232 to 5248	Pass
			-20	120.00	5240.13	5150 to 5250	Pass
			-10	120.00	5240.03	5150 to 5250	Pass
			0	120.00	5240.03	5150 to 5250	Pass
			10	120.00	5240.08	5150 to 5250	Pass
			30	120.00	5240.08	5150 to 5250	Pass
			40	120.00	5240.09	5150 to 5250	Pass
			50	120.00	5240.07	5232 to 5248	Pass
802.11n (HT20)	SISO	5180	20	102.00	5180.02	5172 to 5188	Pass
				120.00	5180.10	5172 to 5188	Pass
				138.00	5180.10	5172 to 5188	Pass
			-30	120.00	5180.05	5172 to 5188	Pass
			-20	120.00	5180.11	5150 to 5250	Pass
			-10	120.00	5180.02	5150 to 5250	Pass
			0	120.00	5180.06	5150 to 5250	Pass
			10	120.00	5180.00	5150 to 5250	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

			30	120.00	5180.12	5150 to 5250	Pass
			40	120.00	5180.08	5150 to 5250	Pass
			50	120.00	5180.05	5172 to 5188	Pass
		5200	20	102.00	5200.04	5192 to 5208	Pass
				120.00	5200.06	5192 to 5208	Pass
				138.00	5200.02	5192 to 5208	Pass
			-30	120.00	5200.06	5192 to 5208	Pass
			-20	120.00	5200.07	5150 to 5250	Pass
			-10	120.00	5200.08	5150 to 5250	Pass
			0	120.00	5200.08	5150 to 5250	Pass
			10	120.00	5200.07	5150 to 5250	Pass
			30	120.00	5200.11	5150 to 5250	Pass
			40	120.00	5200.09	5150 to 5250	Pass
			50	120.00	5200.00	5192 to 5208	Pass
		5240	20	102.00	5240.08	5232 to 5248	Pass
				120.00	5240.06	5232 to 5248	Pass
				138.00	5240.03	5232 to 5248	Pass
			-30	120.00	5240.07	5232 to 5248	Pass
			-20	120.00	5240.12	5150 to 5250	Pass
			-10	120.00	5240.01	5150 to 5250	Pass
			0	120.00	5240.10	5150 to 5250	Pass
			10	120.00	5240.06	5150 to 5250	Pass
			30	120.00	5240.01	5150 to 5250	Pass
			40	120.00	5240.01	5150 to 5250	Pass
			50	120.00	5240.12	5232 to 5248	Pass
802.11n (HT40)	SISO	5190	20	102.00	5190.03	5174 to 5206	Pass
				120.00	5190.13	5174 to 5206	Pass
				138.00	5190.03	5174 to 5206	Pass
			-30	120.00	5190.02	5174 to 5206	Pass
			-20	120.00	5190.11	5150 to 5250	Pass
			-10	120.00	5190.13	5150 to 5250	Pass
			0	120.00	5190.06	5150 to 5250	Pass
			10	120.00	5190.11	5150 to 5250	Pass
			30	120.00	5190.02	5150 to 5250	Pass
			40	120.00	5190.11	5150 to 5250	Pass
			50	120.00	5190.01	5174 to 5206	Pass
		5230	20	102.00	5230.12	5214 to 5246	Pass
				120.00	5230.05	5214 to 5246	Pass
				138.00	5230.00	5214 to 5246	Pass
			-30	120.00	5230.03	5214 to 5246	Pass
			-20	120.00	5230.06	5150 to 5250	Pass
			-10	120.00	5230.04	5150 to 5250	Pass
			0	120.00	5230.11	5150 to 5250	Pass
			10	120.00	5230.08	5150 to 5250	Pass
			30	120.00	5230.04	5150 to 5250	Pass
			40	120.00	5230.08	5150 to 5250	Pass
802.11ac (VHT20)	SISO	5180	20	102.00	5180.13	5172 to 5188	Pass
				120.00	5180.08	5172 to 5188	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

802.11ac (VHT40)	SISO			138.00	5180.04	5172 to 5188	Pass
			-30	120.00	5180.02	5172 to 5188	Pass
			-20	120.00	5180.09	5150 to 5250	Pass
			-10	120.00	5180.12	5150 to 5250	Pass
			0	120.00	5180.09	5150 to 5250	Pass
			10	120.00	5180.03	5150 to 5250	Pass
			30	120.00	5180.06	5150 to 5250	Pass
			40	120.00	5180.10	5150 to 5250	Pass
			50	120.00	5180.06	5172 to 5188	Pass
		5200	20	102.00	5200.09	5192 to 5208	Pass
				120.00	5200.06	5192 to 5208	Pass
				138.00	5200.07	5192 to 5208	Pass
			-30	120.00	5200.11	5192 to 5208	Pass
			-20	120.00	5200.10	5150 to 5250	Pass
			-10	120.00	5200.02	5150 to 5250	Pass
			0	120.00	5200.09	5150 to 5250	Pass
			10	120.00	5200.05	5150 to 5250	Pass
			30	120.00	5200.08	5150 to 5250	Pass
			40	120.00	5200.01	5150 to 5250	Pass
			50	120.00	5200.04	5192 to 5208	Pass
		5240	20	102.00	5240.05	5232 to 5248	Pass
				120.00	5240.12	5232 to 5248	Pass
				138.00	5240.10	5232 to 5248	Pass
			-30	120.00	5240.09	5232 to 5248	Pass
			-20	120.00	5240.11	5150 to 5250	Pass
			-10	120.00	5240.01	5150 to 5250	Pass
			0	120.00	5240.01	5150 to 5250	Pass
			10	120.00	5240.06	5150 to 5250	Pass
			30	120.00	5240.07	5150 to 5250	Pass
			40	120.00	5240.05	5150 to 5250	Pass
			50	120.00	5240.07	5232 to 5248	Pass
		5190	20	102.00	5190.08	5174 to 5206	Pass
				120.00	5190.05	5174 to 5206	Pass
				138.00	5190.06	5174 to 5206	Pass
			-30	120.00	5190.09	5174 to 5206	Pass
			-20	120.00	5190.00	5150 to 5250	Pass
			-10	120.00	5190.04	5150 to 5250	Pass
			0	120.00	5190.04	5150 to 5250	Pass
			10	120.00	5190.07	5150 to 5250	Pass
			30	120.00	5190.02	5150 to 5250	Pass
			40	120.00	5190.12	5150 to 5250	Pass
			50	120.00	5190.10	5174 to 5206	Pass
		5230	20	102.00	5230.01	5214 to 5246	Pass
				120.00	5230.05	5214 to 5246	Pass
				138.00	5230.06	5214 to 5246	Pass
			-30	120.00	5230.13	5214 to 5246	Pass
			-20	120.00	5230.08	5150 to 5250	Pass
			-10	120.00	5230.11	5150 to 5250	Pass
			0	120.00	5230.01	5150 to 5250	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

802.11ax (HEW20)	SISO		10	120.00	5230.13	5150 to 5250	Pass
			30	120.00	5230.12	5150 to 5250	Pass
			40	120.00	5230.05	5150 to 5250	Pass
			50	120.00	5230.06	5214 to 5246	Pass
		5180	20	102.00	5180.09	5172 to 5188	Pass
				120.00	5180.00	5172 to 5188	Pass
				138.00	5180.02	5172 to 5188	Pass
			-30	120.00	5180.03	5172 to 5188	Pass
			-20	120.00	5180.12	5150 to 5250	Pass
			-10	120.00	5180.02	5150 to 5250	Pass
			0	120.00	5180.05	5150 to 5250	Pass
			10	120.00	5180.12	5150 to 5250	Pass
			30	120.00	5180.05	5150 to 5250	Pass
			40	120.00	5180.08	5150 to 5250	Pass
			50	120.00	5180.01	5172 to 5188	Pass
		5200	20	102.00	5200.02	5192 to 5208	Pass
				120.00	5200.03	5192 to 5208	Pass
				138.00	5200.04	5192 to 5208	Pass
			-30	120.00	5200.10	5192 to 5208	Pass
			-20	120.00	5200.11	5150 to 5250	Pass
			-10	120.00	5200.05	5150 to 5250	Pass
			0	120.00	5200.04	5150 to 5250	Pass
			10	120.00	5200.10	5150 to 5250	Pass
			30	120.00	5200.13	5150 to 5250	Pass
			40	120.00	5200.03	5150 to 5250	Pass
			50	120.00	5200.05	5192 to 5208	Pass
		5240	20	102.00	5240.08	5232 to 5248	Pass
				120.00	5240.09	5232 to 5248	Pass
				138.00	5240.11	5232 to 5248	Pass
			-30	120.00	5240.08	5232 to 5248	Pass
			-20	120.00	5240.13	5150 to 5250	Pass
			-10	120.00	5240.03	5150 to 5250	Pass
			0	120.00	5240.03	5150 to 5250	Pass
			10	120.00	5240.08	5150 to 5250	Pass
			30	120.00	5240.08	5150 to 5250	Pass
			40	120.00	5240.09	5150 to 5250	Pass
			50	120.00	5240.07	5232 to 5248	Pass
802.11ax (HEW40)	SISO	5190	20	102.00	5180.02	5174 to 5206	Pass
				120.00	5180.10	5174 to 5206	Pass
				138.00	5180.10	5174 to 5206	Pass
			-30	120.00	5180.05	5174 to 5206	Pass
			-20	120.00	5180.11	5150 to 5250	Pass
			-10	120.00	5180.02	5150 to 5250	Pass
			0	120.00	5180.06	5150 to 5250	Pass
			10	120.00	5180.00	5150 to 5250	Pass
			30	120.00	5180.12	5150 to 5250	Pass
			40	120.00	5180.08	5150 to 5250	Pass
			50	120.00	5180.05	5174 to 5206	Pass
		5230	20	102.00	5200.04	5214 to 5246	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

			120.00	5200.06	5214 to 5246	Pass
			138.00	5200.02	5214 to 5246	Pass
		-30	120.00	5200.06	5214 to 5246	Pass
		-20	120.00	5200.07	5150 to 5250	Pass
		-10	120.00	5200.08	5150 to 5250	Pass
		0	120.00	5200.08	5150 to 5250	Pass
		10	120.00	5200.07	5150 to 5250	Pass
		30	120.00	5200.11	5150 to 5250	Pass
		40	120.00	5200.09	5150 to 5250	Pass
		50	120.00	5200.00	5214 to 5246	Pass

Test Mode: 5.8G							
Mode	TX Type	Frequency (MHz)	Temperature (°C)	Voltage (VAC)	Measured Frequency (MHz)	Limit	Verdict
802.11a	SISO	5745	20	102.00	5745.05	5737 to 5753	Pass
				120.00	5745.12	5737 to 5753	Pass
				138.00	5745.06	5737 to 5753	Pass
			-30	102.00	5745.00	5737 to 5753	Pass
			-20	120.00	5745.03	5725 to 5850	Pass
			-10	120.00	5745.07	5725 to 5850	Pass
			0	120.00	5745.05	5725 to 5850	Pass
			10	120.00	5745.05	5725 to 5850	Pass
			30	120.00	5745.08	5725 to 5850	Pass
			40	120.00	5745.03	5725 to 5850	Pass
			50	120.00	5745.09	5737 to 5753	Pass
		5785	20	102.00	5785.11	5777 to 5793	Pass
				120.00	5785.03	5777 to 5793	Pass
				138.00	5785.05	5777 to 5793	Pass
			-30	102.00	5785.10	5777 to 5793	Pass
			-20	120.00	5785.04	5725 to 5850	Pass
			-10	120.00	5785.04	5725 to 5850	Pass
			0	120.00	5785.03	5725 to 5850	Pass
			10	120.00	5785.02	5725 to 5850	Pass
			30	120.00	5785.12	5725 to 5850	Pass
			40	120.00	5785.00	5725 to 5850	Pass
			50	120.00	5785.13	5777 to 5793	Pass
		5825	20	102.00	5825.04	5817 to 5833	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

				120.00	5825.06	5817 to 5833	Pass
				138.00	5825.00	5817 to 5833	Pass
			-30	102.00	5825.12	5817 to 5833	Pass
			-20	120.00	5825.05	5725 to 5850	Pass
			-10	120.00	5825.03	5725 to 5850	Pass
			0	120.00	5825.02	5725 to 5850	Pass
			10	120.00	5825.06	5725 to 5850	Pass
			30	120.00	5825.03	5725 to 5850	Pass
			40	120.00	5825.01	5725 to 5850	Pass
			50	120.00	5825.00	5817 to 5833	Pass
			802.11n (HT20)	SISO	5745	20	102.00
120.00	5745.01	5737 to 5753					Pass
138.00	5745.06	5737 to 5753					Pass
-30	102.00	5745.00				5737 to 5753	Pass
-20	120.00	5745.05				5725 to 5850	Pass
-10	120.00	5745.09				5725 to 5850	Pass
0	120.00	5745.08				5725 to 5850	Pass
10	120.00	5745.02				5725 to 5850	Pass
30	120.00	5745.09				5725 to 5850	Pass
40	120.00	5745.12				5725 to 5850	Pass
50	120.00	5745.10				5737 to 5753	Pass
5785	20	102.00			5785.07	5777 to 5793	Pass
		120.00			5785.06	5777 to 5793	Pass
		138.00			5785.10	5777 to 5793	Pass
	-30	102.00			5785.11	5777 to 5793	Pass
	-20	120.00			5785.05	5725 to 5850	Pass
	-10	120.00			5785.12	5725 to 5850	Pass
	0	120.00			5785.06	5725 to 5850	Pass
	10	120.00			5785.03	5725 to 5850	Pass
	30	120.00			5785.03	5725 to 5850	Pass
	40	120.00			5785.03	5725 to 5850	Pass
	50	120.00			5785.04	5777 to 5793	Pass
5825	20	102.00			5825.02	5817 to 5833	Pass
		120.00			5825.01	5817 to 5833	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

				138.00	5825.04	5817 to 5833	Pass
			-30	102.00	5825.03	5817 to 5833	Pass
			-20	120.00	5825.04	5725 to 5850	Pass
			-10	120.00	5825.02	5725 to 5850	Pass
			0	120.00	5825.02	5725 to 5850	Pass
			10	120.00	5825.07	5725 to 5850	Pass
			30	120.00	5825.09	5725 to 5850	Pass
			40	120.00	5825.00	5725 to 5850	Pass
			50	120.00	5825.01	5817 to 5833	Pass
802.11n (HT40)	SISO	5755	20	102.00	5755.03	5739 to 5771	Pass
				120.00	5755.03	5739 to 5771	Pass
				138.00	5755.03	5739 to 5771	Pass
			-30	102.00	5755.09	5739 to 5771	Pass
			-20	120.00	5755.02	5725 to 5850	Pass
			-10	120.00	5755.04	5725 to 5850	Pass
			0	120.00	5755.03	5725 to 5850	Pass
			10	120.00	5755.06	5725 to 5850	Pass
			30	120.00	5755.12	5725 to 5850	Pass
			40	120.00	5755.13	5725 to 5850	Pass
			50	120.00	5755.02	5739 to 5771	Pass
		5795	20	102.00	5795.10	5779 to 5811	Pass
				120.00	5795.10	5779 to 5811	Pass
				138.00	5795.06	5779 to 5811	Pass
			-30	102.00	5795.03	5779 to 5811	Pass
			-20	120.00	5795.09	5725 to 5850	Pass
			-10	120.00	5795.01	5725 to 5850	Pass
			0	120.00	5795.06	5725 to 5850	Pass
			10	120.00	5795.02	5725 to 5850	Pass
			30	120.00	5795.01	5725 to 5850	Pass
			40	120.00	5795.08	5725 to 5850	Pass
			50	120.00	5795.08	5779 to 5811	Pass
802.11ac (VHT20)	SISO	5745	20	102.00	5745.08	5737 to 5753	Pass
				120.00	5745.08	5737 to 5753	Pass
				138.00	5745.11	5737 to 5753	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

			-30	102.00	5745.12	5737 to 5753	Pass		
			-20	120.00	5745.06	5725 to 5850	Pass		
			-10	120.00	5745.04	5725 to 5850	Pass		
			0	120.00	5745.07	5725 to 5850	Pass		
			10	120.00	5745.08	5725 to 5850	Pass		
			30	120.00	5745.04	5725 to 5850	Pass		
			40	120.00	5745.10	5725 to 5850	Pass		
			50	120.00	5745.05	5737 to 5753	Pass		
		5785	20	102.00	5785.11	5777 to 5793	Pass		
				120.00	5785.01	5777 to 5793	Pass		
				138.00	5785.10	5777 to 5793	Pass		
			-30	102.00	5785.10	5777 to 5793	Pass		
			-20	120.00	5785.06	5725 to 5850	Pass		
			-10	120.00	5785.05	5725 to 5850	Pass		
			0	120.00	5785.06	5725 to 5850	Pass		
			10	120.00	5785.12	5725 to 5850	Pass		
			30	120.00	5785.05	5725 to 5850	Pass		
			40	120.00	5785.05	5725 to 5850	Pass		
			50	120.00	5785.03	5777 to 5793	Pass		
		5825	20	102.00	5825.09	5817 to 5833	Pass		
				120.00	5825.05	5817 to 5833	Pass		
				138.00	5825.03	5817 to 5833	Pass		
			-30	102.00	5825.12	5817 to 5833	Pass		
			-20	120.00	5825.01	5725 to 5850	Pass		
			-10	120.00	5825.05	5725 to 5850	Pass		
			0	120.00	5825.04	5725 to 5850	Pass		
			10	120.00	5825.06	5725 to 5850	Pass		
			30	120.00	5825.11	5725 to 5850	Pass		
			40	120.00	5825.04	5725 to 5850	Pass		
			50	120.00	5825.13	5817 to 5833	Pass		
		802.11ac (VHT40)	SISO	5755	20	102.00	5755.10	5739 to 5771	Pass
						120.00	5755.11	5739 to 5771	Pass
						138.00	5755.03	5739 to 5771	Pass
					-30	102.00	5755.02	5739 to 5771	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

802.11ax (HEW20)	SISO	5795	-20	120.00	5755.07	5725 to 5850	Pass
			-10	120.00	5755.01	5725 to 5850	Pass
			0	120.00	5755.08	5725 to 5850	Pass
			10	120.00	5755.03	5725 to 5850	Pass
			30	120.00	5755.06	5725 to 5850	Pass
			40	120.00	5755.12	5725 to 5850	Pass
			50	120.00	5755.08	5739 to 5771	Pass
		5795	20	102.00	5795.05	5779 to 5811	Pass
				120.00	5795.10	5779 to 5811	Pass
				138.00	5795.13	5779 to 5811	Pass
			-30	102.00	5795.10	5779 to 5811	Pass
			-20	120.00	5795.10	5725 to 5850	Pass
			-10	120.00	5795.12	5725 to 5850	Pass
			0	120.00	5795.13	5725 to 5850	Pass
			10	120.00	5795.07	5725 to 5850	Pass
			30	120.00	5795.05	5725 to 5850	Pass
			40	120.00	5795.07	5725 to 5850	Pass
			50	120.00	5795.00	5779 to 5811	Pass
		5745	20	102.00	5745.05	5172 to 5188	Pass
				120.00	5745.12	5172 to 5188	Pass
				138.00	5745.06	5172 to 5188	Pass
			-30	102.00	5745.00	5172 to 5188	Pass
			-20	120.00	5745.03	5150 to 5250	Pass
			-10	120.00	5745.07	5150 to 5250	Pass
			0	120.00	5745.05	5150 to 5250	Pass
			10	120.00	5745.05	5150 to 5250	Pass
			30	120.00	5745.08	5150 to 5250	Pass
			40	120.00	5745.03	5150 to 5250	Pass
			50	120.00	5745.09	5172 to 5188	Pass
		5785	20	102.00	5785.11	5192 to 5208	Pass
				120.00	5785.03	5192 to 5208	Pass
				138.00	5785.05	5192 to 5208	Pass
			-30	102.00	5785.10	5192 to 5208	Pass
			-20	120.00	5785.04	5150 to 5250	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

802.11ax (HEW40)	SISO	5825	-10	120.00	5785.04	5150 to 5250	Pass
			0	120.00	5785.03	5150 to 5250	Pass
			10	120.00	5785.02	5150 to 5250	Pass
			30	120.00	5785.12	5150 to 5250	Pass
			40	120.00	5785.00	5150 to 5250	Pass
			50	120.00	5785.13	5192 to 5208	Pass
		5825	20	102.00	5825.04	5232 to 5248	Pass
				120.00	5825.06	5232 to 5248	Pass
				138.00	5825.00	5232 to 5248	Pass
			-30	102.00	5825.12	5232 to 5248	Pass
			-20	120.00	5825.05	5150 to 5250	Pass
			-10	120.00	5825.03	5150 to 5250	Pass
			0	120.00	5825.02	5150 to 5250	Pass
			10	120.00	5825.06	5150 to 5250	Pass
			30	120.00	5825.03	5150 to 5250	Pass
			40	120.00	5825.01	5150 to 5250	Pass
			50	120.00	5825.00	5232 to 5248	Pass
		5755	20	102.00	5745.12	5174 to 5206	Pass
				120.00	5745.01	5174 to 5206	Pass
				138.00	5745.06	5174 to 5206	Pass
			-30	102.00	5745.00	5174 to 5206	Pass
			-20	120.00	5745.05	5150 to 5250	Pass
			-10	120.00	5745.09	5150 to 5250	Pass
			0	120.00	5745.08	5150 to 5250	Pass
			10	120.00	5745.02	5150 to 5250	Pass
			30	120.00	5745.09	5150 to 5250	Pass
			40	120.00	5745.12	5150 to 5250	Pass
			50	120.00	5745.10	5174 to 5206	Pass
		5795	20	102.00	5785.07	5214 to 5246	Pass
				120.00	5785.06	5214 to 5246	Pass
				138.00	5785.10	5214 to 5246	Pass
			-30	102.00	5785.11	5214 to 5246	Pass
			-20	120.00	5785.05	5150 to 5250	Pass
			-10	120.00	5785.12	5150 to 5250	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

			0	120.00	5785.06	5150 to 5250	Pass
			10	120.00	5785.03	5150 to 5250	Pass
			30	120.00	5785.03	5150 to 5250	Pass
			40	120.00	5785.03	5150 to 5250	Pass
			50	120.00	5785.04	5214 to 5246	Pass

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

8. Band edge emissions (Conducted)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																										
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table border="1"> <thead> <tr> <th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr> </thead> <tbody> <tr> <td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr> <tr> <td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr> <tr> <td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr> <tr> <td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr> <tr> <td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr> <tr> <td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr> <tr> <td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr> <tr> <td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr> <tr> <td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr> <tr> <td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr> <tr> <td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr> <tr> <td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr> <tr> <td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr> <tr> <td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr> <tr> <td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr> <tr> <td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr> <tr> <td>13.36-13.41</td><td></td><td></td><td></td></tr> </tbody> </table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.			MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41			
MHz	MHz	MHz	GHz																																																																								
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																								
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																								
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																								
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																								
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																								
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																								
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																								
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																								
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																								
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																								
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																								
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																								
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																								
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																								
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																								
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																								
13.36-13.41																																																																											


	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.																								

	i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

8.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

8.2. Test Setup



8.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.

9. Band edge emissions (Radiated)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																										
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table border="1"> <thead> <tr> <th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr> </thead> <tbody> <tr> <td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr> <tr> <td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr> <tr> <td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr> <tr> <td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr> <tr> <td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr> <tr> <td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr> <tr> <td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr> <tr> <td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr> <tr> <td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr> <tr> <td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr> <tr> <td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr> <tr> <td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr> <tr> <td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr> <tr> <td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr> <tr> <td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr> <tr> <td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr> <tr> <td>13.36-13.41</td><td></td><td></td><td></td></tr> </tbody> </table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.			MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41			
MHz	MHz	MHz	GHz																																																																								
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																								
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																								
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																								
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																								
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																								
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																								
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																								
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																								
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																								
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																								
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																								
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																								
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																								
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																								
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																								
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																								
13.36-13.41																																																																											


	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst																								

	case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. $\text{Result(dB}\mu\text{V/m)} = \text{Reading(dB}\mu\text{V)} + \text{Factor(dB/m)}; \text{Over Limit(dB)} = \text{Result(dB}\mu\text{V/m)} - \text{Limit(dB}\mu\text{V/m)}$ 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

9.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

9.2. Test Setup



9.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

TM1 / Band: 5150-5250 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	37.19	15.99	53.18	68.20	-15.02	H	Peak
5150.00	39.30	15.99	55.29	68.20	-12.91	V	Peak
5150.00	27.07	15.99	43.06	54.00	-10.94	H	AVG
5150.00	29.18	15.99	45.17	54.00	-8.83	V	AVG
TM1 / Band: 5150-5250 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	37.58	16.43	54.01	68.20	-14.19	H	Peak
5350.00	40.66	16.43	57.09	68.20	-11.11	V	Peak
5350.00	28.98	16.43	45.41	54.00	-8.59	H	AVG
5350.00	29.80	16.43	46.23	54.00	-7.77	V	AVG

Remark: 1. Result=Reading + Factor

TM2 / Band: 5150-5250 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	36.06	15.99	52.05	68.20	-16.15	H	Peak
5150.00	37.51	15.99	53.50	68.20	-14.70	V	Peak
5150.00	26.78	15.99	42.77	54.00	-11.23	H	AVG
5150.00	27.75	15.99	43.74	54.00	-10.26	V	AVG
TM2 / Band: 5150-5250 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	37.92	16.43	54.35	68.20	-13.85	H	Peak
5350.00	38.92	16.43	55.35	68.20	-12.85	V	Peak
5350.00	27.97	16.43	44.40	54.00	-9.60	H	AVG
5350.00	29.48	16.43	45.91	54.00	-8.09	V	AVG

Remark: 1. Result=Reading + Factor

TM2 / Band: 5150-5250 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	36.70	15.99	52.69	68.20	-15.51	H	Peak
5150.00	38.53	15.99	54.52	68.20	-13.68	V	Peak
5150.00	27.29	15.99	43.28	54.00	-10.72	H	AVG
5150.00	28.84	15.99	44.83	54.00	-9.17	V	AVG
TM2 / Band: 5150-5250 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	38.23	16.43	54.66	68.20	-13.54	H	Peak
5350.00	37.04	16.43	53.47	68.20	-14.73	V	Peak
5350.00	28.54	16.43	44.97	54.00	-9.03	H	AVG
5350.00	29.78	16.43	46.21	54.00	-7.79	V	AVG

Remark: 1. Result=Reading + Factor

TM3 / Band: 5150-5250 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	37.18	15.99	53.17	68.20	-15.03	H	Peak
5150.00	38.97	15.99	54.96	68.20	-13.24	V	Peak
5150.00	26.69	15.99	42.68	54.00	-11.32	H	AVG
5150.00	28.96	15.99	44.95	54.00	-9.05	V	AVG
TM3 / Band: 5150-5250 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	38.01	16.43	54.44	68.20	-13.76	H	Peak
5350.00	38.24	16.43	54.67	68.20	-13.53	V	Peak
5350.00	27.96	16.43	44.39	54.00	-9.61	H	AVG
5350.00	28.60	16.43	45.03	54.00	-8.97	V	AVG

Remark: 1. Result=Reading + Factor

TM3 / Band: 5150-5250 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	36.11	15.99	52.10	68.20	-16.10	H	Peak
5150.00	36.48	15.99	52.47	68.20	-15.73	V	Peak
5150.00	26.39	15.99	42.38	54.00	-11.62	H	AVG
5150.00	27.03	15.99	43.02	54.00	-10.98	V	AVG
TM3 / Band: 5150-5250 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	38.22	16.43	54.65	68.20	-13.55	H	Peak
5350.00	37.31	16.43	53.74	68.20	-14.46	V	Peak
5350.00	27.62	16.43	44.05	54.00	-9.95	H	AVG
5350.00	27.77	16.43	44.20	54.00	-9.80	V	AVG

Remark: 1. Result=Reading + Factor

TM4 / Band: 5150-5250 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	36.10	15.99	52.09	68.20	-16.12	H	Peak
5150.00	37.56	15.99	53.55	68.20	-14.65	V	Peak
5150.00	26.82	15.99	42.81	54.00	-11.20	H	AVG
5150.00	27.78	15.99	43.77	54.00	-10.23	V	AVG
TM4 / Band: 5150-5250 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5350.00	37.97	16.43	54.40	68.20	-13.81	H	Peak
5350.00	38.96	16.43	55.39	68.20	-12.82	V	Peak
5350.00	28.02	16.43	44.45	54.00	-9.55	H	AVG
5350.00	29.55	16.43	45.98	54.00	-8.03	V	AVG

Remark: 1. Result=Reading + Factor

TM4 / Band: 5150-5250 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5150.00	36.76	15.99	52.75	68.20	-15.45	H	Peak
5150.00	38.59	15.99	54.58	68.20	-13.63	V	Peak
5150.00	27.36	15.99	43.35	54.00	-10.66	H	AVG
5150.00	28.87	15.99	44.86	54.00	-9.15	V	AVG
TM4 / Band: 5150-5250 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5250.00	38.27	16.43	54.70	68.20	-13.50	H	Peak
5250.00	37.07	16.43	53.50	68.20	-14.71	V	Peak
5250.00	28.61	16.43	45.04	54.00	-8.97	H	AVG
5250.00	29.86	16.43	46.29	54.00	-7.72	V	AVG

Remark: 1. Result=Reading + Factor

TM1 / Band: 5725-5850 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	38.47	17.05	55.52	68.20	-12.68	H	Peak
5725.00	39.96	17.05	57.01	68.20	-11.19	V	Peak
5725.00	29.25	17.05	46.30	54.00	-7.70	H	AVG
5725.00	30.39	17.05	47.44	54.00	-6.56	V	AVG
TM1 / Band: 5725-5850 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	39.47	17.21	56.68	68.20	-11.52	H	Peak
5850.00	39.89	17.21	57.10	68.20	-11.10	V	Peak
5850.00	29.40	17.21	46.61	54.00	-7.39	H	AVG
5850.00	29.36	17.21	46.57	54.00	-7.43	V	AVG

Remark: 1. Result=Reading + Factor

TM2 / Band: 5725-5850 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	38.47	17.05	55.52	68.20	-12.68	H	Peak
5725.00	39.13	17.05	56.18	68.20	-12.02	V	Peak
5725.00	27.76	17.05	44.81	54.00	-9.19	H	AVG
5725.00	28.37	17.05	45.42	54.00	-8.58	V	AVG
TM2 / Band: 5725-5850 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	37.71	17.21	54.92	68.20	-13.28	H	Peak
5850.00	38.24	17.21	55.45	68.20	-12.75	V	Peak
5850.00	28.06	17.21	45.27	54.00	-8.73	H	AVG
5850.00	28.78	17.21	45.99	54.00	-8.01	V	AVG

Remark: 1. Result=Reading + Factor

TM2 / Band: 5725-5850 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	38.05	17.05	55.10	68.20	-13.10	H	Peak
5725.00	39.01	17.05	56.06	68.20	-12.14	V	Peak
5725.00	27.29	17.05	44.34	54.00	-9.66	H	AVG
5725.00	28.56	17.05	45.61	54.00	-8.39	V	AVG
TM2 / Band: 5725-5850 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	38.41	17.21	55.62	68.20	-12.58	H	Peak
5850.00	38.71	17.21	55.92	68.20	-12.28	V	Peak
5850.00	28.61	17.21	45.82	54.00	-8.18	H	AVG
5850.00	29.62	17.21	46.83	54.00	-7.17	V	AVG

Remark: 1. Result=Reading + Factor

TM3 / Band: 5725-5850 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	37.64	17.05	54.69	68.20	-13.51	H	Peak
5725.00	37.66	17.05	54.71	68.20	-13.49	V	Peak
5725.00	28.48	17.05	45.53	54.00	-8.47	H	AVG
5725.00	29.42	17.05	46.47	54.00	-7.53	V	AVG
TM3 / Band: 5725-5850 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	38.38	17.21	55.59	68.20	-12.61	H	Peak
5850.00	39.21	17.21	56.42	68.20	-11.78	V	Peak
5850.00	28.20	17.21	45.41	54.00	-8.59	H	AVG
5850.00	29.38	17.21	46.59	54.00	-7.41	V	AVG

Remark: 1. Result=Reading + Factor

TM3 / Band: 5725-5850 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	36.56	17.05	53.61	68.20	-14.59	H	Peak
5725.00	38.00	17.05	55.05	68.20	-13.15	V	Peak
5725.00	27.76	17.05	44.81	54.00	-9.19	H	AVG
5725.00	28.42	17.05	45.47	54.00	-8.53	V	AVG
TM3 / Band: 5725-5850 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	37.88	17.21	55.09	68.20	-13.11	H	Peak
5850.00	38.82	17.21	56.03	68.20	-12.17	V	Peak
5850.00	27.91	17.21	45.12	54.00	-8.88	H	AVG
5850.00	27.61	17.21	44.82	54.00	-9.18	V	AVG

Remark: 1. Result=Reading + Factor

TM4 / Band: 5725-5850 MHz / BW: 20 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	37.84	17.05	54.89	68.20	-13.31	H	Peak
5725.00	37.76	17.05	54.81	68.20	-13.39	V	Peak
5725.00	28.62	17.05	45.67	54.00	-8.33	H	AVG
5725.00	29.66	17.05	46.71	54.00	-7.29	V	AVG
TM4 / Band: 5725-5850 MHz / BW: 20 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	38.58	17.21	55.79	68.20	-12.41	H	Peak
5850.00	39.37	17.21	56.58	68.20	-11.62	V	Peak
5850.00	28.36	17.21	45.57	54.00	-8.43	H	AVG
5850.00	29.62	17.21	46.83	54.00	-7.17	V	AVG

Remark: 1. Result=Reading + Factor

TM4 / Band: 5725-5850 MHz / BW: 40 / L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5725.00	36.74	17.05	53.79	68.20	-14.41	H	Peak
5725.00	38.12	17.05	55.17	68.20	-13.03	V	Peak
5725.00	27.90	17.05	44.95	54.00	-9.05	H	AVG
5725.00	28.54	17.05	45.59	54.00	-8.41	V	AVG
TM4 / Band: 5725-5850 MHz / BW: 40 / H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
5850.00	38.04	17.21	55.25	68.20	-12.95	H	Peak
5850.00	39.06	17.21	56.27	68.20	-11.93	V	Peak
5850.00	28.09	17.21	45.30	54.00	-8.70	H	AVG
5850.00	27.85	17.21	45.06	54.00	-8.94	V	AVG

Remark: 1. Result=Reading + Factor

10. Undesirable emission limits (below 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(9)		
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.		
	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:		
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.7.4, 12.7.5		
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin		


	would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamplifier Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamplifier Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB
--	--

	below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Remark: Result(dBuV) = Reading(dBuV) + Factor(dB) Over Limit(dB) = Result(dBuV) - Limit(dBuV)
--	---

10.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.


10.2. Test Setup




10.3. Test Data

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------




Shenzhen Anbotek Compliance Laboratory Limited


Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



Temperature:	23 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



Note: Only record the worst data in the report.

11. Undesirable emission limits (above 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																										
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table border="1"> <thead> <tr> <th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr> </thead> <tbody> <tr> <td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr> <tr> <td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr> <tr> <td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr> <tr> <td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr> <tr> <td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr> <tr> <td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr> <tr> <td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr> <tr> <td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr> <tr> <td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr> <tr> <td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr> <tr> <td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr> <tr> <td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr> <tr> <td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr> <tr> <td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr> <tr> <td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr> <tr> <td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr> <tr> <td>13.36-13.41</td><td></td><td></td><td></td></tr> </tbody> </table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.			MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41			
MHz	MHz	MHz	GHz																																																																								
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																								
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																								
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																								
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																								
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																								
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																								
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																								
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																								
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																								
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																								
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																								
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																								
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																								
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																								
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																								
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																								
13.36-13.41																																																																											


	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.																								

	i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

11.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11a mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report. 2: 802.11n mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 3: 802.11ac mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report. 4: 802.11ax mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ax modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

11.2. Test Setup



11.3. Test Data

Temperature:	23.1 °C	Humidity:	68 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

TM3 / Band: 5150-5250 MHz / BW: 20 / CH: L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
10360.00	31.46	23.81	55.27	68.20	-12.93	V	Peak
15540.00	32.78	28.68	61.46	68.20	-6.74	V	Peak
10360.00	31.83	23.81	55.64	68.20	-12.56	H	Peak
15540.00	32.87	28.68	61.55	68.20	-6.65	H	Peak
10360.00	20.828	23.81	44.64	54.00	-9.36	V	AVG
15540.00	21.897	28.68	50.58	54.00	-3.42	V	AVG
10360.00	21.018	23.81	44.83	54.00	-9.17	H	AVG
15540.00	21.559	28.68	50.24	54.00	-3.76	H	AVG
TM3 / Band: 5150-5250 MHz / BW: 20 / CH: M							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
10400.00	30.82	23.81	54.63	68.20	-13.57	V	Peak
15600.00	32.31	29.13	61.44	68.20	-6.76	V	Peak
10400.00	31.32	23.81	55.13	68.20	-13.07	H	Peak
15600.00	32.39	29.13	61.52	68.20	-6.68	H	Peak
10400.00	21.098	23.81	44.91	54.00	-9.09	V	AVG
15600.00	22.017	29.13	51.15	54.00	-2.85	V	AVG
10400.00	21.008	23.81	44.82	54.00	-9.18	H	AVG
15600.00	21.639	29.13	50.77	54.00	-3.23	H	AVG
TM3 / Band: 5150-5250 MHz / BW: 20 / CH: H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
10480.00	30.39	23.80	54.19	68.20	-14.01	V	Peak
15720.00	31.79	30.03	61.82	68.20	-6.38	V	Peak
10480.00	30.96	23.80	54.76	68.20	-13.44	H	Peak
15720.00	31.30	30.03	61.33	68.20	-6.87	H	Peak
10480.00	19.77	23.80	43.57	54.00	-10.43	V	AVG
15720.00	20.78	30.03	50.81	54.00	-3.19	V	AVG
10480.00	20.22	23.80	44.02	54.00	-9.98	H	AVG
15720.00	20.43	30.03	50.46	54.00	-3.54	H	AVG

Remark:

1. Result = Reading + Factor
2. Only the worst case (802.11ac(VHT20)) is recorded in the report.
3. Test frequency are from 1GHz to 40GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

TM4 / Band: 5725-5850 MHz / BW: 20 / CH: L							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
11490.00	28.56	23.36	51.92	68.20	-16.28	V	Peak
17235.00	29.93	31.97	61.90	68.20	-6.30	V	Peak
11490.00	29.06	23.36	52.42	68.20	-15.78	H	Peak
17235.00	30.14	31.97	62.11	68.20	-6.09	H	Peak
11490.00	17.88	23.36	41.24	54.00	-12.76	V	AVG
17235.00	18.68	31.97	50.65	54.00	-3.35	V	AVG
11490.00	18.09	23.36	41.45	54.00	-12.55	H	AVG
17235.00	18.09	31.97	50.06	54.00	-3.94	H	AVG
TM4 / Band: 5725-5850 MHz / BW: 20 / CH: M							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
11570.00	29.14	23.42	52.56	68.20	-15.64	V	Peak
17355.00	29.81	32.18	61.99	68.20	-6.21	V	Peak
11570.00	29.26	23.42	52.68	68.20	-15.52	H	Peak
17355.00	30.23	32.18	62.41	68.20	-5.79	H	Peak
11570.00	19.154	23.42	42.57	54.00	-11.43	V	AVG
17355.00	18.998	32.18	51.18	54.00	-2.82	V	AVG
11570.00	19.076	23.42	42.50	54.00	-11.50	H	AVG
17355.00	18.470	32.18	50.65	54.00	-3.35	H	AVG
TM4 / Band: 5725-5850 MHz / BW: 20 / CH: H							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna Pol.	Detector
11650.00	28.65	23.49	52.14	68.20	-16.06	V	Peak
17475.00	30.05	32.39	62.44	68.20	-5.76	V	Peak
11650.00	29.00	23.49	52.49	68.20	-15.71	H	Peak
17475.00	29.84	32.39	62.23	68.20	-5.97	H	Peak
11650.00	18.22	23.49	41.71	54.00	-12.29	V	AVG
17475.00	18.80	32.39	51.19	54.00	-2.81	V	AVG
11650.00	18.26	23.49	41.75	54.00	-12.25	H	AVG
17475.00	18.44	32.39	50.83	54.00	-3.17	H	AVG

Remark:

1. Result = Reading + Factor
2. Only the worst case (802.11ax(HEW20)) is recorded in the report.
3. Test frequency are from 1GHz to 40GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- EUT External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- EUT Internal Photograph

----- End of Report -----