

Appendix B

RF Test Data for BT LE (Conducted Measurement)

Product Name: Wireless Earphone

Test Model: PIN AI

Environmental Conditions


Temperature:	23.8°C
Relative Humidity:	52.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Suichao Lai
Supervised by:	Yan Chen


B.1 DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant	2402	0.660	2401.660	2402.320	0.5	PASS
		2440	0.664	2439.660	2440.324	0.5	PASS
		2480	0.660	2479.660	2480.320	0.5	PASS

Test Graphs







B.2 Maximum Peak Conducted Output Power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE	Ant	2402	-3.42	≤30	PASS
		2440	0.18	≤30	PASS
		2480	-0.52	≤30	PASS

Test Graphs Peak







B.3 Maximum Power Spectral Density Level

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant	2402	-20.45	≤8.00	PASS
		2440	-16.67	≤8.00	PASS
		2480	-17.37	≤8.00	PASS

Test Graphs






B.4 Band Edge

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant	Low	2402	-4.81	-45.04	≤-24.81	PASS
		High	2480	-1.22	-45.13	≤-21.22	PASS

Test Graphs





B.5 Conducted RF Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant	2402	Reference	-4.31	-4.31	---	PASS
			30~1000	-4.31	-60.11	≤-24.31	PASS
			1000~26500	-4.31	-42.62	≤-24.31	PASS
		2440	Reference	-0.53	-0.53	---	PASS
			30~1000	-0.53	-62.23	≤-20.53	PASS
			1000~26500	-0.53	-40.01	≤-20.53	PASS
		2480	Reference	-1.20	-1.20	---	PASS
			30~1000	-1.20	-58.78	≤-21.2	PASS
			1000~26500	-1.20	-43.37	≤-21.2	PASS

Test Graphs






Guangzhou LCS Compliance Testing Laboratory Ltd.


Add: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Tel: +(86) 020-39166689 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com


BLE_Ant_2440_1000~26500



BLE_Ant_2480_0~Reference



BLE_Ant_2480_30~1000





B.6 Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE	Ant	2402	1.64	1.88	0.8723	87.23	0.59	---	---
		2440	1.64	1.88	0.8723	87.23	0.59	---	---
		2480	1.64	1.88	0.8723	87.23	0.59	---	---

Test Graphs





B.7 Restrict Band

Test Result

Test Mode	Antenna	Channel Name	Freq (MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Gain [dBi]	DC Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant	Low	2402	AV	2310.000	-56.86	≤-43.79	2.7	0.59	42.39	≤54	PASS
				AV	2323.625	-56.05	≤-43.79	2.7	0.59	43.20	≤54	PASS
				AV	2390.000	-56.84	≤-43.79	2.7	0.59	42.41	≤54	PASS
				Peak	2310.000	-48.82	≤-23.20	2.7	0.00	49.84	≤74	PASS
				Peak	2382.005	-45.49	≤-23.20	2.7	0.00	53.17	≤74	PASS
				Peak	2390.000	-48.87	≤-23.20	2.7	0.00	49.79	≤74	PASS
		High	2480	AV	2483.500	-56.34	≤-43.79	2.7	0.59	42.91	≤54	PASS
				AV	2485.360	-55.8	≤-43.79	2.7	0.59	43.45	≤54	PASS
				AV	2500.000	-56.31	≤-43.79	2.7	0.59	42.94	≤54	PASS
				Peak	2483.500	-48.07	≤-23.20	2.7	0.00	50.59	≤74	PASS
				Peak	2492.640	-46.19	≤-23.20	2.7	0.00	52.47	≤74	PASS
				Peak	2500.000	-48.09	≤-23.20	2.7	0.00	50.57	≤74	PASS

Note:

1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

