


Prüfbericht-Nr.: Test report no.:	CN26MBKV 002	Auftrags-Nr.: Order no.:	27226937	Seite 1 von 24 Page 1 of 24	
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-04-01		
Auftraggeber: Client:	AgiBot Innovation (Shanghai) Technology Co., Ltd. 8/F, Building 29, No.2555 Xiupu Road, Pudong New Area, 200120 Shanghai P.R. China				
Prüfgegenstand: Test item:	Wireless Terminal				
Bezeichnung / Typ-Nr.: Identification / Type no.:	GWC11T-W01				
Auftrags-Inhalt: Order content:	Test Report				
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15: Subpart C Section 15.247 RSS-247 Issue 4 July 2025 RSS-Gen Issue 5 February 2021				
Wareneingangsdatum: Date of sample receipt:	2026-03-27	Please refer to photo documents			
Prüfmuster-Nr.: Test sample no.:	A004233979-001~003				
Prüfzeitraum: Testing period:	2026-04-26 - 2026-05-20				
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von: tested by:			genehmigt von: authorized by:		
Datum: Date:	2026-07-03	Signed by: Bell Hu		Ausstellungsdatum: Issue date:	2026-07-03
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2BTPT-GWC11T-W01 IC: 35022-GWC11TW01 HVIN: GWC11T-W01 This report is for Bluetooth LE and 2.4GHz Wi-Fi.				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged				
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Prüfbericht-Nr.: CN26MBKV 002
Test report no.:

Seite 2 von 24
Page 2 of 24

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 6dB BANDWIDTH

RESULT: Pass

5.1.5 99% BANDWIDTH

RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.8 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	11
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	11
3.5	SUBMITTED DOCUMENTS.....	11
4	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE.....	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	12
4.5	TEST SETUP DIAGRAM	13
5	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	15
5.1.1	<i>Antenna Requirement</i>	<i>15</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>16</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>18</i>
5.1.4	<i>6dB Bandwidth</i>	<i>19</i>
5.1.5	<i>99% Bandwidth</i>	<i>20</i>
5.1.6	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>21</i>
5.1.7	<i>Radiated Spurious Emission</i>	<i>22</i>
5.1.8	<i>Conducted Emission on AC Mains.....</i>	<i>23</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	24
7	LIST OF TABLES.....	24

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of Bluetooth LE

Appendix B: Test Results of 2.4GHz Wi-Fi

Appendix C: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

FCC Accreditation Designation No.: 694916

ISED Wireless Device Testing Laboratory: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (SRD-Tonscend 1)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Wireless Connectivity Tester	R&S	CMW270	102505	2025-09-23	2026-09-22
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2025-09-23	2026-09-22
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2025-09-23	2026-09-22
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2025-09-23	2026-09-22
DC power supply	Keysight	E3642A	MY61276100	2025-09-23	2026-09-22
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2025-09-23	2026-09-22
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2025-09-23	2026-09-22
Test Software	Tonscend	JS1120-3	N/A	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A	N/A
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13
Unwanted Emission Testing (TS9975)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2025-09-22	2026-09-21
Signal Analyzer	R&S	FSV 40	101439	2025-09-22	2026-09-21
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2025-09-22	2026-09-21
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2025-09-22	2026-09-21
Amplifier	R&S	SCU-18F	180070	2025-09-22	2026-09-21
Amplifier	R&S	SCU40A	100475	2025-09-22	2026-09-21
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-09-28	2026-09-27

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:

Seite 7 von 24
Page 7 of 24

Double-Ridged Antenna (1-18 GHz)	ETS-LINDGREN	3117	00218717	2024-09-28	2026-09-27
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2024-09-28	2026-09-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2024-09-28	2026-09-27
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-09-14	2027-09-13

Conducted Emission				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESR3	102428	2026-07-18
Artificial Mains Network	R&S	ENV432	101411	2026-07-18
EMC32 Test Software	R&S	EMC32(Ver.10.50.00)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.24 dB / ± 3.24 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

Prüfbericht - Nr.: CN26MBKV 002
*Test Report No.:*Seite 8 von 24
Page 8 of 24

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The product is Wireless Terminal, which supports Bluetooth, 2.4GHz Wi-Fi and 5.2/5.8GHz Wi-Fi wireless functions.

This report is for Bluetooth LE and 2.4GHz Wi-Fi operation.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Wireless Terminal
Type Designation:	GWC11T-W01
FCC ID:	2BTPT-GWC11T-W01
IC:	35022-GWC11TW01
PMN:	Wireless Terminal
HVIN:	GWC11T-W01
Operating Voltage:	3.85V DC Battery Powered or Charging by adapter (AC 120V, 60Hz)
Testing Voltage:	Fully charged battery or AC 120V, 60Hz
Technical Specification of Bluetooth LE	
Operating Frequency:	2402 MHz to 2480 MHz for 1Mbps, 2404 MHz to 2478 MHz for 2Mbps
Type of Modulation:	GFSK
Channel Number:	BLE 1M: 40 channels BLE 2M: 38 channels
Channel Separation:	2MHz
Data Rate:	1Mbps, 2Mbps
Antenna Type:	Integral Antenna
Antenna Gain:	3.5 dBi (Provided by the Client)
Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20) 2422 - 2452 MHz for 802.11n(HT40)
Type of Modulation:	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM)
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 for 802.11n
Channel Number:	11 channels for 802.11b/g/n(HT20) 7 channels for 802.11n(HT40)
Channel Separation:	5 MHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx
Antenna Gain:	3.5 dBi (Provided by the Client)

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 4: RF Test Channel and Frequency of Bluetooth LE

Technologies	Test Channels (MHz)
Bluetooth LE	L/M/H: 2402, 2440, 2480 (for 1Mbps) L/M/H: 2404, 2440, 2478 (for 2Mbps)

Table 5: RF Test Channel and Frequency of 2.4GHz Wi-Fi

Technologies	Bandwidth	Test Channels (MHz)
2.4GHz Wi-Fi	20MHz	L/M/H: 2412, 2437, 2462
	40MHz	L/M/H: 2422, 2437, 2452

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, 2.4GHz Wi-Fi transmitting mode
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- C. On, Bluetooth with 5GHz Wi-Fi co-location
- D. On, Charging + Normal working
- E. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - User Manual |
| - Operation Description | - FCC/IC Label and Location Info |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024.

According to clause 3.1, all tests were performed on model *GWC11T-W01* in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 6: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Laptop	Lenovo	T480	S/N: PF-16A6N8
A/DC adapter	XIAOMI	MDY-14-EU	--

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 6.8

According to the manufacturer declared, the EUT has Integral Antenna, permanent attachment and no consideration of replacement, refer to section 3.2 for details.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 16 von 24
Page 16 of 24

5.1.2 Maximum Peak Conducted Output Power

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(b)(3) RSS-247 Clause 6.3.2
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 1.0 W
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-09 to 2026-05-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

Table 7: Test Result of Maximum Conducted Output Power, Bluetooth LE

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
Bluetooth LE (1 Mbps)	2402	6.34	0.0043	< 1.0
	2440	5.84	0.0038	
	2480	5.90	0.0039	
Bluetooth LE (2 Mbps)	2404	6.92	0.0049	
	2440	5.68	0.0037	
	2478	6.05	0.0040	
Max. Measured Value		6.92	0.0049	

Max. e.i.r.p.=6.92dBm+3.5dBi=10.42dBm, which is less than 36dBm=4W.

Table 8: Test Result of Maximum Conducted Output Power, 2.4GHz Wi-Fi

Test Mode	Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
			(dBm)	(W)	
802.11b	1 Mbps	2412	14.62	0.0290	< 1.0
		2437	15.02	0.0318	
		2462	14.01	0.0252	
802.11g	6 Mbps	2412	18.73	0.0746	
		2437	18.71	0.0743	
		2462	18.34	0.0682	
802.11n (HT20)	MCS0	2412	18.73	0.0746	
		2437	18.63	0.0729	
		2462	17.76	0.0597	
802.11n (HT40)	MCS0	2422	16.91	0.0491	
		2437	18.38	0.0689	
		2452	15.76	0.0377	
Maximum Measured Value			18.73	0.0746	

Max. e.i.r.p.=18.73dBm+3.5dBi=22.23dBm, which is less than 36dBm=4W.

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 3.5dBi for Bluetooth & 2.4GHz Wi-Fi
e.i.r.p.=P_(Peak power)+ G, which is far below the 4 W

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 18 von 24
Page 18 of 24

5.1.3 Conducted Power Spectral Density

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(e) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 8 dBm / 3kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-09 to 2026-05-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 19 von 24
Page 19 of 24

5.1.4 6dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(2) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: > 500 kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-09 to 2026-05-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 20 von 24
Page 20 of 24

5.1.5 99% Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a) RSS-Gen Clause 6.7
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Within assigned band 2400-2483.5MHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-09 to 2026-05-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 21 von 24
Page 21 of 24

5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(d) RSS-247 Clause 6.6
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-09 to 2026-05-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 45 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A, B.

5.1.7 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 2.4
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Section 8.9 & 8.10
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2026-04-26 to 2026-05-02
Input voltage	: Fully charged battery
Operation mode	: A, B, C
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test results
Relative humidity	: Refer to test results
Atmospheric pressure	: 101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN26MBKV 002
Test Report No.:Seite 23 von 24
Page 23 of 24

5.1.8 Conducted Emission on AC Mains

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.207(a) RSS-Gen Section 8.8
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Frequency range	: 0.15 – 30MHz
Classification	: Class B
Limits	: FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-17
Input voltage	: AC 120V, 60Hz
Operation mode	: D
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A, B.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix C.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT.....	9
Table 4: RF Channel and Frequency of Bluetooth LE.....	10
Table 5: RF Channel and Frequency of 2.4GHz Wi-Fi.....	10
Table 6: List of Accessories and Auxiliary Equipment.....	12
Table 7: Test Result of Maximum Conducted Output Power, Bluetooth LE	17
Table 8: Test Result of Maximum Conducted Output Power, 2.4GHz Wi-Fi	17