TEST REPORT

Reference No......	:	WTX25X10281776W001
FCC ID.....	:	2BTQ6-TM10B
Applicant	:	Huizhou Oule Technology Co., Ltd.
Address	:	East side, 4/F, Block A, Factory Building, No. 1 Xinxing Road (Factory Building No. 6), Daya Bay West District, Huizhou, China
Manufacturer.....	:	The same as Applicant
Address	:	The same as Applicant
Product Name	:	Barcode Scanner
Model No......	:	TM-10B
Standards	:	FCC Part 15.247
Date of Receipt sample....	:	2025-10-27
Date of Test.....	:	2025-11-03 to 2025-12-11
Date of Issue	:	2025-12-15
Test Report Form No.	:	WTX_Part 15_247W
Test Result.....	:	**Pass**

Remarks:
The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:
Waltek Testing Group (Shenzhen) Co., Ltd.
Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Mike Shi/Project Engineer

Approved by:

Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION **4**
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
1.2 TEST STANDARDS 5
1.3 TEST METHODOLOGY 5
1.4 TEST FACILITY 5
1.5 EUT SETUP AND TEST MODE 6
1.6 MEASUREMENT UNCERTAINTY 7
1.7 TEST EQUIPMENT LIST AND DETAILS 8
2. SUMMARY OF TEST RESULTS **12**
3. ANTENNA REQUIREMENT **13**
3.1 STANDARD APPLICABLE 13
3.2 EVALUATION INFORMATION 13
4. POWER SPECTRAL DENSITY **14**
4.1 STANDARD APPLICABLE 14
4.2 TEST SETUP BLOCK DIAGRAM 14
4.3 TEST PROCEDURE 14
4.4 SUMMARY OF TEST RESULTS/PLOTS 14
5. DTS BANDWIDTH **15**
5.1 STANDARD APPLICABLE 15
5.2 TEST SETUP BLOCK DIAGRAM 15
5.3 TEST PROCEDURE 15
5.4 SUMMARY OF TEST RESULTS/PLOTS 15
6. RF OUTPUT POWER **16**
6.1 STANDARD APPLICABLE 16
6.2 TEST SETUP BLOCK DIAGRAM 16
6.3 TEST PROCEDURE 16
6.4 SUMMARY OF TEST RESULTS/PLOTS 16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS **17**
7.1 STANDARD APPLICABLE 17
7.2 TEST PROCEDURE 17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION 19
7.4 SUMMARY OF TEST RESULTS/PLOTS 19
8. OUT OF BAND EMISSIONS **23**
8.1 STANDARD APPLICABLE 23
8.2 TEST PROCEDURE 23
8.3 SUMMARY OF TEST RESULTS/PLOTS 24
9. CONDUCTED EMISSIONS **29**
9.1 TEST PROCEDURE 29
9.2 BASIC TEST SETUP BLOCK DIAGRAM 29
9.3 TEST RECEIVER SETUP 29
9.4 SUMMARY OF TEST RESULTS/PLOTS 29
APPENDIX SUMMARY **32**
APPENDIX A: DTS BANDWIDTH 33
APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER 36
APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY 39
APPENDIX D: REFERENCE LEVEL MEASUREMENT 42
APPENDIX E: BAND EDGE MEASUREMENTS 45
APPENDIX F: CONDUCTED SPURIOUS EMISSION 48
APPENDIX G: DUTY CYCLE 53
APPENDIX PHOTOGRAPHS **56**

Report version

Version No.	Date of issue	Description
Rev.00	2025-12-15	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Barcode Scanner
Trade Name	/
Model No.:	TM-10B
Adding Model(s):	/
Rated Voltage:	USB Port:DC5V Battery:DC3.7V
Battery Capacity:	2600mAh
Power Adapter:	/
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Bluetooth Version:	V5.4 (LE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	1Mbps: -0.41dBm (Conducted) 2Mbps: -0.40dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	3.79dBi
Note The Antenna Gain is provided by the customer and can affect the validity of results.	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.
558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.
ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 15.247 Meas Guidance v05r02.
The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory
Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.
Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990
Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is mai ntained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A
The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB cable	1.5	Unshielded	With Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Computer	Lenovo	Pro14IHU2021	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.57dB
Occupied Bandwidth	Conducted	±0.015MHz
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emission 1#	Conducted	@9kHz to 150kHz: ±3.74dB
		@150kHz to 30MHz: ±3.34dB
Conducted Emission 2#	Conducted	@9kHz to 150kHz: ±3.74dB
		@150kHz to 30MHz: ±3.34dB
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: ±3.0dB
		@30MHz to 1GHz: ±5.70dB
		@1GHz to 6GHz: ±5.88dB
		@6GHz to 18GHz: ±5.96dB
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: ±5.36dB
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: ±3.0dB
		@30MHz to 1GHz: ±5.28dB
		@1GHz to 6GHz: ±5.56dB
		@6GHz to 18GHz: ±5.72dB

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1005A1005	Spectrum Analyzer	Agilent	N9020A	US47140102	2025-02-23	2026-02-22
WTXE1084A1001	Spectrum Analyzer	Agilent	N9020A	MY54320548	2025-02-23	2026-02-22
WTXE1004A1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
WTXW1105A1010	Spectrum Analyzer	KEYSIGHT	N9020A	MY51285677	2025-02-23	2026-02-22
WTXE1105A1008	RF Control Unit	Tonscend	JS0806-2	24F80620870	2025-02-23	2026-02-22
WTXE1103A1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003A1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐Chamber A: Below 1GHz						
WTXE1005A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2025-02-23	2026-02-22
WTXE1001A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007A1002	Amplifier	HP	8447F	2805A03475	2025-02-23	2026-02-22
WTXE1010A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010A1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104A1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐Chamber A: Above 1GHz						
WTXE1005A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2025-02-23	2026-02-22
WTXE1001A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22

WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2025-02-23	2026-02-22
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2025-02-23	2026-02-22
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2025-02-23	2026-02-22
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22

WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
					2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☒Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	**Manufacturer**	**Model**	**Version**
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
RF Test System	Tonscend	JS1120-3	V3.5.39

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an Integral antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.2, the test method of power spectral density as below:

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to: 3kHz ≤ RBW ≤ 100kHz.
d) Set the VBW ≥ 3 × RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat.

4.4 Summary of Test Results/Plots

Please refer to Appendix D

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

a) Set RBW = 100kHz.
b) Set the video bandwidth (VBW) ≥ 3 × RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots

Please refer to Appendix A&B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2020 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

a) Set the RBW ≥ DTS bandwidth.
b) Set VBW ≥ 3 × RBW.
c) Set span ≥ 3 x RBW
d) Sweep time = auto couple.
e) Detector = peak.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use peak marker function to determine the peak amplitude level.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10kHz,	RBW=120kHz,	RBW=1MHz,
VBW =30kHz	VBW=300kHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold

Detector function = peak Detector function = peak, QP Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss – Ampl. Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15 Limit

7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

- Spurious Emissions Below 1GHz
- LE 1Mbps(worst case)

Test Channel	Low(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	51.8999	25.86	-8.30	17.56	40.00	-22.44	-	-	peak
2	57.2654	26.61	-8.64	17.97	40.00	-22.03	-	-	peak
3	152.0902	27.25	-8.53	18.72	43.50	-24.78	-	-	peak
4	424.2999	27.51	-5.71	21.80	46.00	-24.20	-	-	peak
5	512.9478	28.61	-3.23	25.38	46.00	-20.62	-	-	peak
6	793.0281	29.44	1.63	31.07	46.00	-14.93	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	49.7571	25.13	-8.28	16.85	40.00	-23.15	-	-	peak
2	57.2654	25.96	-8.64	17.32	40.00	-22.68	-	-	peak
3	171.3890	27.75	-8.86	18.89	43.50	-24.61	-	-	peak
4	384.5447	28.16	-6.63	21.53	46.00	-24.47	-	-	peak
5	655.9766	28.40	-0.11	28.29	46.00	-17.71	-	-	peak
6	765.6482	28.78	1.31	30.09	46.00	-15.91	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- LE 1Mbps(worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	65.44	-13.23	52.21	74	-21.79	H	PK
4804	62.87	-13.23	49.64	54	-4.36	H	AV
7206	60.41	-6.85	53.56	74	-20.44	H	PK
7206	57.36	-6.85	50.51	54	-3.49	H	AV
4804	63.44	-13.23	50.21	74	-23.79	V	PK
4804	59.71	-13.23	46.48	54	-7.52	V	AV
7206	57.63	-6.85	50.78	74	-23.22	V	PK
7206	55.03	-6.85	48.18	54	-5.82	V	AV
Middle Channel-2440MHz							
4882	65.48	-13.10	52.38	74	-21.62	H	PK
4882	62.82	-13.10	49.72	54	-4.28	H	AV
7323	60.10	-7.12	52.98	74	-21.02	H	PK
7323	57.51	-7.12	50.39	54	-3.61	H	AV
4882	62.59	-13.10	49.49	74	-24.51	V	PK
4882	59.98	-13.10	46.88	54	-7.12	V	AV
7323	57.86	-7.12	50.74	74	-23.26	V	PK
7323	55.45	-7.12	48.33	54	-5.67	V	AV
High Channel-2480MHz							
4960	65.15	-13.03	52.12	74	-21.88	H	PK
4960	63.25	-13.03	50.22	54	-3.78	H	AV
7440	59.89	-7.52	52.37	74	-21.63	H	PK
7440	56.95	-7.52	49.43	54	-4.57	H	AV
4960	63.37	-13.03	50.34	74	-23.66	V	PK
4960	60.26	-13.03	47.23	54	-6.77	V	AV
7440	58.35	-7.52	50.83	74	-23.17	V	PK
7440	55.07	-7.52	47.55	54	-6.45	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Conducted Spurious Emission Please refer to Appendix G

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:
Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)
RBW = 1MHz, VBW = 1MHz for peak value measured
RBW = 1MHz, VBW = 10Hz for average value measured
Sweep = auto; Detector function = peak/average; Trace = max hold
All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 9.

b) VBW ≥ [3 × RBW].

c) Detector = peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

Frequency	RBW
9kHz to 150kHz	200Hz to 300Hz
0.15MHz to 30MHz	9kHz to 10kHz
30MHz to 1000MHz	100kHz to 120kHz
>1000MHz	1MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots

➢ Radiated test

LE 1Mbps

Test Channel	Low(worst case)	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.34	-19.50	23.84	54.00	-30.16	Average Detector
	2310.000	61.46	-19.50	41.96	74.00	-32.04	Peak Detector
2	2370.120	53.84	-19.36	34.48	54.00	-19.52	Average Detector
	2386.353	77.64	-19.32	58.32	74.00	-15.68	Peak Detector
3	2390.000	44.51	-19.31	25.20	54.00	-28.80	Average Detector
	2390.000	66.39	-19.31	47.08	74.00	-26.92	Peak Detector
4	2402.184	113.74	-19.29	94.45	/	/	Average Detector
	2401.784	114.34	-19.29	95.05	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.010	114.84	-19.09	95.75	/	/	Average Detector
	2479.960	115.37	-19.09	96.28	/	/	Peak Detector
2	2483.500	63.52	-19.09	44.43	54.00	-9.57	Average Detector
	2483.500	76.24	-19.09	57.15	74.00	-16.85	Peak Detector
3	2500.000	44.15	-19.05	25.10	54.00	-28.90	Average Detector
	2500.000	60.69	-19.05	41.64	74.00	-32.36	Peak Detector

LE 2Mbps

Test Channel	Low(worst case)	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	43.22	-19.50	23.72	54.00	-30.28	Average Detector
	2310.000	62.40	-19.50	42.90	74.00	-31.10	Peak Detector
2	2370.120	52.70	-19.36	33.34	54.00	-20.66	Average Detector
	2386.353	77.72	-19.32	58.40	74.00	-15.60	Peak Detector
3	2390.000	44.13	-19.31	24.82	54.00	-29.18	Average Detector
	2390.000	66.66	-19.31	47.35	74.00	-26.65	Peak Detector
4	2402.184	112.66	-19.29	93.37	/	/	Average Detector
	2401.583	114.81	-19.29	95.52	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.010	113.68	-19.09	94.59	/	/	Average Detector
	2480.461	116.09	-19.09	97.00	/	/	Peak Detector
2	2483.500	64.45	-19.09	45.36	54.00	-8.64	Average Detector
	2483.500	76.24	-19.09	57.15	74.00	-16.85	Peak Detector
3	2500.000	50.55	-19.05	31.50	54.00	-22.50	Average Detector
	2500.000	63.73	-19.05	44.68	74.00	-29.32	Peak Detector

- Conducted test

Please refer to Appendix E&F

9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram



9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150kHz
Stop Frequency 30MHz
Sweep Speed ..... Auto
IF Bandwidth..... 10kHz
Quasi-Peak Adapter Bandwidth 9kHz
Quasi-Peak Adapter Mode ..... Normal

9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1500	39.02	9.43	48.45	65.99	-17.54	QP
2	0.1500	32.12	9.43	41.55	55.99	-14.44	AVG
3	0.2300	45.90	9.63	55.53	62.45	-6.92	QP
4*	0.2300	38.67	9.63	48.30	52.45	-4.15	AVG
5	0.3580	22.65	9.64	32.29	48.77	-16.48	AVG
6	0.3660	34.83	9.64	44.47	58.59	-14.12	QP
7	0.4860	31.43	9.65	41.08	56.24	-15.16	QP
8	0.4860	20.49	9.65	30.14	46.24	-16.10	AVG
9	11.3700	22.80	9.73	32.53	50.00	-17.47	AVG
10	11.4020	36.96	9.73	46.69	60.00	-13.31	QP
11	25.3540	17.43	9.55	26.98	50.00	-23.02	AVG
12	25.7939	31.18	9.55	40.73	60.00	-19.27	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1539	42.45	9.45	51.90	65.78	-13.88	QP
2	0.1539	30.15	9.45	39.60	55.78	-16.18	AVG
3	0.2420	45.23	9.63	54.86	62.02	-7.16	QP
4*	0.2460	37.37	9.63	47.00	51.89	-4.89	AVG
5	0.3500	35.26	9.63	44.89	58.96	-14.07	QP
6	0.3700	23.66	9.64	33.30	48.50	-15.20	AVG
7	0.4900	19.89	9.65	29.54	46.17	-16.63	AVG
8	0.5020	30.83	9.65	40.48	56.00	-15.52	QP
9	11.2299	31.88	9.74	41.62	60.00	-18.38	QP
10	11.4140	16.99	9.72	26.71	50.00	-23.29	AVG
11	25.3779	31.77	9.55	41.32	60.00	-18.68	QP
12	25.3779	18.53	9.55	28.08	50.00	-21.92	AVG

APPENDIX SUMMARY

Project No.	WTX25X10281776W001	Test Engineer	BAIdi Zhong
Start date	2025-12-09	Finish date	2025-12-11
Temperature	25℃	Humidity	56%
RF specifications	LE		

APPENDIX	Description of Test Item	Result
A	DTS Bandwidth	Compliant
B	Occupied Channel Bandwidth	Compliant
C	Maximum conducted output power	Compliant
D	Maximum power spectral density	Compliant
E	Reference level measurement	Compliant
F	Band edge measurements	Compliant
G	Conducted Spurious Emission	Compliant
H	Duty Cycle	Compliant

Appendix A: DTS Bandwidth

Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE_1M	Ant1	2402	0.672	2401.680	2402.352	0.5	PASS
LE_1M	Ant1	2440	0.668	2439.676	2440.344	0.5	PASS
LE_1M	Ant1	2480	0.640	2479.704	2480.344	0.5	PASS
LE_2M	Ant1	2402	1.108	2401.480	2402.588	0.5	PASS
LE_2M	Ant1	2440	1.056	2439.512	2440.568	0.5	PASS
LE_2M	Ant1	2480	1.244	2479.364	2480.608	0.5	PASS

Test Graphs



LE_1M-Ant1-2402-PASS



LE_1M-Ant1-2440-PASS



LE_1M-Ant1-2480-PASS

LE_2M-Ant1-2402-PASS

LE_2M-Ant1-2440-PASS

LE_2M-Ant1-2480-PASS

Appendix B: Maximum conducted output power

Test Result Peak

TestMode	Antenna	Frequency [MHz]	Conducted Peak Powert[dBm]	Conducted Limit[dBm]	Verdict
LE_1M	Ant1	2402	-0.81	≤30	PASS
LE_1M	Ant1	2440	-0.96	≤30	PASS
LE_1M	Ant1	2480	-0.41	≤30	PASS
LE_2M	Ant1	2402	-0.88	≤30	PASS
LE_2M	Ant1	2440	-1.03	≤30	PASS
LE_2M	Ant1	2480	-0.40	≤30	PASS

Test Graphs Peak



LE_1M-Ant1-2402-PASS



LE_1M-Ant1-2440-PASS



LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2402-PASS



LE_2M-Ant1-2440-PASS



LE_2M-Ant1-2480-PASS

Appendix C: Maximum power spectral density

Test Result

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
LE_1M	Ant1	2402	-16.20	≤8.00	PASS
LE_1M	Ant1	2440	-16.80	≤8.00	PASS
LE_1M	Ant1	2480	-15.78	≤8.00	PASS
LE_2M	Ant1	2402	-19.48	≤8.00	PASS
LE_2M	Ant1	2440	-19.09	≤8.00	PASS
LE_2M	Ant1	2480	-17.98	≤8.00	PASS

Test Graphs



LE_1M-Ant1-2402-PASS

LE_1M-Ant1-2440-PASS

LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2402-PASS



LE_2M-Ant1-2440-PASS



LE_2M-Ant1-2480-PASS

Appendix D: Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
LE_1M	Ant1	2402	2402.27	-2.01
LE_1M	Ant1	2440	2440.26	-2.28
LE_1M	Ant1	2480	2479.76	-1.86
LE_2M	Ant1	2402	2402.00	-2.55
LE_2M	Ant1	2440	2440.02	-2.75
LE_2M	Ant1	2480	2480.20	-3.89

Test Graphs



LE_1M-Ant1-2402-PASS

LE_1M-Ant1-2440-PASS



LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2402-PASS

LE_2M-Ant1-2440-PASS

LE_2M-Ant1-2480-PASS

Appendix E: Band edge measurements

Test Result

TestMode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
LE_1M	Ant1	Low	2402	-2.01	-46.65	≤-22.01	PASS
LE_1M	Ant1	High	2480	-1.86	-47.09	≤-21.86	PASS
LE_2M	Ant1	Low	2402	-2.55	-39.28	≤-22.55	PASS
LE_2M	Ant1	High	2480	-3.89	-46.67	≤-23.89	PASS

Test Graphs



LE_1M-Ant1-2402-PASS



LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2402-PASS



LE_2M-Ant1-2480-PASS

Appendix F: Conducted Spurious Emission

Test Result

TestMode	Antenna	Frequency [MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
LE_1M	Ant1	2402	30~1000	-2.01	-47.89	≤-22.01	PASS
LE_1M	Ant1	2402	1000~26500	-2.01	-34.01	≤-22.01	PASS
LE_1M	Ant1	2440	30~1000	-2.28	-47.88	≤-22.28	PASS
LE_1M	Ant1	2440	1000~26500	-2.28	-33.41	≤-22.28	PASS
LE_1M	Ant1	2480	30~1000	-1.86	-47.74	≤-21.86	PASS
LE_1M	Ant1	2480	1000~26500	-1.86	-34.09	≤-21.86	PASS
LE_2M	Ant1	2402	30~1000	-2.55	-48.07	≤-22.55	PASS
LE_2M	Ant1	2402	1000~26500	-2.55	-33.83	≤-22.55	PASS
LE_2M	Ant1	2440	30~1000	-2.75	-48.28	≤-22.75	PASS
LE_2M	Ant1	2440	1000~26500	-2.75	-34.07	≤-22.75	PASS
LE_2M	Ant1	2480	30~1000	-3.89	-46.26	≤-23.89	PASS
LE_2M	Ant1	2480	1000~26500	-3.89	-34.19	≤-23.89	PASS

Test Graphs



LE_1M-Ant1-2402-30~1000-PASS



LE_1M-Ant1-2402-1000~26500-PASS



LE_1M-Ant1-2440-30~1000-PASS



LE_1M-Ant1-2440-1000~26500-PASS



LE_1M-Ant1-2480-30~1000-PASS

LE_1M-Ant1-2480-1000~26500-PASS



LE_2M-Ant1-2402-30~1000-PASS

LE_2M-Ant1-2402-1000~26500-PASS



LE_2M-Ant1-2440-30~1000-PASS

LE_2M-Ant1-2440-1000~26500-PASS



LE_2M-Ant1-2480-30~1000-PASS

LE_2M-Ant1-2480-1000~26500-PASS

Appendix G: Duty Cycle

Test Result

TestMode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
LE_1M	Ant1	2402	2.14	5.81	36.83	4.34
LE_1M	Ant1	2440	2.14	5.81	36.83	4.34
LE_1M	Ant1	2480	2.15	5.81	37.01	4.32
LE_2M	Ant1	2402	1.08	4.76	22.69	6.44
LE_2M	Ant1	2440	1.07	4.75	22.53	6.47
LE_2M	Ant1	2480	1.08	4.75	22.74	6.43

Test Graphs



NTNV-LE_1M-Ant1-2402



NTNV-LE_1M-Ant1-2440



NTNV-LE_1M-Ant1-2480



NTNV-LE_2M-Ant1-2402



NTNV-LE_2M-Ant1-2440



NTNV-LE_2M-Ant1-2480

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******