


RF Exposure evaluation

Product Name : ANMUT EGO
Brand Name : N/A
Model : 251226E
Series Model : N/A
FCC ID : 2BTQ7-251226E
Applicant : **Suzhou ShaoHao Tech Co., Ltd.**
Address : Jinfeng Business Creative Center, Wuzhong District, Suzhou City,
Jiangsu Province, China
Manufacturer : **Suzhou ShaoHao Tech Co., Ltd.**
Address : Jinfeng Business Creative Center, Wuzhong District, Suzhou City,
Jiangsu Province, China
Standard(s) : 47CFR §1.1310, 47CFR §2.1091
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt : Jan. 29, 2026
Date of Test : Jan. 29, 2026~ Mar. 04, 2026
Issued Date : Mar. 04, 2026

Issued By: **Guangdong Asia Hongke Test Technology Limited**
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community,
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

Reviewed by: 
Aalen.Ye

Approved by: 
Allen Wang



Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.



Report Revise Record

Report Version	Issued Date	Notes
M0	Mar. 04, 2026	Initial Release

Contents

1	GENERAL INFORMATION.....	4
1.1	ENVIRONMENTAL CONDITIONS	4
1.2	GENERAL DESCRIPTION OF EUT	4
1.3	TEST FACILITY	6
1.4	MEASUREMENT UNCERTAINTY	6
2	METHOD OF MEASUREMENT.....	7
2.1	APPLICABLE STANDARD.....	7
2.2	LIMIT	7
2.3	MPE CALCULATION METHOD.....	8
2.4	ANTENNA INFORMATION	8
2.5	MANUFACTURING TOLERANCE	8
2.6	MPE RESULT.....	14
2.7	CONCLUSION.....	16

1 GENERAL INFORMATION

1.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

1.2 General Description of EUT

Product Name:	ANMUT EGO
Model/Type reference:	251226E
Serial Model:	N/A
Power Supply:	DC 12V from adapter
Adapter information	Model: SG-1205000B68U Output: AC 100-240V~50/60Hz 1.5A MAX Input: DC 12.0V---5.0A
Hardware Version:	TURNER_AME_V1.0
Software Version:	EGO_RK3566AUX122625_V08
Sample(s) Status:	AiTSZ-260119003-1(Normal sample) AiTSZ-260119003-2(Engineer sample)
Bluetooth:	
Supported type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	FPC antenna
Antenna gain:	3.87dBi
Bluetooth LE:	
Supported type:	Bluetooth LE 1M/2M
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	FPC antenna
Antenna gain:	3.87dBi
2.4G WIFI:	
Supported type:	802.11b/g/n(HT20)/n(HT40)/ax(HEW20)/ax(HEW40)
Modulation:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

	802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)			
Operation frequency:	802.11b/g/n(HT20)/ax(HEW20): 2412MHz~2462MHz 802.11n(HT40)/ax(HEW40):2422MHz~2452MHz			
Channel number:	802.11b/g/n(HT20)/ax(HEW20):11 802.11n(HT40)/ax(HEW40):7			
Channel separation:	5MHz			
Antenna type:	FPC antenna			
Antenna gain:	3.87dBi			
5G WIFI:				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac 802.11ax	802.11n 802.11ac 802.11ax	N/A	N/A
Operation frequency:	5180-5240MHz 5260-5320MHz 5500-5700MHz 5745-5825MHz	5190-5230MHz 5270-5310MHz 5510-5670MHz 5755-5795MHz	N/A	N/A
Modulation:	OFDM/OFDMA	OFDM/OFDMA	N/A	N/A
Channel number:	24	11	N/A	N/A
Channel separation:	20MHz	40MHz	N/A	N/A
MIMO	Not Support			
Antenna type:	FPC antenna			
Antenna gain:	4.76dBi			
Remark: The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.				

1.3 Test Facility

Test Laboratory:

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Guangdong Asia Hongke Test Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Asia Hongke laboratory is reported:

Test	Measurement Uncertainty	Notes
Power Line Conducted Emission	9KHz~30MHz ± 1.20 dB	(1)
Radiated Emission	9KHz~30MHz ± 3.10 dB	(1)
Radiated Emission	30MHz~1GHz ± 3.75 dB	(1)
Radiated Emission	1GHz~18GHz ± 3.88 dB	(1)
Radiated Emission	18GHz~40GHz ± 3.88 dB	(1)
RF power, conducted	30MHz~6GHz ± 0.16 dB	(1)
RF power density, conducted	± 0.24 dB	(1)
Spurious emissions, conducted	± 0.21 dB	(1)
Temperature	$\pm 1^{\circ}\text{C}$	(1)
Humidity	$\pm 3\%$	(1)
DC and low frequency voltages	$\pm 1.5\%$	(1)
Time	$\pm 2\%$	(1)
Duty cycle	$\pm 2\%$	(1)

The report uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

2 Method of measurement

2.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures

2.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

2.3 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

2.4 Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
WIFI/BLE	/	FPC antenna	BLE/2.4G WIFI: 3.87dBi 5G WIFI: 4.76dBi	2412-2462MHz 5180-5825MHz

2.5 Manufacturing Tolerance

2.4GHz WLAN				
IEEE 802.11b (Peak)				
Frequency (MHz)	Antenna 1			
	2412	2437	2462	
Target (dBm)	16.0	15.0	14.0	
Tolerance ± (dB)	1.0	1.0	1.0	
IEEE 802.11g (Peak)				
Frequency (MHz)	Antenna 1			
	2412	2437	2462	
Target (dBm)	15.0	14.5	14.5	
Tolerance ± (dB)	1.0	1.0	1.0	
IEEE 802.11n HT20 (Peak)				
Frequency (MHz)	Antenna 1			
	2412	2437	2462	
Target (dBm)	15.0	15.0	14.5	
Tolerance ± (dB)	1.0	1.0	1.0	
IEEE 802.11n HT40 (Peak)				
Frequency (MHz)	Antenna 1			
	2422	2437	2452	
Target (dBm)	15.5	15.0	14.5	
Tolerance ± (dB)	1.0	1.0	1.0	
IEEE 802.11ax HEW20 (Peak)				
Frequency (MHz)	Antenna 1			
	2412	2437	2462	
Target (dBm)	15.5	15.0	14.5	
Tolerance ± (dB)	1.0	1.0	1.0	
IEEE 802.11ax HEW40 (Peak)				
Frequency (MHz)	Antenna 1			
	2422	2437	2452	
Target (dBm)	15.5	15.5	15.0	
Tolerance ± (dB)	1.0	1.0	1.0	

5GHz WLAN Band 1

IEEE 802.11a (Average)			
Frequency (MHz)	Antenna 1		
	5180	5200	5240
Target (dBm)	9.0	8.0	7.5
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Frequency (MHz)	Antenna 1		
	5180	5200	5240
Target (dBm)	8.5	8.0	7.5
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Frequency (MHz)	Antenna 1		
	5180	5200	5240
Target (dBm)	8.5	8.0	7.5
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ax HEW20 (Average)			
Frequency (MHz)	Antenna 1		
	5180	5200	5240
Target (dBm)	8.5	8.0	7.5
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Frequency (MHz)	Antenna 1		
	5190	5230	
Target (dBm)	8.0	7.5	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT40 (Average)			
Frequency (MHz)	Antenna 1		
	5190	5230	
Target (dBm)	8.0	7.5	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ax HEW40 (Average)			
Frequency (MHz)	Antenna 1		
	5190	5230	
Target (dBm)	8.5	7.5	
Tolerance ± (dB)	1.0	1.0	

5GHz WLAN Band 2A

IEEE 802.11a (Average)

Frequency (MHz)	Antenna 1		
	5260	5300	5320
Target (dBm)	8.0	8.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n HT20 (Average)

Frequency (MHz)	Antenna 1		
	5260	5300	5320
Target (dBm)	8.0	8.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ac VHT20 (Average)

Frequency (MHz)	Antenna 1		
	5260	5300	5320
Target (dBm)	8.0	8.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ax HEW20 (Average)

Frequency (MHz)	Antenna 1		
	5260	5300	5320
Target (dBm)	10.0	10.0	10.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n HT40 (Average)

Frequency (MHz)	Antenna 1	
	5270	5310
Target (dBm)	8.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0

IEEE 802.11ac VHT40 (Average)

Frequency (MHz)	Antenna 1	
	5270	5310
Target (dBm)	8.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0

IEEE 802.11ax HEW40 (Average)

Frequency (MHz)	Antenna 1	
	5270	5310
Target (dBm)	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0

5GHz WLAN Band 2C

IEEE 802.11a (Average)

Frequency (MHz)	Antenna 1		
	5500	5580	5700
Target (dBm)	9.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n HT20 (Average)

Frequency (MHz)	Antenna 1		
	5500	5580	5700
Target (dBm)	9.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ac VHT20 (Average)

Frequency (MHz)	Antenna 1		
	5500	5580	5700
Target (dBm)	9.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ax HEW20 (Average)

Frequency (MHz)	Antenna 1		
	5500	5580	5700
Target (dBm)	11.0	9.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n HT40 (Average)

Frequency (MHz)	Antenna 1		
	5510	5550	5670
Target (dBm)	9.5	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ac VHT40 (Average)

Frequency (MHz)	Antenna 1		
	5510	5550	5670
Target (dBm)	9.5	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11ax HEW40 (Average)

Frequency (MHz)	Antenna 1		
	5510	5550	5670
Target (dBm)	9.5	9.5	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5GHz WLAN Band 3

IEEE 802.11a (Average)			
Frequency (MHz)	Antenna 1		
	5745	5785	5825
Target (dBm)	9.0	9.0	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Frequency (MHz)	Antenna 1		
	5745	5785	5825
Target (dBm)	8.5	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Frequency (MHz)	Antenna 1		
	5745	5785	5825
Target (dBm)	9.0	9.0	8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HEW20 (Average)			
Frequency (MHz)	Antenna 1		
	5745	5785	5825
Target (dBm)	9.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Frequency (MHz)	Antenna 1		
	5755		5795
Target (dBm)	9.0		9.0
Tolerance $\pm$ (dB)	1.0		1.0
IEEE 802.11ac VHT40 (Average)			
Frequency (MHz)	Antenna 1		
	5755		5795
Target (dBm)	9.0		9.0
Tolerance $\pm$ (dB)	1.0		1.0
IEEE 802.11ax HEW40 (Average)			
Frequency (MHz)	Antenna 1		
	5755		5795
Target (dBm)	10.0		9.0
Tolerance $\pm$ (dB)	1.0		1.0

BLE

BLE 1M GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0.5	1.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
BLE 2M GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0.5	1.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Bluetooth

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	1.0	0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.5	0.5	-0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.5	0.5	-0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.6 MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 2.4, the RF power density can be obtained.

Stand alone

WIFI2.4G Antenna 1

Modulation Type	Output power with tune up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	17.0	50.1187	3.87	2.4378	0.02431	1.0000
IEEE 802.11g	16.5	44.6684	3.87	2.4378	0.02166	1.0000
IEEE 802.11n HT20	16.0	39.8107	3.87	2.4378	0.01931	1.0000
IEEE 802.11n HT40	16.5	44.6684	3.87	2.4378	0.02166	1.0000
IEEE 802.11ax HEW20	16.5	44.6684	3.87	2.4378	0.02166	1.0000
IEEE 802.11ax HEW40	16.5	44.6684	3.87	2.4378	0.02166	1.0000

5GHz WLAN Band 1 Antenna 1

Modulation Type	Output power with tune up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	9.0	7.9433	4.76	2.9923	0.00473	1.0000
IEEE 802.11n HT20	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ac VHT20	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ax HEW20	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11n HT40	9.0	7.9433	4.76	2.9923	0.00473	1.0000
IEEE 802.11ac VHT40	9.0	7.9433	4.76	2.9923	0.00473	1.0000
IEEE 802.11ax HEW40	9.5	8.9125	4.76	2.9923	0.00531	1.0000

5GHz WLAN Band 2A Antenna 1

Modulation Type	Output power with tune up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11n HT20	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ac VHT20	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ax HEW20	11.5	14.1254	4.76	2.9923	0.00841	1.0000
IEEE 802.11n HT40	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ac VHT40	9.5	8.9125	4.76	2.9923	0.00531	1.0000
IEEE 802.11ax HEW40	11.0	12.5893	4.76	2.9923	0.00749	1.0000

5GHz WLAN Band 2C Antenna 1

Modulation Type	Output power with tune up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11n HT20	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ac VHT20	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ax HEW20	12.0	15.8489	4.76	2.9923	0.00943	1.0000
IEEE 802.11n HT40	10.5	11.2202	4.76	2.9923	0.00668	1.0000
IEEE 802.11ac VHT40	10.5	11.2202	4.76	2.9923	0.00668	1.0000
IEEE 802.11ax HEW40	10.5	11.2202	4.76	2.9923	0.00668	1.0000

5GHz WLAN Band 3 Antenna 1

Modulation Type	Output power with tune up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11n HT20	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ac VHT20	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ax HEW20	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11n HT40	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ac VHT40	10.0	10.0000	4.76	2.9923	0.00595	1.0000
IEEE 802.11ax HEW40	11.0	12.5893	4.76	2.9923	0.00749	1.0000

EDR / BLE

Modulation Type	Output power with tune_up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	2.0	1.5849	3.87	2.4378	0.00077	1.0000
PI/4DQPSK	1.5	1.4125	3.87	2.4378	0.00069	1.0000
8DPSK	1.5	1.4125	3.87	2.4378	0.00069	1.0000
BLE/1M	3.0	1.9953	3.87	2.4378	0.00097	1.0000
BLE/2M	3.0	1.9953	3.87	2.4378	0.00097	1.0000

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

simultaneous transmission Evaluation

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is.

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WLAN 2.4 + BT
2	WLAN 5G + BT

Simultaneous Combination	Max. Result Ratio WIFI	Max. Result Ratio BT	Total Ratio	Limit	Result
1	0.02431	0.00097	0.02528	1.0	Pass
2	0.00943	0.00097	0.0104	1.0	Pass

2.7 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

***** End of Report *****