



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

RF Exposure MPE

Report Reference No.....: CTA25111302303

FCC ID.....: 2BTT6-MMA21-4-A

Compiled by

(position+printed name+signature) : File administrators Zoey Cao

Supervised by

(position+printed name+signature) : Project Engineer Ace Chai

Approved by

(position+printed name+signature) : RF Manager Eric Wang

Date of issue: Dec. 02, 2025

Testing Laboratory Name: Shenzhen CTA Testing Technology Co., Ltd.

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: Shenzhen Vikcent Technology Co., Ltd.

Address.....: Room 601, Building 3, 10th Industrial Zone, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City

Standard: 47CFR §1.1310
47CFR §2.1091
KDB447498 D01 General RF Exposure Guidance v06

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Magic Mirror Appliance

Trade Mark: N/A

Manufacturer: Shenzhen Vikcent Technology Co., Ltd.

Model/Type reference: MMA21-4-A

Listed Models: MMA21-X

Rating: Input: 12V --- 7A

Result: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : Magic Mirror Appliance

Model /Type : MMA21-4-A

Listed Models : MMA21-X

Model difference : The PCB board, circuit, structure and internal of these models are the same, Only model number and colour is different for these model.

Applicant : **Shenzhen Vikcent Technology Co., Ltd.**

Address : Room 601, Building 3, 10th Industrial Zone, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City

Manufacturer : **Shenzhen Vikcent Technology Co., Ltd.**

Address : Room 601, Building 3, 10th Industrial Zone, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

Contents

1	TEST STANDARDS	4
2	SUMMARY	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Special Accessories	6
2.4	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Statement of the measurement uncertainty	7
4	Test limit	8
4.1	Requirement	8
4.2	MPE Calculation Method	8
4.3	Conducted Power Results	8
4.4	Manufacturing tolerance	12
4.5	Standalone MPE Result	12
4.6	Simultaneous Transmission for MPE Result	13
5	Conclusion	13

1 TEST STANDARDS

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Nov. 13, 2025
Testing commenced on	:	Nov. 13, 2025
Testing concluded on	:	Dec. 02, 2025

2.2 Product Description

Product Name:	Magic Mirror Appliance
Model/Type reference:	MMA21-4-A
Power supply:	Input: 12V--- 7A
Adapter information:	Model: HKA09012070-7U Input: 100-240V~, 50/60Hz, 1.5A MAX Output: 12.0V--- 7.0A, 84.0W
Hardware version:	/
Software version:	/
Testing sample ID:	CTA251113023-1# (Engineer sample) CTA251113023-2# (Normal sample)
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Internal Antenna
Antenna gain:	2.09dBi(Max.)
Bluetooth BLE	
Supported type:	Bluetooth low Energy
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2 MHz
Antenna type:	Internal Antenna
Antenna gain:	2.09dBi(Max.)
2.4GWIFI :	
Supported type:	802.11b/802.11g/802.11n(HT20)/ax(HE20)
Modulation:	802.11b: DSSS 802.11g/802.11n(HT20): OFDM 802.11ax(HE20): OFDMA
Operation frequency:	802.11b/802.11g/802.11n(HT20)/ax(HE20): 2412MHz~2462MHz
Channel number:	802.11b/802.11g/802.11n(HT20)/ax(HE20): 11
Channel separation:	5MHz

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

Antenna type:	Internal Antenna
Antenna gain:	2.09dBi(Max.)

5GWIFI	
WLAN	Supported 802.11 a/n/ac/ax
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac20/40/80: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax20/40/80: OFDMA (1024QAM,256QAM,64QAM, 16QAM, QPSK,BPSK)
Operation frequency	IEEE 802.11a:5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11n HT20: 5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11n HT40: 5190-5230MHz,5270-5310MHz,5510-5670MHz,5755-5795MHz IEEE 802.11ac20: 5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11ac40: 5190-5230MHz,5270-5310MHz,5510-5670MHz,5755-5795MHz IEEE 802.11ac80:5210MHz,5290MHz,5530-5610MHz,5775MHz IEEE 802.11ax20: 5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11ax40: 5190-5230MHz,5270-5310MHz,5510-5670MHz,5755-5795MHz IEEE 802.11ax80:5210MHz,5290MHz,5530-5610MHz,5775MHz
Channel number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530MHz,5610MHz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna type:	Internal Antenna
Antenna gain:	4.58dBi(Max.)

2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

Description	Manufacturer	Model	Technical Parameters	Certificate	Provided by
/	/	/	/	/	/

2.4 Modifications

No modifications were implemented to meet testing criteria.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27890 CAB identifier: CN0127

Shenzhen CTA Testing Technology Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)
Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)
Time	/	±2%	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

4 Test limit

4.1 Requirement

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4.2 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4.3 Conducted Power Results

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]
DH5	Ant1	2402	0.58
DH5	Ant1	2441	3.69
DH5	Ant1	2480	4.05
2DH5	Ant1	2402	2.17
2DH5	Ant1	2441	4.89
2DH5	Ant1	2480	4.99
3DH5	Ant1	2402	2.4
3DH5	Ant1	2441	5.03
3DH5	Ant1	2480	5.1

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TestMode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]
BLE_1M	Ant1	2402	-1.07
BLE_1M	Ant1	2440	2.91
BLE_1M	Ant1	2480	3.05
BLE_2M	Ant1	2402	-1.29
BLE_2M	Ant1	2440	2.83
BLE_2M	Ant1	2480	3

TestMode	Antenna	Frequency [MHz]	Peak Power[dBm]
11B	Ant1	2412	16.3
11B	Ant1	2437	16.57
11B	Ant1	2462	16.46
11G	Ant1	2412	14.95
11G	Ant1	2437	15.12
11G	Ant1	2462	14.88
11N20SISO	Ant1	2412	14.79
11N20SISO	Ant1	2437	15.23
11N20SISO	Ant1	2462	14.84
11AX20SISO	Ant1	2412	14.83
11AX20SISO	Ant1	2437	15.27
11AX20SISO	Ant1	2462	14.55

Test Mode	Antenna	Frequency [MHz]	Result [dBm]
11A	Ant1	5180	9.39
11A	Ant1	5200	9.45
11A	Ant1	5240	8.83
11N20SISO	Ant1	5180	9.00
11N20SISO	Ant1	5200	8.59
11N20SISO	Ant1	5240	8.84
11N40SISO	Ant1	5190	9.02
11N40SISO	Ant1	5230	8.83
11AC20SISO	Ant1	5180	9.17
11AC20SISO	Ant1	5200	8.81
11AC20SISO	Ant1	5240	8.62
11AC40SISO	Ant1	5190	8.80
11AC40SISO	Ant1	5230	9.15
11AC80SISO	Ant1	5210	9.14
11AX20SISO	Ant1	5180	9.11
11AX20SISO	Ant1	5200	8.82
11AX20SISO	Ant1	5240	8.70
11AX40SISO	Ant1	5190	9.14
11AX40SISO	Ant1	5230	8.76
11AX80SISO	Ant1	5210	9.07

Test Mode	Antenna	Frequency [MHz]	Result [dBm]
11A	Ant1	5260	9.03
11A	Ant1	5280	8.75
11A	Ant1	5320	8.69
11N20SISO	Ant1	5260	8.97
11N20SISO	Ant1	5280	8.63
11N20SISO	Ant1	5320	8.73
11N40SISO	Ant1	5270	8.90
11N40SISO	Ant1	5310	8.91
11AC20SISO	Ant1	5260	9.15
11AC20SISO	Ant1	5280	9.04
11AC20SISO	Ant1	5320	8.52
11AC40SISO	Ant1	5270	8.69
11AC40SISO	Ant1	5310	8.77
11AC80SISO	Ant1	5290	8.81
11AX20SISO	Ant1	5260	8.69
11AX20SISO	Ant1	5280	8.45
11AX20SISO	Ant1	5320	8.53
11AX40SISO	Ant1	5270	8.46
11AX40SISO	Ant1	5310	8.43
11AX80SISO	Ant1	5290	8.51

Test Mode	Antenna	Frequency[MHz]	Result [dBm]
11A	Ant1	5500	10.54
11A	Ant1	5580	9.62
11A	Ant1	5700	8.85
11N20SISO	Ant1	5500	10.50
11N20SISO	Ant1	5580	9.71
11N20SISO	Ant1	5700	8.96
11N40SISO	Ant1	5510	11.41
11N40SISO	Ant1	5550	10.93
11N40SISO	Ant1	5670	9.95
11AC20SISO	Ant1	5500	10.59
11AC20SISO	Ant1	5580	9.77
11AC20SISO	Ant1	5700	8.97
11AC40SISO	Ant1	5510	11.38
11AC40SISO	Ant1	5550	10.88
11AC40SISO	Ant1	5670	10.12
11AC80SISO	Ant1	5530	10.74
11AC80SISO	Ant1	5610	9.51
11AX20SISO	Ant1	5500	10.64
11AX20SISO	Ant1	5580	9.77
11AX20SISO	Ant1	5700	9.06
11AX40SISO	Ant1	5510	11.34
11AX40SISO	Ant1	5550	10.82
11AX40SISO	Ant1	5670	10.04
11AX80SISO	Ant1	5530	10.53
11AX80SISO	Ant1	5610	9.61

Test Mode	Antenna	Frequency[MHz]	Result dBm]
11A	Ant1	5745	10.83
11A	Ant1	5785	10.72
11A	Ant1	5825	10.91
11N20SISO	Ant1	5745	10.67
11N20SISO	Ant1	5785	10.56
11N20SISO	Ant1	5825	10.79
11N40SISO	Ant1	5755	10.49
11N40SISO	Ant1	5795	10.40
11AC20SISO	Ant1	5745	10.77
11AC20SISO	Ant1	5785	10.33
11AC20SISO	Ant1	5825	10.74
11AC40SISO	Ant1	5755	10.35
11AC40SISO	Ant1	5795	10.57
11AC80SISO	Ant1	5775	10.87
11AX20SISO	Ant1	5745	10.81
11AX20SISO	Ant1	5785	10.46
11AX20SISO	Ant1	5825	10.73
11AX40SISO	Ant1	5755	10.46
11AX40SISO	Ant1	5795	10.57
11AX80SISO	Ant1	5775	10.81

4.4 Manufacturing tolerance

Mode	Max. Peak Conducted Output Power (dBm)	Max. tune-up
BLE	3.05	3.0 ± 1
BR/EDR	5.1	5.0 ± 1
2.4GWIFI	16.57	16.0 ± 1
Mode	Max. Average Conducted Output Power (dBm)	Max. tune-up
5.2GWIFI	9.45	10.0 ± 1
5.3GWIFI	9.15	10.0 ± 1
5.5GWIFI	11.41	11.0 ± 1
5.8GWIFI	10.91	10.0 ± 1

4.5 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 2.2, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BLE	4.0	2.5119	2.09	1.6181	0.0008	1.0000
BR/EDR	6.0	3.9811	2.09	1.6181	0.0013	1.0000
2.4GWIFI	17.0	50.1187	2.09	1.6181	0.0161	1.0000
5.2GWIFI	11.0	12.5893	4.58	2.8708	0.0072	1.0000
5.3GWIFI	11.0	12.5893	4.58	2.8708	0.0072	1.0000
5.5GWIFI	12.0	15.8489	4.58	2.8708	0.0091	1.0000
5.8GWIFI	11.0	12.5893	4.58	2.8708	0.0072	1.0000

GSM/WCDMA/LTE:

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducted Average Output Power (dBm)	Output Power to Antenna (dBm)	EIRP(ERP) Limit (dBm)	Output Power to Antenna (mw)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Gain according to EIRP (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
GSM850	824.2	2.29	25.81	25.95	38.45	381.0658	0.1284	0.5495	14.79	8.60	8.60	Pass
GSM1900	1850.2	1.59	22.81	24.40	33.00	190.9853	0.0548	1.0000	10.19	14.20	10.19	Pass
WCDMA B2	1852.4	1.59	25.00	26.59	33.00	316.2278	0.0907	1.0000	8.00	12.01	8.00	Pass
WCDMA B4	1712.4	2.00	25.00	27.00	30.00	316.2278	0.0997	1.0000	5.00	12.01	5.00	Pass
WCDMA B5	826.4	2.29	25.00	25.14	38.45	316.2278	0.1066	0.5509	15.60	9.42	9.42	Pass
LTE B2	1850.7	1.59	25.00	26.59	33.00	316.2278	0.0907	1.0000	8.00	12.01	8.00	Pass
LTE B4	1710.7	2.00	25.00	27.00	30.00	316.2278	0.0997	1.0000	5.00	12.01	5.00	Pass
LTE B5	824.70	2.29	25.00	25.14	38.45	316.2278	0.1066	0.5498	15.60	9.41	9.41	Pass
LTE B7	2502.50	3.00	25.00	28.00	33.00	316.2278	0.1255	1.0000	8.00	12.01	8.00	Pass
LTE B12	699.70	3.26	25.00	26.11	34.77	316.2278	0.1333	0.4665	11.92	8.70	8.70	Pass
LTE B13	779.50	4.45	25.00	27.30	34.77	316.2278	0.1753	0.5197	11.92	9.16	9.16	Pass
LTE B25	1850.7	1.59	25.00	26.59	33.00	316.2278	0.0907	1.0000	8.00	12.01	8.00	Pass
LTE B26(814-824)	814.7	2.53	25.00	25.38	50.00	316.2278	0.1126	0.5431	27.15	9.36	9.36	Pass
LTE B26(824-849)	824.7	2.53	25.00	25.38	38.45	316.2278	0.1126	0.5498	15.60	9.41	9.41	Pass
LTE B38	2572.5	2.06	25.00	27.06	33.00	316.2278	0.1011	1.0000	8.00	12.01	8.00	Pass
LTE B41	2498.5	3.00	25.00	28.00	33.00	316.2278	0.1255	1.0000	8.00	12.01	8.00	Pass

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

3. *LTE MPE referring to the FCC ID No: XMR201903EG25G issued by the Testing Lab (SGS-CSTC Standards Technical Services Co., Ltd)*

4.6 Simultaneous Transmission for MPE Result

2.4GWIFI MPE (Ratio)	LTE B13 MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
0.0161	0.3373	0.3534	1.0000

5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device Threshold per KDB 447498 D01v06

***** End of Report *****