

TEST REPORT

Applicant Name: McGrath Locks PTY LTD
Address: 4/36 Windorah St, Stafford Qld 4053, Australia
Report Number: 2504Z01847E-RF-00B
FCC ID: 2BTTC-ML-HAMILTON

Test Standard (s)

FCC PART 15.247

Sample Description

Product Name: Digital Lock
Model No.: ML-Hamilton
Trade Mark: 
Date Received: 2025-11-27
Report Date: 2026-04-08

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Amanda Wei

Amanda Wei
EMC Engineer

Approved By:

Bob. Liao

Bob.Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked. This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	6
TEST METHODOLOGY	6
TEST FACILITY	6
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE AND POWER LEVEL [#]	7
SPECIAL ACCESSORIES AND EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
RADIATED SPURIOUS EMISSION	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE	14
CALCULATION	14
TEST DATA	15
6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	73
APPLICABLE STANDARD	73
TEST PROCEDURE	73
TEST DATA	74
MAXIMUM CONDUCTED OUTPUT POWER	75
APPLICABLE STANDARD	75
TEST PROCEDURE	75
TEST DATA	75
CONDUCTED SPURIOUS EMISSION	76
APPLICABLE STANDARD	76
TEST PROCEDURE	76
TEST DATA	76
POWER SPECTRAL DENSITY	77
APPLICABLE STANDARD	77
TEST PROCEDURE	77
TEST DATA	77
DUTY CYCLE	78
TEST PROCEDURE	78
TEST DATA	78

APPENDIX 79

6dB EMISSION BANDWIDTH 80

99% OCCUPIED BANDWIDTH 84

MAXIMUM CONDUCTED OUTPUT POWER 88

POWER SPECTRAL DENSITY 89

DUTY CYCLE..... 93

CONDUCTED SPURIOUS EMISSION 95

EXHIBIT A-EUT PHOTOGRAPHS 102

EXHIBIT B-TEST SETUP PHOTOGRAPHS 103

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504Z01847E-RF-00B	Original Report	2026-04-08

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name	Digital Lock
Tested Model	ML-Hamilton
Voltage Range [#]	DC 6V from 4*AA Alkaline batteries
Note: The device (Digital Lock) has two parts: Exterior Assembly and Interior Assembly.	

The Interior Assembly has 2.4G Wi-Fi function, it was tested and recorded in this report.	
Frequency Range	2.4G Wi-Fi: 802.11 b/g/n20/n40/ax20: 2412-2462MHz
Maximum Conducted Peak Output Power (actual test result)	25.03 dBm
Modulation Technique	DSSS, OFDM, OFDMA
Antenna Specification [#]	Internal Antenna, Gain: 2.62 dBi (It is provided by the applicant.)
Sample Serial Number	For RSE Test: 3DLK-1 For RF Conducted Test: 3DLK-2 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, and KDB 558074 D01 15.247 Meas Guidance v05r02.

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5 %
RF Frequency		0.064×10^{-7}
RF output power, conducted		0.3 dB
Unwanted Emission, conducted		1.2 dB
AC Power Lines Conducted Emissions		2.7 dB
Radiated Spurious Emissions	9kHz - 30MHz	2.1 dB
	30MHz - 1GHz	4.3 dB
	1GHz - 18GHz	4.9 dB
	18GHz - 26.5GHz	5.2 dB
Temperature		1 °C
Humidity		2 %
Supply voltages		0.4 %

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4G Wi-Fi, total 11 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

802.11b/g/n20/ax20 mode was tested with Channel 1, 6 and 11.

802.11n40 mode was tested with Channel 3, 6 and 9.

EUT Exercise Software and Power Level[#]

Exercise Software:		RDTool		
Mode	Data Rate	Power Level		
		Low Channel	Middle Channel	High Channel
802.11 b	1Mbps	-20	-20	-20
802.11 g	6Mbps	-20	-20	-20
802.11 n20	MCS0	-20	-20	-20
802.11 n40	MCS0	-20	-20	-20
802.11 ax20	MCS0	-20	-20	-20

Note 1: The information in the above table is provided by the applicant.

Note 2: The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Note 3: For 802.11 ax mode, the device not support partial RU mode.

Special Accessories and Equipment Modifications

No special accessories or modifications were used on the device under test (EUT) during the test.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
/	/	/	/	/

Block Diagram of Test Setup

For Radiated Emission Below 1GHz:



For Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209 §15.247(d)	Radiated Spurious Emissions	Compliance
§15.247(a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	Conducted Spurious Emission	Compliance
§15.247(e)	Power Spectral Density	Compliance

Not Applicable: The device was powered by battery when operating.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Spurious Emission Test(Below 1GHz)					
Rohde & Schwarz	Test Receiver	ESR	102725	2025/09/18	2026/09/17
SONOMA INSTRUMENT	Amplifier	310N	186131	2025/03/26	2026/03/25
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2024/08/08	2027/08/07
Unknown	RF Coaxial Cable	No.12	N040	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.13	N300	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.14	N800	2025/05/30	2026/05/29
BACL	LOOP ANTENNA	1313-1A	3110711	2024/01/16	2027/01/15
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Above 1GHz)					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2025/09/17	2026/09/16
Decentest	Filter Switch Unit	DT7220FSU	DQ77927	2025/09/18	2026/09/17
Decentest	Multiplex Switch Test Control Set	DT7220CSU	DQ77924	2025/09/18	2026/09/17
A.H. Systems, inc.	Preamplifier	PAM-0118	226	2025/03/20	2026/03/19
A.H. Systems, inc.	Preamplifier	PAM-0118	226	2026/01/20	2027/01/19
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	Horn Antenna	BBHA9120D	837	2026/01/29	2029/01/30
COM-MW	Band Reject Filter	ZBSF8	12232062	2025/10/13	2026/10/12
Unknown	RF Coaxial Cable	No.10	N050	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.11	N1000	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.19	N500	2025/05/30	2026/05/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2023/12/12	2026/12/11
BACL	Amplifier	BACL-1313-A1840	4012521	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.15	N600	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.16	N650	2025/05/30	2026/05/29
Test Software: e3 191218 (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101590	2025/09/17	2026/09/16
Anritsu	Microwave Peak Power Sensor	MA24418A	12619	2025/03/26	2026/03/25
WEINSCHEL	10dB Attenuator	5324	AU 3842	2025/03/26	2026/03/25
Test Software: JDAutoTestSystem V1.0.0					

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which were permanently attached to the EUT. The antenna is 2.62dBi[#]. Fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


RADIATED SPURIOUS EMISSION

Applicable Standard


FCC §15.205; §15.209; §15.247(d)


EUT Setup

9kHz - 30MHz:



30MHz - 1GHz:



Above 1GHz:

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9kHz to 25GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz -1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9kHz - 150kHz	PK	0.3kHz	1kHz	/	PK
	QP/AV	/	/	200Hz	QP/AV
150kHz - 30MHz	PK	10kHz	30kHz	/	PK
	QP/AV	/	/	9kHz	QP/AV
30MHz - 1000MHz	PK	100kHz	300kHz	/	PK
	QP	/	/	120kHz	QP

1GHz-25GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	5kHz
		<98%	1MHz	≥1/T, no less than 3kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	10Hz
		<98%	1MHz	≥1/T

Note 1: T is minimum transmission duration

Note 2: The 1GHz-18GHz testing use the notch filter.

Note 3: The band edge testing use 10dB attenuator.

Note 4: The filters and attenuators are all integrated within the filter switch unit.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to FCC §15.209(e), the provisions in §15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

According to FCC§15.31 measurement standard (f)(2), at frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

For 9kHz-30MHz, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10}\left(\frac{d_{\text{Standard}}}{d_{\text{measure}}}\right)$$

Note 1: If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Note 2: For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level / Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

For Radiated Spurious Emissions, this device is installed vertically in Y-axes orientation. It was provided by applicant. The Y-axes orientation was tested and recorded in the report.

9kHz-1GHz

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	59 %
ATM Pressure:	100.9 kPa
Test Engineer:	Colin Lin
Test Date:	2025-12-19
EUT Operation Mode:	2.4G WIFI Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: The Loop Antenna were tested in parallel, perpendicular, and ground-parallel. The worst orientation was parallel and the data was recorded in report.


Note 2: The pre-scan maximum output power mode and channel: 2.4G WiFi 802.11n20 Low Channel 2412MHz was tested.

9kHz~30MHz:



Site : chamber
Condition : 3m
Job No. : 2504Z01847E-RF
Polarization : Parallel Tester: Colin Lin
Test Mode : 2.4G WIFI Transmitting
Receiver Setting: RBW:300Hz VBW:1kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.012	35.03	25.61	60.64	126.17	-65.53	Peak
2	0.017	32.81	25.97	58.78	123.09	-64.31	Peak
3	0.030	26.95	25.53	52.48	118.06	-65.58	Peak
4	0.047	23.50	19.91	43.41	114.22	-70.81	Peak
5	0.073	19.49	19.94	39.43	110.31	-70.88	Peak
6	0.113	15.84	21.48	37.32	106.53	-69.21	Peak



Site : chamber
Condition : 3m
Job No. : 2504Z01847E-RF
Polarization : Parallel Tester: Colin Lin
Test Mode : 2.4G WIFI Transmitting
Receiver Setting: RBW:10kHz VBW:30kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1.223	-2.62	54.89	52.27	65.69	-13.42	Peak
2	2.167	-5.45	58.52	53.07	69.54	-16.47	Peak
3	3.293	-5.97	64.10	58.13	69.54	-11.41	Peak
4	6.219	-6.17	40.94	34.77	69.54	-34.77	Peak
5	10.620	-5.20	42.06	36.86	69.54	-32.68	Peak
6	16.226	-3.86	36.81	32.95	69.54	-36.59	Peak

30MHz~1GHz:



Site : chamber
 Condition : 3m HORIZONTAL
 Job No. : 2504Z01847E-RF Tester: Colin Lin
 Test Mode : 2.4G WIFI Transmitting
 Receiver Setting: RBW:100kHz VBW:300kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	49.729	-9.92	29.31	19.39	40.00	-20.61	Peak
2	102.225	-11.25	28.70	17.45	43.50	-26.05	Peak
3	196.166	-9.89	28.25	18.36	43.50	-25.14	Peak
4	283.358	-9.17	30.11	20.94	46.00	-25.06	Peak
5	426.334	-4.97	30.77	25.80	46.00	-20.20	Peak
6	769.760	0.47	29.08	29.55	46.00	-16.45	Peak



Site : chamber
Condition : 3m VERTICAL
Job No. : 2504Z01847E-RF Tester: Colin Lin
Test Mode : 2.4G WIFI Transmitting
Receiver Setting: RBW:100kHz VBW:300kHz

	Freq		Read		Limit	Over	Remark
	Factor		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.127	-11.43	36.55	25.12	40.00	-14.88	Peak
2	104.353	-11.14	28.92	17.78	43.50	-25.72	Peak
3	190.823	-10.30	29.32	19.02	43.50	-24.48	Peak
4	371.027	-6.89	30.42	23.53	46.00	-22.47	Peak
5	445.828	-4.91	31.48	26.57	46.00	-19.43	Peak
6	654.519	-1.20	29.88	28.68	46.00	-17.32	Peak

1GHz-25GHz

Environmental Conditions


Temperature:	23.1 to 24.5 °C
Relative Humidity:	52 to 54 %
ATM Pressure:	100.4 to 100.9 kPa
Test Engineer:	Angel Chen
Test Date:	2025-12-25 to 2026-03-27
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: For 1GHz-18GHz, the fundamental with band reject filter.

Note 2: For 18GHz-25GHz, the pre-scan maximum output power mode and channel: 2.4G WiFi 802.11n20 Low Channel 2412MHz was tested.

2.4G WIFI 802.11b Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11b Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2094.375	-10.92	60.95	50.03	54.00	-3.97 Average
2	2094.375	-10.92	67.40	56.48	74.00	-17.52 Peak
3	2736.125	-9.88	63.24	53.36	74.00	-20.64 Peak
4	4824.000	-6.64	56.89	50.25	74.00	-23.75 peak
5	7236.000	-1.32	53.20	51.88	74.00	-22.12 peak
6	13898.750	8.13	39.67	47.80	54.00	-6.20 average
7	13898.750	8.13	53.03	61.16	74.00	-12.84 peak

2.4G WIFI 802.11b Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 2.4G WIFI 802.11b Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Read	Limit	Over	
Freq Factor	Level	Level	Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m
1 2092.250	-10.94	61.82	50.88	54.00 -3.12 Average
2 2092.250	-10.94	69.74	58.80	74.00 -15.20 Peak
3 2251.625	-10.16	57.72	47.56	54.00 -6.44 Average
4 2251.625	-10.16	66.03	55.87	74.00 -18.13 Peak
5 2734.000	-9.88	63.72	53.84	74.00 -20.16 Peak
6 4824.000	-6.64	55.62	48.98	74.00 -25.02 peak
7 7236.000	-1.32	52.29	50.97	74.00 -23.03 peak
8 17938.380	8.18	39.68	47.86	54.00 -6.14 Average
9 17938.380	8.18	53.19	61.37	74.00 -12.63 peak

2.4G WIFI 802.11b Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11b Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.790	-10.25	52.94	42.69	54.00	-11.31 Average
2	2386.790	-10.25	76.31	66.06	74.00	-7.94 Peak
3	2390.000	-10.25	62.70	52.45	74.00	-21.55 peak

2.4G WIFI 802.11b Low Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11b Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.170	-10.25	55.25	45.00	54.00	-9.00 Average
2	2389.170	-10.25	78.39	68.14	74.00	-5.86 Peak
3	2390.000	-10.25	55.59	45.34	54.00	-8.66 average
4	2390.000	-10.25	75.53	65.28	74.00	-8.72 peak

2.4G WIFI 802.11b Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11b Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2109.250	-10.79	62.13	51.34	54.00	-2.66 Average
2	2109.250	-10.79	67.15	56.36	74.00	-17.64 Peak
3	2763.750	-10.04	62.62	52.58	74.00	-21.42 Peak
4	4874.000	-6.58	53.58	47.00	74.00	-27.00 peak
5	7311.000	-1.12	52.55	51.43	74.00	-22.57 peak
6	14464.000	8.40	39.36	47.76	54.00	-6.24 average
7	14464.000	8.40	52.62	61.02	74.00	-12.98 peak

2.4G WIFI 802.11b Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11b Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2113.500	-10.77	61.71	50.94	54.00	-3.06 Average
2	2113.500	-10.77	69.17	58.40	74.00	-15.60 Peak
3	2759.500	-10.01	63.13	53.12	74.00	-20.88 Peak
4	4874.000	-6.58	54.47	47.89	74.00	-26.11 peak
5	7311.000	-1.12	52.74	51.62	74.00	-22.38 peak
6	17997.880	8.44	39.41	47.85	54.00	-6.15 average
7	17997.880	8.44	52.88	61.32	74.00	-12.68 peak

2.4G WIFI 802.11b High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11b High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2134.750	-10.66	61.49	50.83	54.00	-3.17 Average
2	2134.750	-10.66	66.28	55.62	74.00	-18.38 Peak
3	4924.000	-6.48	53.24	46.76	74.00	-27.24 peak
4	7386.000	-1.31	51.90	50.59	74.00	-23.41 peak
5	17732.250	7.71	40.02	47.73	54.00	-6.27 average
6	17732.250	7.71	54.09	61.80	74.00	-12.20 peak

2.4G WIFI 802.11b High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11b High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2134.750	-10.66	62.12	51.46	54.00	-2.54 Average
2	2134.750	-10.66	68.33	57.67	74.00	-16.33 Peak
3	4924.000	-6.48	53.46	46.98	74.00	-27.02 peak
4	7386.000	-1.31	52.57	51.26	74.00	-22.74 peak
5	17995.750	8.42	39.30	47.72	54.00	-6.28 average
6	17995.750	8.42	52.66	61.08	74.00	-12.92 peak

2.4G WIFI 802.11b High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11b High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500 -10.23	52.34	42.11	54.00	-11.89	average
2	2483.500 -10.23	70.67	60.44	74.00	-13.56	peak
3	2493.035 -10.25	50.48	40.23	54.00	-13.77	Average
4	2493.035 -10.25	73.27	63.02	74.00	-10.98	Peak

2.4G WIFI 802.11b High Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11b High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	55.87	45.64	54.00	-8.36 average
2	2483.500	-10.23	71.66	61.43	74.00	-12.57 peak


2.4G WIFI 802.11g Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504Z01847E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2.4G WIFI 802.11g Low Channel 2412MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.64	53.80	47.16	74.00	-26.84	peak
2	7236.000	-1.32	51.80	50.48	74.00	-23.52	peak

2.4G WIFI 802.11g Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2092.250	-10.94	64.33	53.39	74.00	-20.61 Peak
2	2247.375	-10.15	62.95	52.80	74.00	-21.20 Peak
3	4824.000	-6.64	54.28	47.64	74.00	-26.36 peak
4	7236.000	-1.32	52.24	50.92	74.00	-23.08 peak


2.4G WIFI 802.11g Low Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504Z01847E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2.4G WIFI 802.11g Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.240	-10.25	57.19	46.94	54.00	-7.06 Average
2	2389.240	-10.25	73.42	63.17	74.00	-10.83 Peak
3	2390.000	-10.25	57.97	47.72	54.00	-6.28 Average
4	2390.000	-10.25	72.59	62.34	74.00	-11.66 peak

2.4G WIFI 802.11g Low Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.25	59.78	49.53	54.00	-4.47 Average
2	2390.000	-10.25	76.55	66.30	74.00	-7.70 peak

2.4G WIFI 802.11g Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2113.500	-10.77	64.16	53.39	74.00	-20.61 Peak
2	4874.000	-6.58	55.61	49.03	74.00	-24.97 peak
3	7311.000	-1.12	52.32	51.20	74.00	-22.80 peak

2.4G WIFI 802.11g Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2115.625	-10.76	58.16	47.40	54.00	-6.60 Average
2	2115.625	-10.76	67.71	56.95	74.00	-17.05 Peak
3	4874.000	-6.58	56.55	49.97	74.00	-24.03 peak
4	7311.000	-1.12	52.07	50.95	74.00	-23.05 peak

2.4G WIFI 802.11g High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2130.500	-10.68	59.01	48.33	54.00	-5.67 Average
2	2130.500	-10.68	66.99	56.31	74.00	-17.69 Peak
3	4924.000	-6.48	55.82	49.34	74.00	-24.66 peak
4	7386.000	-1.31	52.74	51.43	74.00	-22.57 peak

2.4G WIFI 802.11g High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11g High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2136.875	-10.65	60.23	49.58	54.00	-4.42 Average
2	2136.875	-10.65	68.99	58.34	74.00	-15.66 Peak
3	4924.000	-6.48	57.67	51.19	74.00	-22.81 peak
4	7386.000	-1.31	51.72	50.41	74.00	-23.59 peak

2.4G WIFI 802.11g High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11g High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	58.60	48.37	54.00	-5.63 Average
2	2483.500	-10.23	73.19	62.96	74.00	-11.04 peak

2.4G WIFI 802.11g High Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 2.4G WIFI 802.11g High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	60.50	50.27	54.00	-3.73 Average
2	2483.500	-10.23	75.76	65.53	74.00	-8.47 peak
3	2484.185	-10.23	61.47	51.24	54.00	-2.76 Average
4	2484.185	-10.23	75.83	65.60	74.00	-8.40 Peak

2.4G WIFI 802.11n20 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.64	53.87	47.23	74.00	-26.77 peak
2	7236.000	-1.32	52.22	50.90	74.00	-23.10 peak

2.4G WIFI 802.11n20 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2092.250	-10.94	55.67	44.73	54.00	-9.27 Average
2	2092.250	-10.94	65.70	54.76	74.00	-19.24 Peak
3	2247.375	-10.15	63.28	53.13	74.00	-20.87 Peak
4	4824.000	-6.64	54.34	47.70	74.00	-26.30 peak
5	7236.000	-1.32	52.35	51.03	74.00	-22.97 peak

2.4G WIFI 802.11n20 Low Channel 18GHz-25GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WiFi 802.11n20 Low Channel 2412MHz 18GHz-25GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 21771.250	0.08	53.13	53.21	74.00	-20.79	Peak

2.4G WIFI 802.11n20 Low Channel 18GHz-25GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WiFi 802.11n20 Low Channel 2412MHz 18GHz-25GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1 22256.880	0.82	52.00	52.82	74.00	-21.18	Peak

2.4G WIFI 802.11n20 Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.25	54.69	44.44	54.00	-9.56 average
2	2390.000	-10.25	74.37	64.12	74.00	-9.88 peak

2.4G WIFI 802.11n20 Low Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.25	56.46	46.21	54.00	-7.79 average
2	2390.000	-10.25	76.04	65.79	74.00	-8.21 peak

2.4G WIFI 802.11n20 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2115.625	-10.76	63.74	52.98	74.00	-21.02 Peak
2	4874.000	-6.58	53.54	46.96	74.00	-27.04 peak
3	7311.000	-1.12	51.43	50.31	74.00	-23.69 peak

2.4G WIFI 802.11n20 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2113.500	-10.77	64.40	53.63	74.00	-20.37	Peak
2 4874.000	-6.58	52.98	46.40	74.00	-27.60	peak
3 7311.000	-1.12	50.86	49.74	74.00	-24.26	peak

2.4G WIFI 802.11n20 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2134.750	-10.66	64.21	53.55	74.00	-20.45 Peak
2	4924.000	-6.48	55.52	49.04	74.00	-24.96 peak
3	7386.000	-1.31	51.96	50.65	74.00	-23.35 peak

2.4G WIFI 802.11n20 High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2134.750	-10.66	56.89	46.23	54.00	-7.77 Average
2	2134.750	-10.66	66.73	56.07	74.00	-17.93 Peak
3	4924.000	-6.48	55.93	49.45	74.00	-24.55 peak
4	7386.000	-1.31	51.95	50.64	74.00	-23.36 peak

2.4G WIFI 802.11n20 High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500 -10.23	55.41	45.18	54.00	-8.82	average
2	2483.500 -10.23	72.07	61.84	74.00	-12.16	peak

2.4G WIFI 802.11n20 High Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n20 High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	58.17	47.94	54.00	-6.06 average
2	2483.500	-10.23	75.40	65.17	74.00	-8.83 peak


2.4G WIFI 802.11n40 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504Z01847E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-6.64	53.84	47.20	74.00	-26.80 peak
2	7266.000	-1.23	52.96	51.73	74.00	-22.27 peak

2.4G WIFI 802.11n40 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-6.64	51.90	45.26	74.00	-28.74 peak
2	7266.000	-1.23	52.37	51.14	74.00	-22.86 peak

2.4G WIFI 802.11n40 Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.428	-10.24	56.61	46.37	54.00	-7.63 Average
2	2386.428	-10.24	70.67	60.43	74.00	-13.57 Peak
3	2390.000	-10.25	58.31	48.06	54.00	-5.94 average
4	2390.000	-10.25	70.08	59.83	74.00	-14.17 peak


2.4G WIFI 802.11n40 Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504Z01847E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.478	-10.24	58.36	48.12	54.00	-5.88 Average
2	2386.478	-10.24	72.55	62.31	74.00	-11.69 Peak
3	2390.000	-10.25	59.91	49.66	54.00	-4.34 average
4	2390.000	-10.25	72.33	62.08	74.00	-11.92 peak

2.4G WIFI 802.11n40 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.58	51.70	45.12	74.00	-28.88 peak
2	7311.000	-1.12	52.11	50.99	74.00	-23.01 peak

2.4G WIFI 802.11n40 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.58	52.80	46.22	74.00	-27.78 peak
2	7311.000	-1.12	51.61	50.49	74.00	-23.51 peak

2.4G WIFI 802.11n40 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n40 High Channel 2452MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4904.000	-6.52	51.43	44.91	74.00	-29.09 peak
2	7356.000	-1.26	51.92	50.66	74.00	-23.34 peak

2.4G WIFI 802.11n40 High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11n40 High Channel 2452MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4904.000	-6.52	52.32	45.80	74.00	-28.20 peak
2	7356.000	-1.26	51.73	50.47	74.00	-23.53 peak

2.4G WIFI 802.11n40 High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Note : 2.4G WIFI 802.11n40 High Channel 2452MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Tester:Angel Chen

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	56.44	46.21	54.00	-7.79 average
2	2483.500	-10.23	67.49	57.26	74.00	-16.74 peak
3	2487.645	-10.24	54.48	44.24	54.00	-9.76 Average
4	2487.645	-10.24	67.91	57.67	74.00	-16.33 Peak

2.4G WIFI 802.11n40 High Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11n40 High Channel 2452MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	60.12	49.89	54.00	-4.11 average
2	2483.500	-10.23	70.77	60.54	74.00	-13.46 peak
3	2485.764	-10.25	57.85	47.60	54.00	-6.40 Average
4	2485.764	-10.25	71.64	61.39	74.00	-12.61 Peak

2.4G WIFI 802.11ax20 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2092.250	-10.94	63.96	53.02	74.00	-20.98 Peak
2	4824.000	-6.64	54.67	48.03	74.00	-25.97 peak
3	7236.000	-1.32	51.72	50.40	74.00	-23.60 peak

2.4G WIFI 802.11ax20 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2094.375	-10.92	55.17	44.25	54.00	-9.75 Average
2	2094.375	-10.92	66.95	56.03	74.00	-17.97 Peak
3	4824.000	-6.64	54.73	48.09	74.00	-25.91 peak
4	7236.000	-1.32	52.04	50.72	74.00	-23.28 peak

2.4G WIFI 802.11ax20 Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : Transmitting Tester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.25	57.04	46.79	54.00	-7.21 average
2	2390.000	-10.25	72.50	62.25	74.00	-11.75 peak

2.4G WIFI 802.11ax20 Low Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : Transmitting Tester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2388.442	-10.24	57.30	47.06	54.00	-6.94 Average
2	2388.442	-10.24	74.00	63.76	74.00	-10.24 Peak
3	2390.000	-10.25	58.34	48.09	54.00	-5.91 average
4	2390.000	-10.25	74.05	63.80	74.00	-10.20 peak

2.4G WIFI 802.11ax20 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.58	54.06	47.48	74.00	-26.52 peak
2	7311.000	-1.12	52.02	50.90	74.00	-23.10 peak

2.4G WIFI 802.11ax20 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2119.875	-10.74	55.66	44.92	54.00	-9.08 Average
2	2119.875	-10.74	67.35	56.61	74.00	-17.39 Peak
3	4874.000	-6.58	54.50	47.92	74.00	-26.08 peak
4	7311.000	-1.12	52.30	51.18	74.00	-22.82 peak

2.4G WIFI 802.11ax20 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2130.500	-10.68	64.06	53.38	74.00	-20.62 Peak
2	4924.000	-6.48	53.94	47.46	74.00	-26.54 peak
3	7386.000	-1.31	52.58	51.27	74.00	-22.73 peak

2.4G WIFI 802.11ax20 High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2136.875	-10.65	55.71	45.06	54.00	-8.94 Average
2	2136.875	-10.65	66.07	55.42	74.00	-18.58 Peak
3	4924.000	-6.48	54.87	48.39	74.00	-25.61 peak
4	7386.000	-1.31	52.49	51.18	74.00	-22.82 peak

2.4G WIFI 802.11ax20 High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504Z01847E-RF


Test Mode : Transmitting Tester:Angel Chen

Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500 -10.23	55.90	45.67	54.00	-8.33	average
2	2483.500 -10.23	70.96	60.73	74.00	-13.27	peak
3	2484.927 -10.23	54.84	44.61	54.00	-9.39	Average
4	2484.927 -10.23	72.19	61.96	74.00	-12.04	Peak

2.4G WIFI 802.11ax20 High Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504Z01847E-RF

Test Mode : TransmittingTester:Angel Chen

Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.23	58.88	48.65	54.00	-5.35 average
2	2483.500	-10.23	74.77	64.54	74.00	-9.46 peak
3	2485.010	-10.25	57.60	47.35	54.00	-6.65 Average
4	2485.010	-10.25	74.93	64.68	74.00	-9.32 Peak

6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

According to FCC §15.247(a)(2):

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020, section 11.8 and section 6.9

The steps for the first option are as follows:


- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

According to ANSI C63.10-2020, section 7.8.6 and section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

- h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Note: Offset = RF cable loss(0.5dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b)(3):

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


Test Procedure

According to ANSI C63.10-2020, section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

According to ANSI C63.10-2020, section 11.9.2.3

- Measurement using a power meter (PM)(Method AVGPM)
 - a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent, if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
 - b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
 - c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
 - d) Correct the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.



Note: Offset = RF cable loss(0.5dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

CONDUCTED SPURIOUS EMISSION

Applicable Standard

According to FCC §15.247(d):


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020, section 11.11

- Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution. NOTE—the number of points can also be increased for large spans to retain frequency resolution
- Set the RBW: 100 kHz
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Note: Offset = RF cable loss(0.5dB[#]/3.0dB[#]) + Attenuator(10dB)

The cable loss of 0.5dB[#] has been added into test result, except for test result of frequencies from 30 MHz to 25 GHz, where a maximum cable loss of 3.0dB[#] has been added.

Test Data

Test Result: Compliance. Please refer to the Appendix.

POWER SPECTRAL DENSITY

Applicable Standard

According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


Test Procedure

According to ANSI C63.10-2020, section 11.10.2

- Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span >1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.



Note: Offset = RF cable loss($0.5\text{dB}^\#$) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.


DUTY CYCLE

Test Procedure

According to ANSI C63.10-2020 Section 11.6

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



Note: Offset = RF cable loss(0.5dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

APPENDIX

Test Information:

Sample No.:	3DLK-2	Test Date:	2025/12/26~2026/01/05
Test Site:	RF	Test Mode:	Transmitting
Tester:	Benny Li	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	19.7~20.2	Relative Humidity: (%)	47~52	ATM Pressure: (kPa)	100.9~101.8
----------------------	-----------	------------------------------	-------	------------------------	-------------

6dB Emission Bandwidth


Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11b	2412	10.250	≥0.5	Pass
	2437	10.250	≥0.5	Pass
	2462	10.250	≥0.5	Pass
802.11g	2412	16.296	≥0.5	Pass
	2437	16.336	≥0.5	Pass
	2462	16.256	≥0.5	Pass
802.11n20	2412	17.297	≥0.5	Pass
	2437	17.297	≥0.5	Pass
	2462	17.337	≥0.5	Pass
802.11n40	2422	33.634	≥0.5	Pass
	2437	33.554	≥0.5	Pass
	2452	33.634	≥0.5	Pass
802.11ax20_RU_Full	2412	19.019	≥0.5	Pass
	2437	18.979	≥0.5	Pass
	2462	18.979	≥0.5	Pass

802.11b_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:54:36

802.11b_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:59:10

802.11b_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:04:32

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:34:02

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:37:27

802.11g_2462MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:53:13


802.11n20_2412MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li

Date: 5.JAN.2026 18:57:11


802.11n20_2437MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li

Date: 5.JAN.2026 19:01:28


802.11n20_2462MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li

Date: 5.JAN.2026 19:04:20


802.11n40_2422MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li

Date: 5.JAN.2026 19:07:07


802.11n40_2437MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li

Date: 5.JAN.2026 19:10:15


802.11n40_2452MHz



ProjectNo.:2504Z01847E-RF Tester:Benny Li


Date: 5.JAN.2026 19:13:08

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:41:44

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:45:24

802.11ax20_2462MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:48:47

99% Occupied Bandwidth


Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11b	2412	15.840
	2437	15.720
	2462	15.720
802.11g	2412	16.480
	2437	16.440
	2462	16.480
802.11n20	2412	17.560
	2437	17.560
	2462	17.560
802.11n40	2422	35.600
	2437	35.600
	2452	35.600
802.11ax20_RU_Full	2412	18.880
	2437	18.920
	2462	18.880

802.11b_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:53:52

802.11b_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:58:35

802.11b_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:03:51

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:33:17

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:36:51

802.11g_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:52:34

802.11n20_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:56:25

802.11n20_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:00:50

802.11n20_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:03:40

802.11n40_2422MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:06:55

802.11n40_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:10:04

802.11n40_2452MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:12:56

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:40:58

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:44:48

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:48:08


Maximum Conducted Output Power

Mode	Test Frequency (MHz)	Peak Output Power(dBm)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11b	2412	22.82	20.55	30	Pass
	2437	22.37	20.06	30	Pass
	2462	22.24	20.00	30	Pass
802.11g	2412	23.72	14.71	30	Pass
	2437	24.16	15.89	30	Pass
	2462	23.83	15.19	30	Pass
802.11n20	2412	25.03	16.35	30	Pass
	2437	24.82	15.62	30	Pass
	2462	24.64	14.98	30	Pass
802.11n40	2422	23.11	13.72	30	Pass
	2437	22.43	12.80	30	Pass
	2452	22.25	12.55	30	Pass
802.11ax20_RU_Full	2412	24.65	16.56	30	Pass
	2437	24.59	16.73	30	Pass
	2462	24.29	16.08	30	Pass

Power Spectral Density


Mode	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	2412	-4.73	8	Pass
	2437	-5.13	8	Pass
	2462	-5.32	8	Pass
802.11g	2412	-10.36	8	Pass
	2437	-11.51	8	Pass
	2462	-10.56	8	Pass
802.11n20	2412	-9.70	8	Pass
	2437	-10.96	8	Pass
	2462	-9.22	8	Pass
802.11n40	2422	-12.05	8	Pass
	2437	-14.38	8	Pass
	2452	-13.54	8	Pass
802.11ax20_RU_Full	2412	-10.02	8	Pass
	2437	-9.94	8	Pass
	2462	-10.78	8	Pass

802.11b_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:56:48

802.11b_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:00:39

802.11b_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:06:25

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:16:10

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:39:06

802.11g_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:55:15

802.11n20_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:59:20

802.11n20_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:03:14

802.11n20_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:06:26

802.11n40_2422MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:09:40

802.11n40_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:12:28

802.11n40_2452MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:15:41

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504201847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:44:03

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504201847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:47:15

802.11ax20_2462MHz_RU_Full




ProjectNo.:2504201847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:51:01

Duty Cycle

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	2437	0.321	0.345	93.04	0.31	3115	5
802.11g	2437	1.349	1.373	98.25	/	/	0.010
802.11n20	2437	5.065	5.093	99.45	/	/	0.010
802.11n40	2437	2.457	2.482	98.99	/	/	0.010
802.11ax20_RU_FULLL	2437	3.867	3.895	99.28	/	/	0.010


Duty Cycle = Ton/(Ton+Toff)*100%

802.11b_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:43:59

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:44:45

802.11n20_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:48:00

802.11n40_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:48:54

802.11ax20_2437MHz_RU_FULL




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 09:49:45


Conducted Spurious Emission




ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:19:31




ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:19:54




ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:20:23



ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:21:02




ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:21:33




ProjectNo.:2504Z01847E-RF Tester:Benny LI
Date: 5.JAN.2026 19:22:11

802.11b_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:22:33

802.11b_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:23:03

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:23:49

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:24:11

802.11g_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:24:41

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:37:48

802.11g_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:38:19

802.11g_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:53:37

802.11g_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:53:59

802.11g_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:54:28

802.11n20_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:57:39

802.11n20_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:58:01

802.11n20_2412MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 18:58:30

802.11n20_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:01:51

802.11n20_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:02:23

802.11n20_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:04:44

802.11n20_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:05:06

802.11n20_2462MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:05:36

802.11n40_2422MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:07:16

802.11n40_2422MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:07:38

802.11n40_2422MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:08:08

802.11n40_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:10:25

802.11n40_2437MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:10:56

802.11n40_2452MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:13:17

802.11n40_2452MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:13:39

802.11n40_2452MHz




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 5.JAN.2026 19:14:09

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:42:18

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:42:41

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:43:10

802.11ax20_2437MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:45:50

802.11ax20_2437MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:46:22

802.11ax20_2462MHz_RU_Full




ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:49:16

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:49:38

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504Z01847E-RF Tester:Benny Li
Date: 26.DEC.2025 10:50:08

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504Z01847E-RF EUT External Photos and Attachment No.2 2504Z01847E-RF EUT Internal Photos.

EXHIBIT B-TEST SETUP PHOTOGRAPHS

Please refer to the Attachment No.3 2504Z01847E-RF-00A Test Photos.

******* END OF REPORT *******