

## RF EXPOSURE

FCC ID: 2BTVDDMRN-1000

KDB447498 was used as the guidance.

### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and test separation distances  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):<sup>32</sup>

1)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz

2)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

1) For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$

**2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$**

3) SAR measurement procedures are not established below 100 MHz.

## Appendix C

(SAR Test Exclusion Thresholds for < 100 MHz and < 200 mm)

| MHz  | <50        | 50   | 60   | 70   | 80   | 90   | 100  | 110  | mm |
|------|------------|------|------|------|------|------|------|------|----|
| 100  | 237        | 474  | 481  | 487  | 494  | 501  | 507  | 514  | mW |
| 50   | <b>308</b> | 617  | 625  | 634  | 643  | 651  | 660  | 669  |    |
| 10   | <b>474</b> | 948  | 961  | 975  | 988  | 1001 | 1015 | 1028 |    |
| 1    | 711        | 1422 | 1442 | 1462 | 1482 | 1502 | 1522 | 1542 |    |
| 0.1  | 948        | 1896 | 1923 | 1949 | 1976 | 2003 | 2029 | 2056 |    |
| 0.05 | 1019       | 2039 | 2067 | 2096 | 2125 | 2153 | 2182 | 2211 |    |
| 0.01 | 1185       | 2370 | 2403 | 2437 | 2470 | 2503 | 2537 | 2570 |    |
| MHz  | 120        | 130  | 140  | 150  | 160  | 170  | 180  | 190  | mm |
| 100  | 521        | 527  | 534  | 541  | 547  | 554  | 561  | 567  | mW |
| 50   | 677        | 686  | 695  | 703  | 712  | 721  | 729  | 738  |    |
| 10   | 1041       | 1055 | 1068 | 1081 | 1095 | 1108 | 1121 | 1135 |    |
| 1    | 1562       | 1582 | 1602 | 1622 | 1642 | 1662 | 1682 | 1702 |    |
| 0.1  | 2083       | 2109 | 2136 | 2163 | 2189 | 2216 | 2243 | 2269 |    |
| 0.05 | 2239       | 2268 | 2297 | 2325 | 2354 | 2383 | 2411 | 2440 |    |
| 0.01 | 2603       | 2637 | 2670 | 2703 | 2737 | 2770 | 2803 | 2837 |    |

## SAR Test Exclusion Considerations : RFID 13.56 MHz

- Frequency : 13.56 MHz
- Measured Maximum Field Strength : 58.50 dBuV/m ( at 3 m )
- MAX Field Strength : 59.50 dBuV/m ( at 3 m )
- MAX Tuneup EIRP : -35.73 dBm

The EUT will only be used with a separation of 5 millimeters or lesser between the antenna and the body of the SAR Exclusion calculation for this exposure is shown below.

|                                                                                                                                                             |                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| - EIRP = $P + (20 * \text{Log}(D)) - 104.77$<br>= <u>59.50</u> + <u>9.542</u> - <u>104.77</u><br>= <u>-35.73</u> dBm<br>P(mW) = <u>0.000267</u> mW < 442.65 | - NOTE<br>P : Max Field Strength (dBuV/m)<br>D : Measured Distance (m)<br>P(mW) : Max Tuneup Power (EIRP, mW) |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|

### Power threshold limit

|                                                                                                          |                                                                                                                     |
|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| $P_{th} = 474\text{mW} * [1 + \log(100 / f(\text{MHz}))] / 2$<br>= 474 * [ 1 + 0.86774 ] / 2<br>= 442.65 | - NOTE<br>P <sub>th</sub> : Power allowed at numeric threshold<br>f(MHz) : The RF Channel Transmit Frequency in GHz |
|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|

According to KDB447498 D01 V6, threshold at which no SAR required is  $\leq 442.65$  for Power allowed at numeric threshold, separation distance is 5mm, and no simultaneous SAR measurement is required.

The SAR measurement is not necessary.