



FCC Test Report

Application No.: DNT2606153787R07315-11307

Applicant: Huaou Tonghui(Suzhou)Technology Co., Ltd.

Address of Applicant: No.299,Shengxin Road,Bache,Dongtaihu Ecological Tourist Resort(Taihu New City) Wujiang District,Suzhou City China

EUT Description: TWS Wireless Headset

Model No.: AETHER-O2

Additional Model(s): N/A

FCC ID: 2BTWM-O2

Power Supply (Charging Box): Input:DC 5V;DC 3.7V from rechargeable lithium-ion battery

Power Supply (Earphone): DC 3.7V from rechargeable lithium-ion battery

Trade Mark: 

Standards: 47 CFR Part 2, Subpart J
47 CFR Part 15, Subpart C
ANSI C63.10: 2020


Date of Receipt: 2026/06/15


Date of Test: 2026/06/16 to 2026/07/14


Date of Issue: 2026/07/14

Test Result:

PASS

Prepared By:  (Testing Engineer)

Reviewed By:  (Project Engineer)

Approved By:  (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

GUANGDONG DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	July 14, 2026	Valid	Original Report



1 Test Summary

Test Item	Test Requirement	Test Method	Test Result	Result
Antenna Requirement	15.203/247(b)	--	Clause 3.1	PASS
20dB Emission Bandwidth	15.247 (a)(1)	ANSI C63.10: 2020	Clause 3.2	PASS
Conducted Peak Output Power	15.247 (b)(1)	ANSI C63.10: 2020	Clause 3.3	PASS
Carrier Frequencies Separation	15.247 (a)(1)	ANSI C63.10: 2020	Clause 3.4	PASS
Dwell Time	15.247 (a)(1)	ANSI C63.10: 2020	Clause 3.5	PASS
Hopping Channel Number	15.247 (a)(1)	ANSI C63.10: 2020	Clause 3.6	PASS
Band-edge for RF Conducted Emissions	15.247(d)	ANSI C63.10: 2020	Clause 3.7	PASS
RF Conducted Spurious Emissions	15.247(d)	ANSI C63.10: 2020	Clause 3.8	PASS
Radiated Spurious emissions	15.247(d); 15.205/15.209	ANSI C63.10: 2020	Clause 3.9	PASS
Restricted bands around fundamental frequency (Radiated Emission)	15.247(d); 15.205/15.209	ANSI C63.10: 2020	Clause 3.10	PASS
AC Power Line Conducted Emission	15.207	ANSI C63.10: 2020	Clause 3.11	PASS

Note:

1. "N/A" denotes test is not applicable in this test report.



Contents

1 Test Summary	3
2 General Information	5
2.1 Test Location	5
2.2 General Description of EUT	5
2.3 Test Environment	6
2.4 Channel List	6
2.5 Power Setting of Test Software	7
2.6 Assistant equipment used for test	7
2.7 Description of Support Units	7
2.8 Test Facility	7
2.9 Equipment List	8
2.10 Measurement Uncertainty (95% confidence levels, k=2)	10
3 Test results and Measurement Data	11
3.1 Antenna Requirement	11
3.2 20dB Emission Bandwidth	12
3.3 Conducted Output Power	13
3.4 Carrier Frequencies Separation	14
3.5 Dwell Time	15
3.6 Hopping Channel Number	16
3.7 Band-edge for RF Conducted Emissions	17
3.8 RF Conducted Spurious Emissions	18
3.9 Radiated Spurious Emissions	19
3.10 Restricted bands around fundamental frequency	30
3.11 AC Power Line Conducted Emissions	34
4 Appendix	37
Appendix A: 20dB Emission Bandwidth	37
Appendix B: Maximum conducted output power	41
Appendix C: Carrier frequency separation	48
Appendix D: Dwell Time	50
Appendix E: Number of hopping channels	54
Appendix F: Band edge measurements	56
Appendix G: Conducted Spurious Emission	61



2 General Information

2.1 Test Location

Company:	GuangDong DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang' an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Gali Lin

2.2 General Description of EUT

Manufacturer:	Huaou Tonghui(Suzhou)Technology Co., Ltd.
Address of Manufacturer:	No.299,Shengxin Road,Bache,Dongtaihu Ecological Tourist Resort(Taihu New City) Wujiang District,Suzhou City China
Factory:	Huaou Tonghui(Suzhou)Technology Co., Ltd.
Address of Factory:	No.299,Shengxin Road,Bache,Dongtaihu Ecological Tourist Resort(Taihu New City) Wujiang District,Suzhou City China
EUT Description:	TWS Wireless Headset
Model No.:	AETHER-O2
Additional Model(s):	N/A
Power Supply (Charging Box):	Input:DC 5V;DC 3.7V from rechargeable lithium-ion battery
Power Supply (Earphone):	DC 3.7V from rechargeable lithium-ion battery
Trade Mark:	KOUO
Hardware Version:	V1.0
Software Version:	V1.0
Serial number:	PR2606153787R07315
Chip Type:	AB5636D
Operation Frequency:	2402MHz to 2480MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK,8-DPSK
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Sample Type:	☒ Portable Device, ☐ Module, ☐ Mobile Device
Antenna Type:	☐ External, ☒ Integrated
Antenna Ports:	☒ Ant 1, ☐ Ant 2, ☐ Ant 3
Antenna Gain*:	☒ Provided by applicant 2.8dBi
RF Cable*:	☒ Provided by applicant 0.5dB(0.6~1GHz); 0.8dB(1.4~2GHz); 1.0dB(2.1~2.7GHz); 1.5dB(3~4GHz); 1.8dB(4.4~6GHz);

Note:

*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

GUANGDONG DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel:+86-769-88087383

E-mail: service@dn-testing.com



2.3 Test Environment

Operating Environment:	
Temperature:	20~25.0 °C
Humidity:	45~56 % RH
Atmospheric Pressure:	101.0~101.30 KPa
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

2.4 Channel List

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



2.5 Power Setting of Test Software

Software Name	bt_tool_v1.1.2		
Frequency(MHz)	2402	2441	2480
GFSK Setting	7	7	7
$\pi/4$ -DQPSK Setting	7	7	7
8-DPSK Setting	7	7	7

2.6 Assistant equipment used for test

Code	Equipment	Manufacturer	Model No.	Equipment No.
1	Computer	acer	N22C8	EMC notebook01
2	Adapter	Xiaomi	HW-100225C00	NA

2.7 Description of Support Units

The EUT has been tested as an independent unit.

2.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Lab A:

• FCC, USA

Designation Number: CN1348

• A2LA (Certificate No. 7050.01)

GUANGDONG DN TESTING CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 7050.01.

• Innovation, Science and Economic Development Canada

GUANGDONG DN TESTING CO., LTD. EMC Laboratory has been recognized by ISED as an accredited testing laboratory. CAB identifier is CN0149.

IC#: 30755.



2.9 Equipment List

For Connect EUT Antenna Terminal Test					
Description	Manufacturer	Model	Serial Number	Cal date	Due date
Signal Generator	Keysight	N5181A-6G	MY48180415	2025-10-21	2026-10-20
Signal Generator	Keysight	N5182B	MY57300617	2025-10-21	2026-10-20
Power supply	Keysight	E3640A	ZB2022656	2025-10-21	2026-10-20
Radio Communication Tester	R&S	CMW500	105082	2025-10-21	2026-10-20
Spectrum Analyzer	Aglient	N9010A	MY52220200	2025-10-21	2026-10-20
BT/WIFI Test Software	Tonscend	JS1120 V3.1.83	NA	NA	NA
RF Control Unit	Tonscend	JS0806-2	22F8060581	NA	NA
Power Sensor	Anritsu	ML2495A	2129005	2025-10-21	2026-10-20
Pulse Power Sensor	Anritsu	MA2411B	1911397	2025-10-21	2026-10-20
temperature and humidity box	SCOTEK	SCD-C40-80PRO	6866682020008	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	RFC-NMS-100-NMS-350-IN	NA	2025-10-21	2026-10-20

Test Equipment for Conducted Emission					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESCI3	101152	2025-10-21	2026-10-20
LISN	R&S	ENV216	102874	2025-10-21	2026-10-20
ISN	R&S	ENY81-CA6	1309.8590.03	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	Cable-CE TS01	/	2025-10-21	2026-10-20

Test Equipment for Radiated Emission(30MHz-1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESR7	102497	2025-10-21	2026-10-20
Test Software	Tonscend	JS32-RE	NA	NA	NA
RF Cable	ETS-LINDGREN	RE Cable-TS01	NA	2025-10-21	2026-10-20



Log periodic antenna	ETS-LINDGREN	VULB 9168	01475	2025-10-21	2026-10-20
Pre-amplifier	Schwarzbeck	BBV9743B	00423	2025-10-21	2026-10-20
Attenuator 1	Shanghai Huaxiang	TS2-6-18-A	22061803	2025-10-21	2026-10-20
Attenuator 2	Shanghai Huaxiang	TS2-6-6-A	230927163	2025-10-21	2026-10-20

Test Equipment for Radiated Emission(Above 1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Frequency analyser	Keysight	N9010A	MY52221458	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	RE Cable-TS02	NA	2025-10-21	2026-10-20
Horn Antenna	ETS-LINDGREN	3117	00252567	2025-10-21	2026-10-20
Double ridged waveguide antenna	ETS-LINDGREN	3116C	00251780	2025-10-21	2026-10-20
Test Software	Tonscend	JS32-RE	NA	NA	NA
Pre-amplifier	ETS-LINDGREN	3117-PA	252567	2025-10-21	2026-10-20
Pre-amplifier	ETS-LINDGREN	3116C-PA	251780	2025-10-21	2026-10-20



2.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	20dB Emission Bandwidth	$\pm 0.0196\%$
2	Carrier Frequency Separation	$\pm 1.9\%$
3	Number of Hopping Channel	$\pm 1.9\%$
4	Time of Occupancy	$\pm 0.028\%$
5	Max Peak Conducted Output Power	± 0.743 dB
6	Band-edge Spurious Emission	± 1.328 dB
7	Conducted RF Spurious Emission	9KHz-1GHz: ± 0.746 dB 1GHz-26GHz: ± 1.328 dB

No.	Item	Measurement Uncertainty
1	Conduction Emission	± 3.0 dB (150kHz to 30MHz)
2	Radiated Emission	± 4.8 dB (Below 1GHz)
		± 4.8 dB (1GHz to 6GHz)
		± 4.5 dB (6GHz to 18GHz)
		± 5.02 dB (Above 18GHz)




3 Test results and Measurement Data

3.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.	
The antenna is integrated to the motherboard, The best case gain of the antenna is 2.8dBi .	




3.2 20dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10: 2020 Section 6.9.2
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	NA
Test Results:	Pass

The detailed test data see: **Appendix A**




3.3 Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10: 2020 Section 7.8.5
Test Setup:	
Test Instruments:	Refer to section 2.9 for details
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	(20.97dBm) 125mW
Test Results:	Pass

The detailed test data see: **Appendix B**




3.4 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10: 2020 Section 7.8.2
Test Setup:	
Test Instruments:	Refer to section 2.9 for details
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Test Results:	Pass

The detailed test data see: **Appendix C**




3.5 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10: 2020 Section 7.8.4
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

The detailed test data see: **Appendix D**




3.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10: 2020 Section 7.8.3
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Test Mode:	Hopping transmitting with all kind of modulation
Limit:	At least 15 channels
Test Results:	Pass

The detailed test data see: **Appendix E**




3.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2020 Section 7.8.7.2
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix F**



3.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2020 Section 7.8.7.1
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix G**



3.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2020 Section 7.8.8 /6.3 / 6.4/ 6.5 /6.6				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz (DC $\geq$ 0.98) $\geq$ 1/T (DC<0.98)	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				


**Test Setup:**

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

GUANGDONG DN Testing Co., Ltd.




Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge+Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode. Through Pre-scan, find the DH5 of data type is the worst case of All modulation type.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass




Test data

For 30-1000MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	72.01	27.99	-10.47	17.52	40.00	22.48	100	267	PK	H
2	158.83	29.02	-7.79	21.23	43.50	22.27	100	178	PK	H
3	243.42	29.19	-9.08	20.11	46.00	25.89	100	303	PK	H
4	341.79	28.84	-5.89	22.95	46.00	23.05	100	196	PK	H
5	522.52	29.29	-1.17	28.12	46.00	17.88	100	89	PK	H
6	715.08	31.19	2.46	33.65	46.00	12.35	100	54	PK	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	55.51	27.56	-8.31	19.25	40.00	20.75	100	223	PK	V
2	116.53	29.33	-10.57	18.76	43.50	24.74	100	357	PK	V
3	137.87	29.24	-8.68	20.56	43.50	22.94	100	49	PK	V
4	169.89	28.60	-8.29	20.31	43.50	23.19	100	84	PK	V
5	348.39	29.25	-5.84	23.41	46.00	22.59	100	258	PK	V
6	603.33	29.49	0.80	30.29	46.00	15.71	100	117	PK	V




For above 1GHz(Left earphone)

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	55.84	-4.61	51.23	74.00	22.77	150	306	PK	H
2	7206.00	43.86	-1.76	42.10	74.00	31.90	150	248	PK	H
3	9608.00	47.03	0.88	47.91	74.00	26.09	150	248	PK	H
4	4804.00	52.31	-4.61	47.70	54.00	6.30	150	76	AV	H
5	7206.00	35.11	-1.76	33.35	54.00	20.65	150	18	AV	H
6	9608.00	44.65	0.88	45.53	54.00	8.47	150	248	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	50.61	-4.61	46.00	74.00	28.00	150	132	PK	V
2	7206.00	44.48	-1.76	42.72	74.00	31.28	150	307	PK	V
3	9608.00	47.83	0.88	48.71	74.00	25.29	150	279	PK	V
4	4804.00	46.00	-4.61	41.39	54.00	12.61	150	70	AV	V
5	7206.00	35.41	-1.76	33.65	54.00	20.35	150	44	AV	V
6	9608.00	46.63	0.88	47.51	54.00	6.49	150	279	AV	V



DH5 2441MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	54.66	-4.72	49.94	74.00	24.06	150	274	PK	H
2	7323.00	43.11	-1.49	41.62	74.00	32.38	150	355	PK	H
3	9764.00	45.97	1.64	47.61	74.00	26.39	150	162	PK	H
4	4882.00	49.55	-4.72	44.83	54.00	9.17	150	305	AV	H
5	7323.00	35.57	-1.49	34.08	54.00	19.92	150	334	AV	H
6	9764.00	42.50	1.64	44.14	54.00	9.86	150	248	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	50.43	-4.72	45.71	74.00	28.29	150	42	PK	V
2	7323.00	44.27	-1.49	42.78	74.00	31.22	150	227	PK	V
3	9764.00	48.57	1.64	50.21	74.00	23.79	150	281	PK	V
4	4882.00	46.63	-4.72	41.91	54.00	12.09	150	42	AV	V
5	7323.00	35.70	-1.49	34.21	54.00	19.79	150	0	AV	V
6	9764.00	47.37	1.64	49.01	54.00	4.99	150	281	AV	V



DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	44.77	-4.86	39.91	74.00	34.09	150	273	PK	H
2	7440.00	43.45	-1.34	42.11	74.00	31.89	150	301	PK	H
3	9920.00	45.67	2.27	47.94	74.00	26.06	150	248	PK	H
4	4960.00	39.22	-4.86	34.36	54.00	19.64	150	301	AV	H
5	7440.00	36.17	-1.34	34.83	54.00	19.17	150	166	AV	H
6	9920.00	43.78	2.27	46.05	54.00	7.95	150	248	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	44.18	-4.86	39.32	74.00	34.68	150	27	PK	V
2	7440.00	43.76	-1.34	42.42	74.00	31.58	150	189	PK	V
3	9920.00	49.43	2.27	51.70	74.00	22.30	150	276	PK	V
4	4960.00	37.23	-4.86	32.37	54.00	21.63	150	50	AV	V
5	7440.00	34.78	-1.34	33.44	54.00	20.56	150	352	AV	V
6	9920.00	47.66	2.27	49.93	54.00	4.07	150	302	AV	V




For above 1GHz(Right earphone)

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	47.33	-4.61	42.72	74.00	31.28	150	217	PK	H
2	7206.00	43.88	-1.76	42.12	74.00	31.88	150	3	PK	H
3	9608.00	44.77	0.88	45.65	74.00	28.35	150	248	PK	H
4	4804.00	42.55	-4.61	37.94	54.00	16.06	150	102	AV	H
5	7206.00	34.97	-1.76	33.21	54.00	20.79	150	275	AV	H
6	9608.00	42.40	0.88	43.28	54.00	10.72	150	248	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	45.24	-4.61	40.63	74.00	33.37	150	330	PK	V
2	7206.00	43.52	-1.76	41.76	74.00	32.24	150	18	PK	V
3	9608.00	47.46	0.88	48.34	74.00	25.66	150	299	PK	V
4	4804.00	38.09	-4.61	33.48	54.00	20.52	150	71	AV	V
5	7206.00	35.25	-1.76	33.49	54.00	20.51	150	182	AV	V
6	9608.00	46.35	0.88	47.23	54.00	6.77	150	299	AV	V



DH5 2441MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	54.47	-4.72	49.75	74.00	24.25	150	274	PK	H
2	7323.00	44.42	-1.49	42.93	74.00	31.07	150	274	PK	H
3	9764.00	46.78	1.64	48.42	74.00	25.58	150	246	PK	H
4	4882.00	50.92	-4.72	46.20	54.00	7.80	150	103	AV	H
5	7323.00	34.97	-1.49	33.48	54.00	20.52	150	356	AV	H
6	9764.00	44.96	1.64	46.60	54.00	7.40	150	246	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	49.03	-4.72	44.31	74.00	29.69	150	69	PK	V
2	7323.00	43.61	-1.49	42.12	74.00	31.88	150	1	PK	V
3	9764.00	48.85	1.64	50.49	74.00	23.51	150	301	PK	V
4	4882.00	44.54	-4.72	39.82	54.00	14.18	150	40	AV	V
5	7323.00	35.19	-1.49	33.70	54.00	20.30	150	301	AV	V
6	9764.00	47.64	1.64	49.28	54.00	4.72	150	301	AV	V



DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	49.99	-4.86	45.13	74.00	28.87	150	73	PK	H
2	7440.00	43.35	-1.34	42.01	74.00	31.99	150	16	PK	H
3	9920.00	48.18	2.27	50.45	74.00	23.55	150	248	PK	H
4	4960.00	46.56	-4.86	41.70	54.00	12.30	150	272	AV	H
5	7440.00	35.53	-1.34	34.19	54.00	19.81	150	219	AV	H
6	9920.00	45.52	2.27	47.79	54.00	6.21	150	248	AV	H



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	47.27	-4.86	42.41	74.00	31.59	150	43	PK	V
2	7440.00	45.05	-1.34	43.71	74.00	30.29	150	213	PK	V
3	9920.00	48.81	2.27	51.08	74.00	22.92	150	302	PK	V
4	4960.00	42.40	-4.86	37.54	54.00	16.46	150	43	AV	V
5	7440.00	36.36	-1.34	35.02	54.00	18.98	150	354	AV	V
6	9920.00	47.40	2.27	49.67	54.00	4.33	150	302	AV	V



Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:
$$\text{Result Level} = \text{Reading Level} + \text{Correct Factor}(\text{including Ant.Factor, Cable Factor etc.})$$
2. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
3. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be report.
4. All channels had been pre-test, DH5 is the worst case, only the worst case was reported.
5. Both left and right earphone have tested for the amplitude of 30MHz to 1GHz spurious emission ,
The Right earphone is the worst and only the worse case was reported.



3.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2020 Section 7.8.8 /6.3 / 6.6		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel - Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.
Test Configuration:	Measurements Below 1000MHz

GUANGDONG DN Testing Co., Ltd.




	• RBW = 120 kHz • VBW = 300 kHz • Detector = Peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT Transmitting mode. Through Pre-scan, find the DH5 of data type is the worst case of all modulation type. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass




Test Date

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2384.55	56.16	-0.82	55.34	74.00	18.66	150	18	PK	H
2	2390.01	55.19	-0.80	54.39	74.00	19.61	150	349	PK	H
3	2384.51	45.33	-0.82	44.51	54.00	9.49	150	358	AV	H
4	2390.00	44.54	-0.80	43.74	54.00	10.26	150	287	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2380.14	55.75	-0.83	54.92	74.00	19.08	150	248	PK	V
2	2390.00	54.96	-0.80	54.16	74.00	19.84	150	129	PK	V
3	2383.68	45.53	-0.82	44.71	54.00	9.29	150	129	AV	V
4	2390.00	44.83	-0.80	44.03	54.00	9.97	150	268	AV	V



DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2483.50	49.63	-0.29	49.34	74.00	24.66	150	43	PK	H
2	2486.20	51.25	-0.27	50.98	74.00	23.02	150	248	PK	H
3	2483.50	39.91	-0.29	39.62	54.00	14.38	150	130	AV	H
4	2487.12	40.75	-0.26	40.49	54.00	13.51	150	64	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2485.86	49.35	-0.27	49.08	74.00	24.92	150	208	PK	V
2	2489.19	51.14	-0.24	50.90	74.00	23.10	150	166	PK	V
3	2485.86	40.44	-0.27	40.17	54.00	13.83	150	69	AV	V
4	2488.99	40.68	-0.24	40.44	54.00	13.56	150	140	AV	V

Note:

- All channels had been pre-test, DH5 is the worst case, only the worst case was reported
- The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including Ant.Factor ,Cable Factor etc.)
- Both left and right earphone have tested, The Right earphone is the worst, only the worse case was reported.



3.11 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2020 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.		
Test Setup:			
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Charge + Transmitting mode.		
Final Test Mode:	Through Pre-scan, find the the worst case.		




Instruments Used:	Refer to section 2.9 for details
Test Results:	PASS

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2136	9.92	32.18	63.06	30.88	19.97	53.06	33.09	PASS
2	0.6051	9.82	43.91	56.00	12.09	33.54	46.00	12.46	PASS
3	0.9635	9.72	31.95	56.00	24.05	21.91	46.00	24.09	PASS
4	1.9404	9.74	30.15	56.00	25.85	20.79	46.00	25.21	PASS
5	2.5630	9.73	32.71	56.00	23.29	20.32	46.00	25.68	PASS
6	4.3933	9.77	34.05	56.00	21.95	20.00	46.00	26.00	PASS



Neutral Line:



NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2657	9.87	32.34	61.25	28.91	17.47	51.25	33.78	PASS
2	0.6073	9.79	34.76	56.00	21.24	27.67	46.00	18.33	PASS
3	0.8479	9.77	28.38	56.00	27.62	18.66	46.00	27.34	PASS
4	3.1938	9.89	28.66	56.00	27.34	15.88	46.00	30.12	PASS
5	4.3131	9.97	37.58	56.00	18.42	20.12	46.00	25.88	PASS
6	4.8424	9.97	34.63	56.00	21.37	20.37	46.00	25.63	PASS

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including LISN Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including LISN Factor, Cable Factor etc.)



4 Appendix

Appendix A: 20dB Emission Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.978	2401.526	2402.504	---	---
		2441	0.981	2440.508	2441.489	---	---
		2480	0.957	2479.535	2480.492	---	---
2DH5	Ant1	2402	1.335	2401.331	2402.666	---	---
		2441	1.332	2440.328	2441.660	---	---
		2480	1.323	2479.334	2480.657	---	---
3DH5	Ant1	2402	1.332	2401.337	2402.669	---	---
		2441	1.305	2440.349	2441.654	---	---
		2480	1.308	2479.346	2480.654	---	---


Note:

Both left and right earphone have tested, The Right earphone is the worst, only the worse case was reported.




Test Graphs


DH5_Ant1_2402



DH5_Ant1_2441




DH5_Ant1_2480







2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480







3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



**Appendix B: Maximum conducted output power****Test Result(Left earphone)**

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	-4.65	≤30	PASS
		2441	-4.70	≤30	PASS
		2480	-4.33	≤30	PASS
2DH5	Ant1	2402	-2.63	≤20.97	PASS
		2441	-2.58	≤20.97	PASS
		2480	-2.28	≤20.97	PASS
3DH5	Ant1	2402	-2.02	≤20.97	PASS
		2441	-2.03	≤20.97	PASS
		2480	-1.64	≤20.97	PASS


Test Result(Right earphone)

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	-1.62	≤30	PASS
		2441	-1.78	≤30	PASS
		2480	-1.35	≤30	PASS
2DH5	Ant1	2402	0.06	≤20.97	PASS
		2441	0.10	≤20.97	PASS
		2480	0.47	≤20.97	PASS
3DH5	Ant1	2402	0.53	≤20.97	PASS
		2441	0.75	≤20.97	PASS
		2480	1.13	≤20.97	PASS




Test Graphs(Left earphone)


DH5_Ant1_2402



DH5_Ant1_2441




DH5_Ant1_2480







2DH5_Ant1_2402



2DH5_Ant1_2441




2DH5_Ant1_2480







3DH5_Ant1_2402



3DH5_Ant1_2441




3DH5_Ant1_2480






Test Graphs(Right earphone)


DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480





Page: 46 / 70

Agilent Spectrum Analyzer - Sweep 5A

SENSE:PLB| SOURCE:OFF | REF:NAUTO | 09-17-22 AM MOL-008

Center Freq 2.402000000 GHz PWD: Fast IF Gain: Low Trig: Free Run #Att: 40 dB #Avg Type: RMS Avg/Hold: 100/100 TRACE[1] 2 3 4 5 TYPE[M] WWWWMM DET[P] P P P P P

Ref Offset 5.03 dB
Ref 28.03 dBm

Mkr1 2.402 204 GHz
0.063 dBm

10 dB/div
Log

18.0
8.03
-1.97
-12.0
-22.0
-32.0
-42.0
-52.0
-62.0

Auto Tun
Center Freq
2.402000000 GHz
Start Freq
2.399000000 GHz
Stop Freq
2.405000000 GHz
CF Step
600.000 kHz
Auto
Freq Offset
0 Hz

Center 2.402000 GHz
#Res BW 2.0 MHz
#VBW 6.0 MHz
Sweep 1.000 ms (1001 pts)
Span 6.000 MHz

Agilent Spectrum Analyzer - Sweep 5A

REF L F 50 G DC SENSE/PAISE SOURCE OFF SENSE/AUTO 09:17:37 AM M01, 0005

Center Freq 2.441000000 GHz #Avg Type: RMS #Sig Hold: 100/100 TRACE [1] 2 3 4 5
 FWD: Fast → IF Gain: 1.0w Trig: Free Run #Atten: 40 dB TYPE [M] WWWW DET [P] P P P P P

Ref Offset: 5.05 dB
 Ref 28.05 dBm

Mkr1 2.440 964 GHz
 0.104 dBm

10 dB/div
 18.1
 8.06
 1.95
 -12.0
 -22.0
 -32.0
 -42.0
 -52.0
 -62.0

Center 2.441000 GHz
 #Res BW 2.0 MHz #VBW 6.0 MHz Span 6.000 MHz
 Sweep 1.000 ms (1001 pts)

Frequency
 Auto Tun
 Center Freq
 2.441000000 GHz
 Start Freq
 2.438000000 GHz
 Stop Freq
 2.444000000 GHz
 CF Stop
 600.000 kHz
 Ma
 Auto
 Freq Offset
 0 Hz

Agilent Spectrum Analyzer - Sweep SA

RF 50 Q DC SENSE/PULSE SOURCE OFF ALIGN/AUTO 09:17:54 AM MOI, 2005

Center Freq 2.480000000 GHz #Avg Type: RMS #Trig: Free Run #Att: 40 dB
 PWD: Fast IF Gain Low Avg Hold: 100/100 TYPE: Normal DET: P P P P P

Frequency Auto Tun

Center Freq 2.48000000 GHz

Start Freq 2.477000000 GHz

Stop Freq 2.483000000 GHz

CF Stop 600.000 kHz

Auto

Freq Offset 0 Hz

10 dB/div Ref Offset 5.09 dB
 Ref 28.09 dBm

Mkr1 2.480 210 GHz
 0.466 dBm

Center 2.480000 GHz
 Res BW 2.0 MHz #VBW 6.0 MHz Span 6.000 MHz
 Sweep 1.000 ms (1001 pts)